1 pC Charge Injection, 100 pA Leakage, CMOS, ±5 V/+5 V/+3 V, Quad SPST Switches

ADG611/ADG612/ADG613

FEATURES

1 pC charge injection
±2.7 V to ±5.5 V dual-supply operation
+2.7 V to +5.5 V single-supply operation
Automotive temperature range: −40°C to +125°C
100 pA maximum at 25°C leakage currents
85 Ω on resistance
Rail-to-rail switching operation
Fast switching times
16-lead TSSOP and SOIC packages
Typical power consumption: <0.1 µW
TTL-/CMOS-compatible inputs

APPLICATIONS

Automatic test equipment
Data acquisition systems
Battery-powered systems
Communications systems
Sample-and-hold systems
Audio signal routing
Relay replacement
Avionics

FUNCTIONAL BLOCK DIAGRAM



Figure 1.

GENERAL DESCRIPTION

The ADG611/ADG612/ADG613 are monolithic CMOS devices containing four independently selectable switches. These switches offer ultralow charge injection of 1 pC over the full input signal range and typical leakage currents of 10 pA at 25°C.

The devices are fully specified for ±5 V, +5 V, and +3 V supplies. Each contains four independent single-pole, single-throw (SPST) switches. The ADG611 and ADG612 differ only in that the digital control logic is inverted. The ADG611 switches are turned on with a logic low on the appropriate control input, whereas a logic high is required to turn on the switches of the ADG612. The ADG613 contains two switches with digital control logic similar to that of the ADG611 and two switches in which the logic is inverted.

Each switch conducts equally well in both directions when on and has an input signal range that extends to the supplies. The ADG613 exhibits break-before-make switching action. The ADG611/ADG612/ADG613 are available in a small, 16-lead TSSOP package, and the ADG611 is also available in a 16-lead SOIC package.

PRODUCT HIGHLIGHTS

1. Ultralow charge injection (1 pC typically).
2. Dual ±2.7 V to ±5.5 V or single +2.7 V to +5.5 V operation.
3. Automotive temperature range: −40°C to +125°C.
4. Small, 16-lead TSSOP and SOIC packages.

Rev. A
Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 **www.analog.com**
Fax: 781.461.3113 **©2002–2009 Analog Devices, Inc. All rights reserved.**

TABLE OF CONTENTS

Features 1
Applications 1
Functional Block Diagram 1
General Description 1
Product Highlights 1
Revision History 2
Specifications 3
Dual-Supply Operation 3
Single-Supply Operation 4
Absolute Maximum Ratings 6
ESD Caution 6
Pin Configuration and Function Descriptions 7
Typical Performance Characteristics 8
Terminology 10
Test Circuits 11
Applications Information 13
Outline Dimensions 14
Ordering Guide 14

REVISION HISTORY

11/09—Rev. 0 to Rev. A

Changes to Analog Signal Range Parameter and to On Resistance, R_{ON} Parameter, Table 1 3
Change to Digital Input Capacitance, C_{IN} Parameter, Table 2 4
Changes to Table 4 and to Absolute Maximum Ratings Section 6
Added Table 5; Renumbered Sequentially 7
Updated Outline Dimensions 14
Changes to Ordering Guide 14

1/02—Revision 0: Initial Version

SPECIFICATIONS

DUAL-SUPPLY OPERATION

V_{DD} = +5 V ± 10%, V_{SS} = −5 V ± 10%, GND = 0 V, unless otherwise noted.

Table 1.

Parameter	+25°C	−40°C to +85°C	−40°C to +125°C[1]	Unit	Test Conditions/Comments
ANALOG SWITCH					
Analog Signal Range			V_{SS} to V_{DD}	V	
On Resistance, R_{ON}	85			Ω typ	V_S = ±3 V, I_S = −1 mA; see Figure 14
	115	140	160	Ω max	V_S = ±3 V, I_S = −1 mA; see Figure 14
On-Resistance Match Between Channels, ΔR_{ON}	2			Ω typ	V_S = ±3 V, I_S = −1 mA
	4	5.5	6.5	Ω max	V_S = ±3 V, I_S = −1 mA
On-Resistance Flatness, $R_{FLAT(ON)}$	25			Ω typ	V_S = ±3 V, I_S = −1 mA
	40	55	60	Ω max	V_S = ±3 V, I_S = −1 mA
LEAKAGE CURRENTS					V_{DD} = +5.5 V, V_{SS} = −5.5 V
Source Off Leakage, $I_{S(OFF)}$	±0.01			nA typ	V_D = ±4.5 V, VS = ∓4.5 V; see Figure 15
	±0.1	±0.25	±2	nA max	V_D = ±4.5 V, VS = ∓4.5 V; see Figure 15
Drain Off Leakage, $I_{D(OFF)}$	±0.01			nA typ	V_D = ±4.5 V, V_S = ∓ 4.5 V; see Figure 15
	±0.1	±0.25	±2	nA max	V_D = ±4.5 V, V_S = ∓ 4.5 V; see Figure 15
Channel On Leakage, $I_{D(ON)}$, $I_{S(ON)}$	±0.01			nA typ	V_D = V_S = ±4.5 V; see Figure 16
	±0.1	± 0.25	± 6	nA max	V_D = V_S = ±4.5 V; see Figure 16
DIGITAL INPUTS					
Input High Voltage, V_{INH}			2.4	V min	
Input Low Voltage, V_{INL}			0.8	V max	
Input Current, I_{INL} or I_{INH}	0.005			μA typ	V_{IN} = V_{INL} or V_{INH}
			±0.1	μA max	V_{IN} = V_{INL} or V_{INH}
Digital Input Capacitance, C_{IN}	2			pF typ	
DYNAMIC CHARACTERISTICS[2]					
t_{ON}	45			ns typ	R_L = 300 Ω, C_L = 35 pF, V_S = 3.0 V; see Figure 17
	65	75	90	ns max	R_L = 300 Ω, C_L = 35 pF, V_S = 3.0 V; see Figure 17
t_{OFF}	25			ns typ	R_L = 300 Ω, C_L = 35 pF, V_S = 3.0 V; see Figure 17
	40	45	50	ns max	R_L = 300 Ω, C_L = 35 pF, V_S = 3.0 V; see Figure 17
Break-Before-Make Time Delay, t_{BBM}	15			ns typ	R_L = 300 Ω, C_L = 35 pF, V_{S1} = V_{S2} = 3.0 V; see Figure 18
			10	ns min	R_L = 300 Ω, C_L = 35 pF, V_{S1} = V_{S2} = 3.0 V; see Figure 18
Charge Injection	−0.5			pC typ	V_S = 0 V, R_S = 0 Ω, C_L = 1 nF; see Figure 19
Off Isolation	−65			dB typ	R_L = 50 Ω, C_L = 5 pF, f = 10 MHz; see Figure 20
Channel-to-Channel Crosstalk	−90			dB typ	R_L = 50 Ω, C_L = 5 pF, f = 10 MHz; see Figure 21
−3 dB Bandwidth	680			MHz typ	R_L = 50 Ω, C_L = 5 pF; see Figure 22
$C_{S(OFF)}$	5			pF typ	f = 1 MHz
$C_{D(OFF)}$	5			pF typ	f = 1 MHz
$C_{D(ON)}$, $C_{S(ON)}$	5			pF typ	f = 1 MHz
POWER REQUIREMENTS					V_{DD} = +5.5 V, V_{SS} = −5.5 V
I_{DD}	0.001			μA typ	Digital inputs = 0 V or 5.5 V
			1.0	μA max	Digital inputs = 0 V or 5.5 V
I_{SS}	0.001			μA typ	Digital inputs = 0 V or 5.5 V
			1.0	μA max	Digital inputs = 0 V or 5.5 V

[1] The temperature range for the Y version is −40°C to +125°C.
[2] Guaranteed by design; not subject to production test.

SINGLE-SUPPLY OPERATION

V_{DD} = 5 V ± 10%, V_{SS} = 0 V, GND = 0 V, unless otherwise noted.

Table 2.

Parameter	+25°C	−40°C to +85°C	−40°C to +125°C[1]	Unit	Test Conditions/Comments
ANALOG SWITCH					
Analog Signal Range			0 to V_{DD}	V	
On Resistance, R_{ON}	210			Ω typ	V_S = 3.5 V, I_S = −1 mA; see Figure 14
	290	350	380	Ω max	V_S = 3.5 V, I_S = −1 mA; see Figure 14
On-Resistance Match Between Channels, ΔR_{ON}	3			Ω typ	V_S = 3.5 V, I_S = −1 mA
	10	12	13	Ω max	V_S = 3.5 V, I_S = −1 mA
LEAKAGE CURRENTS					V_{DD} = 5.5 V
Source Off Leakage, $I_{S(OFF)}$	±0.01			nA typ	V_S = 1 V/4.5 V, V_D = 4.5 V/1 V; see Figure 15
	±0.1	±0.25	±2	nA max	V_S = 1 V/4.5 V, V_D = 4.5 V/1 V; see Figure 15
Drain Off Leakage, $I_{D(OFF)}$	±0.01			nA typ	V_S = 1 V/4.5 V, V_D = 4.5 V/1 V; see Figure 15
	±0.1	±0.25	±2	nA max	V_S = 1 V/4.5 V, V_D = 4.5 V/1 V; see Figure 15
Channel On Leakage, $I_{D(ON)}$, $I_{S(ON)}$	±0.01			nA typ	V_S = V_D = 1 V or 4.5 V; see Figure 16
	±0.1	±0.25	±6	nA max	V_S = V_D = 1 V or 4.5 V; see Figure 16
DIGITAL INPUTS					
Input High Voltage, V_{INH}			2.4	V min	
Input Low Voltage, V_{INL}			0.8	V max	
Input Current, I_{INL} or I_{INH}	0.005			μA typ	V_{IN} = V_{INL} or V_{INH}
			±0.1	μA max	V_{IN} = V_{INL} or V_{INH}
Digital Input Capacitance, C_{IN}	2			pF typ	
DYNAMIC CHARACTERISTICS[2]					
t_{ON}	70			ns typ	R_L = 300 Ω, C_L = 35 pF, V_S = 3.0 V; see Figure 17
	100	130	150	ns max	R_L = 300 Ω, C_L = 35 pF, V_S = 3.0 V; see Figure 17
t_{OFF}	25			ns typ	R_L = 300 Ω, C_L = 35 pF, V_S = 3.0 V; see Figure 17
	40	45	50	ns max	R_L = 300 Ω, C_L = 35 pF, V_S = 3.0 V; see Figure 17
Break-Before-Make Time Delay, t_{BBM}	25			ns typ	R_L = 300 Ω, C_L = 35 pF, V_{S1} = V_{S2} = 3.0 V; see Figure 18
			10	ns min	R_L = 300 Ω, C_L = 35 pF, V_{S1} = V_{S2} = 3.0 V; see Figure 18
Charge Injection	1			pC typ	V_S = 0 V, R_S = 0 Ω, C_L = 1 nF; see Figure 19
Off Isolation	−62			dB typ	R_L = 50 Ω, C_L = 5 pF, f = 10 MHz; see Figure 20
Channel-to-Channel Crosstalk	−90			dB typ	R_L = 50 Ω, C_L = 5 pF, f = 10 MHz; see Figure 21
−3 dB Bandwidth	680			MHz typ	R_L = 50 Ω, C_L = 5 pF; see Figure 22
$C_{S(OFF)}$	5			pF typ	f = 1 MHz
$C_{D(OFF)}$	5			pF typ	f = 1 MHz
$C_{D(ON)}$, $C_{S(ON)}$	5			pF typ	f = 1 MHz
POWER REQUIREMENTS					V_{DD} = 5.5 V
I_{DD}	0.001			μA typ	Digital inputs = 0 V or 5.5 V
			1.0	μA max	Digital inputs = 0 V or 5.5 V

[1] The temperature range for the Y version is −40°C to +125°C.
[2] Guaranteed by design; not subject to production test.

V_{DD} = 3 V ± 10%, V_{SS} = 0 V, GND = 0 V, unless otherwise noted.

Table 3.

Parameter	+25°C	−40°C to +85°C	−40°C to +125°C[1]	Unit	Test Conditions/Comments
ANALOG SWITCH					
Analog Signal Range			0 to V_{DD}	V	
On Resistance, R_{ON}	380	420	460	Ω typ	V_S = 1.5 V, I_S = −1 mA; see Figure 14
LEAKAGE CURRENTS					V_{DD} = 3.3 V
Source Off Leakage, $I_{S(OFF)}$	±0.01			nA typ	V_S = 1 V/3 V, V_D = 3 V/1 V; see Figure 15
	±0.1	±0.25	± 2	nA max	V_S = 1 V/3 V, V_D = 3 V/1 V; see Figure 15
Drain Off Leakage, $I_{D(OFF)}$	±0.01			nA typ	V_S = 1 V/3 V, V_D = 3 V/1 V; see Figure 15
	±0.1	±0.25	±2	nA max	V_S = 1 V/3 V, V_D = 3 V/1 V; see Figure 15
Channel On Leakage, $I_{D(ON)}$, $I_{S(ON)}$	±0.01			nA typ	V_S = V_D = 1 V or 3 V; see Figure 16
	±0.1	±0.25	±6	nA max	V_S = V_D = 1 V or 3 V; see Figure 16
DIGITAL INPUTS					
Input High Voltage, V_{INH}			2.0	V min	
Input Low Voltage, V_{INL}			0.8	V max	
Input Current, I_{INL} or I_{INH}	0.005			μA typ	V_{IN} = V_{INL} or V_{INH}
			±0.1	μA max	V_{IN} = V_{INL} or V_{INH}
Digital Input Capacitance, C_{IN}	2			pF typ	
DYNAMIC CHARACTERISTICS[2]					
t_{ON}	130			ns typ	R_L = 300 Ω, C_L = 35 pF, V_S = 2 V; see Figure 17
	185	230	260	ns max	R_L = 300 Ω, C_L = 35 pF, V_S = 2 V; see Figure 17
t_{OFF}	40			ns typ	R_L = 300 Ω, C_L = 35 pF, V_S = 2 V; see Figure 17
	55	60	65	ns max	R_L = 300 Ω, C_L = 35 pF, V_S = 2 V; see Figure 17
Break-Before-Make Time Delay, t_{BBM}	50			ns typ	R_L = 300 Ω, C_L = 35 pF, V_{S1} = V_{S2} = 2 V; see Figure 18
			10	ns min	R_L = 300 Ω, C_L = 35 pF, V_{S1} = V_{S2} = 2 V; see Figure 18
Charge Injection	1.5			pC typ	V_S = 0 V, R_S = 0 Ω, C_L = 1 nF; see Figure 19
Off Isolation	−62			dB typ	R_L = 50 Ω, C_L = 5 pF, f = 10 MHz; see Figure 20
Channel-to-Channel Crosstalk	−90			dB typ	R_L = 50 Ω, C_L = 5 pF, f = 10 MHz; see Figure 21
−3 dB Bandwidth	680			MHz typ	R_L = 50 Ω, C_L = 5 pF; see Figure 22
$C_{S(OFF)}$	5			pF typ	f = 1 MHz
$C_{D(OFF)}$	5			pF typ	f = 1 MHz
$C_{D(ON)}$, $C_{S(ON)}$	5			pF typ	f = 1 MHz
POWER REQUIREMENTS					V_{DD} = 3.3 V
I_{DD}	0.001			μA typ	Digital inputs = 0 V or 3.3 V
			1.0	μA max	Digital inputs = 0 V or 3.3 V

[1] The temperature range for the Y version is −40°C to +125°C.
[2] Guaranteed by design; not subject to production test.

ABSOLUTE MAXIMUM RATINGS

T_A = 25°C, unless otherwise noted

Table 4.

Parameter	Rating
V_{DD} to V_{SS}	13 V
V_{DD} to GND	−0.3 V to +6.5 V
V_{SS} to GND	+0.3 V to −6.5 V
Analog Inputs[1]	V_{SS} − 0.3 V to V_{DD} + 0.3 V
Digital Inputs[1]	GND − 0.3 V to V_{DD} + 0.3 V or 30 mA, whichever occurs first
Peak Current, S or D	20 mA (pulsed at 1 ms, 10% duty cycle maximum)
Continuous Current, S or D	10 mA
3 V operation 85°C to 125°C	7.5 mA
Operating Temperature Range	
Automotive (Y Version)	−40°C to +125°C
Storage Temperature Range	−65°C to +150°C
Junction Temperature	150°C
θ_{JA} Thermal Impedance	
16-Lead TSSOP	150.4°C/W
16-Lead SOIC, 4-Layer Board	80.6°C/W
Lead Soldering	
Lead Temperature, Soldering (10 sec)	300°C
IR Reflow, Peak Temperature (<20 sec)	220°C
(Pb-Free) Soldering	
Reflow, Peak Temperature	260(+0/−5)°C
Time at Peak Temperature	20 sec to 40 sec

[1]Overvoltages at IN, S, or D are clamped by internal diodes. The current should be limited to the maximum ratings given.

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Only one absolute maximum rating can be applied at any one time.

ESD CAUTION

ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

PIN CONFIGURATION AND FUNCTION DESCRIPTIONS



Figure 2. Pin Configuration

Table 5. Pin Function Descriptions

Pin No.	Mnemonic	Description
1	IN1	Switch 1 Digital Control Input.
2	D1	Drain Terminal of Switch 1. Can be an input or output.
3	S1	Source Terminal of Switch 1. Can be an input or output.
4	V_{SS}	Most Negative Power Supply Terminal. Tie this pin to GND when using the device with single-supply voltages.
5	GND	Ground (0 V) Reference.
6	S4	Source Terminal of Switch 4. Can be an input or output.
7	D4	Drain Terminal of Switch 4. Can be an input or output.
8	IN4	Switch 4 Digital Control Input.
9	IN3	Switch 3 Digital Control Input.
10	D3	Drain Terminal of Switch 3. Can be an input or output.
11	S3	Source Terminal of Switch 3. Can be an input or output.
12	NC	Not Internally Connected.
13	V_{DD}	Most Positive Power Supply Terminal.
14	S2	Source Terminal of Switch 2. Can be an input or output.
15	D2	Drain Terminal of Switch 2. Can be an input or output.
16	IN2	Switch 2 Digital Control Input.

Table 6. ADG611/ADG612 Truth Table

ADG611 Input	ADG612 Input	Switch Condition
0	1	On
1	0	Off

Table 7. ADG613 Truth Table

Logic	Switch 1, Switch 4	Switch 2, Switch 3
0	Off	On
1	On	Off

TYPICAL PERFORMANCE CHARACTERISTICS



Figure 3. On Resistance vs. V_D (V_S), Dual Supplies



Figure 6. On Resistance vs. V_D (V_S) for Various Temperatures, Single Supply



Figure 4. On Resistance vs. V_D (V_S), Single Supply



Figure 7. Leakage Current vs. Temperature, Dual Supplies



Figure 5. On Resistance vs. V_D (V_S) for Various Temperatures, Dual Supplies



Figure 8. Leakage Current vs. Temperature, Single Supply



Figure 9. Charge Injection vs. Source Voltage



Figure 12. Off Isolation vs. Frequency



Figure 10. t_{ON}/t_{OFF} Times vs. Temperature



Figure 13. Crosstalk vs. Frequency



Figure 11. On Response vs. Frequency

TERMINOLOGY

V_{DD}
Most positive power supply potential.

V_{SS}
Most negative power supply potential.

I_{DD}
Positive supply current.

I_{SS}
Negative supply current.

GND
Ground (0 V) reference.

S
Source terminal. Can be an input or output.

D
Drain terminal. Can be an input or output.

IN
Logic control input.

V_D (V_S)
Analog voltage on Terminal D and Terminal S.

R_{ON}
Ohmic resistance between Terminal D and Terminal S.

ΔR_{ON}
On-resistance match between any two channels, that is, $R_{ONMAX} - R_{ONMIN}$.

$R_{FLAT(ON)}$
Flatness is defined as the difference between the maximum and minimum value of on resistance as measured over the specified analog signal range.

$I_{S(OFF)}$
Source leakage current with the switch off.

$I_{D(OFF)}$
Drain leakage current with the switch off.

$I_{D(ON)}$, $I_{S(ON)}$
Channel leakage current with the switch on.

V_{INL}
Maximum input voltage for Logic 0.

V_{INH}
Minimum input voltage for Logic 1.

I_{INL}, I_{INH}
Input current of the digital input.

$C_{S(OFF)}$
Off switch source capacitance. Measured with reference to ground.

$C_{D(OFF)}$
Off switch drain capacitance. Measured with reference to ground.

$C_{D(ON)}$, $C_{S(ON)}$
On switch capacitance. Measured with reference to ground.

C_{IN}
Digital input capacitance.

t_{ON}
Delay between applying the digital control input and the output switching on (see Figure 17).

t_{OFF}
Delay between applying the digital control input and the output switching off (see Figure 17).

Charge Injection
A measure of the glitch impulse transferred from the digital input to the analog output during switching.

Off Isolation
A measure of unwanted signal coupling through an off switch.

Crosstalk
A measure of unwanted signal that is coupled through from one channel to another as a result of parasitic capacitance.

On Response
Frequency response of the on switch.

Insertion Loss
Loss due to the on resistance of the switch.

TEST CIRCUITS



Figure 14. On Resistance



Figure 15. Off Leakage



Figure 16. On Leakage



Figure 17. Switching Times



Figure 18. Break-Before-Make Time Delay



Figure 19. Charge Injection



Figure 20. Off Isolation



Figure 22. Bandwidth



Figure 21. Channel-to-Channel Crosstalk

APPLICATIONS INFORMATION

Figure 23 illustrates a photodetector circuit with programmable gain. With the resistor values shown in this figure, gains in the range of 2 to 16 can be achieved by using different combinations of switches.



Figure 23. Photodetector Circuit with Programmable Gain

OUTLINE DIMENSIONS



Figure 24. 16-Lead Thin Shrink Small Outline Package [TSSOP]
(RU-16)
Dimensions shown in millimeters



Figure 25. 16-Lead Standard Small Outline Package [SOIC_N]
Narrow Body
(R-16)
Dimensions shown in millimeters and (inches)

ORDERING GUIDE

Model	Temperature Range	Package Description	Package Option
ADG611YRUZ[1]	−40°C to +125°C	16-Lead Thin Shrink Small Outline Package [TSSOP]	RU-16
ADG611YRUZ-REEL[1]	−40°C to +125°C	16-Lead Thin Shrink Small Outline Package [TSSOP]	RU-16
ADG611YRUZ-REEL7[1]	−40°C to +125°C	16-Lead Thin Shrink Small Outline Package [TSSOP]	RU-16
ADG611YRZ[1]	−40°C to +125°C	16-Lead Standard Small Outline Package [SOIC_N]	R-16
ADG612YRUZ[1]	−40°C to +125°C	16-Lead Thin Shrink Small Outline Package [TSSOP]	RU-16
ADG612YRUZ-REEL[1]	−40°C to +125°C	16-Lead Thin Shrink Small Outline Package [TSSOP]	RU-16
ADG612YRUZ-REEL7[1]	−40°C to +125°C	16-Lead Thin Shrink Small Outline Package [TSSOP]	RU-16
ADG612WRUZ-REEL[1]	−40°C to +125°C	16-Lead Thin Shrink Small Outline Package [TSSOP]	RU-16
ADG613YRUZ[1]	−40°C to +125°C	16-Lead Thin Shrink Small Outline Package [TSSOP]	RU-16
ADG613YRUZ-REEL[1]	−40°C to +125°C	16-Lead Thin Shrink Small Outline Package [TSSOP]	RU-16
ADG613YRUZ-REEL7[1]	−40°C to +125°C	16-Lead Thin Shrink Small Outline Package [TSSOP]	RU-16

[1] Z = RoHS Compliant Part.

NOTES

NOTES

©2002–2009 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners.
D02753-0-11/09(A)

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9