

Request a Sample

Customer Specification PART NO. 7602F

Construction

Constructi	<u> </u>				
				Diameters (In)	
1) Component 1		1 X 4 PAIR			
a) Conductor		24 (7/32) AWG Copper Alloy		0.024	
b) Insulation		0.011" Wall, Nom. Polyplefin(PO)		0.046	
(1) Color(s)					
Pair	Color	Pair	Color	Pair	Color
1	BLUE - WHITE/BLUE	3	GREEN - WHITE/GREEN		
2	ORANGE - WHITE/ORANGE	4	BROWN - WHITE/BROWN		
c) Pair		2/Cond Cabled Together			
(1) Twists:		13.7 Twists/foot (approx.)			
d) Cabling		4 PAIR Cabled			
(1) Twists:		3.0 Twists/foot (min)			
e) Jacket		0.020" Wall, Nom.,TPE		0.254 (0.268 Max.)	
(1) Color(s)		WHITE			
2) Shield:		Alum/Mylar Tape, 25% Overlap, Min.			
a) Foil Direction		Foil Facing Out			
b) Braid		Tinned Copper,85% Coverage, Min.			
3) Jacket		0.030" Wall, Nom.,TPE		0.342 (0.364 Max.)	
a) Color(s)		BLACK			
b) Ripcord		1300 1/E NATURAL POLYESTER			
c) Print		ALPHA WIRE-* P/N 7602F 4PR 24 AWG CONTINUOUS FLEX INDUSTRIAL ETHERNET (UL) C(UL) TYPE CM 75C FT1 ANSI/TIA-568-C.2 CAT5E PATCH VERIFIED CE ROHS (SEQ FOOTAGE) * = Factory Code [Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]			

Applicable Specifications

1) UL	VW-1		
	AWM/STYLE 20626	80°C / 300 V _{RMS}	
2) CSA International	C(UL) FT1		
3) Other	ISO/IEC 11801 Category 5e Patch Cable		
	ICEA 661 Category 5 Patch		
	NEMA WC-63.1 Category 5e Patch		
4) CE:	EU Low Voltage Directive 2006/95/EC		

Environmental

1) CE: EU Directive 2011/65/EU(RoHS2):				
	This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011. No Exemptions are required for RoHS Compliance on this item. Consult Alpha Wire's web site for RoHS C of C.			
2) REACH Regulation (EC 1907/2006):				
	This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration.			
3) California Proposition 65:	The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.			

Properties

Physical & Mechanical Properties			
1) Temperature Range	-40 to 80°C(static), -10 to 80°C (dynamic)		
2) Bend Radius	8X Cable Diameter(static), 10X Cable Diameter(dynamic)		
3) Pull Tension	40 Lbs, Maximum		
4) Sunlight Resistance	Yes		
5) Cable Weight	60 Lbs/1000Ft		
6) Flex Life	10,000,000 Cycles		
Electrical Properties	(For Engineering purposes only)		
1) Voltage Rating	300 V _{RMS}		
2) Characteristic Impedance	100 Ω +/- 15		
3) Mutual Capacitance	15 pf/ft		
4) Velocity of Propagation	69 %		
5) Conductor DCR	11 Ω/100m Max		
6) Skew	45 NS/100m Max		
7) Pair to Ground Unbalance	330 pf/100m Max		
8) DC Unbalance of a Pair	5% Max		
9) Insertion Loss	2.5 (Max dB/100m) @ 1 MHz		
	4.9 (Max dB/100m) @ 4 MHz		
	6.9 (Max dB/100m) @ 8 MHz		
	7.8 (Max dB/100m) @ 10 MHz		
	9.9 (Max dB/100m) @ 16 MHz		
	11.1 (Max dB/100m) @ 20 MHz		
	12.5 (Max dB/100m) @ 25 MHz		
	14.1 (Max dB/100m) @ 31.25 MHz		
	20.4 (Max dB/100m) @ 62.5 MHz		
	26.4 (Max dB/100m) @ 100 MHz		

Other

Packaging	Flange x Traverse x Barrel (inches)
a) 1000 FT	18 x 12 x 8 Continuous length
b) 500 FT	16 x 11 x 8 Continuous length
	[Spool dimensions may vary slightly]

www.alphawire.com

Alpha Wire | 711 Lidgerwood Avenue, Elizabeth, NJ 07207 Tel: 1-800-52 ALPHA (25742)

Although Alpha Wire ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha had been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE - CONFIDENTIAL AND PROPRIETARY

Notice to persons receiving this document and/or technical information. This document is confidential and is the exclusive property of ALPHA WIRE, and is merely on loan and subject to recall by ALPHA WIRE at any time. By taking possession of this document, the recipient acknowledges and agrees that this document cannot be used in any manner adverse to the interests of ALPHA WIRE, and that no portion of this document may be copied or otherwise reproduced without the prior written consent of ALPHA WIRE. In the case of conflicting contractual provisions, this notice shall govern the status of this document. ©2013 ALPHA WIRE - all rights reserved.



EU/China ROHS CERTIFICATE OF COMPLIANCE

To Whom It May Concern:

Alpha Wire Part Number: 7602F

7602F, RoHS-Compliant Commencing With 9/30/2013 Production

This document certifies that the Alpha part number cited above is manufactured in accordance with Directive 2011/65/EU of the European Parliament, better known as the RoHS Directive, with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. The reader is referred to this Directive for the specific definitions and extents of this Directive. **No Exemptions are required for RoHS Compliance on this item**. Additionally, Alpha certifies that the listed part number is in compliance with China RoHS "Marking for Control of Pollution by Electronic Information Products" standard SJ/T 11364-2006.

 Substance
 Maximum Control Value

 Lead
 0.1% by weight (1000 ppm)

 Mercury
 0.1% by weight (1000 ppm)

 Cadmium
 0.01% by weight (100 ppm)

 Hexavalent Chromium
 0.1% by weight (1000 ppm)

Polybrominated Diphenyl Ethers (PBDE),

Polybrominated Biphenyls (PBB)

Including Deca-BDE 0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

0.1% by weight (1000 ppm)

Authorized Signatory for the Alpha Wire Company:

Dave Watson, Director of Engineering & QA

Alpha Wire

711 Lidgerwood Ave. Elizabeth, NJ 07207 Tel: 1-908-925-8000 6/11/2016

ПОСТАВКА ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

многоканальный

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru_6 moschip.ru 4 moschip.ru 9