

### Description

GM7230 series is designed to provide all the active function for a step-down (buck) switching regulator, and drives a maximum load current as high as 3A line and load regulations. GM7230 is available in fixed output voltages of 3.3V, 5V, and a versatile Adjustable output version.

These regulators are simple to use and require minimum number of external components. The features include internal frequency compensation and a fixed-frequency oscillator.

The GM7230 is high-efficiency replacements for popular three-terminal linear regulators, and is requiring a smaller heat sink or even no need heat sink.

GM7230 performs well with standard inductors from most of manufacturers, and simplifying the design of switch-mode power supplies. External shutdown is included with 80  $\mu$ A (typical) standby current. The output switch has cycle-by-cycle current limiting as well as thermal shutdown for full protection under fault conditions.

GM7230 operates at a switching frequency of 150 kHz which allowing smaller size filter components than what would be needed with lower frequency switching regulators.

GM7230 series are available in a standard 5-lead TO-220, TO220B and TO263 packages.

### Features

- ◆ 3.3V, 5V, 12V and Adjustable output versions
- ◆ Adjustable version output voltage range 1.23V to 37V
- ◆  $V_{OUT}$  accuracy is to  $\pm 2\%$  under specified input voltage the output load conditions
- ◆ Input voltage range up to 40V
- ◆ Requires only 4 external components with High efficiency
- ◆ TTL shutdown capability, low power standby mode
- ◆ Built-in thermal shutdown, current limit protection
- ◆ Uses standard inductors
- ◆ 150 kHz fixed frequency internal oscillator

### Application

Pre-regulator for linear regulators


High-efficiency step-down buck regulator

On-card/board switching regulators


Positive to negative converter (buck-boost)

LCD Monitors

### Typical Application Circuits




### Marking Information and Pin Configurations (Top View)



G: Green Product  
 VV: Voltage suffix (15 = 1.5V, 50 = 5.0V...A = Adj)  
 A: Assembly / Test site code  
 Y: Year  
 WW: Week

### Marking Information and Pin Configurations – Green Products (Top View)



G: Green Product  
 VV: Voltage suffix (15 = 1.5V, 50 = 5.0V...A = Adj)  
 A: Assembly / Test site code  
 Y: Year  
 WW: Week

### Ordering Information – Pb Free Products

| Ordering Number | Output Voltage | Package   | Shipping         |
|-----------------|----------------|-----------|------------------|
| GM7230-ATA5T    | Adj            | TO-263-5  | 50 Units / Tube  |
| GM7230-ATA5R    |                | TO-263-5  | 800 Units / Reel |
| GM7230-ATB5T    |                | TO-220-5  | 50 Units / Tube  |
| GM7230-ATB5BT   |                | TO-220-5B | 50 Units / Tube  |
| GM7230-3.3TA5T  | 3.3            | TO-263-5  | 50 Units / Tube  |
| GM7230-3.3TA5R  |                | TO-263-5  | 800 Units / Reel |
| GM7230-3.3TB5T  |                | TO-220-5  | 50 Units / Tube  |
| GM7230-3.3TB5BT |                | TO-220-5B | 50 Units / Tube  |
| GM7230-5.0TA5T  | 5.0            | TO-263-5  | 50 Units / Tube  |
| GM7230-5.0TA5R  |                | TO-263-5  | 800 Units / Reel |
| GM7230-5.0TB5T  |                | TO-220-5  | 50 Units / Tube  |
| GM7230-12TB5BT  |                | TO-220-5B | 50 Units / Tube  |
| GM7230-12TA5T   | 12             | TO-263-5  | 50 Units / Tube  |
| GM7230-12TA5R   |                | TO-263-5  | 800 Units / Reel |
| GM7230-12TB5T   |                | TO-220-5  | 50 Units / Tube  |
| GM7230-12TB5BT  |                | TO-220-5B | 50 Units / Tube  |


### Ordering Information – Green Products

| Ordering Number  | Output Voltage | Package   | Shipping         |
|------------------|----------------|-----------|------------------|
| GM7230-ATA5TG    | Adj            | TO-263-5  | 50 Units / Tube  |
| GM7230-ATA5RG    |                | TO-263-5  | 800 Units / Reel |
| GM7230-ATB5TG    |                | TO-220-5  | 50 Units / Tube  |
| GM7230-ATB5BTG   |                | TO-220-5B | 50 Units / Tube  |
| GM7230-3.3TA5TG  | 3.3            | TO-263-5  | 50 Units / Tube  |
| GM7230-3.3TA5RG  |                | TO-263-5  | 800 Units / Reel |
| GM7230-3.3TB5TG  |                | TO-220-5  | 50 Units / Tube  |
| GM7230-3.3TB5BTG |                | TO-220-5B | 50 Units / Tube  |
| GM7230-5.0TA5TG  | 5.0            | TO-263-5  | 50 Units / Tube  |
| GM7230-5.0TA5RG  |                | TO-263-5  | 800 Units / Reel |
| GM7230-5.0TB5TG  |                | TO-220-5  | 50 Units / Tube  |
| GM7230-12TB5BTG  |                | TO-220-5B | 50 Units / Tube  |
| GM7230-12TA5TG   | 12             | TO-263-5  | 50 Units / Tube  |
| GM7230-12TA5RG   |                | TO-263-5  | 800 Units / Reel |
| GM7230-12TB5TG   |                | TO-220-5  | 50 Units / Tube  |
| GM7230-12TB5BTG  |                | TO-220-5B | 50 Units / Tube  |

### Absolute Maximum Ratings (Note 1)

| Rating                                                                                                                                           | Value                 | Unit                        |
|--------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------------|
| Maximum Supply Voltage                                                                                                                           | 45                    | V                           |
| SD Pin Input Voltage / Feed Back Pin Voltage                                                                                                     | $-0.3 + V_{IN} + 0.3$ | V                           |
| Output Voltage to Ground (Steady State)                                                                                                          | $-0.3 + V_{IN} + 0.3$ | V                           |
| Power Dissipation                                                                                                                                | Internally Limited    | -                           |
| Thermal Resistance – Junction to Ambient ( $\theta_{JA}$ )<br>** 2 square inch of FR-4, double sided, 1oz. minimum copper weight, is recommended | 36                    | $^{\circ}\text{C}/\text{W}$ |
| Storage Temperature Range                                                                                                                        | - 65 to 150           | $^{\circ}\text{C}$          |
| Maximum Junction Temperature                                                                                                                     | + 150                 | $^{\circ}\text{C}$          |
| Operating Temperature Range                                                                                                                      | - 40 to 125           | $^{\circ}\text{C}$          |
| Minimum EDS Rating (Note 2)                                                                                                                      | 2                     | kV                          |
| Lead Temperature (Soldering, 10 sec)                                                                                                             | + 260                 | $^{\circ}\text{C}$          |

### Block Diagram



### Electrical Characteristics: GM7230-ADJ

(Specifications with standard type face are for T = 25°C, and those with bold face type apply over full Operating Temperature rage)

| Parameter      | Condition                                                             | Symbol    | Min          | Typ   | Max          | Unit |
|----------------|-----------------------------------------------------------------------|-----------|--------------|-------|--------------|------|
| Output Voltage | $4.5V \leq V_{IN} \leq 40V, 0.2A \leq I_{LOAD} \leq 3A, V_{OUT} = 3V$ | $V_{OUT}$ | 1.193        | 1.230 | 1.267        | V    |
|                |                                                                       |           | <b>1.180</b> |       | <b>1.280</b> |      |
| Efficiency     | $V_{IN} = 12V, I_{LOAD} = 2.0A, V_{OUT} = 3V$                         | $\eta$    |              | 73    |              | %    |

### Electrical Characteristics: GM7230-3.3

(Specifications with standard type face are for T = 25°C, and those with bold face type apply over full Operating Temperature rage)

| Parameter      | Condition                                                | Symbol    | Min          | Typ   | Max          | Unit |
|----------------|----------------------------------------------------------|-----------|--------------|-------|--------------|------|
| Output Voltage | $4.75V \leq V_{IN} \leq 40V, 0.2A \leq I_{LOAD} \leq 3A$ | $V_{OUT}$ | 3.168        | 3.300 | 3.432        | V    |
|                |                                                          |           | <b>3.135</b> |       | <b>3.465</b> |      |
| Efficiency     | $V_{IN} = 12V, I_{LOAD} = 2.0A$                          | $\eta$    |              | 73    |              | %    |

### Electrical Characteristics: GM7230-5.0

(Specifications with standard type face are for T = 25°C, and those with bold face type apply over full Operating Temperature rage)

| Parameter      | Condition                                             | Symbol    | Min           | Typ   | Max          | Unit |
|----------------|-------------------------------------------------------|-----------|---------------|-------|--------------|------|
| Output Voltage | $7V \leq V_{IN} \leq 40V, 0.2A \leq I_{LOAD} \leq 3A$ | $V_{OUT}$ | 4.800         | 5.000 | 5.200        | V    |
|                |                                                       |           | <b>4.7500</b> |       | <b>5.250</b> |      |
| Efficiency     | $V_{IN} = 12V, I_{LOAD} = 2.0A$                       | $\eta$    |               | 80    |              | %    |

### Electrical Characteristics: GM7230-12

(Specifications with standard type face are for T = 25°C, and those with bold face type apply over full Operating Temperature rage)

| Parameter      | Condition                                              | Symbol    | Min          | Typ   | Max          | Unit |
|----------------|--------------------------------------------------------|-----------|--------------|-------|--------------|------|
| Output Voltage | $15V \leq V_{IN} \leq 40V, 0.5A \leq I_{LOAD} \leq 3A$ | $V_{OUT}$ | 11.52        | 12.00 | 12.48        | V    |
|                |                                                        |           | <b>11.40</b> |       | <b>12.60</b> |      |
| Efficiency     | $V_{IN} = 15V, I_{LOAD} = 3.0A$                        | $\eta$    |              | 88    |              | %    |

### Electrical Characteristics: All Output Voltage Versions

(Specifications with standard type face are for  $T_J = 25^\circ\text{C}$ , and those with bold type face apply over full Operating Temperature range. Unless otherwise specified,  $V_{IN} = 12\text{V}$  for 3.3V, 5V, and Adjustable version, and  $V_{IN} = 24\text{V}$  for 12V version,  $I_{LOAD} = 500\text{mA}$ )

| Parameter                 | Condition                                        | Symbol     | Min        | Typ  | Max        | Unit          |
|---------------------------|--------------------------------------------------|------------|------------|------|------------|---------------|
| Feedback Bias Current     | $V_{FB} = 1.3\text{V}$ (Adjustable Version Only) | $I_b$      | -          | 10   | 50         | nA            |
|                           |                                                  |            |            |      | <b>100</b> |               |
| Oscillator Frequency      | (Note 6)                                         | $f_o$      | 127        | 150  | 173        | kHz           |
|                           |                                                  |            | <b>110</b> |      | <b>173</b> |               |
| Saturation Voltage        | $I_{OUT} = 3\text{A}$ (Notes 7, 8)               | $V_{SAT}$  | -          | 1.16 | 1.4        | V             |
|                           |                                                  |            |            |      | <b>1.5</b> |               |
| Max Duty Cycle (ON)       | (Note 8)                                         | DC         |            | 100  | -          | %             |
| Min Duty Cycle (OFF)      | (Note 9)                                         | DC         |            | 0    |            | %             |
| Current Limit             | Peak Current (Notes 7, 8)                        | $I_{CL}$   | 3.4        |      |            | A             |
| Output Leakage Current    | Output = 0V (Notes 7, 9, 10)                     | $I_L$      | -          | -    | 100        | $\mu\text{A}$ |
|                           | Output = -0.9V (Note 10)                         |            | -          | 2    | -          | mA            |
| Quiescent Current         | (Note 9)                                         | $I_Q$      | -          | 5    | -          | mA            |
| Standby Quiescent Current | SD Pin = 5V (OFF), Note 10                       | $I_{STBY}$ | -          | 70   | 200        | $\mu\text{A}$ |
| SD Pin Logic Input Level  | Low (ON)                                         | $V_{IH}$   | -          | 1.3  | 0.6        | V             |
|                           | High (OFF)                                       | $V_{IL}$   | 2.0        | 1.3  | -          |               |
| SD Pin Input Current      | $V_{LOGIC} = 2.5\text{V}$ (OFF)                  | $I_H$      |            | 5    | 15         | $\mu\text{A}$ |
|                           | $V_{LOGIC} = 0.5\text{V}$ (ON)                   | $I_L$      |            | 0.02 | 5          | $\mu\text{A}$ |

**Note 1:** Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is intended to be functional, but do not guarantee specific performance limits. For guaranteed specifications and test conditions, see the Electrical Characteristics.

**Note 2:** The human body model is a 100pF capacitor discharged through a 1.5K $\Omega$  resistor into each pin.

**Note 3:** Typical numbers are at  $25^\circ\text{C}$  and represent the most likely norm.

**Note 4:** All limits guaranteed at room temperature (standard type face) and at temperature extremes (bold type face). All room temperature limits are 100% production tested. All limits at temperature extremes are guaranteed via correlation using standard Statistical Quality Control (SQC) methods. All limits are used to calculate Average Outgoing Quality Level (AOQL).

**Note 5:** External components such as the catch diode, inductor, input and output capacitors, and voltage programming resistors can affect switching regulator system performance. When the GM7230 is used as shown in the Figure 1 test circuit, system performance will be as shown in system parameters section of Electrical Characteristics.

**Note 6:** The switching frequency is reduced when the second stage current limit is activated.


**Note 7:** No diode, inductor or capacitor connected to output pin.

**Note 8:** Feedback pin removed from output and connected to 0V to force the output transistor switch ON.

**Note 9:** Feedback pin removed from output and connected to 12V for the 3.3V, 5V, and the ADJ. version.


### Test Circuit and Layout Guidelines

Careful layout is important with any switching regulators. Rapidly switching currents associated with wiring inductance generate voltage transients which can cause problems. To minimize inductance and ground loops, the lengths of the leads indicated by heavy lines in Figure 1&2 below should be kept as short as possible. Single point grounding (as indicated) or ground plane construction should be used for best results. When using the Adjustable version, place the programming resistors as close as possible to GM7230, to keep the sensitive feedback wiring short.



**Figure 1 Fixed Output Voltage Versions**

$C_{IN} = 470\mu\text{F}$ , Aluminum Electrolytic  
 $C_{OUT} = 220\mu\text{F}$ , 25V, Aluminum Electrolytic  
 $D1 = \text{Schottky, } 5\text{A}/40\text{V}$   
 $L1 = 68\mu\text{H}$



**Figure 2 Adjustable Output Voltage Versions**

$C_{IN} = 470\mu\text{F}$ , Aluminum Electrolytic  
 $C_{OUT} = 220\mu\text{F}$ , 25V, Aluminum Electrolytic  
 $D1 = \text{Schottky, } 5\text{A}/40\text{V}$   
 $L1 = 68\mu\text{H}$   
 $V_{OUT} = V_{REF} (1 + R2/R1)$

### Typical Performance Characteristics

Figure 3. Switch Saturation Voltage




Figure 4. Switch Current Limit




Figure 5. Dropout Voltage




Figure 6. Operating Quiescent Current




Figure 7. Shutdown Quiescent Current




Figure 8. Minimum Operating Supply Voltage




Figure 9. SD Pin Current (Sinking)







Figure 10. Switching Frequency




**Package Outline Dimensions – TO-263-5**



**Package Outline Dimensions – TO-220-5**



### Package Outline Dimensions – TO-220B-5



**Inches**  
**(mm)**

### Ordering Number

**GM 7230 A TA5 R G**

| APM<br>Gamma<br>Micro | Circuit<br>Type | Output<br>Voltage                                | Package Type                                     | Shipping Type               |                            |
|-----------------------|-----------------|--------------------------------------------------|--------------------------------------------------|-----------------------------|----------------------------|
|                       |                 | A: Adj<br>3.3 = 3.3V<br>5.0 = 5.0V<br>12 = 12.0V | TA5: TO263-5<br>TB5: TO-220-5<br>TB5B: TO-220B-5 | R: Taping & Reel<br>T: Tube | Blank: Pb-Free<br>G: Green |

Note:

#### Pb-free products:

- ◆ RoHS compliant and compatible with the current requirements of IPC/JEDEC J-STD-020.
- ◆ Suitable for use in Pb-free soldering processes with 100% matte tin (Sn) plating.

#### Green products:

- ◆ Lead-free (RoHS compliant)
- ◆ Halogen free (Br or Cl does not exceed 900ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500ppm by weight)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9