

SIDE ROTARY




FIGURE 1 - SIDE ROTARY HEAD WITH GLZ51 SERIES LEVER

ALUMINUM ROD
GLZ54J: 200.00 / 7.870 MAX
GLZ54K: 140.00 / 5.510 MAX
STAINLESS STEEL ROD
GLZ54N: 318.00 / 12.490 MAX




FIGURE 2 - SIDE ROTARY HEAD WITH GLZ54 SERIES LEVER OTHERWISE REFER TO FIGURE 1

FIGURE	CATALOG LISTING	CONDUIT ENTRY
1A	GL*A SERIES	1/2-14 NPT
1B	GL*B SERIES	PG13.5
1C	GL*C SERIES	20mm
1D	GL*D SERIES	PF1/2

ELECTRICAL RATING $\Delta 5$			
AC		DC	
A600 Ue	AC15 Ie	Q300 Ue	DC13 Ie
(VOLTS)	(AMPS)	(VOLTS)	(AMPS)
120	6	24	2.8
240	3	125	.55
380	1.9	250	.27
480	1.5		
500	1.4		
600	1.2		

ENVIRONMENTAL RATING
IP67
NEMA/UL TYPES 1, 4, 12, 13

NOTES

- HEADS MAY BE INDEXED IN 90° INCREMENTS.
- LEVERS MAY BE KEYED TO THE SHAFT AT 90° INCREMENTS. THEY MAY ALSO BE ATTACHED, BUT NOT KEYED ANYWHERE ON THE SHAFT.
- FOR ADDITIONAL LEVERS SEE "M" DRAWING CHART GLZ5
- THE RIGHT INDICATOR IS YELLOW AND INDICATES "OUTPUT STATUS" IT IS ON GLG SERIES PRODUCTS ONLY.
- THE MAXIMUM VOLTAGE, V_e OF GLG SERIES PRODUCTS IS THE MAXIMUM RATED VOLTAGE OF INDICATION LIGHTS
- FREE POSITION, OPERATE POINT, OVERTRAVEL AND PRETRAVEL ALL TO EN50041
- CAM TRAVEL FOR FIG 9 ONLY APPLIES WHEN LEVER IS ADJUSTED TO 38.1 / 1.50
- TEMPERATURE RANGE
(ALL PRODUCTS EXCEPT w/SIDE ROTARY OPERATING HEAD)
OPERATING: -25°C TO +85°C / -13°F TO +185°F
STORAGE: -40°C TO +85°C / -40°F TO +185°F
(PRODUCTS w/SIDE ROTARY OPERATING HEAD)
OPERATING: -40°C TO +85°C / -40°F TO +185°F
STORAGE: -40°C TO +85°C / -40°F TO +185°F





FIGURE 3 - SIDE ROTARY HEAD WITH GLZ52 SERIES LEVERS OTHERWISE REFER TO FIGURE 1

LEVER	ROLLER MATL	X DIM	Y DIM	Z DIM
GLZ52A	NYLON	19.1 .75	65.9 2.59	6.4 .25
GLZ52B	STEEL	19.1 .75	65.9 2.59	6.4 .25
GLZ52D	NYLON	38.1 1.5	65.9 2.59	6.4 .25
GLZ52E	NYLON	19.1 .75	79.37 3.125	33.07 1.300
GLZ52W	RUBBER	40.0 1.5	71.5 2.81	12.7 .5
GLZ52Y	RUBBER	50.9 2.0	71.5 2.81	12.7 .5


CATALOG LISTING	BODY DIMENSIONS, FIGURE	HEAD DIMENSIONS, FIGURE	HEAD ACTUATION, FIGURE
GLB***	I	N/A	N/A
GLG***	I	N/A	N/A
GLJ***	I	N/A	N/A
GL*A***	1A	N/A	N/A
GL*B***	1B	N/A	N/A
GL*C***	1C	N/A	N/A
GL*D***	1D	N/A	N/A
GL***A1*	I	8	
GL***A2*	I	3	9
GL***A4*	I	2	10
GL***A5*	I		8
GL***B	I	4	11
GL***C	I	5	13A, 13B
GL***D	I	6	14A, 14B
GL***E7A	I	7A	12
GL***E7B	I	7	12
GL***E7C	I	7E	12
GL***E7D	I	7B	12
GL***K8A	I	7C	15
GL***K8B	I	7D	15
GL***K8C	I	7	15

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.		CATALOG LISTING	
FED. MFG. CODE 91929		SWITCH, ENCLOSED	
MICRO SWITCH a Honeywell Division		GL SERIES CHART 2	
DESIGN UNITS		WEIGHT	

THIRD ANGLE PROJECTION			
SCALE FULL			
DO NOT SCALE PRINT			
TOLERANCES			
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE:			
NO PLACES	1/16	1/32	1/64
ONE PLACE	1/8	1/16	1/32
TWO PLACES	1/4	1/8	1/16
THREE PLACES	1/2	1/4	1/8
ANGLES	1/16	1/32	1/64
SI METRIC		US CUSTOMARY	
DESIGN UNITS		WEIGHT	



Technical drawing of a lamp head. The drawing shows a cross-section of the lamp head with a central vertical rod. Two horizontal dimension lines are present: one at the top indicating a width of 16,0, and another below it indicating a width of 4,7. The lamp head has a tiered, cylindrical shape with a small rectangular opening at the top.



THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.		<table border="1"> <tr> <td>DIM</td> <td>TOL</td> <td>DIM</td> <td>TOL</td> </tr> <tr> <td>INCHES</td> <td>FRACTIONS</td> <td>INCHES</td> <td>FRACTIONS</td> </tr> <tr> <td>NO PLACES</td> <td>0</td> <td>0.01</td> <td>0.01</td> </tr> <tr> <td>ONE PLACE</td> <td>0.4</td> <td>0.01</td> <td>0.01</td> </tr> <tr> <td>TWO PLACES</td> <td>0.004</td> <td>0.01</td> <td>0.01</td> </tr> <tr> <td>THREE PLACES</td> <td>0.0004</td> <td>0.01</td> <td>0.01</td> </tr> <tr> <td>ANGLES</td> <td>± 1</td> <td></td> <td></td> </tr> </table>		DIM	TOL	DIM	TOL	INCHES	FRACTIONS	INCHES	FRACTIONS	NO PLACES	0	0.01	0.01	ONE PLACE	0.4	0.01	0.01	TWO PLACES	0.004	0.01	0.01	THREE PLACES	0.0004	0.01	0.01	ANGLES	± 1		
DIM	TOL	DIM	TOL																												
INCHES	FRACTIONS	INCHES	FRACTIONS																												
NO PLACES	0	0.01	0.01																												
ONE PLACE	0.4	0.01	0.01																												
TWO PLACES	0.004	0.01	0.01																												
THREE PLACES	0.0004	0.01	0.01																												
ANGLES	± 1																														
FED. MFG. CODE 91929	CATALOG LISTING																														
MICRO SWITCH a Honeywell Division	SWITCH, ENCLOSED		GL SERIES CHART 2																												
			DESIGN UNITS ☒ SI METRIC ☐ US CUSTOMARY ☐																												
			WEIGHT																												









FIGURE 7 - WOBBLE HEAD, AND CAT WHISKER HEAD
COIL ACTUATOR,
OTHERWISE REFER TO
FIGURE 1

FED. MFG. CODE 91929
MICRO SWITCH
a Honeywell Division

CATALOG LISTING

GL SERIES CHART 2

THIRD ANGLE PROJECTION

FULL


DO NOT SCALE PRINT

TOLERANCES

APPLY TO DESIGN UNITS, CONVERSIONS ARE ONLY FOR REFERENCE, UNLESS NOTED, TOLERANCES ARE:

	DIM	TOL	DIM	TOL
	FRACTION	1/16, 1/8, 1/4 0.015, 0.030 0.060, 0.125 0.150, 0.300 0.375, 0.625 0.750, 1.500 1.875, 3.000 3.750, 6.000 7.500, 15.000 18.750, 30.000 37.500, 75.000 93.750, 187.500 250.000, 500.000 750.000, 1500.000 1875.000, 3750.000 4687.500, 9375.000 11718.750, 23437.500 29296.875, 58593.750 73242.1875, 146484.375 183105.46875, 366210.9375 457763.671875, 915527.34375 1144409.1796875, 2288818.359375 2861022.94921875, 5722045.8984375 7152557.373046875, 14305114.74609375 18310546.875, 36621093.75 45776367.1875, 91552734.375 114440917.96875, 228881835.9375 286102294.921875, 572204589.84375 715255737.3046875, 1430511474.609375 1831054687.5, 3662109375.0 4577636718.75, 9155273437.5 11444091796.875, 22888183593.75 28610229492.1875, 57220458984.375 71525573730.46875, 143051147460.9375 183105468750.0, 366210937500.0 457763671875.0, 915527343750.0 1144409179687.5, 2288818359375.0 2861022949218.75, 5722045898437.5 7152557373046.875, 14305114746093.75 18310546875000.0, 36621093750000.0 45776367187500.0, 91552734375000.0 114440917968750.0, 228881835937500.0 286102294921875.0, 572204589843750.0 715255737304687.5, 1430511474609375.0 1831054687500000.0, 3662109375000000.0 4577636718750000.0, 9155273437500000.0 11444091796875000.0, 22888183593750000.0 28610229492187500.0, 57220458984375000.0 71525573730468750.0, 143051147460937500.0 18310546875000000.0, 36621093750000000.0 45776367187500000.0, 91552734375000000.0 114440917968750000.0, 228881835937500000.0 286102294921875000.0, 572204589843750000.0 715255737304687500.0, 1430511474609375000.0 183105468750000000.0, 366210937500000000.0 457763671875000000.0, 915527343750000000.0 1144409179687500000.0, 2288818359375000000.0 2861022949218750000.0, 5722045898437500000.0 7152557373046875000.0, 14305114746093750000.0 1831054687500000000.0, 3662109375000000000.0 4577636718750000000.0, 9155273437500000000.0 11444091796875000000.0, 22888183593750000000.0 28610229492187500000.0, 57220458984375000000.0 71525573730468750000.0, 143051147460937500000.0 18310546875000000000.0, 36621093750000000000.0 45776367187500000000.0, 91552734375000000000.0 114440917968750000000.0, 228881835937500000000.0 286102294921875000000.0, 572204589843750000000.0 715255737304687500000.0, 1430511474609375000000.0 183105468750000000000.0, 366210937500000000000.0 457763671875000000000.0, 915527343750000000000.0 1144409179687500000000.0, 2288818359375000000000.0 2861022949218750000000.0, 5722045898437500000000.0 7152557373046875000000.0, 14305114746093750000000.0 1831054687500000000000.0, 3662109375000000000000.0 4577636718750000000000.0, 9155273437500000000000.0 11444091796875000000000.0, 22888183593750000000000.0 28610229492187500000000.0, 57220458984375000000000.0 71525573730468750000000.0, 143051147460937500000000.0 18310546875000000000000.0, 36621093750000000000000.0 45776367187500000000000.0, 91552734375000000000000.0 114440917968750000000000.0, 228881835937500000000000.0 286102294921875000000000.0, 572204589843750000000000.0 715255737304687500000000.0, 1430511474609375000000000.0 183105468750000000000000.0, 366210937500000000000000.0 457763671875000000000000.0, 915527343750000000000000.0 1144409179687500000000000.0, 2288818359375000000000000.0 2861022949218750000000000.0, 5722045898437500000000000.0 7152557373046875000000000.0, 14305114746093750000000000.0 1831054687500000000000000.0, 3662109375000000000000000.0 4577636718750000000000000.0, 9155273437500000000000000.0 11444091796875000000000000.0, 22888183593750000000000000.0 28610229492187500000000000.0, 57220458984375000000000000.0 71525573730468750000000000.0, 143051147460937500000000000.0 18310546875000000000000000.0, 36621093750000000000000000.0 45776367187500000000000000.0, 91552734375000000000000000.0 114440917968750000000000000.0, 228881835937500000000000000.0 286102294921875000000000000.0, 572204589843750000000000000.0 715255737304687500000000000.0, 1430511474609375000000000000.0 183105468750000000000000000.0, 366210937500000000000000000.0 457763671875000000000000000.0, 915527343750000000000000000.0 1144409179687500000000000000.0, 2288818359375000000000000000.0 2861022949218750000000000000.0, 5722045898437500000000000000.0 7152557373046875000000000000.0, 14305114746093750000000000000.0 1831054687500000000000000000.0, 3662109375000000000000000000.0 4577636718750000000000000000.0, 9155273437500000000000000000.0 11444091796875000000000000000.0, 22888183593750000000000000000.0 28610229492187500000000000000.0, 57220458984375000000000000000.0 71525573730468750000000000000.0, 143051147460937500000000000000.0 18310546875000000000000000000.0, 36621093750000000000000000000.0 45776367187500000000000000000.0, 91552734375000000000000000000.0 114440917968750000000000000000.0, 228881835937500000000000000000.0 286102294921875000000000000000.0, 572204589843750000000000000000.0 715255737304687500000000000000.0, 1430511474609375000000000000000.0 183105468750000000000000000000.0, 366210937500000000000000000000.0 457763671875000000000000000000.0, 915527343750000000000000000000.0 1144409179687500000000000000000.0, 2288818359375000000000000000000.0 2861022949218750000000000000000.0, 5722045898437500000000000000000.0 7152557373046875000000000000000.0, 14305114746093750000000000000000.0 1831054687500000000000000000000.0, 3662109375000000000000000000000.0 4577636718750000000000000000000.0, 9155273437500000000000000000000.0 11444091796875000000000000000000.0, 22888183593750000000000000000000.0 28610229492187500000000000000000.0, 57220458984375000000000000000000.0 71525573730468750000000000000000.0, 143051147460937500000000000000000.0 18310546875000000000000000000000.0, 36621093750000000000000000000000.0 45776367187500000000000000000000.0, 91552734375000000000000000000000.0 114440917968750000000000000000000.0, 228881835937500000000000000000000.0 286102294921875000000000000000000.0, 572204589843750000000000000000000.0 715255737304687500000000000000000.0, 1430511474609375000000000000000000.0 183105468750000000000000000000000.0, 366210937500000000000000000000000.0 457763671875000000000000000000000.0, 915527343750000000000000000000000.0 1144409179687500000000000000000000.0, 2288818359375000000000000000000000.0 2861022949218750000000000000000000.0, 5722045898437500000000000000000000.0 7152557373046875000000000000000000.0, 14305114746093750000000000000000000.0 1831054687500000000000000000000000.0, 3662109375000000000000000000000000.0 4577636718750000000000000000000000.0, 9155273437500000000000000000000000.0 11444091796875000000000000000000000.0, 22888183593750000000000000000000000.0 28610229492187500000000000000000000.0, 57220458984375000000000000000000000.0 71525573730468750000000000000000000.0, 143051147460937500000000000000000000.0 18310546875000000000000000000000000.0, 36621093750000000000000000000000000.0 45776367187500000000000000000000000.0, 91552734375000000000000000000000000.0 114440917968750000000000000000000000.0, 228881835937500000000000000000000000.0 286102294921875000000000000000000000.0, 572204589843750000000000000000000000.0 715255737304687500000000000000000000.0, 1430511474609375000000000000000000000.0 183105468750000000000000000000000000.0, 366210937500000000000000000000000000.0 457763671875000000000000000000000000.0, 91552734375000000000000000000000000.0 1144409179687500000000000000000000000.0, 228881835937500000000000000000000000.0 2861022949218750000000000000000000000.0, 572204589843750000000000000000000000.0 7152557373046875000000000000000000000.0, 1430511474609375000000000000000000000.0 1831054687500000000000000000000000000.0, 366210937500000000000000000000000000.0 4577636718750000000000000000000000000.0, 91552734375000000000000000000000000.0 11444091796875000000000000000000000000.0, 228881835937500000000000000000000000.0 28610229492187500000000000000000000000.0, 572204589843750000000000000000000000.0 71525573730468750000000000000000000000.0, 1430511474609375000000000000000000000.0 18310546875000000000000000000000000000.0, 366210937500000000000000000000000000.0 45776367187500000000000000000000000000.0, 91552734375000000000000000000000000.0 114440917968750000000000000000000000000.0, 228881835937500000000000000000000000.0 286102294921875000000000000000000000000.0, 572204589843750000000000000000000000.0 715255737304687500000000000000000000000.0, 1430511474609375000000000000000000000.0 183105468750000000000000000000000000000.0, 366210937500000000000000000000000000.0 457763671875000000000000000000000000000.0, 91552734375000000000000000000000000.0 1144409179687500000000000000000000000000.0, 228881835937500000000000000000000000.0 2861022949218750000000000000000000000000.0, 572204589843750000000000000000000000.0 7152557373046875000000000000000000000000.0, 1430511474609375000000000000000000000.0 1831054687500000000000000000000000000000.0, 366210937500000000000000000000000000.0 4577636718750000000000000000000000000000.0, 91552734375000000000000000000000000.0 11444091796875000000000000000000000000000.0, 228881835937500000000000000000000000.0 28610229492187500000000000000000000000000.0, 572204589843750000000000000000000000.0 71525573730468750000000000000000000000000.0, 1430511474609375000000000000000000000.0 18310546875000000000000000000000000000000.0, 366210937500000000000000000000000000.0 45776367187500000000000000000000000000000.0, 91552734375000000000000000000000000.0 114440917968750000000000000000000000000000.0, 228881835937500000000000000000000000.0 286102294921875000000000000000000000000000.0, 572204589843750000000000000000000000.0 715255737304687500000000000000000000000000.0, 1430511474609375000000000000000000000.0 183105468750000000000000000000000000000000.0, 366210937500000000000000000000000000.0 457763671875000000000000000000000000000000.0, 91552734375000000000000000000000000.0 1144409179687500000000000000000000000000000.0, 228881835937500000000000000000000000.0 2861022949218750000000000000000000000000000.0, 572204589843750000000000000000000000.0 7152557373046875000000000000000000000000000.0, 1430511474609375000000000000000000000.0 1831054687500000000000000000000000000000000.0, 366210937500000000000000000000000000.0 4577636718750000000000000000000000000000000.0, 91552734375000000000000000000000000.0 11444091796875000000000000000000000000000000.0, 228881835937500000000000000000000000.0 28610229492187500000000000000000000000000000.0, 572204589843750000000000000000000000.0 71525573730468750000000000000000000000000000.0, 1430511474609375000000000000000000000.0 18310546875000000000000000000000000000000000.0, 366210937500000000000000000000000000.0 45776367187500000000000000000000000000000000.0, 91552734375000000000000000000000000.0 114440917968750000000000000000000000000000000.0, 228881835937500000000000000000000000.0 286102294921875000000000000000000000000000000.0, 572204589843750000000000000000000000.0 715255737304687500000000000000000000000000000.0, 1430511474609375000000000000000000000.0 183105468750000000000000000000000000000000000.0, 366210937500000000000000000000000000.0 457763671875000000000000000000000000000000000.0, 91552734375000000000000000000000000.0 1144409179687500000000000000000000000000000000.0, 228881835937500000000000000000000000.0 2861022949218750000000000000000000000000000000.0, 572204589843750000000000000000000000.0 7152557373046875000000000000000000000000000000.0, 1430511474609375000000000000000000000.0 1831054687500000000000000000000000000000000000.0, 366210937500000000000000000000000000.0 4577636718750000000000000000000000000000000000.0, 91552734375000000000000000000000000.0 11444091796875000000000000000000000000000000000.0, 228881835937500000000000000000000000.0 28610229492187500000000000000000000000000000000.0, 572204589843750000000000000000000000.0 71525573730468750000000000000000000000000000000.0, 1430511474609375000000000000000000000.0 18310546875000000000000000000000000000000000000.0, 366210937500000000000000000000000000.0 45776367187		



CAM ACTUATION PER EN50041, FIGURES 8 AND 9 							
CATALOG LISTING	CONTACT BLOCK DIAGRAM	 NOMINAL TRAVELS AND RELATED TERMINALS  CONTACT CLOSED,  CONTACT OPEN,  CONTACT CLOSED DIFFERENTIAL TRAVEL, ** POSITIVE OPENING TO IEC 947-5 DIMENSIONS IN mm	MAXIMUM OPERATING FORCE  LB	MAXIMUM DISCONNECT FORCE  LB	MAX OPERATE VEL  $\frac{in}{s}$	MIN OPERATE VEL  $\frac{in}{s}$	MAX OPERATE FREQUENCY OPS/MIN
GL**02A*	SNAP - ACTION CONTACTS SINGLE POLE 		$\frac{9.7}{2.2}$	$\frac{11.4}{2.6}$	$\frac{.85}{33.5}$	$\frac{8.5}{.33}$	250

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.			
FED. MFG. CODE 91929		CATALOG LISTING	
MICRO SWITCH a Honeywell Division	SWITCH, ENCLOSED	GL SERIES CHART 2	
		DESIGN UNITS ☒ SI METRIC ☐ US CUSTOMARY ☐	
		WEIGHT	




FIGURE 11




FIGURE 12



FIGURES 11, PIN PLUNGER HEAD, LINEAR ACTUATION						
CATALOG LISTING	CONTACT BLOCK DIAGRAM	NOMINAL TRAVELS AND RELATED TERMINALS CONTACT CLOSED, CONTACT OPEN, CONTACT CLOSED DIFFERENTIAL TRAVEL, ** POSITIVE OPENING TO IEC 947-5-1	MAXIMUM OPERATING FORCE N LB	MAXIMUM DISCONNECT FORCE N LB	MAX OPERATE VEL M/S in/S	MIN OPERATE VEL mm/S in/S
GL**02B	SNAP - ACTION CONTACTS SINGLE POLE 	 37.5 35 33** 30.5 21-22 13-14 0.9 DIFFERENTIAL TRAVEL	16 3.6	27 6.0	0.1 3.9	1.0 .04
						250

FIGURE 12, WOBBLE HEAD, ANGULAR ACTUATION						
CATALOG LISTING	CONTACT BLOCK DIAGRAM	NOMINAL TRAVELS AND RELATED TERMINALS CONTACT CLOSED, CONTACT OPEN, CONTACT CLOSED DIFFERENTIAL TRAVEL, ** POSITIVE OPENING TO IEC 947-5-1	MAXIMUM OPERATING TORQUE m LB/in	MAXIMUM DISCONNECT TORQUE m LB/in	MAX OPERATE DEGREE/S	MIN OPERATE VELOCITY DEGREE/S
GL**02E	SNAP - ACTION CONTACTS SINGLE POLE 	 21-22 13-14 18° 8° DIFFERENTIAL TRAVEL	0.2 1.8	N/A	360	8
						100

FIGURE 12, WOBBLE HEAD, SIDE ACTUATION AT 100mm						
CATALOG LISTING	CONTACT BLOCK DIAGRAM	NOMINAL TRAVELS AND RELATED TERMINALS CONTACT CLOSED, CONTACT OPEN, CONTACT CLOSED DIFFERENTIAL TRAVEL, ** POSITIVE OPENING TO IEC 947-5-1	MAXIMUM OPERATING FORCE N LB	MAXIMUM DISCONNECT FORCE N LB	MAX OPERATE VEL M/S in/S	MIN OPERATE VEL mm/S in/S
GL**02E	SNAP - ACTION CONTACTS SINGLE POLE 	 21-22 13-14 26 12 DIFFERENTIAL TRAVEL	2.5 0.6	N/A	.5 19.7	11 .43
						100

REVISIONS		
A	CO	78529
B	CS	81101
C	CO	93188
D	CO	93188
E	CO	93188
F	CO	93188
G	CO	93188
H	CO	93188
I	CO	93188
J	CO	93188
K	CO	93188
L	CO	93188
M	CO	93188
N	CO	93188
O	CO	93188
P	CO	93188
Q	CO	93188
R	CO	93188
S	CO	93188
T	CO	93188
U	CO	93188
V	CO	93188
W	CO	93188
X	CO	93188
Y	CO	93188
Z	CO	93188

FIGURE 13A, ROLLER PLUNGER HEAD, PIN ACTUATION

CATALOG LISTING	CONTACT BLOCK DIAGRAM	NOMINAL TRAVELS AND RELATED TERMINALS CONTACT CLOSED, CONTACT OPEN, CONTACT CLOSED DIFFERENTIAL TRAVEL, ** POSITIVE OPENING TO IEC 947-5-1	MAXIMUM OPERATING FORCE N LB	MAXIMUM DISCONNECT FORCE N LB	MAX OPERATE VEL M/S in/s	MIN OPERATE VEL mm/s in/s	MAX OPERATE FREQUENCY OPS/MIN
GL**02C	SNAP - ACTION CONTACTS SINGLE POLE 	 0.9 DIFFERENTIAL TRAVEL	$\frac{16}{3.6}$	$\frac{27}{6.0}$	$\frac{0.1}{3.9}$	$\frac{1.0}{.04}$	250




FIGURE 13A







FIGURE 13B

FIGURE 13B, TOP ROLLER PLUNGER HEAD, CAM ACTUATION PER EN50041

CATALOG LISTING	CONTACT BLOCK DIAGRAM	NOMINAL TRAVELS AND RELATED TERMINALS CONTACT CLOSED, CONTACT OPEN, CONTACT CLOSED DIFFERENTIAL TRAVEL, ** POSITIVE OPENING TO IEC 947-5-1	MAXIMUM OPERATING FORCE N LB	MAXIMUM DISCONNECT FORCE N LB	MAX OPERATE VEL M/S in/s	MIN OPERATE VEL mm/s in/s	MAX OPERATE FREQUENCY OPS/MIN
GL**02C	SNAP - ACTION CONTACTS SINGLE POLE 	 1.8 DIFFERENTIAL TRAVEL	$\frac{9.3}{2.1}$	$\frac{15.6}{3.5}$	$\frac{0.17}{6.7}$	$\frac{1.7}{.067}$	250

THIRD ANGLE PROJECTION			
			
SCALE FULL			
DO NOT SCALE PRINT			
TOLERANCES APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE 1			
NO PLACES ONE PLACES TWO PLACES THREE PLACES ANGLES	SI METRIC X X.X X.XX X.XXX	TOL mm 0.04 0.01/0.05 0.15/0.06 ±Z	US CUSTOMARY X X.X X.XX X.XXX
DESIGN UNITS X			
WEIGHT			

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.		CATALOG LISTING	
FED. MFG. CODE 91929		GL SERIES CHART 2	
MICRO SWITCH a Honeywell Division		SWITCH, ENCLOSED	

REVISIONS		
A	1	180292
B	1	01
C	20	SEP 94
D	CO	93789
E	REV	200788
F	0000401	
G	011	2 JUN 93
H	0002986	
I	20	JAN 94
J	0017532	
K	0000005	

FIGURE 14A, TOP ROLLER LEVER HEAD WITH PIN ACTUATION

CATALOG LISTING	CONTACT BLOCK DIAGRAM	NOMINAL TRAVELS AND RELATED TERMINALS CONTACT CLOSED, CONTACT OPEN, CONTACT CLOSED DIFFERENTIAL TRAVEL, ** POSITIVE OPENING TO IEC 947-5-1	MAXIMUM OPERATING FORCE N LB	MAXIMUM DISCONNECT FORCE N LB	MAX OPERATE VEL M/S in/S	MIN OPERATE VEL M/S in/S	MAX OPERATE FREQUENCY OPS/MIN
GL**02D	SNAP - ACTION CONTACTS SINGLE POLE 	 1.7 DIFFERENTIAL TRAVEL	9.5 2.1	12 2.7	0.17 6.7	1.7 .067	250




FIGURE 14A


FIGURE 14B


FIGURE 14B, TOP ROLLER LEVER HEAD WITH CAM ACTUATION

CATALOG LISTING	CONTACT BLOCK DIAGRAM	NOMINAL TRAVELS AND RELATED TERMINALS CONTACT CLOSED, CONTACT OPEN, CONTACT CLOSED DIFFERENTIAL TRAVEL, ** POSITIVE OPENING TO IEC 947-5-1	MAXIMUM OPERATING FORCE N LB	MAXIMUM DISCONNECT FORCE N LB	MAX OPERATE VEL M/S in/S	MIN OPERATE VEL M/S in/S	MAX OPERATE FREQUENCY OPS/MIN
GL**02D	SNAP - ACTION CONTACTS SINGLE POLE 	 4.1 DIFFERENTIAL TRAVEL	5.5 1.2	7.0 1.6	0.29 11.4	2.9 .11	250

THIRD ANGLE PROJECTION			
SCALE FULL			
DO NOT SCALE PRINT			
TOLERANCES			
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE:			
NO PLACES	TOL	MM	TOL
ONE PLACE	0.1	0.04	0.05
TWO PLACES	0.01	0.01	0.01
THREE PLACES	0.005	0.005	0.005
ANGLES	± 2°		
SI METRIC		US CUSTOMARY	
WEIGHT			



CATALOG LISTING	CONTACT BLOCK DIAGRAM	NOMINAL TRAVELS AND RELATED TERMINALS ■ CONTACT CLOSED, □ CONTACT OPEN, ▨ DIFFERENTIAL TRAVEL	MAXIMUM OPERATING TORQUE $\frac{0-1}{.9}$ LB-IN	MAXIMUM DISCONNECT TORQUE $\frac{N-M}{LB-IN}$	MAX OPERATE DEGREE/S	MIN OPERATE VELOCITY DEGREE/S	MAX OPERATE RATE CYCLES/MIN
GL**02K	SNAP - ACTION CONTACTS SINGLE POLE 	 18° 21-22 > 13-14 < 8° DIFFERENTIAL TRAVEL	$\frac{0-1}{.9}$	N/A	360	8	100



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9