


## 901-910 SERIES CHIPSET HEAT SINKS




PIN FIN &  
ELLIPTICAL  
HEAT SINKS




Wakefield-Vette's 901-910 Series Heat Sinks for Chipset can match up to devices from Intel, Broadcom, Xilinx, TI, Motorola and many more! These heat sinks are designed for air flow applications. Enclosed pages have thermal performance data for natural forced convection values.

**4 Springs at  
each corner**



**wakefield-vette**  
**New Chip Set Heat Sinks**



Wakefield-Vette heat sink assembles onto chip set using the space that is between the PCB and the substrate of the solder balls. The solder balls provide a minimal gap of .5mm to .7mm. Attachment feature is below a .4mm thickness. The clipping system will not interfere or damage chip. Contact area is the edge of chip.



**Thermal Cooling Solutions from SMART to FINISH**

## 901-910 SERIES CHIPSET HEAT SINKS



**Material:** AL 6063

**Finish:** Black Anodize


All dimensions in millimeters (mm)



### Part Numbering System

| Series             | Chip Size        | Construction      | Height           | Spring Type *   | Finish         | Interface     |
|--------------------|------------------|-------------------|------------------|-----------------|----------------|---------------|
| <u>901-</u><br>XXX | <u>19-</u><br>XX | <u>1-</u><br>X    | <u>12-</u><br>XX | <u>1-</u><br>X  | <u>B-</u><br>X | <u>1</u><br>X |
| 901                | 19               | 1= Elliptical Fin | 12 = 11.6        | 1 = .9-2.1 CST  | B = BLK ANO    | 0 = None      |
| 902                | 21               | 2= Pin Fin        | 15 = 14.6        | 2 = 2.2-3.4 CST |                | 1 = T725      |
| 903                | 23               |                   | 18 = 17.6        |                 |                |               |
| 904                | 27               |                   | 21 = 20.6        |                 |                |               |
| 905                | 29               |                   | 23 = 22.6        |                 |                |               |
| 906                | 31               |                   | 28 = 27.6        |                 |                |               |
| 907                | 33               |                   | 33 = 32.6        |                 |                |               |
| 908                | 35               |                   |                  |                 |                |               |
| 909                | 37.5             |                   |                  |                 |                |               |
| 910                | 40               |                   |                  |                 |                |               |

\*Note: When selecting part number chip set thickness (CST) relates to spring selection!



**Thermal Cooling Solutions from SMART to FINISH**

## 901-910 SERIES CHIPSET HEAT SINKS



wakefield-vette

### THERMAL PERFORMANCE



|     | HT | CHIP SIZE | PIN FIN            |                         |          |          | ELLIPTICAL FIN     |                         |           |          |
|-----|----|-----------|--------------------|-------------------------|----------|----------|--------------------|-------------------------|-----------|----------|
|     |    |           | NATURAL CONVECTION | FORCED CONVECTION (C/W) |          |          | NATURAL CONVECTION | FORCED CONVECTION (C/W) |           |          |
|     |    |           |                    | 200 LFM                 | 400 LFM  | 600 LFM  |                    | 200 LFM                 | 400 LFM   | 600 LFM  |
| 901 | 12 | 19mm      | 12.74 C/W          | 6.6 C/W                 | 4.79 C/W | 4.16 C/W | 14.77 C/W          | 6.63 C/W                | 5.09 C/W  | 4.38 C/W |
|     | 15 | 19mm      | 12.05 C/W          | 6.3 C/W                 | 4.51 C/W | 3.86 C/W | 14 C/W             | 6.12 C/W                | 4.63 C/W  | 3.95 C/W |
|     | 18 | 19mm      | 11.35 C/W          | 5.97 C/W                | 4.16 C/W | 3.47 C/W | 13.23 C/W          | 5.67 C/W                | 4.17 C/W  | 3.58 C/W |
|     | 21 | 19mm      | 10.66 C/W          | 5.66 C/W                | 3.89 C/W | 3.21 C/W | 12.46 C/W          | 5.28 C/W                | 3.87 C/W  | 3.24 C/W |
|     | 23 | 19mm      | 10.55 C/W          | 5.36 C/W                | 3.64 C/W | 2.99 C/W | 11.98 C/W          | 4.89 C/W                | 3.58 C/W  | 3.06 C/W |
|     | 28 | 19mm      | 10.27 C/W          | 4.91 C/W                | 3.36 C/W | 2.71 C/W | 11.5 C/W           | 4.38 C/W                | 3.26 C/W  | 2.80 C/W |
| 902 | 33 | 19mm      | 9.99 C/W           | 4.52 C/W                | 3.07 C/W | 2.49 C/W | 9.57 C/W           | 4.04 C/W                | 2.98 C/W  | 2.62 C/W |
|     | 12 | 21mm      | 12.4 C/W           | 6.61 C/W                | 4.37 C/W | 3.7 C/W  | 14.31 C/W          | 5.81 C/W                | 3.86 C/W  | 3.16 C/W |
|     | 15 | 21mm      | 11.73 C/W          | 5.84 C/W                | 4.09 C/W | 3.42 C/W | 13.57 C/W          | 5.3 C/W                 | 3.5 C/W   | 2.89 C/W |
|     | 18 | 21mm      | 11.06 C/W          | 5.51 C/W                | 3.76 C/W | 3.07 C/W | 12.83 C/W          | 4.95 C/W                | 3.35 C/W  | 2.66 C/W |
|     | 21 | 21mm      | 10.38 C/W          | 5.20 C/W                | 3.49 C/W | 2.84 C/W | 12.09 C/W          | 4.61 C/W                | 3.111 C/W | 2.47 C/W |
|     | 23 | 21mm      | 10.27 C/W          | 4.9 C/W                 | 3.26 C/W | 2.62 C/W | 11.63 C/W          | 4.32 C/W                | 2.91 C/W  | 2.32 C/W |
| 903 | 28 | 21mm      | 9.98 C/W           | 4.55 C/W                | 2.98 C/W | 2.42 C/W | 10.47 C/W          | 3.89 C/W                | 2.61 C/W  | 2.09 C/W |
|     | 33 | 21mm      | 9.7 C/W            | 4.18 C/W                | 2.73 C/W | 2.21 C/W | 9.3 C/W            | 3.57 C/W                | 2.37 C/W  | 1.95 C/W |
|     | 12 | 23mm      | 12.06 C/W          | 5.72 C/W                | 3.95 C/W | 3.24 C/W | 13.85 C/W          | 4.75 C/W                | 3.31 C/W  | 2.79 C/W |
|     | 15 | 23mm      | 11.41 C/W          | 5.39 C/W                | 3.67 C/W | 2.99 C/W | 13.14 C/W          | 4.38 C/W                | 3.05 C/W  | 2.53 C/W |
|     | 18 | 23mm      | 10.76 C/W          | 5.05 C/W                | 3.35 C/W | 2.67 C/W | 12.44 C/W          | 4.07 C/W                | 2.81 C/W  | 2.32 C/W |
|     | 21 | 23mm      | 10.11 C/W          | 4.74 C/W                | 3.1 C/W  | 2.46 C/W | 11.73 C/W          | 3.84 C/W                | 2.57 C/W  | 2.11 C/W |
| 904 | 23 | 23mm      | 9.99 C/W           | 4.44 C/W                | 2.87 C/W | 2.31 C/W | 11.28 C/W          | 3.59 C/W                | 2.4 C/W   | 1.97 C/W |
|     | 28 | 23mm      | 9.70 C/W           | 4.09 C/W                | 2.62 C/W | 2.12 C/W | 10.16 C/W          | 3.22 C/W                | 2.17 C/W  | 1.8 C/W  |
|     | 33 | 23mm      | 9.41 C/W           | 3.83 C/W                | 2.43 C/W | 1.96 C/W | 9.04 C/W           | 2.93 C/W                | 1.95 C/W  | 1.64 C/W |
|     | 12 | 27mm      | 11.38 C/W          | 4.84 C/W                | 3.11 C/W | 2.32 C/W | 12.93 C/W          | 4.34 C/W                | 3 C/W     | 2.53 C/W |
|     | 15 | 27mm      | 10.78 C/W          | 4.48 C/W                | 2.84 C/W | 2.12 C/W | 12.29 C/W          | 4.05 C/W                | 2.76 C/W  | 2.29 C/W |
|     | 18 | 27mm      | 10.17 C/W          | 4.13 C/W                | 2.56 C/W | 1.88 C/W | 11.64 C/W          | 3.73 C/W                | 2.5 C/W   | 2.07 C/W |
| 905 | 21 | 27mm      | 9.56 C/W           | 3.82 C/W                | 2.32 C/W | 1.72 C/W | 11 C/W             | 3.43 C/W                | 2.31 C/W  | 1.9 C/W  |
|     | 23 | 27mm      | 9.44 C/W           | 3.51 C/W                | 2.11 C/W | 1.6 C/W  | 10.58 C/W          | 3.21 C/W                | 2.11 C/W  | 1.71 C/W |
|     | 28 | 27mm      | 9.13 C/W           | 3.26 C/W                | 1.97 C/W | 1.49 C/W | 9.54 C/W           | 2.89 C/W                | 1.84 C/W  | 1.51 C/W |
|     | 33 | 27mm      | 8.82 C/W           | 3.07 C/W                | 1.82 C/W | 1.39 C/W | 8.51 C/W           | 2.62 C/W                | 1.66 C/W  | 1.35 C/W |
|     | 12 | 29mm      | 11.04 C/W          | 4.08 C/W                | 2.55 C/W | 1.98 C/W | 12.47 C/W          | 4.09 C/W                | 2.74 C/W  | 2.25 C/W |
|     | 15 | 29mm      | 10.46 C/W          | 3.82 C/W                | 2.32 C/W | 1.78 C/W | 11.86 C/W          | 3.81 C/W                | 2.52 C/W  | 2.02 C/W |
|     | 18 | 29mm      | 9.87 C/W           | 3.58 C/W                | 2.14 C/W | 1.58 C/W | 11.25 C/W          | 3.56 C/W                | 2.31 C/W  | 1.84 C/W |
|     | 21 | 29mm      | 9.28 C/W           | 3.33 C/W                | 1.96 C/W | 1.44 C/W | 10.63 C/W          | 3.3 C/W                 | 2.12 C/W  | 1.65 C/W |
|     | 23 | 29mm      | 9.16 C/W           | 3.13 C/W                | 1.82 C/W | 1.34 C/W | 10.23 C/W          | 3.06 C/W                | 1.91 C/W  | 1.49 C/W |
|     | 28 | 29mm      | 8.84 C/W           | 2.82 C/W                | 1.64 C/W | 1.2 C/W  | 9.24 C/W           | 2.72 C/W                | 1.69 C/W  | 1.33 C/W |
|     | 33 | 29mm      | 8.53 C/W           | 2.59 C/W                | 1.47 C/W | 1.07 C/W | 8.24 C/W           | 2.47 C/W                | 1.49 C/W  | 1.18 C/W |

Thermal Cooling Solutions from SMART to FINISH

## 901-910 SERIES CHIPSET HEAT SINKS



wakefield-vette

### THERMAL PERFORMANCE



|     |    |           | PIN FIN            |                         |          |          | ELLIPTICAL FIN     |                         |          |          |          |
|-----|----|-----------|--------------------|-------------------------|----------|----------|--------------------|-------------------------|----------|----------|----------|
|     | HT | CHIP SIZE | NATURAL CONVECTION | FORCED CONVECTION (C/W) |          |          | NATURAL CONVECTION | FORCED CONVECTION (C/W) |          |          |          |
|     |    |           |                    | 200 LFM                 | 400 LFM  | 600 LFM  |                    | 200 LFM                 | 400 LFM  | 600 LFM  |          |
| 906 | 12 | 31mm      | 10.71 C/W          | 3.49 C/W                | 2.28 C/W | 1.69 C/W |                    | 12.02 C/W               | 3.37 C/W | 2.25 C/W | 1.87 C/W |
|     | 15 | 31mm      | 10.14 C/W          | 3.18 C/W                | 2.03 C/W | 1.5 C/W  |                    | 11.43 C/W               | 3.13 C/W | 2.02 C/W | 1.66 C/W |
|     | 18 | 31mm      | 9.57 C/W           | 2.93 C/W                | 1.86 C/W | 1.33 C/W |                    | 10.85 C/W               | 2.85 C/W | 1.79 C/W | 1.45 C/W |
|     | 21 | 31mm      | 9.01 C/W           | 2.72 C/W                | 1.69 C/W | 1.2 C/W  |                    | 10.27 C/W               | 2.63 C/W | 1.63 C/W | 1.31 C/W |
|     | 23 | 31mm      | 8.88 C/W           | 2.5 C/W                 | 1.54 C/W | 1.07 C/W |                    | 9.88 C/W                | 2.44 C/W | 1.5 C/W  | 1.19 C/W |
|     | 28 | 31mm      | 8.56 C/W           | 2.26 C/W                | 1.38 C/W | .96 C/W  |                    | 8.93 C/W                | 2.21 C/W | 1.36 C/W | 1.05 C/W |
| 907 | 33 | 31mm      | 8.24 C/W           | 2.09 C/W                | 1.27 C/W | .88 C/W  |                    | 7.98 C/W                | 2.02 C/W | 1.19 C/W | .93 C/W  |
|     | 12 | 33mm      | 10.37 C/W          | 3.32 C/W                | 2.18 C/W | 1.62 C/W |                    | 11.56 C/W               | 3.23 C/W | 2.09 C/W | 1.73 C/W |
|     | 15 | 33mm      | 9.82 C/W           | 3.14 C/W                | 1.99 C/W | 1.45 C/W |                    | 11 C/W                  | 2.97 C/W | 1.88 C/W | 1.54 C/W |
|     | 18 | 33mm      | 9.28 C/W           | 2.89 C/W                | 1.78 C/W | 1.3 C/W  |                    | 10.45 C/W               | 2.69 C/W | 1.7 C/W  | 1.37 C/W |
|     | 21 | 33mm      | 8.73 C/W           | 2.67 C/W                | 1.60 C/W | 1.13 C/W |                    | 9.9 C/W                 | 2.5 C/W  | 1.52 C/W | 1.22 C/W |
|     | 23 | 33mm      | 8.60 C/W           | 2.45 C/W                | 1.43 C/W | .99 C/W  |                    | 9.54 C/W                | 2.3 C/W  | 1.37 C/W | 1.08 C/W |
| 908 | 28 | 33mm      | 8.27 C/W           | 2.24 C/W                | 1.28 C/W | .87 C/W  |                    | 8.62 C/W                | 2.08 C/W | 1.23 C/W | .98 C/W  |
|     | 33 | 33mm      | 7.94 C/W           | 2.03 C/W                | 1.15 C/W | .77 C/W  |                    | 7.71 C/W                | 1.89 C/W | 1.08 C/W | .86 C/W  |
|     | 12 | 35mm      | 10.03 C/W          | 3.06 C/W                | 1.97 C/W | 1.49 C/W |                    | 11.1 C/W                | 3.07 C/W | 2.07 C/W | 1.64 C/W |
|     | 15 | 35mm      | 9.5 C/W            | 2.85 C/W                | 1.81 C/W | 1.34 C/W |                    | 10.58 C/W               | 2.79 C/W | 1.87 C/W | 1.46 C/W |
|     | 18 | 35mm      | 8.98 C/W           | 2.6 C/W                 | 1.64 C/W | 1.19 C/W |                    | 10.06 C/W               | 2.54 C/W | 1.69 C/W | 1.27 C/W |
|     | 21 | 35mm      | 8.46 C/W           | 2.4 C/W                 | 1.5 C/W  | 1.07 C/W |                    | 9.53 C/W                | 2.35 C/W | 1.52 C/W | 1.15 C/W |
| 909 | 23 | 35mm      | 8.32 C/W           | 2.19 C/W                | 1.34 C/W | .97 C/W  |                    | 8.75 C/W                | 2.13 C/W | 1.35 C/W | 1.01 C/W |
|     | 28 | 35mm      | 7.99 C/W           | 1.97 C/W                | 1.19 C/W | .83 C/W  |                    | 7.93 C/W                | 1.94 C/W | 1.19 C/W | .86 C/W  |
|     | 33 | 35mm      | 7.65 C/W           | 1.82 C/W                | 1.06 C/W | .7 C/W   |                    | 7.11 C/W                | 1.69 C/W | 1.02 C/W | .72 C/W  |
|     | 12 | 37.5mm    | 9.60 C/W           | 2.93 C/W                | 1.90 C/W | 1.36 C/W |                    | 10.52 C/W               | 3.11 C/W | 2.01 C/W | 1.61 C/W |
|     | 15 | 37.5mm    | 9.11 C/W           | 2.71 C/W                | 1.72 C/W | 1.19 C/W |                    | 10.04 C/W               | 2.82 C/W | 1.79 C/W | 1.41 C/W |
|     | 18 | 37.5mm    | 8.61 C/W           | 2.52 C/W                | 1.53 C/W | 1.05 C/W |                    | 9.56 C/W                | 2.59 C/W | 1.59 C/W | 1.22 C/W |
| 910 | 21 | 37.5mm    | 8.11 C/W           | 2.25 C/W                | 1.36 C/W | .88 C/W  |                    | 9.08 C/W                | 2.38 C/W | 1.41 C/W | 1.06 C/W |
|     | 23 | 37.5mm    | 7.98 C/W           | 2.04 C/W                | 1.2 C/W  | .75 C/W  |                    | 8.75 C/W                | 2.15 C/W | 1.24 C/W | .94 C/W  |
|     | 28 | 37.5mm    | 7.63 C/W           | 1.82 C/W                | 1.01 C/W | .63 C/W  |                    | 7.93 C/W                | 1.88 C/W | 1.08 C/W | .8 C/W   |
|     | 33 | 37.5mm    | 7.29 C/W           | 1.6 C/W                 | .87 C/W  | .52 C/W  |                    | 7.11 C/W                | 1.64 C/W | .93 C/W  | .68 C/W  |
|     | 12 | 40mm      | 9.18 C/W           | 2.84 C/W                | 1.86 C/W | 1.36 C/W |                    | 9.95 C/W                | 3.09 C/W | 1.93 C/W | 1.56 C/W |
|     | 15 | 40mm      | 8.71 C/W           | 2.64 C/W                | 1.65 C/W | 1.18 C/W |                    | 9.51 C/W                | 2.77 C/W | 1.73 C/W | 1.37 C/W |
|     | 18 | 40mm      | 8.24 C/W           | 2.4 C/W                 | 1.44 C/W | .98 C/W  |                    | 9.06 C/W                | 2.74 C/W | 1.52 C/W | 1.17 C/W |
|     | 21 | 40mm      | 7.77 C/W           | 2.21 C/W                | 1.27 C/W | .86 C/W  |                    | 8.62 C/W                | 2.22 C/W | 1.35 C/W | .99 C/W  |
|     | 23 | 40mm      | 7.63 C/W           | 2 C/W                   | 1.15 C/W | .73 C/W  |                    | 8.3 C/W                 | 2.01C/W  | 1.19 C/W | .87 C/W  |
|     | 28 | 40mm      | 7.27 C/W           | 1.77 C/W                | .99 C/W  | .62 C/W  |                    | 7.55 C/W                | 1.8 C/W  | 1.04 C/W | .75 C/W  |
|     | 33 | 40mm      | 6.92 C/W           | 1.58 C/W                | .85 C/W  | .51 C/W  |                    | 6.78 C/W                | 1.61 C/W | .88 C/W  | .64 C/W  |

Thermal Cooling Solutions from SMART to FINISH

## 901-910 SERIES CHIPSET HEAT SINKS



### SHOCK TEST SPECIFICATION :

Wave Form : Half sine wave

Acceleration : 50 g

Duration Time : 11 ms

No. of Shock : Each axis 3 times

Shock Direction :  $\pm X$ ,  $\pm Y$ ,  $\pm Z$  axis

Reliability & Communication Testing  
Instruments

### Random Vibration test

Frequency : 5 Hz to 500 Hz

Acceleration : 3.13 grms


P.S.D : 0.01 g<sup>2</sup>/HZ (5 Hz)

0.02 g<sup>2</sup>/HZ (20 Hz to 500 Hz)


Test Axis : X, Y, Z axis

Test Time : 10 mins (Each axis)


Total Test Time : 30 mins



**STEP 1:** Center heat Sink onto BGA. Tilt and hook one side of the clip under the BGA chip.



**STEP 2:** Press down the other side of clip to snap it onto the BGA chip.



**STEP :3** Make sure the stop pin is not on top of the chip set. Installation Done!



**Thermal Cooling Solutions from SMART to FINISH**

## 901-910 SERIES CHIPSET HEAT SINKS



## Contact Us / Corporate Location Information

Wakefield-Vette is Global. Global presence means our engineering, design, sales and support are close to our customers, in the Americas, Europe, Middle East and Asia. It means multi-national manufacturing and delivery. And it means a global Wakefield-Vette supply chain that can deliver, and provide support quickly, anywhere, with the highest quality solutions.

Contact sales for a list of Distributors that carry stock.

East Coast Operations

New Hampshire

33 Bridge Street

Pelham.NH 03076

Phone: 603-635-2800

Fax: 603-635-1900

[Info@wakefield-vette.com](mailto:Info@wakefield-vette.com)

(Wakefield-Vette Headquarters)

2013 Wakefield-Vette. All rights reserved. Information is subject to change without notice. Wakefield-Vette assumes no liability for the errors that may appear in this document.

Visit us on the web at: [www.wakefield-vette.com](http://www.wakefield-vette.com)



## Thermal Cooling Solutions from SMART to FINISH

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9