



Product: [83322E](#)

Electronic, 2 C #16 Str SPC, TFE Ins, OA SPC Brd, TFE Tape Jkt, MIL-W-16878/4 (Type E)

Request Sample

Product Description

High Temperature Electronic, 2 Conductor 16AWG (19x29) Silver Plated Copper, TFE Insulation, Overall Silver Plated Copper Braid(85%) Shield, TFE Tape Outer Jacket, MIL-W-16878/4 (Type E)

Technical Specifications

Product Overview

|                        |                                                                                                                     |
|------------------------|---------------------------------------------------------------------------------------------------------------------|
| Suitable Applications: | MIL-W-16878/4 (Type E) Spec; Extreme High/Low Temperature Environments; up to 600V analog signals & voltage control |
|------------------------|---------------------------------------------------------------------------------------------------------------------|

Construction Details

Conductor

| Element      | Number of Element | AWG | Stranding | Material             |
|--------------|-------------------|-----|-----------|----------------------|
| Conductor(s) | 2                 | 16  | 19x29     | SC - Silvered Copper |

Insulation

| Element      | Material                       | Thickness [in] | Color Code   |
|--------------|--------------------------------|----------------|--------------|
| Conductor(s) | PTFE - Polytetrafluoroethylene | 0.011          | White, Black |

Outer Shield Material

| Type  | Material             | Coverage |
|-------|----------------------|----------|
| Braid | SC - Silvered Copper | 85%      |

Outer Jacket Material

| Material                       | Thickness | Diameter |
|--------------------------------|-----------|----------|
| PTFE - Polytetrafluoroethylene | 0.011 in  | 0.197 in |

Electrical Characteristics

Electricals

| Element      | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Max. Current                 |
|--------------|--------------------|-------------------------------|-------------------------------------------------|------------------------------|
| Conductor(s) | 4.4 Ohm/1000ft     | 36 pF/ft                      | 60 pF/ft                                        | 11 Amps per conductor @ 25°C |

Voltage

| Non-UL Voltage Rating |
|-----------------------|
| 600 V                 |

Mechanical Characteristics

Temperature

| Operating       |
|-----------------|
| -65°C to +200°C |

Bend Radius

| Stationary Min. |
|-----------------|
| 2 in            |

|                    |               |
|--------------------|---------------|
| Max. Pull Tension: | 95.5 lbs      |
| Bulk Cable Weight: | 33 lbs/1000ft |

Standards and Compliance

|                                 |                                                                                                         |
|---------------------------------|---------------------------------------------------------------------------------------------------------|
| Sustainability:                 | CA Prop 65                                                                                              |
| Flammability / Fire Resistance: | IEC 60332-1-2                                                                                           |
| NEMA Compliance:                | NEMA HP3                                                                                                |
| Military Compliance:            | MIL-W-16878/4 (Type E except stranding), (insulated conductors)                                         |
| CPR Euroclass:                  | Eca                                                                                                     |
| European Directive Compliance:  | EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE) |
| APAC Compliance:                | China RoHS II (GB/T 26572-2011)                                                                         |

Product Notes

|        |                                                                                                         |
|--------|---------------------------------------------------------------------------------------------------------|
| Notes: | Teflon« is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc. |
|--------|---------------------------------------------------------------------------------------------------------|

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.329 Revision Date: 06-15-2020 |
|----------------------|--------------------------------------------------|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9