



LAY OUT OF 50P CONNECTOR







VIEW OF MATING FACE

"This LF product meets European Union Directives and other country regulations as described in GS-22-008"

Packaging as per GS-14-920

Housing will withstand exposure to 260°c peak temp for 3.5sec

TECHNICAL SPECIFICATIONS

SHELLS	:	MATT TIN / ZINC PLATED STEEL
INSULATOR MATERIAL	:	SELF EXTINGUISHING THERMOPLASTIC - UL CLASS 94 V0 THE HOUSING WILL WITHSTAND EXPOSURE TO 260-265°C IF WE USE PROTECTIVE ADHESIVE (type Kapton or Teflon) OR PROTECTIVE METALLIC DEVICE
CONTACTS DIA ON ACTIVE AREA	:	Ø1 MM.
CONTACTS MATERIAL	:	COPPER ALLOY
CONTACT PLATING	:	GXT / GOLD OVER NICKEL (ACTIVE ZONE)
	:	TIN OVER NICKEL (TERMINATION ZONE)
FOR LEAD FREE PLATING	:	2 μMIN. TIN TOP OVER 1.27 μ MIN.NICKEL UNDER PLATE(ON TERMINATION ZONE)
OPERATING TEMPERATURE	:	-55°C +125°C
OPERATING CURRENT	:	5 A PER CONTACT
CONTACT RESISTANCE	:	≤10m Ω
INSULATION RESISTANCE	:	≥5000M Ω
MAXIMUM VOLTAGE	:	1000 V.r.m.s
MECHANICAL ENDURANCE	:	200 MATINGS (For 64 code) 500 MATINGS (For 65 code).
DAMP HEAT	:	21 DAYS.
WIRE SIZE	:	0.6 MM^2 (AWG 20) MAX.

ORDERING INFORMATION

D B V 25 P 0 64 H T X B XXX LF

- SERIES
- SHELL SIZE: E,A,B,C,D
- OPTIONS: BLANK-STANDARD; F - FLOAT MOUNTING; L - CLINCH NUT (M3); O - CLINCH NUT (UNC); V - FEM. SCREW LOCK HEX. (UNC)
- NO.OF CONTACTS: 09,15,25,37,50
- CONTACTS: P - PIN; S - SOCKET
- TERMINATION TYPE: 0 - SOLDER BUCKET
- CONTACT PLATING: 64 - 200 Mating cycles; 65 - 500 Mating cycles
- OPTIONS: BLANK - STD; H - WITH SHIELDING TERMINATION FINGERS
- SHELL PLATING: BLANK-ZINC; T-STD. TIN over Cu
- INSULATOR COLOUR: BLANK- NATURAL; B - BLACK
- SPECIAL CODES
- DIMPLES: X-ON MALE CONNECTORS ONLY
- LEAD FREE

SHELL SIZE		A +0,76 0	B +0,25 0	C ±0,12	D +0,25 0	E +0,76 0	F MAX	G +0,15 0	H +0,51 0	J +0,51 0	K ±0,2	L +0,22 0
		DIMENSIONS										
50	P	66.65	52.68	61.11	11.08	14.99	11.09	5.85	55.07	13.31	1.50	1.0
	S	66.65	52.30	61.11	10.62	14.99	11.21	6.05	55.07	13.31	1.10	0.8
37	P	68.94	55.30	63.50	8.23	12.17	11.09	5.85	57.45	10.46	1.50	1.0
	S	68.94	54.71	63.50	7.77	12.17	11.21	6.05	57.45	10.46	1.10	0.8
25	P	52.65	38.84	47.04	8.23	12.17	11.07	5.85	41.02	10.46	1.10	0.8
	S	52.65	38.25	47.04	7.77	12.17	11.21	6.05	41.02	10.46	1.10	0.8
15	P	38.76	25.12	33.32	8.23	12.17	10.99	5.85	27.25	10.46	1.10	0.8
	S	38.76	24.54	33.32	7.77	12.17	11.21	6.05	27.25	10.46	1.10	0.8
09	P	30.43	16.79	24.99	8.23	12.17	10.99	5.85	19.02	10.46	1.10	0.8
	S	30.43	16.21	24.99	7.77	12.17	11.21	6.05	19.02	10.46	1.10	0.8

NOTE:– 1) INSIDE DIMENSIONS OF THE MALE AND OUTSIDE DIMENSIONS OF THE FEMALE CONNECTOR

2) ALL ACCESSORIES SHOWN IN ASSEMBLY OPTIONS SHOULD BE ORDERED SEPARETELY

ASSEMBLY OPTIONS

FEMALE SCREW LOCK EXTENDED TYPE



ORD CODE 8630–01–061

FEMALE SCREW LOCK



ORD–CODE	EXTERNAL THREAD	INTERNAL THREAD
8630–01LF	M3	M3
8630–01ALF	M3	4–40 UNC 2B
8630–01BLF	4–40 UNC 2A	4–40 UNC 2B
8630–01CLF	4–40 UNC 2A	M3

MALE LEVER LOCK



ORD CODE 8630–3427(EABC)

ORD CODE 8630–3428(D)

CONNECTOR WITH SPECIAL RIVETTED FEMALE SCREW LOCK



CLINCH NUT



PREFIX:

O – UNC4–40

L – M3

WITH SHIELDING TERMINATION FINGERS



OPTION: H

FEMALE LEVER LOCK



ORD CODE 8630–3425(EABC)

ORD CODE 8630–3426(D)

mat'l. code				surface		tolerance		projection	product family	
SEE NOTE 4				ISO 1302		ISO 406 ISO 1101			D-SUB	
ltr	ecn no	dr	date	tolerances unless otherwise specified					title	
N	I11-0003	AMR	2011-01-06	angles	linear			MM	D- SUB SOLDER BUCKET CONNECTOR	
-	-	-	-			.00±0.1			(WITH ASSEMBLY OPTIONS)	
H	I07-0175	MRA	2007-12-17	0°±1°		.000±.00X		scale –		
J	I08-0131	MRA	2008-10-06	dr	GEORGE.V.JOSEPH		1999-03-20		dwg no	sheet 1 of 1 size
K	I09-0121	MRA	2009-07-01	engr	GEORGE.V.JOSEPH		1999-03-20		C-DSUB-0064	A3
L	I09-0140	MRA	2009-07-14	chr	ABHILASH.M.R		2009-07-01		type Product Customer Drawing	
M	I09-0195	MRA	2009-09-18	appd	SUDHIR.VARMA		2009-07-01			
sheet index	revision	N								
	sheet	1								

Copyright FCI
FCIconnect.com

form: A3

PDM: Rev:N STATUS:Released Printed: Mar 01, 2011

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9