

**SURFACE MOUNT GLASS PASSIVATED  
HIGH EFFICIENCY SILICON RECTIFIER**  
**VOLTAGE RANGE 50 to 1000 Volts CURRENT 1.0 Ampere**

**FEATURES**

- \* Glass passivated device
- \* Ideal for surface mounted applications
- \* Low leakage current
- \* Metallurgically bonded construction
- \* Mounting position: Any
- \* Weight: 0.057 gram


**MECHANICAL DATA**

- \* Epoxy: Device has UL flammability classification 94V-O

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25 °C ambient temperature unless otherwise specified.  
Single phase, half wave, 60 Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

**DO-214AC**



Dimensions in inches and (millimeters)

**MAXIMUM RATINGS (@ TA=25 °C unless otherwise noted)**

| RATINGS                                                                                           | SYMBOL           | HFM101       | HFM102 | HFM103 | HFM104 | HFM105 | HFM106 | HFM107 | HFM108 | UNITS |    |
|---------------------------------------------------------------------------------------------------|------------------|--------------|--------|--------|--------|--------|--------|--------|--------|-------|----|
| Maximum Recurrent Peak Reverse Voltage                                                            | V <sub>RRM</sub> | 50           | 100    | 200    | 300    | 400    | 600    | 800    | 1000   | Volts |    |
| Maximum RMS Voltage                                                                               | V <sub>RMS</sub> | 35           | 70     | 140    | 210    | 280    | 420    | 490    | 700    | Volts |    |
| Maximum DC Blocking Voltage                                                                       | V <sub>DC</sub>  | 50           | 100    | 200    | 300    | 400    | 600    | 800    | 1000   | Volts |    |
| Maximum Average Forward Rectified Current at T <sub>A</sub> = 50°C                                | I <sub>O</sub>   | 1.0          |        |        |        |        |        |        |        | Amps  |    |
| Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method) | I <sub>FSM</sub> | 30           |        |        |        |        |        |        |        | Amps  |    |
| Typical Thermal Resistance (Note 1)                                                               | R <sub>θJL</sub> | 27           |        |        |        |        |        |        |        | °C/W  |    |
| Typical Thermal Resistance (Note 1)                                                               | R <sub>θJA</sub> | 75           |        |        |        |        |        |        |        | °C/W  |    |
| Typical Junction Capacitance (Note 2)                                                             | C <sub>J</sub>   | 15           |        |        |        |        | 12     |        |        |       | pF |
| Operating Temperature Range                                                                       | T <sub>J</sub>   | 150          |        |        |        |        |        |        |        | °C    |    |
| Storage Temperature Range                                                                         | T <sub>STG</sub> | -55 to + 150 |        |        |        |        |        |        |        | °C    |    |

**ELECTRICAL CHARACTERISTICS (@ TA=25 °C unless otherwise noted)**

| CHARACTERISTICS                                                            |                         | SYMBOL          | HFM101 | HFM102 | HFM103 | HFM104 | HFM105 | HFM106 | HFM107 | HFM108 | UNITS |
|----------------------------------------------------------------------------|-------------------------|-----------------|--------|--------|--------|--------|--------|--------|--------|--------|-------|
| Maximum Instantaneous Forward Voltage at 1.0A DC                           |                         | V <sub>F</sub>  | 1.0    |        |        | 1.3    |        | 1.7    |        |        | Volts |
| Maximum Full Load Reverse Current, Full cycle Average T <sub>A</sub> =55°C |                         | I <sub>R</sub>  | 50     |        |        |        |        |        |        |        | μA    |
| Maximum Average Reverse Current                                            | @T <sub>A</sub> = 25°C  |                 | 5      |        |        |        |        |        |        |        | μA    |
| at Rated DC Blocking Voltage                                               | @T <sub>A</sub> = 125°C |                 | 100    |        |        |        |        |        |        |        | μA    |
| Maximum Reverse Recovery Time (Note 4)                                     |                         | t <sub>rr</sub> | 50     |        |        |        |        | 75     |        |        | nSec  |

NOTES : 1. Thermal Resistance : Mounted on PCB.  
2. Measured at 1 MHz and applied reverse voltage of 4.0 volts.  
3. "Fully ROHS compliant", "100% Sn plating (Pb-free)".  
4. Test Conditions:  $I_F = 0.5\text{A}$ ,  $I_R = -1.0\text{A}$ ,  $I_{RR} = -0.25\text{A}$ .

2006-11

RATING AND CHARACTERISTICS CURVES ( HFM101 THRU HFM108 )



FIG.1 TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC




FIG.2 TYPICAL FORWARD CURRENT DERATING CURVE






FIG.3 TYPICAL REVERSE CHARACTERISTICS


**RATING AND CHARACTERISTICS CURVES ( HFM101 THRU HFM108 )**



**FIG.4 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS**




**FIG.5 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT**



**FIG.6 TYPICAL JUNCTION CAPACITANCE**

## Mounting Pad Layout



Dimensions in inches and (millimeters)

## DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9