

## Controller - RFC 460R PN 3TX - 2700784

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



High-availability Remote Field Controller with redundancy function, 3 x 10/100 Ethernet, PROFINET controller, IP20 protection, plug-in parameterization memory

### Product description

High-availability Remote Field Controller for PROFINET networks

When it comes to high-availability, distributed, and modular automation, Remote Field Controllers (RFCs) with IEC 61131 control intelligence, redundancy technology, and network connection are the ideal solution. Thanks to the integrated fiber optic-based redundancy function, you can reduce system downtimes, work cost-effectively, and also avoid potential hazards, e.g., in tunnels or at airports.

### Product Features

- ✓ The RFC 460R PN 3TX features:
- ✓ Fast startup and automatic configuration of all redundancy functions, thanks to AutoSync technology
- ✓ Uninterrupted process in the event of failure or when a controller is replaced
- ✓ Optimum device integration, thanks to PROFINET standards; redundancy for your future-proof Ethernet network
- ✓ High-resolution display for displaying status and error messages in plain text
- ✓ Uninterrupted visualization - thanks to redundancy-capable OPC server
- ✓ A distance of up to 80 km between the controllers via fiber optics; cost-optimized thanks to plug-in SFP modules
- ✓



AutoSync Technology  
Designed by PHOENIX CONTACT

### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	2120.0 GRM
Custom tariff number	85371091
Country of origin	Germany

### Technical data

#### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

### Dimensions

# Controller - RFC 460R PN 3TX - 2700784

## Technical data

### Dimensions

Width	124 mm
Height	185 mm
Depth	190 mm

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C (from 45°C only with fan module)
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	5 % ... 90 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 90 % (non-condensing)
Air pressure (operation)	80 kPa ... 106 kPa (up to 2000 m above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (up to 3000 m above sea level)
Shock	25g, Criterion 1, according to IEC 60068-2-27
Vibration (operation)	1g, Criterion 1, according to IEC 60068-2-6

### Mechanical design

Format	124 x 185 x 190 mm (W x H x D without fan)
	124 x 210 x 190 mm (W x H x D with fan)
Weight	1870 g
Note on weight specifications	Without fan module
Weight	2010 g
Note on weight specifications	With fan module

### Data interfaces

Interface	Ethernet
Connection method	3x RJ45 sockets
Transmission speed	10/100 MBit/s
Interface	Synchronization interface
Connection method	SFP port
Transmission speed	1 GBit/s
Interface	Other interfaces
Connection method	2x USB

### IEC 61131 runtime system

Programming tool	PC WORX
Processing speed	0.007 ms (1 K mix instructions)
	2 µs (1 K bit instructions)
Program memory	typ. 8 Mbyte (680 K instructions (IL))
Mass storage	16 Mbyte

# Controller - RFC 460R PN 3TX - 2700784

## Technical data

### IEC 61131 runtime system

Retentive mass storage	120 kByte (NVRAM)
Number of data blocks	depends on mass storage
Number of timers, counters	depends on mass storage
Number of control tasks	16
Realtime clock	Integrated (battery backup)

### Power supply

Power supply connection	Screw terminal blocks, plug-in
Typical current consumption	1 A
Supply voltage	24 V DC
Supply voltage range	19.2 V DC ... 30 V DC (including ripple)
Power dissipation	max. 24 W

### Fieldbus function

Module classification	PROFINET controller
Processing speed	0.007 ms

## Classifications

### eCl@ss

eCl@ss 4.0	27240601
eCl@ss 4.1	27240601
eCl@ss 5.0	27242215
eCl@ss 5.1	27242207
eCl@ss 6.0	27242207
eCl@ss 7.0	27242207
eCl@ss 8.0	27242207

### ETIM

ETIM 3.0	EC000236
ETIM 4.0	EC000236
ETIM 5.0	EC000236

### UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

# Controller - RFC 460R PN 3TX - 2700784

## Approvals

### Approvals

---

#### Approvals

UL Listed / cUL Listed / EAC / EAC / UL Listed / cUL Listed / cULus Listed

---

#### Ex Approvals

---

#### Approvals submitted

---


### Approval details

UL Listed 

cUL Listed 

EAC

EAC

UL Listed 

cUL Listed 

cULus Listed 

---



## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9