







Copyright FCI.


PRODUCT NUMBER SEE SHEET 2




spec ref				dr		Zhen-Hua Liu	2015/05/11	projection		MM		size	A3	scale	3:2	
tolerance std ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng		Zhen-Hua Liu	2015/05/19					ecn no				.
				chr		Fancy Zhang	2015/05/19					rel level				Released
				appr		Pei-Ming Zheng	2015/05/19					product family				PowerBlade+
surface ✓	linear	0.X		±0.50			title 5HP + 20S VT STB RECEPTACLE				dwg no	10106130-5005101		rev	A	
		0.XX		±0.25												
		0.XXX		±0.10												
	ASME Y14.5	angular	0°		±2°		www.fci.com	cat. no.		Product - Customer Drw				sheet 1 of 3		

PRODUCT NO.	ROWS		SIGNAL					HIGH POWER					
		E1	5	4	3	2	1	P5	P4	P3	P2	P1	E2
10106130-5005101LF	D C B A		E	E	E	E	E	H3	H3	H3	H3	H3	

CODE	DESCRIPTION
E	STD SIGNAL CONTACT
H3	STD HIGH POWER CONTACT (3.43)



dr	Zhen-Hua Liu	2015/05/11	projection 	MM 	size	A3	scale	3:2	
eng	Zhen-Hua Liu	2015/05/19			ecn no				-
chr	Fancy Zhang	2015/05/19			rel level				Released
appr	Pei-Ming Zheng	2015/05/19	product family			PowerBlade+			
	title	5HP + 20S VT STB RECEPTACLE			dwg no	10106130-5005101		rev	
									A
www.fci.com	cat. no.		Product - Customer Drw			sheet 2 of 3			

A

B

C

D

A

B

C

D

NOTES:

- 1) "FCI", PART NUMBER AND DATE CODE TO BE MARKED ON THIS SURFACE.
THE MARK CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.
- 2) MATERIALS:
-HOUSING - GLASS FILLED WITH HIGH TEMP THERMOPLASTIC, UL94V-0.
-SIGNAL CONTACT - COPPER ALLOY.
-POWER CONTACT - HIGH CONDUCTIVITY COPPER ALLOY.
- 3) PLATING SPECIFICATION : 10124315.
- 4) DENOTES CONNECTOR KEEP OUT ZONE.
- 5) DATUM AND BASIC DIMENIONS WERE ESTABLISHED BY CUSTOMER.
- 6) ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES.
- 7) 1.15 ± 0.025MM DRILLED HOLE PLATED WITH 0.00762MM MIN Sn
OVER 0.0254-0.0762MM Cu PLATING TO ACHIEVE A 1.02 ± 0.07MM HOLE.
- 8) PRODUCT SPECIFICATION : GS-12-658.
APPLICATION SPECIFICATION: GS-20-141.
PACKAGE SPECIFICATION: GS-14-1502.
- 9) THE VOID CORING IN BETWEEN POWER MODULES, SIGNAL
MODULES AND END MODULES ARE OPTIONAL AND THE SHAPE
MAY BE DIFFERENT FOR OPTIMIZE THE MOLDING PROCESS. THE
VOID CORING WILL NOT EFFECT TO PRODUCT FUNCTION.



Copyright FCI.

dr	Zhen-Hua Liu	2015/05/11	projection	MM	size	A3	scale	1:1	
eng	Zhen-Hua Liu	2015/05/19			ecn no	-			
chr	Fancy Zhang	2015/05/19			rel level	Released			
appr	Pei-Ming Zheng	2015/05/19	product family		PowerBlade+				
FCi		title			5HP + 20S	dwg no		10106130-5005101	rev
					VT STB RECEPTACLE				A
www.fci.com		cat. no.		Product - Customer Drw			sheet 3 of 3		

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9