

# Central<sup>TM</sup> Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA  
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

2N4404  
2N4405

PNP SILICON TRANSISTOR

JEDEC TO-39 CASE

## DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N4404, 2N4405 types are PNP Silicon Epitaxial Planar Transistors designed for general purpose and switching applications.

## MAXIMUM RATINGS (T<sub>C</sub> = 25°C)

|                                           | SYMBOL                            |             | UNITS |
|-------------------------------------------|-----------------------------------|-------------|-------|
| Collector-Base Voltage                    | V <sub>CBO</sub>                  | 80          | V     |
| Collector-Emitter Voltage                 | V <sub>CEO</sub>                  | 80          | V     |
| Emitter-Base Voltage                      | V <sub>EBO</sub>                  | 5.0         | V     |
| Collector Current                         | I <sub>C</sub>                    | 1.0         | A     |
| Power Dissipation (T <sub>A</sub> = 25°C) | P <sub>D</sub>                    | 1.25        | W     |
| Power Dissipation                         | P <sub>D</sub>                    | 8.75        | W     |
| Operating and Storage                     |                                   |             |       |
| Junction Temperature                      | T <sub>J</sub> , T <sub>stg</sub> | -65 to +200 | °C    |
| Thermal Resistance                        | θ <sub>JA</sub>                   | 140         | °C/W  |
| Thermal Resistance                        | θ <sub>JC</sub>                   | 25          | °C/W  |

## ELECTRICAL CHARACTERISTICS (T<sub>C</sub> = 25°C unless otherwise noted)

| SYMBOL               | TEST CONDITIONS                                | 2N4404 |      | 2N4405 |      | UNITS |
|----------------------|------------------------------------------------|--------|------|--------|------|-------|
|                      |                                                | MIN    | MAX  | MIN    | MAX  |       |
| I <sub>CBO</sub>     | V <sub>CB</sub> = 60V                          |        | 25   |        | 25   | nA    |
| I <sub>EBO</sub>     | V <sub>EB</sub> = 3.0V                         |        | 25   |        | 25   | nA    |
| BV <sub>CEO</sub>    | I <sub>C</sub> = 10mA                          | 80     |      | 80     |      | V     |
| BV <sub>CBO</sub>    | I <sub>C</sub> = 10μA                          | 80     |      | 80     |      | V     |
| BV <sub>EBO</sub>    | I <sub>E</sub> = 10μA                          | 5.0    |      | 5.0    |      | V     |
| V <sub>CE(SAT)</sub> | I <sub>C</sub> = 10mA, I <sub>B</sub> = 1.0mA  |        | 0.15 |        | 0.15 | V     |
| V <sub>CE(SAT)</sub> | I <sub>C</sub> = 150mA, I <sub>B</sub> = 15mA  |        | 0.2  |        | 0.2  | V     |
| V <sub>CE(SAT)</sub> | I <sub>C</sub> = 500mA, I <sub>B</sub> = 50mA  |        | 0.5  |        | 0.5  | V     |
| V <sub>BE(SAT)</sub> | I <sub>C</sub> = 10mA, I <sub>B</sub> = 1.0mA  |        | 0.8  |        | 0.8  | V     |
| V <sub>BE(SAT)</sub> | I <sub>C</sub> = 500mA, I <sub>B</sub> = 50mA  | 0.85   | 1.2  | 0.85   | 1.2  | V     |
| V <sub>BE(ON)</sub>  | V <sub>CE</sub> = 1.0V, I <sub>C</sub> = 150mA |        | 0.9  |        | 0.9  | V     |
| h <sub>FE</sub>      | V <sub>CE</sub> = 5.0V, I <sub>C</sub> = 0.1mA |        | 30   |        | 75   |       |
| h <sub>FE</sub>      | V <sub>CE</sub> = 5.0V, I <sub>C</sub> = 10mA  |        | 40   |        | 100  |       |
| h <sub>FE</sub>      | V <sub>CE</sub> = 5.0V, I <sub>C</sub> = 150mA |        | 40   | 120    | 300  |       |
| h <sub>FE</sub>      | V <sub>CE</sub> = 5.0V, I <sub>C</sub> = 500mA |        | 30   |        | 50   |       |

# ELECTRICAL CHARACTERISTICS (Continued)

| <u>SYMBOL</u> | <u>TEST CONDITIONS</u>                                         | <u>MIN</u> | <u>MAX</u> | <u>UNITS</u> |
|---------------|----------------------------------------------------------------|------------|------------|--------------|
| $f_T$         | $V_{CE} = 20V, I_C = 50mA, f = 100MHz$                         | 150        | 600        | MHz          |
| $C_{cb}$      | $V_{CB} = 10V, I_E = 0, f = 1.0MHz$                            |            | 20         | pF           |
| $C_{eb}$      | $V_{BE} = 0.5V, I_C = 0, f = 1.0MHz$                           |            | 110        | pF           |
| $t_d$         | $V_{CC} = 30V, V_{BE(off)} = 2.0V, I_C = 500mA, I_{B1} = 50mA$ |            | 40         | ns           |
| $t_r$         | $V_{CC} = 30V, V_{BE(off)} = 2.0V, I_C = 500mA, I_{B1} = 50mA$ |            | 60         | ns           |
| $t_s$         | $V_{CC} = 30V, I_C = 500mA, I_{B1} = I_{B2} = 50mA$            |            | 350        | ns           |
| $t_f$         | $V_{CC} = 30V, I_C = 500mA, I_{B1} = I_{B2} = 50mA$            |            | 50         | ns           |

**Central**<sup>TM</sup>  
**Semiconductor Corp.**

145 Adams Avenue  
Hauppauge, NY 11788 USA  
Tel: (631) 435-1110 • Fax: (631) 435-1824  
[www.centrasemi.com](http://www.centrasemi.com)

## OUTSTANDING SUPPORT AND SUPERIOR SERVICES



---

### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

### REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

---

### CONTACT US

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centrasemi.com](http://www.centrasemi.com)

**Worldwide Field Representatives:**  
[www.centrasemi.com/wwreps](http://www.centrasemi.com/wwreps)

**Worldwide Distributors:**  
[www.centrasemi.com/wwdistributors](http://www.centrasemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centrasemi.com/terms](http://www.centrasemi.com/terms)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9