# Type CPF Series

## Key Features

- Thin film precision resistors with TC's of 15ppm, 25ppm and 50ppm and tolerances to 0.1%. Applications in measurement, telemetry and for sensing circuits.
- Wide range of case sizes from 0201 to 2512
- CPF chip resistors are suitable for all applications where close accuracy and stability are essential
- Terminal finish - electro-plated 100% matte Sn

## Applications

- Communications
- Industrial Controls
- Instrumentation
- Medical

The CPF series is a high stability precision chip resistor range offering various power dissipations relating to a wide range of chip sizes. The CPF series offers TCR's down to 15ppm/°C and resistance tolerances to 0.1%. Standard values are within the IEC 63 E96 and E24 value grids. The CPF has accurate and uniform physical dimensions to facilitate placement.

## Characteristics - Electrical

| | 0201 | | | | 0402 | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Rated Power @ 70°C:** | 0.03125W | | | | 0.063W | | | | | | | | |
| **Resistance Range (Ohms) Min:** | 49R9 | 49R9 | 49R9 | 49R9 | 49R9 | 10R | 10R | 49R9 | 10R | 1R0 | 49R9 | 10R | 1R0 |
| **Max:** | 5K0 | 33K | 5K0 | 33K | 70K | 255K | 205K | 70K | 255K | 205K | 70K | 255K | 205K |
| **Tolerance (%):** | 0.5 | | 1 | | 0.1 | | | 0.5 | | | 1 | | |
| **Code letter:** | D | | F | | B | | | D | | | F | | |
| **Selection Series:** | E24 & E96 | | | | E24 & E96 | | | | | | | | |
| **Temp. Coefficient (ppm/°C):** | 25 | 50 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 |
| **Code Letter:** | E | C | E | C | D | E | C | D | E | C | D | E | C |
| **Limiting Element Voltage:** | 15V | | | | 25V | | | | | | | | |
| **Max. Overload Voltage:** | 30V | | | | 50V | | | | | | | | |
| **Operating Temp. Range:** | -55 to +155°C | | | | -55 to +155°C | | | | | | | | |
| **Climatic Category (°C):** | 55/125/55 | | | | 55/125/55 | | | | | | | | |
| **Insulation Resistance Dry Min:** | 1000MΩ | | | | 1000MΩ | | | | | | | | |
| **Stability:** | 0.5% | | | | 0.5% | | | | | | | | |

| | 0603 | | | | | | | | | 0805 | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Rated Power @ 70°C:** | 0.063W | | | | | | | | | 0.1W | | | | | | | | |
| **Resistance Range (Ohms) Min:** | 4R7 | 4R7 | | 4R7 | 2R0 | | 4R7 | 2R0 | | 4R3 | 4R7 | | 4R3 | 1R0 | | 4R3 | 1R0 | |
| **Max:** | 332K | 1M0 | | 332K | 1M0 | | 332K | 1M0 | | 511K | 2M0 | | 511K | 2M0 | | 511K | 2M0 | |
| **Tolerance (%):** | 0.1 | | | 0.5 | | | 1 | | | 0.1 | | | 0.5 | | | 1 | | |
| **Code letter:** | B | | | D | | | F | | | B | | | D | | | F | | |
| **Selection Series:** | E24 & E96 | | | | | | | | | E24 & E96 | | | | | | | | |
| **Temp. Coefficient (ppm/°C):** | 15 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 |
| **Code Letter:** | D | E | C | D | E | C | D | E | C | D | E | C | D | E | C | D | E | C |
| **Limiting Element Voltage:** | 50V | | | | | | | | | 100V | | | | | | | | |
| **Max. Overload Voltage:** | 100V | | | | | | | | | 200V | | | | | | | | |
| **Operating Temp. Range:** | -55 to +155°C | | | | | | | | | -55 to +155°C | | | | | | | | |
| **Climatic Category (°C):** | 55/125/55 | | | | | | | | | 55/125/55 | | | | | | | | |
| **Insulation Resistance Dry Min:** | 1000MΩ | | | | | | | | | 1000MΩ | | | | | | | | |
| **Stability:** | 0.5% | | | | | | | | | 0.5% | | | | | | | | |



Dimensions are in millimeters and inches unless otherwise specified. Values in brackets are standard equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

# Type CPF Series

| | | 1206 | | | | | | | | | 1210 | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Rated Power @ 70°C:** | | 0.125W | | | | | | | | | 0.2W | | | | | | | | |
| **Resistance Range (Ohms)** | **Min:** | 4R7 | 4R7 | | 4R7 | 1R0 | | 4R7 | 1R0 | | 4R7 | 4R7 | | 4R7 | 1R0 | | 4R7 | 1R0 | |
| | **Max:** | 1M0 | 2M5 | | 1M0 | 2M5 | | 1M0 | 2M5 | | 1M0 | 2M5 | | 1M0 | 2M5 | | 1M0 | 2M5 | |
| **Tolerance (%):** | | 0.1 | | | 0.5 | | | 1 | | | 0.1 | | | 0.5 | | | 1 | | |
| **Code letter:** | | B | | | D | | | F | | | B | | | D | | | F | | |
| **Selection Series:** | | E24 & E96 | | | | | | | | | E24 & E96 | | | | | | | | |
| **Temp. Coefficient (ppm/°C):** | | 15 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 |
| **Code Letter:** | | D | E | C | D | E | C | D | E | C | D | E | C | D | E | C | D | E | C |
| **Limiting Element Voltage:** | | 150V | | | | | | | | | 150V | | | | | | | | |
| **Max. Overload Voltage:** | | 300V | | | | | | | | | 300V | | | | | | | | |
| **Operating Temp. Range:** | | -55 to +155°C | | | | | | | | | -55 to +155°C | | | | | | | | |
| **Climatic Category (°C):** | | 55/125/55 | | | | | | | | | 55/125/55 | | | | | | | | |
| **Insulation Resistance Dry Min:** | | 1000MΩ | | | | | | | | | 1000MΩ | | | | | | | | |
| **Stability:** | | 0.5% | | | | | | | | | 0.5% | | | | | | | | |

| | | 2010 | | | | | | | | | 2512 | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Rated Power @ 70°C:** | | 0.25W | | | | | | | | | 0.5W | | | | | | | | |
| **Resistance Range (Ohms)** | **Min:** | 4R7 | 4R7 | | 4R7 | 1R0 | | 4R7 | 1R0 | | 4R7 | 4R7 | | 4R7 | 1R0 | | 4R7 | 1R0 | |
| | **Max:** | 1M0 | 3M0 | | 1M0 | 3M0 | | 1M0 | 3M0 | | 1M0 | 3M0 | | 1M0 | 3M0 | | 1M0 | 3M0 | |
| **Tolerance (%):** | | 0.1 | | | 0.5 | | | 1 | | | 0.1 | | | 0.5 | | | 1 | | |
| **Code letter:** | | B | | | D | | | F | | | B | | | D | | | F | | |
| **Selection Series:** | | E24 & E96 | | | | | | | | | E24 & E96 | | | | | | | | |
| **Temp. Coefficient (ppm/°C):** | | 15 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 | 15 | 25 | 50 |
| **Code Letter:** | | D | E | C | D | E | C | D | E | C | D | E | C | D | E | C | D | E | C |
| **Limiting Element Voltage:** | | 150V | | | | | | | | | 150V | | | | | | | | |
| **Max. Overload Voltage:** | | 300V | | | | | | | | | 300V | | | | | | | | |
| **Operating Temp. Range:** | | -55 to +155°C | | | | | | | | | -55 to +155°C | | | | | | | | |
| **Climatic Category (°C):** | | 55/125/55 | | | | | | | | | 55/125/55 | | | | | | | | |
| **Insulation Resistance Dry Min:** | | 1000MΩ | | | | | | | | | 1000MΩ | | | | | | | | |
| **Stability:** | | 0.5% | | | | | | | | | 0.5% | | | | | | | | |

## Characteristics - Environmental

| Item | Requirement | | Test Method |
|---|---|---|---|
| | **Tol. ≤ 0.05%** | **Tol. > 0.05%** | |
| **Temperature Coefficient of Resistance (TCR):** | AS per TCRs specified in value range table on page 1 | | +25/-55/+25/+125/+25°C |
| **Short Time Overload:** | ΔR ±0.05% | ΔR ±0.2% | RCWV* 2.5 or max. overload voltage for 5 seconds |
| | ΔR ±0.2% for high power rating | | |
| **Insulation Resistance:** | >1000MΩ | | Apply 100VDC for 1 minute |
| **Endurance:** | ΔR ±0.05% | ΔR ±0.2% | 70 ±2°C, max. working voltage for 1000hrs with 1.5hrs "ON" and 0.5 hrs "OFF" |
| | >7kΩ ΔR ±0.5% | | |
| | ΔR ±0.5% for high power rating | | |
| **Damp Heat with Load:** | ΔR ±0.05% | ΔR ±0.3% | 40 ±2°C, 90 - 95% R.H. max. working voltage hrs with 1.5hrs "ON" and 0.5hrs "OFF" |
| | ΔR ±0.5% for high power rating | | |
| **Bending Strength:** | ΔR ±0.05% | ΔR ±0.2% | Bending amplitude 3mm for 10 seconds |
| **Solderability:** | 95% min. coverage | | 245 ±5°C for 3 seconds |
| **Resistance to Soldering Heat:** | ΔR ±0.05% | ΔR ±0.2% | 260 ±5°C for 10 seconds |
| **Dielectric Withstand Voltage:** | By Type | | Max. overload voltage for 1 minute |
| **Thermal Shock:** | ΔR ±0.05% | ΔR ±0.25% | -55°C to +150°C, 100 cycles |
| **Low Temperature Operation:** | ΔR ±0.05% | ΔR ±0.2% | 1 hour, -65°C, followed by 45 minutes of RCWV |
| | ΔR ±0.5% for high power rating | | |

**Reference Standards: MIL-STD-202, JIS-C 5201-1**

**Storage Temperature: 25±3°C; Humidity < 80%RH**



Dimensions are in millimeters and inches unless otherwise specified. Values in brackets are standard equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

# Type CPF Series

## Marking Codes - Case Sizes 0805 to 2512

### IEC 4 Digit Marking

| | | | | | |
|---|---|---|---|---|---|
| **Resistance:** | 100Ω | 2.2KΩ | 10KΩ | 49.9KΩ | 100KΩ |
| **Marking Code:** | 1000 | 2201 | 1002 | 4992 | 1003 |

## Case Sizes 0603

### E24 3 Digit Marking - Example: 101=100Ω 102=1KΩ

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **E24** | 10 | 11 | 12 | 13 | 15 | 16 | 18 | 20 | 22 | 24 | 27 | 30 |
| | 33 | 36 | 39 | 43 | 47 | 51 | 56 | 62 | 68 | 75 | 82 | 91 |

### E96 3 Digit Marking - Examples: 14C=13K7Ω, 13C=13K3Ω, 68B=4K99Ω, 68X=49.9Ω

### 0603 E96 Marking Code Table

| Code | E96 | Code | E96 | Code | E96 | Code | E96 |
|---|---|---|---|---|---|---|---|
| 01 | 100 | 25 | 178 | 49 | 316 | 73 | 562 |
| 02 | 102 | 26 | 182 | 50 | 324 | 74 | 576 |
| 03 | 105 | 27 | 187 | 51 | 332 | 75 | 590 |
| 04 | 107 | 28 | 191 | 52 | 340 | 76 | 604 |
| 05 | 110 | 29 | 196 | 53 | 348 | 77 | 619 |
| 06 | 113 | 30 | 200 | 54 | 357 | 78 | 634 |
| 07 | 115 | 31 | 205 | 55 | 365 | 79 | 649 |
| 08 | 118 | 32 | 210 | 56 | 374 | 80 | 665 |
| 09 | 121 | 33 | 215 | 57 | 383 | 81 | 681 |
| 10 | 124 | 34 | 221 | 58 | 392 | 82 | 698 |
| 11 | 127 | 35 | 226 | 59 | 402 | 83 | 715 |
| 12 | 130 | 36 | 232 | 60 | 412 | 84 | 732 |
| 13 | 133 | 37 | 237 | 61 | 422 | 85 | 750 |
| 14 | 137 | 38 | 243 | 62 | 432 | 86 | 768 |
| 15 | 140 | 39 | 249 | 63 | 442 | 87 | 787 |
| 16 | 143 | 40 | 255 | 64 | 453 | 88 | 806 |
| 17 | 147 | 41 | 261 | 65 | 464 | 89 | 825 |
| 18 | 150 | 42 | 267 | 66 | 475 | 90 | 845 |
| 19 | 154 | 43 | 274 | 67 | 487 | 91 | 866 |
| 20 | 158 | 44 | 280 | 68 | 499 | 92 | 887 |
| 21 | 162 | 45 | 287 | 69 | 511 | 93 | 909 |
| 22 | 165 | 46 | 294 | 70 | 523 | 94 | 931 |
| 23 | 169 | 47 | 301 | 71 | 536 | 95 | 953 |
| 24 | 174 | 48 | 309 | 72 | 549 | 96 | 976 |

| Code | A | B | C | D | E | F | G | H | X | Y | Z |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Multiplier | $10^0$ | $10^1$ | $10^2$ | $10^3$ | $10^4$ | $10^5$ | $10^6$ | $10^7$ | $10^{-1}$ | $10^{-2}$ | $10^{-3}$ |



Dimensions are in millimeters and inches unless otherwise specified. Values in brackets are standard equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

# Type CPF Series

## Power Derating Curve




For resistors operated in ambient temperatures above 70°C, power rating must be derated in accordance with this curve.

## Dimensions







| | | |
|---|---|---|
| 1. Alumina Substrate | 4. Edge Electrode (NiCr) | 7. Resistor Layer (NiCr) |
| 2. Bottom Electrode (Ag) | 5. Barrier Layer (Ni) | 8. Overcoat (Epoxy) |
| 3. Top Electrode (Ag-Pd) | 6. External Electrode (Sn) | 9. Marking |

| Part Number | L | W | H | a | b | Weight (g) 1000 pieces |
|---|---|---|---|---|---|---|
| **CPF0201** | 0.58 ±0.05 | 0.29 ±0.05 | 0.23 ±0.05 | 0.12 ±0.05 | 0.15 ±0.05 | 0.14 |
| **CPF0402** | 1.00 ±0.05 | 0.50 ±0.05 | 0.30 ±0.05 | 0.20 ±0.10 | 0.20 ±0.10 | 0.54 |
| **CPF0603** | 1.55 ±0.10 | 0.80 ±0.10 | 0.45 ±0.10 | 0.30 ±0.20 | 0.30 ±0.20 | 1.83 |
| **CPF0805** | 2.00 ±0.15 | 1.25 ±0.15 | 0.55 ±0.10 | 0.30 ±0.20 | 0.40 ±0.25 | 4.71 |
| **CPF1206** | 3.05 ±0.15 | 1.55 ±0.15 | 0.55 ±0.10 | 0.42 ±0.20 | 0.35 ±0.25 | 9.02 |
| **CPF1210** | 3.10 ±0.15 | 2.40 ±0.15 | 0.55 ±0.10 | 0.40 ±0.20 | 0.55 ±0.25 | 10.00 |
| **CPF2010** | 4.90 ±0.15 | 2.40 ±0.15 | 0.55 ±0.10 | 0.60 ±0.30 | 0.50 ±0.25 | 23.61 |
| **CPF2512** | 6.30 ±0.15 | 3.10 ±0.15 | 0.55 ±0.10 | 0.60 ±0.30 | 0.50 ±0.25 | 38.08 |

## Recommend Land Pattern




| Type | A | B | C |
|---|---|---|---|
| **CPF0201** | 0.25 | 0.3 | 0.40 ±0.2 |
| **CPF0402** | 0.5 | 0.5 | 0.60 ±0.2 |
| **CPF0603** | 0.8 | 1.0 | 0.90 ±0.2 |
| **CPF0805** | 1.0 | 1.0 | 1.35 ±0.2 |
| **CPF1206** | 2.0 | 1.15 | 1.70 ±0.2 |
| **CPF1210** | 2.0 | 1.15 | 2.50 ±0.2 |
| **CPF2010** | 3.6 | 1.4 | 2.50 ±0.2 |
| **CPF2512** | 4.9 | 1.6 | 3.10 ±0.2 |



Dimensions are in millimeters and inches unless otherwise specified. Values in brackets are standard equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

# Type CPF Series

## Packaging Quantity & Reel Specifications




| Type | øA | øB | øC | W | T | Paper Tape (EA) | Embossed Plastic Tape (EA) |
|---|---|---|---|---|---|---|---|
| **CPF0201** | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ±0.7 | 9.5 ±1.0 | 11.5 ±1.0 | 1000 / 5000 | - |
| **CPF0402** | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ±0.7 | 9.5 ±1.0 | 11.5 ±1.0 | 1000 / 5000 | - |
| **CPF0603** | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ±0.7 | 9.5 ±1.0 | 11.5 ±1.0 | 1000 / 5000 | - |
| **CPF0805** | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ±0.7 | 9.5 ±1.0 | 11.5 ±1.0 | 1000 / 5000 | - |
| **CPF1206** | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ±0.7 | 9.5 ±1.0 | 11.5 ±1.0 | 1000 / 5000 | - |
| **CPF1210** | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ±0.7 | 9.5 ±1.0 | 11.5 ±1.0 | 1000 / 5000 | - |
| **CPF2010** | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ±0.7 | 13.5 ±1.0 | 15.5 ±1.0 | - | 4000 |
| **CPF2512** | 178.0 ±1.0 | 60.0 +1.0 | 13.5 ±0.7 | 13.5 ±1.0 | 15.5 ±1.0 | - | 4000 |

## Paper Tape Specification




| Type | A | B | W | E | F | $P_0$ | $P_1$ | $P_2$ | ø$D_0$ | T |
|---|---|---|---|---|---|---|---|---|---|---|
| **CPF0201** | 0.40 ±0.05 | 0.70 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.10 | 2.00 ±0.05 | 2.00 ±0.05 | 1.55 ±0.03 | 0.42 ±0.02 |
| **CPF0402** | 0.70 ±0.05 | 1.16 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.10 | 2.00 ±0.05 | 2.00 ±0.05 | 1.55 ±0.05 | 0.40 ±0.03 |
| **CPF0603** | 1.10 ±0.05 | 1.90 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.10 | 4.00 ±0.10 | 2.00 ±0.05 | 1.55 ±0.05 | 0.60 ±0.03 |
| **CPF0805** | 1.60 ±0.05 | 2.37 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.10 | 4.00 ±0.10 | 2.00 ±0.05 | 1.55 ±0.05 | 0.75 ±0.05 |
| **CPF1206** | 2.00 ±0.05 | 3.55 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.10 | 4.00 ±0.10 | 2.00 ±0.05 | 1.55 ±0.05 | 0.75 ±0.05 |
| **CPF1210** | 2.75 ±0.05 | 3.40 ±0.05 | 8.00 ±0.10 | 1.75 ±0.05 | 3.5 ±0.05 | 4.00 ±0.05 | 4.00 ±0.10 | 2.00 ±0.05 | 1.60 ±0.10 | 0.75 ±0.05 |



Dimensions are in millimeters and inches unless otherwise specified. Values in brackets are standard equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

# Type CPF Series

## Embossed Plastic Tape Specifications




| Type | A | B | W | E | F | $P_0$ | $P_1$ | $P_2$ | ø$D_0$ | T |
|---|---|---|---|---|---|---|---|---|---|---|
| **CPF2010** | 2.85 ±0.10 | 5.45 ±0.10 | 12.0 ±0.10 | 1.75 ±0.10 | 5.5 ±0.05 | 4.00 ±0.05 | 4.00 ±0.10 | 2.00 ±0.05 | 1.50 +0.10 | 1.00 ±0.20 |
| **CPF2512** | 3.40 ±0.10 | 6.65 ±0.10 | 12.0 ±0.10 | 1.75 ±0.10 | 5.5 ±0.05 | 4.00 ±0.05 | 4.00 ±0.10 | 2.00 ±0.05 | 1.50 +0.10 | 1.00 ±0.20 |

## How to Order

| CPF | 0603 | B | 100R | E | 1 |
|---|---|---|---|---|---|
| **Common Part** | **Package Size** | **Tolerance** | **Value** | **TCR** | **Packaging** |
| CPF - Chip precision film resistor | 0201 1206<br>0402 1210<br>0603 2010<br>0805 2512 | B - ± 0.1%<br>D - ±0.5%<br>F - ± 1% | 100R (100 Ohms)<br>1K0 (1000 Ohms)<br>100K (100,000 Ohms) | D - 15ppm<br>E - 25ppm<br>C - 50ppm | 1 - 1K REEL<br>Blank - 5K REEL |

TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.
Other logos, product and Company names mentioned herein may be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this datasheet, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this datasheet are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

**Данный компонент на территории Российской Федерации**

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

**Офис по работе с юридическими лицами:**

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9