Type 124

TYPE 124

Single Pole Normally Open, or Single Pole Double Throw Contacts. Dust Resistant and Endcaps are Isolated from Bracket

SPECIFICATIONS

Dimensions, 124-105111,-114111,-117111 .... 3.56″L x 3.13″W x 2.19″H
Dimensions, 124-305111,-314111 ..... 4.69″L x 3.13″W x 2.19″H
Weight, 124-105111,-114111,-117111 ..... 16.0 oz.
Weight, 124-305111,-314111 ..... 19.0 oz.
Temperature Range ..... -40° to +149°F
Terminations, Contacts ..... 5/16″-24 UNF-2A thread
Terminations, Coil ..... #10-32 UNF-2A thread
Recommended Mounting ..... Vertical plane with coil terminals up
Hardware Torque, Contact Terminal ..... 60 in. lbs. max.
Hardware Torque, Coil Terminal ..... 12-18 in. lbs.

Caution: A back-up wrench must be used to hold the bottom nut stationary.

Model Number	Duty Cycle	Terminal Type ①	Bracket Style	Coil Voltage D.C.	Coil Resistance (Ohms) ②	Contact Material	Contact Rating (Amps) – Inductive Load: Voltage D.C.	Normally Open: Continuous	Normally Open: Inrush	Normally Closed: Continuous	Normally Closed: Inrush
124-105111	Continuous	4	Standard	12	13.2	Silver Alloy	12	100	400	–	–
124-114111	Continuous	4	Standard	24	53.0	Silver Alloy	24	100	400	–	–
124-314111	Continuous	6	Standard	24	53.0	Silver Alloy	24	100	400	50	100
124-117111	Continuous	4	Standard	36	120.0	Silver Alloy	36	100	400	–	–
124-317111	Continuous	6	Standard	36	120.0	Silver Alloy	36	100	400	50	100

① "4" = Isolated Coil, SPNO
"6" = Isolated Coil, SPDT
② Coil resistance in Ohms @ 25°C
③ Inrush Current: Current applied within the first 1/2 second of contact closure

Type 586 SPNO

TYPE 586

Single Pole Normally Open, or Single Pole Double Throw Contacts. Water Resistant and Case is Isolated from Bracket

SPECIFICATIONS

Dimensions, 586-114111,-117111 ..... 3.69″L x 3.30″W x 2.90″H
Dimensions, 586-317111 ..... 4.61″L x 3.30″W x 2.90″H
Weight, 586-114111,-117111 ..... 24.0 oz.
Weight, 586-317111 ..... 26.0 oz.
Temperature Range ..... -40° to +149°F
Terminations, Contacts ..... 5/16″-24 UNF-2A thread
Terminations, Coil ..... #10-32 UNF-2A thread
Recommended Mounting ..... Vertical plane with coil terminals up
Hardware Torque, Contact Terminal ..... 60 in. lbs. max.
Hardware Torque, Coil Terminal ..... 12-18 in. lbs.

Model Number	Duty Cycle	Terminal Type ①	Bracket Style	Coil Voltage D.C.	Coil Resistance (Ohms) ②	Contact Material	Contact Rating (Amps) – Inductive Load: Voltage D.C.	Normally Open: Continuous	Normally Open: Inrush③	Normally Closed: Continuous	Normally Closed: Inrush③
586-105111	Continuous	4	Standard	12	21.0	Silver Alloy	12	200	600	–	–
586-108111 ④	Continuous	4	Standard	15	32.8	Silver Alloy	15	200	600	–	–
586-114111	Continuous	4	Standard	24	84.0	Silver Alloy	24	200	600	–	–
586-117111	Continuous	4	Standard	36	189.0	Silver Alloy	36	200	600	–	–
586-120111	Continuous	4	Standard	48	336.0	Silver Alloy	36	200	600	–	–
586-314111	Continuous	6	Standard	24	84.0	Silver Alloy	24	200	600	100	200
586-317111	Continuous	6	Standard	36	120.0	Silver Alloy	36	200	600	100	200

① "4" = Isolated Coil, SPNO
"6" = Isolated Coil, SPDT
② Coil resistance in Ohms @ 25°C
③ Inrush Current: Current applied within the first 1/2 second of contact closure
④ Ideal for 12V charging systems

NOTE: CAUTION must be used in coil selection for use in 12 volt sytems where battery charging may expose coil to continuous, higher-than-rated voltage. 15 volt coils are recommended. White-Rodgers will not be responsible for consequences of misapplied solenoids.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9