

NPC-1210 Series

NovaSensor Medium/Low Pressure Sensors



Features

- High sensitivity
- High accuracy
- Interchangeable
- Temperature compensated 0°C to 60°C (32°F to 140°F)
- PCB mountable package
- DIP package
- Solid-state reliability
- Individual device traceability

Applications

- Industrial automation
- Air flow monitors
- Process control
- Medical equipment
- Underground cable leak detection
- Ventilation
- Respirator monitoring

NPC-1210 Series Specifications

Description

The NPC-1210 series of solid-state pressure sensors are designed to provide a cost effective solution for applications that require calibrated performance over a wide temperature range. Packaged in a dual-in-line configuration, the NPC-1210 Series is intended for printed circuit board mounting. Optional pressure port and lead configurations provide superior flexibility in low profile applications where pressure connection orientation is critical.

The NPC-1210 series is based on NovaSensor's advanced SenStable® piezoresistive sensing technology. Silicon micromachining techniques are used to ion implant piezoresistive strain gages into a Wheatstone bridge configuration. The NPC-1210 Series offers the added advantage of superior temperature performance over the temperature compensated range of 0°C to 60°C (32°F to 140°F). A gain set resistor is included to normalize the FSO for field interchangeability.



NPC-1210 Series Schematic Diagram



NPC-1210 Series Package Diagram

NPC-1210 Series Specifications

Medium Pressure Sensors

Pressure Ranges

- Gauge and differential:
 - 5 psi (34 kPa, 0.34 bar)
 - 15 psi (100 kPa, 1.0 bar)
 - 30 psi (210 kPa, 2.1 bar)
 - 50 psi (340 kPa, 3.4 bar)
 - 100 psi (690 kPa, 6.9 bar)
- Absolute:
 - 15 psi (100 kPa, 1.0 bar)
 - 30 psi (210 kPa, 2.1 bar)
 - 50 psi (340 kPa, 3.4 bar)
 - 100 psi (690 kPa, 6.9 bar)
- For other pressure ranges, please contact NovaSensor.

| Parameter | Value | Units | Notes |
|----------------------|------------|-------|-----------------|
| Environmental | | | |
| Temperature Range | | | |
| <i>Operating</i> | -40 to 125 | °C | (-40° to 257°F) |
| <i>Compensated</i> | 0 to 60 | °C | (32°F to 140°F) |
| <i>Storage</i> | -55 to 150 | °C | (-67 to 302 °F) |

| Mechanical | | | |
|--|-----------------------------------|---|------------|
| Weight | 2.5 | g | (0.005 lb) |
| Media Compatibility | Compatible with exposed materials | | 7 |
| <i>Positive differential and gauge ports</i> | <i>Dry gases only</i> | | |
| <i>Absolute. negative differential ports</i> | <i>Dry gases only</i> | | |

| Parameter | Units | Minimum | Typical | Maximum | Notes |
|------------------------------------|-------|---------|---------|---------|---------|
| Performance Parameters * | | | | | |
| FS Output (FSO) | mV | 75 | 100 | 150 | 2, 3 |
| Zero Pressure Output | mV | -2 | — | 2 | 3 |
| Linearity | %FSO | -0.1 | — | 0.1 | 4, 8 |
| Pressure Hysteresis | %FSO | -0.1 | — | 0.1 | |
| Input Impedance | Ω | 2500 | 4000 | 6000 | |
| Output Impedance | Ω | 4000 | 5000 | 6000 | |
| Thermal Accuracy–Span | %FSO | -0.5 | — | 0.5 | 3, 5, 8 |
| Thermal Accuracy–Zero | %FSO | -0.5 | — | 0.5 | 3, 5, 8 |
| Temperature Coefficient–Resistance | %/°C | — | 0.2 | — | 5 |
| Thermal Hysteresis–Zero | %FSO | — | 0.1 | — | 5 |
| Input Excitation | mA | — | 1.5 | 2.0 | |
| Pressure Overload | Rated | — | — | 3X | 6 |

Low Pressure Sensors

Pressure Ranges

- Gauge and differential:
 - 10 in H₂O (2.5 kPa, 0.025 bar)
 - 1 psi (6.9 kPa, 0.069 bar)

| Parameter | Value | Units | Notes |
|----------------------|------------|-------|-----------------|
| Environmental | | | |
| Temperature Range | | | |
| <i>Operating</i> | -40 to 125 | °C | (-40° to 257°F) |
| <i>Compensated</i> | 0 to 60 | °C | (32°F to 140°F) |
| <i>Storage</i> | -55 to 150 | °C | (-67 to 302 °F) |

| Mechanical | | | |
|--|-----------------------------------|---|------------|
| Weight | 2.5 | g | (0.005 lb) |
| Media Compatibility | Compatible with exposed materials | | 7 |
| <i>Positive differential and gauge ports</i> | <i>Dry gases only</i> | | |
| <i>Absolute. negative differential ports</i> | <i>Dry gases only</i> | | |

| Parameter | Units | Minimum | Typical | Maximum | Notes |
|------------------------------------|-----------|----------|---------|---------|-------|
| Performance Parameters * | | | | | |
| FSO 10 inH ₂ O | mV | 25 | 50 | 70 | 2, 3 |
| FSO 1 psi | mV | 50 | 75 | 110 | 2, 3 |
| Zero Pressure Output | mV | -2 | — | 2 | 3 |
| Linearity | %FSO | -0.5 | — | 0.5 | 4 |
| Pressure Hysteresis | %FSO | -0.1 | — | 0.1 | |
| Input Impedance | Ω | 2500 | 4000 | 6000 | |
| Output Impedance | Ω | 4000 | 5000 | 6000 | |
| Thermal Accuracy–Span | %FSO | -1.0 | — | 1.0 | 3, 5 |
| Thermal Accuracy–Zero | %FSO | -1.25 | — | 1.25 | 3, 5 |
| Temperature Coefficient–Resistance | %/°C | — | 0.22 | — | 5 |
| Thermal Hysteresis–Zero | %FSO | — | 0.1 | — | 5 |
| Input Excitation | mA | — | 1.5 | 2.0 | |
| Pressure Overload | psi (bar) | 5 (0.34) | — | — | 6 |

- * 1. Supply current = 1.5 mA and ambient temperature = 77°F (25°C), unless otherwise noted. Gauge and differential pressure devices are calibrated by applying pressure to the positive differential port (P2) and venting to atmosphere the reference port (P1).
2. Output span of unamplified sensor.
3. Compensation resistors are an integral part of the sensor package; no additional external resistors are required. Pins 7 and 8 must be kept open. The NPC-1210 is interchangeable only when used with the gain set resistor shown in the schematic diagram. Maximum gain-set resistor mismatch is 2%.
4. Best fit straight line.
5. Temperature range 32°F to 140°F (0°C to 60°C), reference to 77°F (25°C).
6. 3X or 200 psi (13.78 bar) maximum, whichever is less.
7. Exposed materials are pyrex, ceramic, silicon, epoxy, RTV, and stainless steel.
8. 5 psi (0.34 bar) spec.: Linearity: 0.25 ±%FSO, TC-span: 0.75 ±%FSO, TC-zero: 0.75 ±%FSO. otherwise noted.

NPC-1210 Series Specifications

Ordering Information

The code number to be ordered may be specified as follows:

NPC-1210 (Medium Pressure)

| | | | | | | | | |
|---|---|--|---------------------|---|----------------|-----------------------------------|---------------------|---|
| ↓ | Code 005 015 030 050 100 | Pressure Range 5 psi (0.3 bar) 15 psi (1 bar) 30 psi (2 bar) 50 psi (3.4 bar) 100 psi (7 bar) | Code D A G | Type Differential Absolute Gauge | Code 1 3 | Lead Configurations Up Down | Code L S N | Tube Options Long Short None * |
| NPC-1210 - _ - _ - _ - _ Typical model number | | | | | | | | |

* Order NPC-1210-XXXG-XN in place of NPC-1210-XXXD-XN

The code number to be ordered may be specified as follows:

NPC-1210 (Low Pressure)

| | | | | | | | | |
|---|--------------------|---|----------------|-------------------------------|----------------|-----------------------------------|----------------|-------------------------------|
| ↓ | Code 10W 001 | Pressure Range 10 in H ₂ O (25 mbar) 1 psi (69 mbar) | Code D G | Type Differential Gauge | Code 1 3 | Lead Configurations Up Down | Code L S | Tube Options Long Short |
| NPC-1210 - _ - _ - _ - _ Typical model number | | | | | | | | |

Warranty

Amphenol Advanced Sensors warrants its products against defects in material and workmanship for 12 months from the date of shipment. Products not subjected to misuse will be repaired or replaced. Amphenol Advanced Sensors reserves the right to make changes without further notice to any products herein. NovaSensor makes no warranty, representation or guarantee regarding the suitability of its products for any particular application, nor does Amphenol Advanced Sensors assume any liability arising out of the application or use of any product or circuit and specifically disclaims and all liability without limitation consequential or incidental damages. The foregoing warranties are exclusive and in lieu of all other warranties, whether written, oral, implied or statutory. No implied statutory warranty of merchantability or fitness for particular purpose shall apply.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

[NPC-1210-001G-1-L](#) [NPC-1210-001G-1-N](#) [NPC-1210-005D-1-L](#) [NPC-1210-005D-1-S](#) [NPC-1210-005G-1-L](#) [NPC-1210-005G-1-N](#) [NPC-1210-005G-1-S](#) [NPC-1210-015G-1-L](#) [NPC-1210-015G-1-N](#) [NPC-1210-015G-1-S](#) [NPC-1210-030A-1-L](#) [NPC-1210-030D-1-L](#) [NPC-1210-030G-1-L](#) [NPC-1210-030G-1-N](#) [NPC-1210-050A-1-L](#) [NPC-1210-050A-1-S](#) [NPC-1210-050D-1-L](#) [NPC-1210-050D-1-S](#) [NPC-1210-050G-1-L](#) [NPC-1210-050G-1-N](#) [NPC-1210-050G-1-S](#) [NPC-1210-100A-1-L](#) [NPC-1210-100A-1-S](#) [NPC-1210-100D-1-L](#) [NPC-1210-100G-1-L](#) [NPC-1210-100G-1-S](#) [NPC-1210-10WD-1-L](#) [NPC-1210-10WD-1-S](#) [NPC-1210-10WG-1-L](#) [NPC-1210-10WG-1-N](#) [NPC-1210-10WG-1-S](#) [NPC-1210-015A-1-N](#) [NPC-1210-015G-3-N](#) [NPC-1210-030A-1-N](#) [NPC-1210-030A-3-N](#) [NPC-1210-030A-3-S](#) [NPC-1210-030D-3-L](#) [NPC-1210-030D-3-S](#) [NPC-1210-030G-3-N](#) [NPC-1210-050A-1-N](#) [NPC-1210-050A-3-L](#) [NPC-1210-050A-3-N](#) [NPC-1210-050A-3-S](#) [NPC-1210-050D-3-S](#) [NPC-1210-100A-1-N](#) [NPC-1210-100A-3-N](#) [NPC-1210-100A-3-S](#) [NPC-1210-100G-1-N](#) [NPC-1210-015A-3N](#)

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9