

Manufactured in line with the requirements of MIL 18546 and IEC 115, designed for direct heatsink mounting with thermal compound to achieve maximum performance.

- High Power to volume
- Wound to maximise High Pulse Capability
- Values from R005 to 100K
- Custom designs welcome
- RoHS Compliant



## Characteristics

|                                    |  |
|------------------------------------|--|
| Tolerance (Code):                  | Standard $\pm 5\%$ (J) and $\pm 10\%$ (K). Also available $\pm 1\%$ (F), $\pm 2\%$ (G) and $\pm 3\%$ (H) |
| Tolerance for low $\Omega$ values: | Typically $\geq R05 \pm 5\% \leq R047 \pm 10\%$  |
| Temperature coefficients:          | Typical values $< 1K$ 100ppm Std. $> 1K$ 25ppm Std. For lower TCR's please contact Arcol                 |
| Insulation resistance (Dry):       | 10,000 M $\Omega$ minimum  |
| Power dissipation:                 | At high ambient temperature dissipation derates linearly to zero at 200°C                                |
| Ohmic values:                      | From R005 to 100K depending on wattage size  |
| Low inductive (NHS):               | Specify by adding N before HS Series code, e.g. NHS50  |
| NHS ohmic value:                   | Divide standard HS maximum value by 4  |
| NHS working volts:                 | Divide standard HS maximum working voltage by 1.414  |

## Temp. Rise & Power Dissipation

Surface temperature of resistor related to power dissipation. The resistor is standard heatsink mounted using a proprietary heatsink compound.



## Heat Dissipation

Heat dissipation: Whilst the use of proprietary heat sinks with lower thermal resistances is acceptable, uprating is not recommended. For maximum heat transfer it is recommended that a heat sink compound be applied between the resistor base and heat sink chassis mounting surface. It is essential that the maximum hot spot temperature of 200°C is not exceeded, therefore, the resistor must be mounted on a heat sink of correct thermal resistance for the power being dissipated.

## Ordering Procedure

Standard Resistor. To specify standard: Series, Watts, Ohmic Value, Tolerance Code, e.g.: HS25 2R2 J

Non Inductive Resistor. To specify add N, e.g.: NHS100 10R J

ARCOL UK Limited,  
Threemilestone Ind. Estate,  
Truro, Cornwall, TR4 9LG, UK.  
T +44 (0) 1872 277431  
F +44 (0) 1872 222002  
E sales@arcolresistors.com

[www.arcolresistors.com](http://www.arcolresistors.com)

The information contained herein does not form part of a contract and is subject to change without notice. ARCOL operate a policy of continual product development, therefore, specifications may change.

It is the responsibility of the customer to ensure that the component selected from our range is suitable for the intended application. If in doubt please ask ARCOL.

## Electrical Specifications

| Size  | Style MIL-R 18546 | Power rating on std. heatsink @25°C | Watts with no heatsink @25°C | Resistance range | Limiting element voltage | Voltage proof AC Peak | Voltage proof AC rms. | Approx weight gms | Typical surface rise HS mounted | Standard heatsink |              |
|-------|-------------------|-------------------------------------|------------------------------|------------------|--------------------------|-----------------------|-----------------------|-------------------|---------------------------------|-------------------|--------------|
|       |                   |                                     |                              |                  |                          |                       |                       |                   |                                 | cm <sup>2</sup>   | Thickness mm |
| HS10  | RE 60             | 10                                  | 5                            | R005-10K         | 160                      | 1400                  | 1000                  | 4                 | 5.8                             | 415               | 1            |
| HS15  | RE 65             | 15                                  | 7                            | R005-10K         | 265                      | 1400                  | 1000                  | 7                 | 5.1                             | 415               | 1            |
| HS25  | RE 70             | 25                                  | 9                            | R005-36K         | 550                      | 3500                  | 2500                  | 14                | 4.2                             | 535               | 1            |
| HS50  | RE 75             | 50                                  | 14                           | R01-86K          | 1250                     | 3500                  | 2500                  | 32                | 3.0                             | 535               | 1            |
| HS75  |                   | 75                                  | 24                           | R01-50K          | 1400                     | 6363                  | 4500                  | 85                | 1.1                             | 995               | 3            |
| HS100 |                   | 100                                 | 30                           | R01-70K          | 1900                     | 6363                  | 4500                  | 115               | 1.0                             | 995               | 3            |
| HS150 |                   | 150                                 | 45                           | R01-100K         | 2500                     | 6363                  | 4500                  | 175               | 1.0                             | 995               | 3            |
| HS200 |                   | 200                                 | 50                           | R01-50K          | 1900                     | 7070                  | 5000                  | 475               | 0.7                             | 3750              | 3            |
| HS250 |                   | 250                                 | 55                           | R01-50K          | 2200                     | 7070                  | 5000                  | 600               | 0.6                             | 4765              | 3            |
| HS300 |                   | 300                                 | 60                           | R01-68K          | 2500                     | 7070                  | 5000                  | 700               | 0.6                             | 5780              | 3            |

## HS10-HS300 Standard Resistor



## Dimensions (mm)

| Size  | A Max | B Max | C Max | D Max | E Max | F±0.3 | G±0.3 | H Max | J Max | K Max | L ±0.25* | M Max |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|----------|-------|
| HS10  | 16.5  | 30.0  | 8.8   | 8.5   | 15.9  | 11.3  | 12.4  | 4.5   | 2.4   | 1.8   | 2.4      |       |
| HS15  | 21.0  | 36.5  | 11.0  | 11.2  | 19.9  | 14.3  | 15.9  | 5.5   | 2.8   | 1.8   | 2.4      |       |
| HS25  | 28.0  | 51.0  | 14.8  | 14.2  | 27.3  | 18.3  | 19.8  | 7.7   | 5.2   | 2.6   | 3.2      |       |
| HS50  | 28.0  | 72.5  | 14.8  | 14.2  | 49.1  | 39.7  | 21.4  | 8.4   | 5.2   | 2.6   | 3.2      |       |
| HS75  | 47.5  | 72.0  | 24.1  | 27.3  | 48.7  | 29.0  | 37.0  | 11.8  | 10.4  | 3.7   | 4.4      |       |
| HS100 | 47.5  | 88.0  | 24.1  | 27.3  | 65.2  | 35.0  | 37.0  | 11.8  | 15.4  | 3.7   | 4.4      |       |
| HS150 | 47.5  | 121.0 | 24.1  | 27.3  | 97.7  | 58.0  | 37.0  | 11.8  | 20.4  | 3.7   | 4.4      |       |
| HS200 | 72.5  | 145.7 | 41.8  | 45.5  | 89.7  | 70.0  | 57.2  | 20.5  | 10.4  | 5.5   | 5.1      | 103.4 |
| HS250 | 72.5  | 167.0 | 41.8  | 45.5  | 109.7 | 89.0  | 57.2  | 20.5  | 10.4  | 5.5   | 5.1      | 122.4 |
| HS300 | 72.5  | 184.4 | 41.8  | 45.5  | 127.7 | 104.0 | 59.0  | 20.5  | 12.4  | 5.5   | 6.6      | 141.4 |

\* HS200-HS300 Watts is ± 0.45

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9