

# MachineryMate™ vibration meter kits

## MAC800 series

Wilcoxon's handheld MAC800 vibration meter analyzes and displays vibration signals, helping users identify machine faults before they impact operation or lead to failure. The meter comes with built-in band filters for unbalance, misalignment and looseness, and its low Hz range allows readings on machinery running at speeds as slow as 120 RPM.

When used with the included DataMate software, the MAC800 kit can become the foundation of a plantwide condition monitoring program, supporting up to ten machines. Upgrading to DataMate PRO allows monitoring of up to 1,000 machines. Other options for extended capabilities include Bluetooth headphones for auditory monitoring and a strobelight attachment for run speed analysis.



### Key features

- Data trending software
- Internal data storage
- Built-in ISO alarms and Bluetooth capability
- Standard cable mounted accelerometer with magnet
- BDU reading to easily identify bearing problems
- 800 line FFT spectrum
- Manufactured in an approved ISO 9001 facility

| MachineryMate kits |        |        | Accessories included               |
|--------------------|--------|--------|------------------------------------|
| MAC800             | MAC810 | MAC820 |                                    |
| ✓                  | ✓      | ✓      | MAC800 meter and Datamate software |
| ✓                  | ✓      | ✓      | USB docking cradle                 |
| ✓                  | ✓      | ✓      | Protective boot                    |
| ✓                  | ✓      | ✓      | 100 mV/g sensor with magnet        |
| ✓                  | ✓      | ✓      | Carrying case                      |
|                    | ✓      | ✓      | Strobelight attachment (MAC004)    |
|                    | ✓      | ✓      | DataMate PRO software (MAC005)     |
|                    |        | ✓      | Bluetooth headphones (MAC006)      |
|                    |        | ✓      | Headphones case (MAC007)           |

### Certifications



Note: Due to continuous process improvement, specifications are subject to change without notice.  
This document is cleared for public release.

**Wilcoxon Sensing Technologies**  
An Amphenol Company

8435 Progress Drive  
Frederick, MD 21701  
USA

Tel: +1 (301) 330-8811  
Fax: +1 (301) 330-8873  
[info@wilcoxon.com](mailto:info@wilcoxon.com)

[buy.wilcoxon.com](http://buy.wilcoxon.com)  
[www.wilcoxon.com](http://www.wilcoxon.com)

# MachineryMate™ vibration meter kits

## MAC800 series

### SPECIFICATIONS

| METER                                   |                              |                                                                                                    |
|-----------------------------------------|------------------------------|----------------------------------------------------------------------------------------------------|
| <b>Size</b>                             |                              | 7.95 x 2.36 x 1 in. (20 x 6 x 2.6 cm)                                                              |
| <b>Frequency ranges:</b>                | <b>ISO</b>                   | 10 Hz - 1 kHz (600 - 60,000 CPM)                                                                   |
|                                         | <b>Low speed ISO</b>         | 2 Hz - 1 kHz (120 - 60,000 CPM)                                                                    |
|                                         | <b>BDU</b>                   | 1 Hz - 10 kHz (60 - 600,000 CPM)                                                                   |
| <b>Max frequency resolution</b>         |                              | 75 CPM at 800 lines FFT setting                                                                    |
| <b>Displayed amplitude units</b>        |                              | Acceleration: g<br>Bearing damage: BDU<br>Velocity: in/sec and mm/sec<br>Displacement: mils and mm |
| <b>Displayed frequency units</b>        |                              | CPM or RPM                                                                                         |
| <b>Input range</b>                      |                              | ± 60 g                                                                                             |
| <b>Dynamic range, 0.01 g resolution</b> |                              | 96 dB                                                                                              |
| <b>VA bands</b>                         |                              | Auto set-up                                                                                        |
| <b>Display</b>                          |                              | OLED full color, high contrast                                                                     |
| <b>Selectable languages</b>             |                              | English (default), Spanish, Portuguese, French, Italian, German                                    |
| <b>Weight (excluding magnet)</b>        |                              | 9.8 oz (280 grams)                                                                                 |
| <b>Environmental:</b>                   | <b>Water</b>                 | IP67 waterproof                                                                                    |
|                                         | <b>Operating temperature</b> | 0° to +50°C                                                                                        |
|                                         | <b>Storage temperature</b>   | -20° to +70°C                                                                                      |
| <b>Power supply</b>                     |                              | 2x AA batteries                                                                                    |
| <b>Battery life</b>                     |                              | 20 hours normal use                                                                                |
| SENSOR                                  |                              |                                                                                                    |
| <b>Sensor</b>                           |                              | 780FM-2-J88C integral cable accelerometer                                                          |
| <b>Sensitivity</b>                      |                              | 100 mV/g                                                                                           |
| <b>Sensitivity tolerance</b>            |                              | ± 15%                                                                                              |
| <b>Acceleration range</b>               |                              | 80 g                                                                                               |
| <b>Frequency range, ±3 dB</b>           |                              | 0.4 Hz to 12 kHz                                                                                   |
| <b>Acceleration limit</b>               |                              | 500 g                                                                                              |
| <b>Cable</b>                            |                              | 6 ft. coiled cable                                                                                 |
| <b>Magnet</b>                           |                              | Two-pole 40 lbf, detachable                                                                        |

#### Accessories supplied:

- 780FM-2-J88C accelerometer with integral cable
- DataMate software
- MAC001 docking station with USB cable
- MAC002 protective boot with magnets
- MAC003 carrying case with insert

#### Accessories available:

- MAC004 strobelight attachment
- MAC005 DataMate PRO software
- MAC006 Bluetooth headphones
- MAC007 headphones carrying case

Note: Due to continuous process improvement, specifications are subject to change without notice.  
This document is cleared for public release.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9