



PIN Power Inductor


RCH-875



Dimension - [mm]



Schematics - [mm]



Description

- Ferrite drum core construction.
- Magnetically unshielded.
- L × W × H: 8.3 × 8.3 × 7.5mm Max.
- Product weight: 1.13g(Ref.)
- Moisture Sensitivity Level: 1
- RoHS compliance.

Environmental Data

- Operating temperature range: -40°C ~ +100°C (including coil's self temperature rise)
- Storage temperature range: -40°C ~ +100°C

Packaging


- Box packaging.

Applications

- Ideally Used in Printers, LCD TV, DVD, Printer, Copy Machine, Main board of the compounding machines, etc as DC-DC Converter inductors.

PIN Power Inductor

RCH-875




Electrical Characteristics

Part Name	Stamp	Inductance (μ H) [within] ※ 1	D.C.R (Ω) [Max.] (at20℃)	Saturation Current (A) ※2	Temperature Rise Current (A) ※3
RCH875NP-2R2M	2R2M	2.2 $\pm$ 20%	13.7m	5.8	3.0
RCH875NP-2R8M	2R8M	2.8 $\pm$ 20%	15.3m	5.0	2.9
RCH875NP-3R5M	3R5M	3.5 $\pm$ 20%	17.2m	4.7	2.8
RCH875NP-4R4M	4R4M	4.4 $\pm$ 20%	19.1m	4.5	2.7
RCH875NP-5R1M	5R1M	5.1 $\pm$ 20%	21.2m	4.2	2.6
RCH875NP-6R0M	6R0M	6.0 $\pm$ 20%	22.2m	4.0	2.5
RCH875NP-7R1M	7R1M	7.1 $\pm$ 20%	24.2m	3.4	2.3
RCH875NP-8R2M	8R2M	8.2 $\pm$ 20%	26.5m	3.1	2.2
RCH875NP-100M	100M	10 $\pm$ 20%	0.05	2.9	2.1
RCH875NP-120M	120M	12 $\pm$ 20%	0.06	2.5	1.8
RCH875NP-150K	150K	15 $\pm$ 10%	0.07	2.2	1.4
RCH875NP-180K	180K	18 $\pm$ 10%	0.08	1.9	1.3
RCH875NP-220K	220K	22 $\pm$ 10%	0.09	1.8	1.2
RCH875NP-270K	270K	27 $\pm$ 10%	0.11	1.7	1.0
RCH875NP-330K	330K	33 $\pm$ 10%	0.13	1.5	1.0
RCH875NP-390K	390K	39 $\pm$ 10%	0.14	1.3	0.95
RCH875NP-470K	470K	47 $\pm$ 10%	0.15	1.3	0.90
RCH875NP-560K	560K	56 $\pm$ 10%	0.18	1.2	0.73
RCH875NP-680K	680K	68 $\pm$ 10%	0.20	1.1	0.68
RCH875NP-820K	820K	82 $\pm$ 10%	0.24	1.0	0.63
RCH875NP-101K	101K	100 $\pm$ 10%	0.35	0.89	0.59
RCH875NP-121K	121K	120 $\pm$ 10%	0.36	0.81	0.50
RCH875NP-151K	151K	150 $\pm$ 10%	0.42	0.72	0.46
RCH875NP-181K	181K	180 $\pm$ 10%	0.57	0.66	0.41
RCH875NP-221K	221K	220 $\pm$ 10%	0.63	0.57	0.38
RCH875NP-271K	271K	270 $\pm$ 10%	0.88	0.51	0.32
RCH875NP-331K	331K	330 $\pm$ 10%	1.05	0.46	0.30
RCH875NP-391K	391K	390 $\pm$ 10%	1.17	0.44	0.29

PIN Power Inductor

RCH-875



Electrical Characteristics

Part Name	Stamp	Inductance (μ H) [within] ※ 1	D.C.R. (Ω) [Max.] (at20°C)	Saturation Current (A) ※2	Temperature Rise Current (A) ※3
RCH875NP-471K	471K	470 $\pm$ 10%	1.34	0.41	0.28
RCH875NP-561K	561K	560 $\pm$ 10%	1.72	0.36	0.23
RCH875NP-681K	681K	680 $\pm$ 10%	1.96	0.33	0.22
RCH875NP-821K	821K	820 $\pm$ 10%	2.56	0.30	0.19
RCH875NP-102K	102K	1.0mH $\pm$ 10%	2.94	0.27	0.18
RCH875NP-122K	122K	1.2mH $\pm$ 10%	4.04	0.24	0.16
RCH875NP-152K	152K	1.5mH $\pm$ 10%	4.70	0.22	0.15
RCH875NP-182K	182K	1.8mH $\pm$ 10%	5.05	0.20	0.14
RCH875NP-222K	222K	2.2mH $\pm$ 10%	6.25	0.18	0.13
RCH875NP-272K	272K	2.7mH $\pm$ 10%	8.72	0.16	0.10
RCH875NP-332K	332K	3.3mH $\pm$ 10%	10.6	0.15	95m
RCH875NP-392K	392K	3.9mH $\pm$ 10%	14.2	0.14	81m
RCH875NP-472K	472K	4.7mH $\pm$ 10%	16.7	0.12	74m
RCH875NP-562K	562K	5.6mH $\pm$ 10%	18.7	0.11	69m
RCH875NP-682K	682K	6.8mH $\pm$ 10%	21.8	0.10	67m
RCH875NP-822K	822K	8.2mH $\pm$ 10%	28.7	93m	63m
RCH875NP-103K	103K	10mH $\pm$ 10%	33.0	84m	54m


※1: Inductance measuring frequency: 2.2 μ H ~8.2 μ H at 7.96MHz
 10 μ H ~ 82 μ H at 2.52MHz
 100 μ H ~10mH at 1 kHz

※2: Saturation current: The DC current at which the inductance decreases to 90% of it's initial value.

※3: Temperature rise current: The DC current at which the temperature rise is $\Delta t=20^{\circ}\text{C}$. (Ta=20°C).

PIN Power Inductor


RCH-875




Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT


1. RCH875NP-2R2M




2. RCH875NP-2R8M




3. RCH875NP-3R5M




4. RCH875NP-4R4M




5. RCH875NP-5R1M




6. RCH875NP-6R0M




7. RCH875NP-7R1M




8. RCH875NP-8R2M




9. RCH875NP-100M




10. RCH875NP-120M



11. RCH875NP-150K



12. RCH875NP-180K















PIN Power Inductor

RCH-875



Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT















PIN Power Inductor

RCH-875



Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT




PIN Power Inductor RCH-875



Saturation Current & Temperature Rise Graph

— L (20°C) — L (100°C) — ΔT



Please refer to the sales offices on our website - <http://www.sumida.com>

Hong Kong

Tel.+852-2880-6781
FAX.+852-2565-9600
sales@hk.sumida.com

Saitama(Japan)

Tel.+81-48-691-7300
FAX.+81-48-691-7340
sales@jp.sumida.com

Chicago

Tel.+1-847-545-6700
FAX. +1-847-545-6720
sales@us.sumida.com

Shanghai

Tel.+86-21-5836-3299
FAX.+86-21-5836-3266
shanghai.sales@cn.sumida.com

Seoul

Tel.+82-2-6237-0777
FAX.+82-2-6237-0778
sales@kr.sumida.com

Obernzell

Tel.+49-8591-937-0
FAX. +49-8591-937-103
contact@eu.sumida.com

Shenzhen

Tel.+86-755-8291-0228
FAX.+86-755-8291-0338
shenzhen.sales@cn.sumida.com

Singapore

Tel.+65-6296-3388
FAX.+65-6841-4426
sales@sg.sumida.com

Neumarkt

Tel.+49-9181-4509-110
FAX. +49-9181-4509-310
infocomp@eu.sumida.com

Taipei

Tel.+886-2-8751-2737
FAX.+886-2-8751-2738
sales@tw.sumida.com

San Jose

Tel.+1-408-321-9660
FAX.+1-408-321-9308
sales@us.sumida.com

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9