

# MC74HC4851A, MC74HC4852A

## Analog Multiplexers/ Demultiplexers with Injection Current Effect Control

### Automotive Customized

These devices are pin compatible to standard HC405x and MC1405xB analog mux/demux devices, but feature injection current effect control. This makes them especially suited for usage in automotive applications where voltages in excess of normal logic voltage are common.

The injection current effect control allows signals at disabled analog input channels to exceed the supply voltage range without affecting the signal of the enabled analog channel. This eliminates the need for external diode/ resistor networks typically used to keep the analog channel signals within the supply voltage range.

The devices utilize low power silicon gate CMOS technology. The Channel Select and Enable inputs are compatible with standard CMOS outputs.

#### Features


- Injection Current Cross-Coupling Less than 1mV/mA (See Figure 9)
- Pin Compatible to HC405X and MC1405XB Devices
- Power Supply Range ( $V_{CC} - GND$ ) = 2.0 to 6.0 V
- In Compliance With the Requirements of JEDEC Standard No. 7A
- Chip Complexity: 154 FETs or 36 Equivalent Gates
- NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free and are RoHS Compliant




ON Semiconductor®

<http://onsemi.com>



#### MARKING DIAGRAMS





PDIP-16  
N SUFFIX  
CASE 648




SOIC-16  
D SUFFIX  
CASE 751B



SOIC-16 WIDE  
DW SUFFIX  
CASE 751G



TSSOP-16  
DT SUFFIX  
CASE 948F




x = 1 or 2  
A = Assembly Location  
WL, L = Wafer Lot  
YY, Y = Year  
WW, W = Work Week  
G or ■ = Pb-Free Package  
(Note: Microdot may be in either location)

#### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 12 of this data sheet.


# MC74HC4851A, MC74HC4852A



**Figure 1. MC74HC4851A Logic Diagram  
Single-Pole, 8-Position Plus Common Off**

**FUNCTION TABLE – MC74HC4851A**

| Control Inputs |        |   |   | ON Channels |
|----------------|--------|---|---|-------------|
| Enable         | Select |   |   |             |
|                | C      | B | A |             |
| L              | L      | L | L | X0          |
| L              | L      | L | H | X1          |
| L              | L      | H | L | X2          |
| L              | L      | H | H | X3          |
| L              | H      | L | L | X4          |
| L              | H      | L | H | X5          |
| L              | H      | H | L | X6          |
| L              | H      | H | H | X7          |
| H              | X      | X | X | NONE        |




**Figure 2. MC74HC4851A 16-Lead Pinout (Top View)**


**FUNCTION TABLE – MC74HC4852A**

| Control Inputs |        |   |             |    |
|----------------|--------|---|-------------|----|
| Enable         | Select |   |             |    |
|                | B      | A | ON Channels |    |
| L              | L      | L | Y0          | X0 |
| L              | L      | H | Y1          | X1 |
| L              | H      | L | Y2          | X2 |
| L              | H      | H | Y3          | X3 |
| H              | X      | X | NONE        |    |

X = Don't Care



**Figure 3. MC74HC4852A Logic Diagram  
Double-Pole, 4-Position Plus Common Off**



**Figure 4. MC74HC4852A 16-Lead Pinout (Top View)**

# MC74HC4851A, MC74HC4852A

## MAXIMUM RATINGS

| Symbol    | Parameter                                                                             | Value                  | Unit |
|-----------|---------------------------------------------------------------------------------------|------------------------|------|
| $V_{CC}$  | Positive DC Supply Voltage (Referenced to GND)                                        | -0.5 to + 7.0          | V    |
| $V_{in}$  | DC Input Voltage (Any Pin) (Referenced to GND)                                        | -0.5 to $V_{CC} + 0.5$ | V    |
| I         | DC Current, Into or Out of Any Pin                                                    | $\pm 25$               | mA   |
| $P_D$     | Power Dissipation in Still Air,<br>Plastic DIP†<br>SOIC Package†<br>TSSOP Package†    | 750<br>500<br>450      | mW   |
| $T_{stg}$ | Storage Temperature Range                                                             | -65 to + 150           | °C   |
| $T_L$     | Lead Temperature, 1 mm from Case for 10 Seconds<br>Plastic DIP, SOIC or TSSOP Package | 260                    | °C   |

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high-impedance circuit. For proper operation,  $V_{in}$  and  $V_{out}$  should be constrained to the range  $GND \leq (V_{in} \text{ or } V_{out}) \leq V_{CC}$ . Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or  $V_{CC}$ ). Unused outputs must be left open.

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

†Derating – Plastic DIP: - 10 mW/°C from 65° to 125°C  
SOIC Package: - 7 mW/°C from 65° to 125°C  
TSSOP Package: - 6.1 mW/°C from 65° to 125°C

## RECOMMENDED OPERATING CONDITIONS

| Symbol     | Parameter                                                                                                                                     | Min         | Max                | Unit |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-------------|--------------------|------|
| $V_{CC}$   | Positive DC Supply Voltage (Referenced to GND)                                                                                                | 2.0         | 6.0                | V    |
| $V_{in}$   | DC Input Voltage (Any Pin) (Referenced to GND)                                                                                                | GND         | $V_{CC}$           | V    |
| $V_{IO}^*$ | Static or Dynamic Voltage Across Switch                                                                                                       | 0.0         | 1.2                | V    |
| $T_A$      | Operating Temperature Range, All Package Types                                                                                                | - 55        | + 125              | °C   |
| $t_r, t_f$ | Input Rise/Fall Time<br>(Channel Select or Enable Inputs)<br>$V_{CC} = 2.0 \text{ V}$<br>$V_{CC} = 4.5 \text{ V}$<br>$V_{CC} = 6.0 \text{ V}$ | 0<br>0<br>0 | 1000<br>500<br>400 | ns   |

\*For voltage drops across switch greater than 1.2 V (switch on), excessive  $V_{CC}$  current may be drawn; i.e., the current out of the switch may contain both  $V_{CC}$  and switch input components. The reliability of the device will be unaffected unless the Maximum Ratings are exceeded.

## DC CHARACTERISTICS — Digital Section (Voltages Referenced to GND) $V_{EE} = GND$ , Except Where Noted

| Symbol   | Parameter                                                            | Condition                                                            | $V_{CC}$<br>V            | Guaranteed Limit             |                              |                              | Unit |
|----------|----------------------------------------------------------------------|----------------------------------------------------------------------|--------------------------|------------------------------|------------------------------|------------------------------|------|
|          |                                                                      |                                                                      |                          | -55 to 25°C                  | ≤85°C                        | ≤125°C                       |      |
| $V_{IH}$ | Minimum High-Level Input Voltage,<br>Channel-Select or Enable Inputs | $R_{on} = \text{Per Spec}$                                           | 2.0<br>3.0<br>4.5<br>6.0 | 1.50<br>2.10<br>3.15<br>4.20 | 1.50<br>2.10<br>3.15<br>4.20 | 1.50<br>2.10<br>3.15<br>4.20 | V    |
| $V_{IL}$ | Maximum Low-Level Input Voltage,<br>Channel-Select or Enable Inputs  | $R_{on} = \text{Per Spec}$                                           | 2.0<br>3.0<br>4.5<br>6.0 | 0.50<br>0.90<br>1.35<br>1.80 | 0.50<br>0.90<br>1.35<br>1.80 | 0.50<br>0.90<br>1.35<br>1.80 | V    |
| $I_{in}$ | Maximum Input Leakage Current on Digital Pins<br>(Enable/A/B/C)      | $V_{in} = V_{CC} \text{ or } GND$                                    | 6.0                      | $\pm 0.1$                    | $\pm 1.0$                    | $\pm 1.0$                    | μA   |
| $I_{CC}$ | Maximum Quiescent Supply Current<br>(per Package)                    | $V_{in(digital)} = V_{CC} \text{ or } GND$<br>$V_{in(analog)} = GND$ | 6.0                      | 2                            | 20                           | 40                           | μA   |

# MC74HC4851A, MC74HC4852A

## DC CHARACTERISTICS — Analog Section

| Symbol           | Parameter                                                              | Condition                                                                                                                | V <sub>CC</sub> | Guaranteed Limit |       |        | Unit |
|------------------|------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|-----------------|------------------|-------|--------|------|
|                  |                                                                        |                                                                                                                          |                 | -55 to 25°C      | ≤85°C | ≤125°C |      |
| R <sub>on</sub>  | Maximum "ON" Resistance                                                | V <sub>in</sub> = V <sub>IL</sub> or V <sub>IH</sub> ; V <sub>IS</sub> = V <sub>CC</sub> to GND; I <sub>S</sub> ≤ 2.0 mA | 2.0             | 1700             | 1750  | 1800   | Ω    |
|                  |                                                                        |                                                                                                                          | 3.0             | 1100             | 1200  | 1300   |      |
|                  |                                                                        |                                                                                                                          | 4.5             | 550              | 650   | 750    |      |
|                  |                                                                        |                                                                                                                          | 6.0             | 400              | 500   | 600    |      |
| ΔR <sub>on</sub> | Delta "ON" Resistance                                                  | V <sub>in</sub> = V <sub>IL</sub> or V <sub>IH</sub> ; V <sub>IS</sub> = V <sub>CC</sub> /2; I <sub>S</sub> ≤ 2.0 mA     | 2.0             | 300              | 400   | 500    | Ω    |
|                  |                                                                        |                                                                                                                          | 3.0             | 160              | 200   | 240    |      |
|                  |                                                                        |                                                                                                                          | 4.5             | 80               | 100   | 120    |      |
|                  |                                                                        |                                                                                                                          | 6.0             | 60               | 80    | 100    |      |
| I <sub>off</sub> | Maximum Off-Channel Leakage Current, Any One Channel<br>Common Channel | V <sub>in</sub> = V <sub>CC</sub> or GND                                                                                 | 6.0             | ±0.1             | ±0.1  | ±0.1   | μA   |
|                  |                                                                        |                                                                                                                          |                 | ±0.1             | ±0.1  | ±0.1   |      |
| I <sub>on</sub>  | Maximum On-Channel Leakage Channel-to-Channel                          | V <sub>in</sub> = V <sub>CC</sub> or GND                                                                                 | 6.0             | ±0.1             | ±0.1  | ±0.1   | μA   |

## AC CHARACTERISTICS (C<sub>L</sub> = 50 pF, Input t<sub>r</sub> = t<sub>f</sub> = 6 ns)

| Symbol                                                                                     | Parameter                                                                                                           | V <sub>CC</sub>                                            | -55 to 25°C | ≤85°C | ≤125°C | Unit |
|--------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------|-------------|-------|--------|------|
| t <sub>PHL</sub> ,<br>t <sub>PLH</sub>                                                     | Maximum Propagation Delay, Analog Input to Analog Output                                                            | 2.0                                                        | 160         | 180   | 200    | ns   |
|                                                                                            |                                                                                                                     | 3.0                                                        | 80          | 90    | 100    |      |
|                                                                                            |                                                                                                                     | 4.5                                                        | 40          | 45    | 50     |      |
|                                                                                            |                                                                                                                     | 6.0                                                        | 30          | 35    | 40     |      |
| t <sub>PHL</sub> ,<br>t <sub>PHZ,PZH</sub> ,<br>t <sub>PLH</sub> ,<br>t <sub>PLZ,PZL</sub> | Maximum Propagation Delay, Enable or Channel-Select to Analog Output                                                | 2.0                                                        | 260         | 280   | 300    | ns   |
|                                                                                            |                                                                                                                     | 3.0                                                        | 160         | 180   | 200    |      |
|                                                                                            |                                                                                                                     | 4.5                                                        | 80          | 90    | 100    |      |
|                                                                                            |                                                                                                                     | 6.0                                                        | 78          | 80    | 80     |      |
| C <sub>in</sub>                                                                            | Maximum Input Capacitance<br>(All Switches Off)<br>Any Single Analog Pin<br>(All Switches Off)<br>Common Analog Pin | Digital Pins<br>Any Single Analog Pin<br>Common Analog Pin | 10          | 10    | 10     | pF   |
|                                                                                            |                                                                                                                     |                                                            | 35          | 35    | 35     |      |
|                                                                                            |                                                                                                                     |                                                            | 40          | 40    | 40     |      |
| C <sub>PD</sub>                                                                            | Power Dissipation Capacitance                                                                                       | Typical                                                    | 5.0         | 20    |        | pF   |

## INJECTION CURRENT COUPLING SPECIFICATIONS (V<sub>CC</sub> = 5V, T<sub>A</sub> = -55°C to +125°C)

| Symbol            | Parameter                                                 | Condition                                          | Typ | Max | Unit |
|-------------------|-----------------------------------------------------------|----------------------------------------------------|-----|-----|------|
| VΔ <sub>out</sub> | Maximum Shift of Output Voltage of Enabled Analog Channel | I <sub>in</sub> * ≤ 1 mA, R <sub>S</sub> ≤ 3.9 kΩ  | 0.1 | 1.0 | mV   |
|                   |                                                           | I <sub>in</sub> * ≤ 10 mA, R <sub>S</sub> ≤ 3.9 kΩ | 1.0 | 5.0 |      |
|                   |                                                           | I <sub>in</sub> * ≤ 1 mA, R <sub>S</sub> ≤ 20 kΩ   | 0.5 | 2.0 |      |
|                   |                                                           | I <sub>in</sub> * ≤ 10 mA, R <sub>S</sub> ≤ 20 kΩ  | 5.0 | 20  |      |

\* I<sub>in</sub> = Total current injected into all disabled channels.

# MC74HC4851A, MC74HC4852A




Figure 5. Typical On Resistance  $V_{CC} = 2V$




Figure 6. Typical On Resistance  $V_{CC} = 3V$




Figure 7. Typical On Resistance  $V_{CC} = 4.5V$






Figure 8. Typical On Resistance  $V_{CC} = 6V$

# MC74HC4851A, MC74HC4852A




**Figure 9. Injection Current Coupling Specification**

## MC74HC4851A, MC74HC4852A



**Figure 10. Actual Technology**


Requires 32 passive components and one extra 6V regulator to suppress injection current into a standard HC4051 multiplexer




**Figure 11. MC74HC4851A Solution**

Solution by applying the HC4851A multiplexer


# MC74HC4851A, MC74HC4852A




**Figure 12. On Resistance Test Set-Up**




**Figure 13. Maximum Off Channel Leakage Current, Any One Channel, Test Set-Up**




**Figure 14. Maximum Off Channel Leakage Current, Common Channel, Test Set-Up**



**Figure 15. Maximum On Channel Leakage Current, Channel to Channel, Test Set-Up**




**Figure 16. Propagation Delays, Channel Select to Analog Out**




\*Includes all probe and jig capacitance

**Figure 17. Propagation Delay, Test Set-Up Channel Select to Analog Out**

# MC74HC4851A, MC74HC4852A




**Figure 18. Propagation Delays, Analog In to Analog Out**




\*Includes all probe and jig capacitance


**Figure 19. Propagation Delay, Test Set-Up Analog In to Analog Out**



**Figure 20. Propagation Delays, Enable to Analog Out**




**Figure 21. Propagation Delay, Test Set-Up Enable to Analog Out**




**Figure 22. Power Dissipation Capacitance, Test Set-Up**

## MC74HC4851A, MC74HC4852A




**Figure 23. Diagram of Bipolar Coupling Mechanism**  
Appears if  $V_{in}$  exceeds  $V_{CC}$ , driving injection current into the substrate



**Figure 24. Function Diagram, HC4851A**

## MC74HC4851A, MC74HC4852A



**Figure 25. Function Diagram, HC4852A**

## MC74HC4851A, MC74HC4852A

### ORDERING INFORMATION

| Device            | Package                   | Shipping†                |
|-------------------|---------------------------|--------------------------|
| MC74HC4851ANG     | PDIP–16<br>(Pb–Free)      | 500 Units / Box          |
| MC74HC4851ADG     | SOIC–16<br>(Pb–Free)      | 48 Units / Rail          |
| MC74HC4851ADR2G   |                           | 2500 Units / Tape & Reel |
| NLVHC4851ADR2G*   |                           | 2500 Units / Tape & Reel |
| MC74HC4851ADTR2G  | TSSOP–16<br>(Pb–Free)     | 2500 Units / Tape & Reel |
| SC74HC4851ADTR2G  |                           | 2500 Units / Tape & Reel |
| NLVHC4851ADTR2G*  |                           | 2500 Units / Tape & Reel |
| MC74HC4851ADWG    | SOIC–16 WIDE<br>(Pb–Free) | 48 Units / Rail          |
| MC74HC4851ADWR2G  |                           | 1000 Units / Tape & Reel |
|                   |                           |                          |
| MC74HC4852ANG     | PDIP–16<br>(Pb–Free)      | 500 Units / Box          |
| MC74HC4852ADG     | SOIC–16<br>(Pb–Free)      | 48 Units / Rail          |
| MC74HC4852ADR2G   |                           | 2500 Units / Tape & Reel |
| NLV74HC4852ADR2G* |                           | 2500 Units / Tape & Reel |
| MC74HC4852ADTR2G  | TSSOP–16<br>(Pb–Free)     | 2500 Units / Tape & Reel |
| NLVHC4852ADTR2G*  |                           | 2500 Units / Tape & Reel |


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable.

# MC74HC4851A, MC74HC4852A

## PACKAGE DIMENSIONS

PDIP-16  
N SUFFIX  
CASE 648-08  
ISSUE T



### NOTES:


1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
4. DIMENSION B DOES NOT INCLUDE MOLD FLASH.
5. ROUNDED CORNERS OPTIONAL.

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 0.740     | 0.770 | 18.80       | 19.55 |
| B   | 0.250     | 0.270 | 6.35        | 6.85  |
| C   | 0.145     | 0.175 | 3.69        | 4.44  |
| D   | 0.015     | 0.021 | 0.39        | 0.53  |
| F   | 0.040     | 0.70  | 1.02        | 1.77  |
| G   | 0.100 BSC |       | 2.54 BSC    |       |
| H   | 0.050 BSC |       | 1.27 BSC    |       |
| J   | 0.008     | 0.015 | 0.21        | 0.38  |
| K   | 0.110     | 0.130 | 2.80        | 3.30  |
| L   | 0.295     | 0.305 | 7.50        | 7.74  |
| M   | 0°        | 10°   | 0°          | 10°   |
| S   | 0.020     | 0.040 | 0.51        | 1.01  |

# MC74HC4851A, MC74HC4852A

## PACKAGE DIMENSIONS

SOIC-16  
D SUFFIX  
CASE 751B-05  
ISSUE K




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

| DIM | MILLIMETERS |       | INCHES    |       |
|-----|-------------|-------|-----------|-------|
|     | MIN         | MAX   | MIN       | MAX   |
| A   | 9.80        | 10.00 | 0.386     | 0.393 |
| B   | 3.80        | 4.00  | 0.150     | 0.157 |
| C   | 1.35        | 1.75  | 0.054     | 0.068 |
| D   | 0.35        | 0.49  | 0.014     | 0.019 |
| F   | 0.40        | 1.25  | 0.016     | 0.049 |
| G   | 1.27 BSC    |       | 0.050 BSC |       |
| J   | 0.19        | 0.25  | 0.008     | 0.009 |
| K   | 0.10        | 0.25  | 0.004     | 0.009 |
| M   | 0°          | 7°    | 0°        | 7°    |
| P   | 5.80        | 6.20  | 0.229     | 0.244 |
| R   | 0.25        | 0.50  | 0.010     | 0.019 |

### SOLDERING FOOTPRINT\*




DIMENSIONS: MILLIMETERS

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# MC74HC4851A, MC74HC4852A

## PACKAGE DIMENSIONS

SOIC-16 WB  
DW SUFFIX  
CASE 751G-03  
ISSUE D




### NOTES:

1. DIMENSIONS ARE IN MILLIMETERS.
2. INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 1994.
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 PER SIDE.
5. DIMENSION B DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.13 TOTAL IN EXCESS OF THE B DIMENSION AT MAXIMUM MATERIAL CONDITION.

| MILLIMETERS |       |       |
|-------------|-------|-------|
| DIM         | MIN   | MAX   |
| A           | 2.35  | 2.65  |
| A1          | 0.10  | 0.25  |
| B           | 0.35  | 0.49  |
| C           | 0.23  | 0.32  |
| D           | 10.15 | 10.45 |
| E           | 7.40  | 7.60  |
| e           | 1.27  | BSC   |
| H           | 10.05 | 10.55 |
| h           | 0.25  | 0.75  |
| L           | 0.50  | 0.90  |
| q           | 0 °   | 7 °   |

### SOLDERING FOOTPRINT




DIMENSIONS: MILLIMETERS

# MC74HC4851A, MC74HC4852A

## PACKAGE DIMENSIONS


TSSOP-16  
DT SUFFIX  
CASE 948F  
ISSUE B



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.90        | 5.10 | 0.193     | 0.200 |
| B   | 4.30        | 4.50 | 0.169     | 0.177 |
| C   | ---         | 1.20 | ---       | 0.047 |
| D   | 0.05        | 0.15 | 0.002     | 0.006 |
| F   | 0.50        | 0.75 | 0.020     | 0.030 |
| G   | 0.65 BSC    |      | 0.026 BSC |       |
| H   | 0.18        | 0.28 | 0.007     | 0.011 |
| J   | 0.09        | 0.20 | 0.004     | 0.008 |
| J1  | 0.09        | 0.16 | 0.004     | 0.006 |
| K   | 0.19        | 0.30 | 0.007     | 0.012 |
| K1  | 0.19        | 0.25 | 0.007     | 0.010 |
| L   | 6.40 BSC    |      | 0.252 BSC |       |
| M   | 0°          | 8°   | 0°        | 8°    |



ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

MC74HC4851A/D

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9