

4

3

2

1


THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION
© COPYRIGHT	ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
	C1	ECR-13-017069	05NOV2013	XZ	LZ

REPLACED BY OCEAN STYLE APPLICATOR PART
NUMBER 2151109-6

FOR REPLACEMENT PARTS FOR APPLICATOR 1911009
REFER TO ADDITIONAL PAGE(S). SPARE PARTS KIT (IF LISTED)
WILL REMAIN AVAILABLE.

THE REPLACEMENT OCEAN STYLE APPLICATOR HAS THE
SAME TERMINATOR/PRESS INTERFACE AS APPLICATOR
1911009

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN X. ZHAO	 TE Connectivity			
DIMENSIONS:		CHK X. ZHAO				
		APVD L. ZHANG	NAME SIDE FEED SYSTEM III APPLICATOR			
		PRODUCT SPEC				
		APPLICATION SPEC				
MATERIAL	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ± FINISH	WEIGHT	SIZE A3	CAGE CODE	DRAWING NO C- 1911009	RESTRICTED TO
CUSTOMER DRAWING			SCALE	SHEET 1 OF 2	REV C1	

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

FEED FINGER

1901694-1

SET UP GAGE

1901040-1

LOC

A

DIST

66

REVISIONS

REV	DATE	BY	CHKD	APPD
A1	ECR-07-004822	01MAR2007	RD	ND
B	ECR-07-011464	21MAR2007	GH	ND
C	ECR 08-008186	01APR2008	MEH	GB

APPLICATOR DATA

CRIMP	SIZE	TYPE
WIRE	2.79mm [1.10]	F
INSUL	4.32mm [1.70]	O

APPL INSTRUCTIONS

408-10135

TERMINAL DATA: TE TERMINAL

TYCO ELECTRONICS CRIMP SPEC

TERMINAL NAME: JUNIOR POWER TIMER CONTACT

WIRE STRIP LENGTH

4.9-5.5mm [1.93-.217]

INSULATION DIAMETER RANGE

2.21-2.99mm [1.087-.118]

TERMINAL

114-18050

APPL SPEC

TERMINALS APPLIED

TE TERMINAL	TE TERMINAL	TE SEAL	TE SEAL
929937-3	927766-1	828905-1	-
929937-1	927766-3	-	-
929937-6	927766-8	-	-
929937-7	927766-1	-	-
1-929937-1	2-927766-1	-	-
2-929937-1	-	-	-

WIRE SIZE

2.5mm2

2mm2

1mm2

CRIMP HEIGHT

mm[INCH]

1.77±.05-[1.070±.002]

1.64±.05-[1.065±.002]

1.51±.05-[1.059±.002]

1

RECOMMENDED SPARE PARTS.

2

GREASE BEARING SURFACES LIGHTLY.

3

LUBRICATE DAILY PER THE APPLICATOR INSTRUCTION SHEET SUPPLIED WITH THE APPLICATOR.

4

THIS APPLICATOR APPLIES TERMINAL WITH A SEAL. WIRE INSULATION DIA IS DEPENDENT ON SEAL BEING APPLIED. SEE APPL. SPEC. FOR DETAILS.

5

APPLY TORQ-SEAL IN ALLEN SOCKET TO FILL HOLE AFTER FLAT HD HAS BEEN ADJUSTED TO CORRECT HEIGHT AT QUALIFICATION. APPLY P/N 1-23419-5 LOCTITE(R) TO THREADS.

6

APPLY P/N 1-23419-5 LOCTITE(R) TO THREADS.

7

ITEM 19 - OPTIONAL STRIPPER FOR BENCH MACHINE APPLICATION.

8

APPLICATOR SPECIFIC DATA TO BE ENTERED INTO BLANK MEMORY CHIP AT ASSEMBLY.

9

TERMINAL LUBRICATOR RECOMMENDED.

33

24

30

29

38

64

62

40

39

6

44

177

1

2

3

4

28

5

41

57

5

176

175

52

51

50

6

174

135

2

8

32

31

46

34

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

13

22

19

REF

66

67

60

20

9

12

11

177

REF

17

RETAINING PIN LOCATION

54

54

60

8

54

10

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9