

# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A

## Analog Multiplexers / Demultiplexers with LSTTL Compatible Inputs

### High-Performance Silicon-Gate CMOS

The MC74HCT4051A, MC74HCT4052A and MC74HCT4053A utilize silicon-gate CMOS technology to achieve fast propagation delays, low ON resistances, and low OFF leakage currents. These analog multiplexers/demultiplexers control analog voltages that may vary across the complete power supply range (from  $V_{CC}$  to  $V_{EE}$ ).

The HCT4051A, HCT4052A and HCT4053A are identical in pinout to the metal-gate MC14051AB, MC14052AB and MC14053AB. The Channel-Select inputs determine which one of the Analog Inputs/Outputs is to be connected, by means of an analog switch, to the Common Output/Input. When the Enable pin is HIGH, all analog switches are turned off.

The Channel-Select and Enable inputs are compatible with standard CMOS and LSTTL outputs.

These devices have been designed so that the ON resistance ( $R_{on}$ ) is more linear over input voltage than  $R_{on}$  of metal-gate CMOS analog switches.

For a multiplexer/demultiplexer with injection current protection, see HC4851A and HCT4851A.

#### Features


- Fast Switching and Propagation Speeds
- Low Crosstalk Between Switches
- Diode Protection on All Inputs/Outputs
- Analog Power Supply Range ( $V_{CC} - V_{EE}$ ) = 2.0 to 12.0 V
- Digital (Control) Power Supply Range ( $V_{CC} - GND$ ) = 2.0 to 6.0 V
- Improved Linearity and Lower ON Resistance Than Metal-Gate Counterparts
- Low Noise
- In Compliance with the Requirements of JEDEC Standard No. 7 A
- Chip Complexity: HCT4051A – 184 FETs or 46 Equivalent Gates  
HCT4052A – 168 FETs or 42 Equivalent Gates  
HCT4053A – 156 FETs or 39 Equivalent Gates
- These Devices are Pb-Free and are RoHS Compliant



ON Semiconductor®

<http://onsemi.com>

#### MARKING DIAGRAMS




x = 1, 2, 3  
A = Assembly Location  
WL, L = Wafer Lot  
YY, Y = Year  
WW, W = Work Week  
G or ▪ = Pb-Free Package

(Note: Microdot may be in either location)

#### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 13 of this data sheet.

# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A




**Figure 1. Logic Diagram – MC74HCT4051A**  
**Single-Pole, 8-Position Plus Common Off**

**FUNCTION TABLE – MC74HCT4051A**

| Control Inputs |        |   |   | ON Channels |
|----------------|--------|---|---|-------------|
| Enable         | Select |   |   |             |
|                | C      | B | A |             |
| L              | L      | L | L | X0          |
| L              | L      | L | H | X1          |
| L              | L      | H | L | X2          |
| L              | L      | H | H | X3          |
| L              | H      | L | L | X4          |
| L              | H      | L | H | X5          |
| L              | H      | H | L | X6          |
| L              | H      | H | H | X7          |
| H              | X      | X | X | NONE        |

X = Don't Care




**Figure 2. Pinout: MC74HCT4051A**  
(Top View)


**FUNCTION TABLE – MC74HCT4052A**

| Control Inputs |        |   |             |    |
|----------------|--------|---|-------------|----|
| Enable         | Select |   |             |    |
|                | B      | A | ON Channels |    |
| L              | L      | L | Y0          | X0 |
| L              | L      | H | Y1          | X1 |
| L              | H      | L | Y2          | X2 |
| L              | H      | H | Y3          | X3 |
| H              | X      | X | NONE        |    |

X = Don't Care




**Figure 4. Pinout: MC74HCT4052A** (Top View)



**Figure 3. Logic Diagram – MC74HCT4052A**  
**Double-Pole, 4-Position Plus Common Off**

# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A




NOTE: This device allows independent control of each switch. Channel-Select Input A controls the X-Switch, Input B controls the Y-Switch and Input C controls the Z-Switch

**Figure 5. Logic Diagram – MC74HCT4053A**  
**Triple Single-Pole, Double-Position Plus Common Off**

**FUNCTION TABLE – MC74HCT4053A**

| Control Inputs |   |   |   | ON Channels |    |    |
|----------------|---|---|---|-------------|----|----|
| Enable         | C | B | A |             |    |    |
| L              | L | L | L | Z0          | Y0 | X0 |
| L              | L | L | H | Z0          | Y0 | X1 |
| L              | L | H | L | Z0          | Y1 | X0 |
| L              | L | H | H | Z0          | Y1 | X1 |
| L              | H | L | L | Z1          | Y0 | X0 |
| L              | H | L | H | Z1          | Y0 | X1 |
| L              | H | H | L | Z1          | Y1 | X0 |
| L              | H | H | H | Z1          | Y1 | X1 |
| H              | X | X | X | NONE        |    |    |

X = Don't Care



**Figure 6. Pinout: MC74HCT4053A (Top View)**

## MAXIMUM RATINGS

| Symbol    | Parameter                                                                   | Value                            | Unit |
|-----------|-----------------------------------------------------------------------------|----------------------------------|------|
| $V_{CC}$  | Positive DC Supply Voltage (Referenced to GND)<br>(Referenced to $V_{EE}$ ) | -0.5 to +7.0<br>-0.5 to +14.0    | V    |
| $V_{EE}$  | Negative DC Supply Voltage (Referenced to GND)                              | -7.0 to +5.0                     | V    |
| $V_{IS}$  | Analog Input Voltage                                                        | $V_{EE} - 0.5$ to $V_{CC} + 0.5$ | V    |
| $V_{in}$  | Digital Input Voltage (Referenced to GND)                                   | -0.5 to $V_{CC} + 0.5$           | V    |
| I         | DC Current, Into or Out of Any Pin                                          | $\pm 25$                         | mA   |
| $P_D$     | Power Dissipation in Still Air, SOIC Package†<br>TSSOP Package†             | 500<br>450                       | mW   |
| $T_{stg}$ | Storage Temperature Range                                                   | -65 to +150                      | °C   |

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high-impedance circuit. For proper operation,  $V_{in}$  and  $V_{out}$  should be constrained to the range  $GND \leq (V_{in} \text{ or } V_{out}) \leq V_{CC}$ . Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or  $V_{CC}$ ). Unused outputs must be left open.

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

†Derating – SOIC Package: - 7 mW/°C from 65°C to 125°C  
TSSOP Package: - 6.1 mW/°C from 65°C to 125°C

# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A

## RECOMMENDED OPERATING CONDITIONS

| Symbol                          | Parameter                                                                                                                                                             | Min              | Max                       | Unit |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|---------------------------|------|
| V <sub>CC</sub>                 | Positive DC Supply Voltage (Referenced to GND)<br>(Referenced to V <sub>EE</sub> )                                                                                    | 2.0<br>2.0       | 6.0<br>12.0               | V    |
| V <sub>EE</sub>                 | Negative DC Supply Voltage, Output (Referenced to GND)                                                                                                                | −6.0             | GND                       | V    |
| V <sub>IS</sub>                 | Analog Input Voltage                                                                                                                                                  | V <sub>EE</sub>  | V <sub>CC</sub>           | V    |
| V <sub>in</sub>                 | Digital Input Voltage (Referenced to GND)                                                                                                                             | GND              | V <sub>CC</sub>           | V    |
| V <sub>IO</sub> *               | Static or Dynamic Voltage Across Switch                                                                                                                               |                  | 1.2                       | V    |
| T <sub>A</sub>                  | Operating Temperature Range, All Package Types                                                                                                                        | −55              | +125                      | °C   |
| t <sub>r</sub> , t <sub>f</sub> | Input Rise/Fall Time<br>(Channel Select or Enable Inputs)<br>V <sub>CC</sub> = 2.0 V<br>V <sub>CC</sub> = 3.0 V<br>V <sub>CC</sub> = 4.5 V<br>V <sub>CC</sub> = 6.0 V | 0<br>0<br>0<br>0 | 1000<br>600<br>500<br>400 | ns   |

\*For voltage drops across switch greater than 1.2 V (switch on), excessive  $V_{CC}$  current may be drawn; i.e., the current out of the switch may contain both  $V_{CC}$  and switch input components. The reliability of the device will be unaffected unless the Maximum Ratings are exceeded.

## DC CHARACTERISTICS – Digital Section (Voltages Referenced to GND) $V_{EE} = \text{GND}$ , Except Where Noted

| Symbol          | Parameter                                                         | Condition                                                                                        | V <sub>CC</sub><br>V                             | Guaranteed Limit |        |          | Unit     |    |
|-----------------|-------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------|------------------|--------|----------|----------|----|
|                 |                                                                   |                                                                                                  |                                                  | −55 to 25°C      | ≤85°C  | ≤125°C   |          |    |
| V <sub>IH</sub> | Minimum High-Level Input Voltage, Channel-Select or Enable Inputs | R <sub>on</sub> = Per Spec                                                                       | 4.5 to 5.5                                       | 2.0              | 2.0    | 2.0      | V        |    |
| V <sub>IL</sub> | Maximum Low-Level Input Voltage, Channel-Select or Enable Inputs  | R <sub>on</sub> = Per Spec                                                                       | 4.5 to 5.5                                       | 0.8              | 0.8    | 0.8      | V        |    |
| I <sub>in</sub> | Maximum Input Leakage Current, Channel-Select or Enable Inputs    | V <sub>in</sub> = V <sub>CC</sub> or GND,<br>V <sub>EE</sub> = − 6.0 V                           | 6.0                                              | ±0.1             | ±1.0   | ±1.0     | μA       |    |
| I <sub>CC</sub> | Maximum Quiescent Supply Current (per Package)                    | Channel Select, Enable and<br>V <sub>IS</sub> = V <sub>CC</sub> or GND;<br>V <sub>IO</sub> = 0 V | V <sub>EE</sub> = GND<br>V <sub>EE</sub> = − 6.0 | 6.0<br>6.0       | 1<br>4 | 10<br>40 | 20<br>80 | μA |

## DC CHARACTERISTICS – Analog Section

| Symbol          | Parameter                                                                          | Condition                                                                                                             | $V_{CC}$ | $V_{EE}$ | Guaranteed Limit |       |        | Unit |
|-----------------|------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|----------|----------|------------------|-------|--------|------|
|                 |                                                                                    |                                                                                                                       |          |          | -55 to 25°C      | ≤85°C | ≤125°C |      |
| $R_{on}$        | Maximum "ON" Resistance                                                            | $V_{in} = V_{IL}$ or $V_{IH}$ ; $V_{IS} = V_{CC}$ to $V_{EE}$ ; $I_S \leq 2.0\text{ mA}$<br>(Figures 7, 8)            | 4.5      | 0.0      | 190              | 240   | 280    | Ω    |
|                 |                                                                                    |                                                                                                                       | 4.5      | -4.5     | 120              | 150   | 170    |      |
|                 |                                                                                    |                                                                                                                       | 6.0      | -6.0     | 100              | 125   | 140    |      |
|                 |                                                                                    | $V_{in} = V_{IL}$ or $V_{IH}$ ; $V_{IS} = V_{CC}$ or $V_{EE}$ (Endpoints); $I_S \leq 2.0\text{ mA}$<br>(Figures 7, 8) | 4.5      | 0.0      | 150              | 190   | 230    |      |
|                 |                                                                                    |                                                                                                                       | 4.5      | -4.5     | 100              | 125   | 140    |      |
|                 |                                                                                    |                                                                                                                       | 6.0      | -6.0     | 80               | 100   | 115    |      |
| $\Delta R_{on}$ | Maximum Difference in "ON" Resistance Between Any Two Channels in the Same Package | $V_{in} = V_{IL}$ or $V_{IH}$ ;<br>$V_{IS} = 1/2 (V_{CC} - V_{EE})$ ;<br>$I_S \leq 2.0\text{ mA}$                     | 4.5      | 0.0      | 30               | 35    | 40     | Ω    |
|                 |                                                                                    |                                                                                                                       | 4.5      | -4.5     | 12               | 15    | 18     |      |
|                 |                                                                                    |                                                                                                                       | 6.0      | -6.0     | 10               | 12    | 14     |      |
| $I_{off}$       | Maximum Off-Channel Leakage Current, Any One Channel                               | $V_{in} = V_{IL}$ or $V_{IH}$ ;<br>$V_{IO} = V_{CC} - V_{EE}$ ;<br>Switch Off (Figure 9)                              | 5.0      | -5.0     | 0.1              | 0.5   | 1.0    | μA   |
|                 |                                                                                    |                                                                                                                       |          |          |                  |       |        |      |
|                 | Maximum Off-Channel Leakage Current, Common Channel                                | $V_{in} = V_{IL}$ or $V_{IH}$ ;<br>$V_{IO} = V_{CC} - V_{EE}$ ;<br>Switch Off (Figure 10)                             | 5.0      | -5.0     | 0.2              | 2.0   | 4.0    |      |
|                 |                                                                                    |                                                                                                                       | 5.0      | -5.0     | 0.1              | 1.0   | 2.0    |      |
| $I_{on}$        | Maximum On-Channel Leakage Current, Channel-to-Channel                             | $V_{in} = V_{IL}$ or $V_{IH}$ ;<br>Switch-to-Switch =<br>$V_{CC} - V_{EE}$ ; (Figure 11)                              | 5.0      | -5.0     | 0.2              | 2.0   | 4.0    | μA   |
|                 |                                                                                    |                                                                                                                       | 5.0      | -5.0     | 0.1              | 1.0   | 2.0    |      |
|                 |                                                                                    |                                                                                                                       | 5.0      | -5.0     | 0.1              | 1.0   | 2.0    |      |

# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A

## AC CHARACTERISTICS ( $C_L = 50$ pF, Input $t_r = t_f = 6$ ns)

| Symbol                                 | Parameter                                                                 | V <sub>CC</sub><br>V | Guaranteed Limit |       |        | Unit |
|----------------------------------------|---------------------------------------------------------------------------|----------------------|------------------|-------|--------|------|
|                                        |                                                                           |                      | -55 to 25°C      | ≤85°C | ≤125°C |      |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Maximum Propagation Delay, Channel–Select to Analog Output<br>(Figure 15) | 2.0                  | 270              | 320   | 350    | ns   |
|                                        |                                                                           | 3.0                  | 90               | 110   | 125    |      |
|                                        |                                                                           | 4.5                  | 59               | 79    | 85     |      |
|                                        |                                                                           | 6.0                  | 45               | 65    | 75     |      |
| t <sub>PLH</sub> ,<br>t <sub>PHL</sub> | Maximum Propagation Delay, Analog Input to Analog Output<br>(Figure 16)   | 2.0                  | 40               | 60    | 70     | ns   |
|                                        |                                                                           | 3.0                  | 25               | 30    | 32     |      |
|                                        |                                                                           | 4.5                  | 12               | 15    | 18     |      |
|                                        |                                                                           | 6.0                  | 10               | 13    | 15     |      |
| t <sub>PLZ</sub> ,<br>t <sub>PHZ</sub> | Maximum Propagation Delay, Enable to Analog Output<br>(Figure 17)         | 2.0                  | 160              | 200   | 220    | ns   |
|                                        |                                                                           | 3.0                  | 70               | 95    | 110    |      |
|                                        |                                                                           | 4.5                  | 48               | 63    | 76     |      |
|                                        |                                                                           | 6.0                  | 39               | 55    | 63     |      |
| t <sub>PZL</sub> ,<br>t <sub>PZH</sub> | Maximum Propagation Delay, Enable to Analog Output<br>(Figure 17)         | 2.0                  | 245              | 315   | 345    | ns   |
|                                        |                                                                           | 3.0                  | 115              | 145   | 155    |      |
|                                        |                                                                           | 4.5                  | 49               | 69    | 83     |      |
|                                        |                                                                           | 6.0                  | 39               | 58    | 67     |      |
| C <sub>in</sub>                        | Maximum Input Capacitance, Channel–Select or Enable Inputs                |                      | 10               | 10    | 10     | pF   |
| C <sub>I/O</sub>                       | Maximum Capacitance Analog I/O                                            |                      | 35               | 35    | 35     | pF   |
|                                        | (All Switches Off) Common O/I: HCT4051A                                   |                      | 130              | 130   | 130    |      |
|                                        | HCT4052A                                                                  |                      | 80               | 80    | 80     |      |
|                                        | HCT4053A                                                                  |                      | 50               | 50    | 50     |      |
|                                        | Feed-through                                                              |                      | 1.0              | 1.0   | 1.0    |      |

| C <sub>PD</sub> | Power Dissipation Capacitance (Figure 19)* | HCT4051A<br>HCT4052A<br>HCT4053A | Typical @ 25°C, V <sub>CC</sub> = 5.0 V, V <sub>EE</sub> = 0 V | pF |
|-----------------|--------------------------------------------|----------------------------------|----------------------------------------------------------------|----|
|                 |                                            |                                  | 45<br>80<br>45                                                 |    |

\*Used to determine the no-load dynamic power consumption:  $P_D = C_{PD} V_{CC}^2 f + I_{CC} V_{CC}$ .

# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A

## ADDITIONAL APPLICATION CHARACTERISTICS (GND = 0 V)

| Symbol | Parameter                                                                        | Condition                                                                                                                                                                                                                                                                                  | V <sub>CC</sub><br>V | V <sub>EE</sub><br>V | Limit* |       |     | Unit             |
|--------|----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|----------------------|--------|-------|-----|------------------|
|        |                                                                                  |                                                                                                                                                                                                                                                                                            |                      |                      | 25°C   |       |     |                  |
| BW     | Maximum On-Channel Bandwidth or Minimum Frequency Response (Figure 12)           | f <sub>in</sub> = 1 MHz Sine Wave; Adjust f <sub>in</sub> Voltage to Obtain 0 dBm at V <sub>OS</sub> ; Increase f <sub>in</sub> Frequency Until dB Meter Reads -3 dB; R <sub>L</sub> = 50 Ω, C <sub>L</sub> = 10 pF                                                                        |                      |                      | '51    | '52   | '53 | MHz              |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            |                      |                      | 80     | 95    | 120 |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 2.25                 | -2.25                | 80     | 95    | 120 |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 4.50                 | -4.50                | 80     | 95    | 120 |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 6.00                 | -6.00                | 80     | 95    | 120 |                  |
| -      | Off-Channel Feed-through Isolation (Figure 13)                                   | f <sub>in</sub> = Sine Wave; Adjust f <sub>in</sub> Voltage to Obtain 0 dBm at V <sub>IS</sub><br>f <sub>in</sub> = 10 kHz, R <sub>L</sub> = 600 Ω, C <sub>L</sub> = 50 pF                                                                                                                 | 2.25                 | -2.25                | -50    |       |     | dB               |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 4.50                 | -4.50                | -50    |       |     |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 6.00                 | -6.00                | -50    |       |     |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            |                      |                      | 2.25   | -2.25 | -40 |                  |
|        |                                                                                  | f <sub>in</sub> = 1.0 MHz, R <sub>L</sub> = 50 Ω, C <sub>L</sub> = 10 pF                                                                                                                                                                                                                   | 4.50                 | -4.50                | -40    |       |     |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 6.00                 | -6.00                | -40    |       |     |                  |
| -      | Feedthrough Noise. Channel-Select Input to Common I/O (Figure 14)                | V <sub>in</sub> ≤ 1 MHz Square Wave (t <sub>r</sub> = t <sub>f</sub> = 6 ns); Adjust R <sub>L</sub> at Setup so that I <sub>S</sub> = 0 A; Enable = GND R <sub>L</sub> = 600 Ω, C <sub>L</sub> = 50 pF                                                                                     | 2.25                 | -2.25                | 25     |       |     | mV <sub>PP</sub> |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 4.50                 | -4.50                | 105    |       |     |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 6.00                 | -6.00                | 135    |       |     |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            |                      |                      | 2.25   | -2.25 | 35  |                  |
|        |                                                                                  | R <sub>L</sub> = 10 kΩ, C <sub>L</sub> = 10 pF                                                                                                                                                                                                                                             | 4.50                 | -4.50                | 145    |       |     |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 6.00                 | -6.00                | 190    |       |     |                  |
| -      | Crosstalk Between Any Two Switches (Figure 18) (Test does not apply to HCT4051A) | f <sub>in</sub> = Sine Wave; Adjust f <sub>in</sub> Voltage to Obtain 0 dBm at V <sub>IS</sub><br>f <sub>in</sub> = 10 kHz, R <sub>L</sub> = 600 Ω, C <sub>L</sub> = 50 pF                                                                                                                 | 2.25                 | -2.25                | -50    |       |     | dB               |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 4.50                 | -4.50                | -50    |       |     |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 6.00                 | -6.00                | -50    |       |     |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            |                      |                      | 2.25   | -2.25 | -60 |                  |
|        |                                                                                  | f <sub>in</sub> = 1.0 MHz, R <sub>L</sub> = 50 Ω, C <sub>L</sub> = 10 pF                                                                                                                                                                                                                   | 4.50                 | -4.50                | -60    |       |     |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 6.00                 | -6.00                | -60    |       |     |                  |
| THD    | Total Harmonic Distortion (Figure 20)                                            | f <sub>in</sub> = 1 kHz, R <sub>L</sub> = 10 kΩ, C <sub>L</sub> = 50 pF<br>THD = THD <sub>measured</sub> - THD <sub>source</sub><br>V <sub>IS</sub> = 4.0 V <sub>PP</sub> sine wave<br>V <sub>IS</sub> = 8.0 V <sub>PP</sub> sine wave<br>V <sub>IS</sub> = 11.0 V <sub>PP</sub> sine wave |                      |                      |        |       |     | %                |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            |                      |                      |        |       |     |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 2.25                 | -2.25                | 0.10   |       |     |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 4.50                 | -4.50                | 0.08   |       |     |                  |
|        |                                                                                  |                                                                                                                                                                                                                                                                                            | 6.00                 | -6.00                | 0.05   |       |     |                  |

\*Limits not tested. Determined by design and verified by qualification.




Figure 7a. Typical On Resistance, V<sub>CC</sub> - V<sub>EE</sub> = 2.0 V




Figure 7b. Typical On Resistance, V<sub>CC</sub> - V<sub>EE</sub> = 3.0 V

# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A




Figure 7c. Typical On Resistance,  $V_{CC} - V_{EE} = 4.5$  V




Figure 7d. Typical On Resistance,  $V_{CC} - V_{EE} = 6.0$  V




Figure 7e. Typical On Resistance,  $V_{CC} - V_{EE} = 9.0$  V




Figure 7f. Typical On Resistance,  $V_{CC} - V_{EE} = 12.0$  V






Figure 8. On Resistance Test Set-Up


# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A




**Figure 9. Maximum Off Channel Leakage Current, Any One Channel, Test Set-Up**




**Figure 10. Maximum Off Channel Leakage Current, Common Channel, Test Set-Up**




**Figure 11. Maximum On Channel Leakage Current, Channel to Channel, Test Set-Up**



**Figure 12. Maximum On Channel Bandwidth, Test Set-Up**




**Figure 13. Off Channel Feedthrough Isolation, Test Set-Up**




**Figure 14. Feedthrough Noise, Channel Select to Common Out, Test Set-Up**



# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A




**Figure 15a. Propagation Delays, Channel Select to Analog Out**




\*Includes all probe and jig capacitance

**Figure 15b. Propagation Delay, Test Set-Up Channel Select to Analog Out**




**Figure 16a. Propagation Delays, Analog In to Analog Out**




\*Includes all probe and jig capacitance

**Figure 16b. Propagation Delay, Test Set-Up Analog In to Analog Out**




**Figure 17a. Propagation Delays, Enable to Analog Out**




**Figure 17b. Propagation Delay, Test Set-Up Enable to Analog Out**

## MC74HCT4051A, MC74HCT4052A, MC74HCT4053A




\*Includes all probe and jig capacitance

**Figure 18. Crosstalk Between Any Two Switches, Test Set-Up**




**Figure 19. Power Dissipation Capacitance, Test Set-Up**



\*Includes all probe and jig capacitance

**Figure 20a. Total Harmonic Distortion, Test Set-Up**



**Figure 20b. Plot, Harmonic Distortion**

## APPLICATIONS INFORMATION

The maximum analog voltage swings are determined by the supply voltages  $V_{CC}$  and  $V_{EE}$ . The positive peak analog voltage should not exceed  $V_{CC}$ . Similarly, the negative peak analog voltage should not go below  $V_{EE}$ . In this example, the difference between  $V_{CC}$  and  $V_{EE}$  is ten volts. Therefore, using the configuration of Figure 21, a maximum analog signal of ten volts peak-to-peak can be controlled. Unused analog inputs/outputs may be left floating (i.e., not connected). However, tying unused analog inputs and outputs to  $V_{CC}$  or GND through a low value resistor helps minimize crosstalk and feed-through noise that may be picked up by an unused switch.

Although used here, balanced supplies are not a requirement. The only constraints on the power supplies are that:

$$\begin{aligned} V_{CC} - \text{GND} &= 2 \text{ to } 6 \text{ V} \\ V_{EE} - \text{GND} &= 0 \text{ to } -6 \text{ V} \\ V_{CC} - V_{EE} &= 2 \text{ to } 12 \text{ V} \\ &\text{and } V_{EE} \leq \text{GND} \end{aligned}$$

When voltage transients above  $V_{CC}$  and/or below  $V_{EE}$  are anticipated on the analog channels, external Germanium or Schottky diodes ( $D_x$ ) are recommended as shown in Figure 22. These diodes should be able to absorb the maximum anticipated current surges during clipping.

# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A




Figure 21. Application Example






Figure 22. External Germanium or Schottky Clipping Diodes



a. Using Pull-Up Resistors with a HC Device



b. Using HCT Interface

Figure 23. Interfacing LSTTL/NMOS to CMOS Inputs




Figure 24. Function Diagram, HCT4051A

# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A




Figure 26. Function Diagram, HCT4052A




Figure 25. Function Diagram, HCT4053A

## MC74HCT4051A, MC74HCT4052A, MC74HCT4053A

### ORDERING INFORMATION

| Device           | Package                   | Shipping†          |
|------------------|---------------------------|--------------------|
| MC74HCT4051ADG   | SOIC-16<br>(Pb-Free)      | 48 Units / Rail    |
| MC74HCT4051ADR2G | SOIC-16<br>(Pb-Free)      | 2500 / Tape & Reel |
| MC74HCT4051ADTG  | TSSOP-16*                 | 96 Units / Rail    |
| M74HCT4051ADTR2G | TSSOP-16*                 | 2500 / Tape & Reel |
| MC74HCT4052ADG   | SOIC-16<br>(Pb-Free)      | 48 Units / Rail    |
| MC74HCT4052ADR2G | SOIC-16<br>(Pb-Free)      | 2500 / Tape & Reel |
| MC74HCT4052ADTG  | TSSOP-16*                 | 96 Units / Rail    |
| M74HCT4052ADTR2G | TSSOP-16*                 | 2500 / Tape & Reel |
| MC74HCT4052ADWG  | SOIC-16 WIDE<br>(Pb-Free) | 48 Units / Rail    |
| M74HCT4052ADWR2G | SOIC-16 WIDE<br>(Pb-Free) | 1000 / Tape & Reel |
| MC74HCT4053ADG   | SOIC-16<br>(Pb-Free)      | 48 Units / Rail    |
| MC74HCT4053ADR2G | SOIC-16<br>(Pb-Free)      | 2500 / Tape & Reel |
| MC74HCT4053ADTG  | TSSOP-16*                 | 96 Units / Rail    |
| M74HCT4053ADTR2G | TSSOP-16*                 | 2500 / Tape & Reel |


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*This package is inherently Pb-Free.

# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A

## PACKAGE DIMENSIONS

TSSOP-16  
DT SUFFIX  
CASE 948F-01  
ISSUE B




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH. PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE -W-.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.90        | 5.10 | 0.193     | 0.200 |
| B   | 4.30        | 4.50 | 0.169     | 0.177 |
| C   | ---         | 1.20 | ---       | 0.047 |
| D   | 0.05        | 0.15 | 0.002     | 0.006 |
| F   | 0.50        | 0.75 | 0.020     | 0.030 |
| G   | 0.65 BSC    | ---  | 0.026 BSC | ---   |
| H   | 0.18        | 0.28 | 0.007     | 0.011 |
| J   | 0.09        | 0.20 | 0.004     | 0.008 |
| J1  | 0.09        | 0.16 | 0.004     | 0.006 |
| K   | 0.19        | 0.30 | 0.007     | 0.012 |
| K1  | 0.19        | 0.25 | 0.007     | 0.010 |
| L   | 6.40 BSC    | ---  | 0.252 BSC | ---   |
| M   | 0°          | 8°   | 0°        | 8°    |

## SOLDERING FOOTPRINT\*




\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A

## PACKAGE DIMENSIONS

SOIC-16  
D SUFFIX  
CASE 751B-05  
ISSUE K




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

| DIM | MILLIMETERS |       | INCHES    |       |
|-----|-------------|-------|-----------|-------|
|     | MIN         | MAX   | MIN       | MAX   |
| A   | 9.80        | 10.00 | 0.386     | 0.393 |
| B   | 3.80        | 4.00  | 0.150     | 0.157 |
| C   | 1.35        | 1.75  | 0.054     | 0.068 |
| D   | 0.35        | 0.49  | 0.014     | 0.019 |
| F   | 0.40        | 1.25  | 0.016     | 0.049 |
| G   | 1.27 BSC    |       | 0.050 BSC |       |
| J   | 0.19        | 0.25  | 0.008     | 0.009 |
| K   | 0.10        | 0.25  | 0.004     | 0.009 |
| M   | 0°          | 7°    | 0°        | 7°    |
| P   | 5.80        | 6.20  | 0.229     | 0.244 |
| R   | 0.25        | 0.50  | 0.010     | 0.019 |

## SOLDERING FOOTPRINT\*




\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# MC74HCT4051A, MC74HCT4052A, MC74HCT4053A

## PACKAGE DIMENSIONS

SOIC-16 WIDE  
DW SUFFIX  
CASE 751G-03  
ISSUE C



### NOTES:

1. DIMENSIONS ARE IN MILLIMETERS.
2. INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 1994.
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 PER SIDE.
5. DIMENSION B DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.13 TOTAL IN EXCESS OF THE B DIMENSION AT MAXIMUM MATERIAL CONDITION.

| DIM | MILLIMETERS |       |
|-----|-------------|-------|
|     | MIN         | MAX   |
| A   | 2.35        | 2.65  |
| A1  | 0.10        | 0.25  |
| B   | 0.35        | 0.49  |
| C   | 0.23        | 0.32  |
| D   | 10.15       | 10.45 |
| E   | 7.40        | 7.60  |
| e   | 1.27 BSC    |       |
| H   | 10.05       | 10.55 |
| h   | 0.25        | 0.75  |
| L   | 0.50        | 0.90  |
| q   | 0 °         | 7 °   |

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada

Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910

Japan Customer Focus Center  
Phone: 81-3-5773-3850

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative

MC74HCT4051A/D



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9