

# LQA30T200C, LQA30B200C

## Qspeed™ Family




200 V, 30 A Common-Cathode Diode

### Product Summary

|                                    |      |    |
|------------------------------------|------|----|
| $I_{F(AVG)}$ per diode             | 15   | A  |
| $V_{RRM}$                          | 200  | V  |
| $Q_{RR}$ (Typ at 125 °C)           | 55.4 | nC |
| $I_{RRM}$ (Typ at 125 °C)          | 3.5  | A  |
| Softness $t_b/t_a$ (Typ at 125 °C) | 0.31 |    |

### Pin Assignment



### RoHS Compliant

Package uses Lead-free plating and "Green" mold compound Halogen free per IEC 61249-2-21.

### General Description

This device has the lowest  $Q_{RR}$  of any 200 V Silicon diode. Its recovery characteristics increase efficiency, reduce EMI and eliminate snubbers.

### Applications

- AC/DC and DC/DC output rectification
  - Output and freewheeling diodes
- Motor drive circuits
- DC-AC inverters

### Features

- Low  $Q_{RR}$ , Low  $I_{RRM}$ , Low  $t_{RR}$
- High  $dI_F/dt$  capable (1000A/ $\mu$ s)
- Soft recovery

### Benefits

- Increases efficiency
  - Eliminates need for snubber circuits
  - Reduces EMI filter component size and count
- Enables extremely fast switching

### Absolute Maximum Ratings

Absolute maximum ratings are the values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

| Symbol       | Parameter                            | Conditions                                                                   | Rating     | Units |
|--------------|--------------------------------------|------------------------------------------------------------------------------|------------|-------|
| $V_{RRM}$    | Peak repetitive reverse voltage      | $T_J = 25\text{ °C}$                                                         | 200        | V     |
| $I_{F(AVG)}$ | Average forward current              | Per Diode, $T_J = 150\text{ °C}$ , $T_C = 120\text{ °C}$                     | 15         | A     |
|              |                                      | Per Device, $T_J = 150\text{ °C}$ , $T_C = 120\text{ °C}$                    | 30         | A     |
| $I_{FSM}$    | Non-repetitive peak surge current    | Per Diode, 60 Hz, 1/2 cycle                                                  | 130        | A     |
| $I_{FSM}$    | Non-repetitive peak surge current    | Per Diode, 1/2 cycle of $t = 28\text{ }\mu$ s Sinusoid, $T_C = 25\text{ °C}$ | 350        | A     |
| $T_J$        | Operating junction temperature range |                                                                              | -55 to 150 | °C    |
| $T_{STG}$    | Storage temperature                  |                                                                              | -55 to 150 | °C    |
|              | Lead soldering temperature           | Leads at 1.6 mm from case, 10 sec                                            | 300        | °C    |
| $P_D$        | Power dissipation                    | $T_C = 25\text{ °C}$                                                         | 56.8       | W     |

### Thermal Resistance

| Symbol          | Resistance from:    | Conditions      | Rating | Units |
|-----------------|---------------------|-----------------|--------|-------|
| $R_{\theta JA}$ | Junction to ambient | TO-220AB (only) | 62     | °C/W  |
| $R_{\theta JC}$ | Junction to case    | Per Diode       | 2.2    | °C/W  |
|                 |                     | Per Device      | 1.1    | °C/W  |

## Electrical Specifications at $T_J = 25\text{ }^{\circ}\text{C}$ (unless otherwise specified)

| Symbol                            | Parameter                                   | Conditions                                                                         | Min                     | Typ  | Max  | Units |    |
|-----------------------------------|---------------------------------------------|------------------------------------------------------------------------------------|-------------------------|------|------|-------|----|
| DC Characteristics per diode      |                                             |                                                                                    |                         |      |      |       |    |
| I <sub>R</sub>                    | Reverse current per diode                   | V <sub>R</sub> = 200 V, T <sub>J</sub> = 25 °C                                     | -                       | -    | 500  | μA    |    |
|                                   |                                             | V <sub>R</sub> = 200 V, T <sub>J</sub> = 125 °C                                    | -                       | 0.6  | -    | mA    |    |
| V <sub>F</sub>                    | Forward voltage per diode                   | I <sub>F</sub> = 15 A, T <sub>J</sub> = 25 °C                                      | -                       | 0.98 | 1.2  | V     |    |
|                                   |                                             | I <sub>F</sub> = 15 A, T <sub>J</sub> = 150 °C                                     | -                       | 0.86 | -    | V     |    |
| C <sub>J</sub>                    | Junction capacitance per diode              | V <sub>R</sub> = 10 V, 1 MHz                                                       | -                       | 54   | -    | pF    |    |
| Dynamic Characteristics per diode |                                             |                                                                                    |                         |      |      |       |    |
| t <sub>RR</sub>                   | Reverse recovery time, per diode            | dI <sub>F</sub> /dt = 200 A/μs<br>V <sub>R</sub> = 130 V,<br>I <sub>F</sub> = 15 A | T <sub>J</sub> = 25 °C  | -    | 16.5 | -     | ns |
|                                   |                                             |                                                                                    | T <sub>J</sub> = 125 °C | -    | 25.4 | -     | ns |
| Q <sub>RR</sub>                   | Reverse recovery charge, per diode          | dI <sub>F</sub> /dt = 200 A/μs<br>V <sub>R</sub> = 130 V,<br>I <sub>F</sub> = 15 A | T <sub>J</sub> = 25 °C  | -    | 21.5 | 33    | nC |
|                                   |                                             |                                                                                    | T <sub>J</sub> = 125 °C | -    | 55.4 | -     | nC |
| I <sub>RRM</sub>                  | Maximum reverse recovery current, per diode | dI <sub>F</sub> /dt = 200 A/μs<br>V <sub>R</sub> = 130 V,<br>I <sub>F</sub> = 15 A | T <sub>J</sub> = 25 °C  | -    | 2.1  | 3.1   | A  |
|                                   |                                             |                                                                                    | T <sub>J</sub> = 125 °C | -    | 3.5  | -     | A  |
| S                                 | Softness per diode = $\frac{t_b}{t_a}$      | dI <sub>F</sub> /dt = 200 A/μs<br>V <sub>R</sub> = 130 V,<br>I <sub>F</sub> = 15 A | T <sub>J</sub> = 25 °C  | -    | 0.44 | -     |    |
|                                   |                                             |                                                                                    | T <sub>J</sub> = 125 °C | -    | 0.31 | -     |    |

**Note to component engineers:** Q-Series diodes employ Schottky technologies in their design and construction. Therefore, component engineers should plan their test setups to be similar to traditional Schottky test setups. (For further details, see application note AN-300.)




Figure 1. Reverse Recovery Definitions




Figure 2. Reverse Recovery Test Circuit

## Electrical Specifications at $T_J = 25\text{ }^{\circ}\text{C}$ (unless otherwise specified)







Figure 3. Typical  $I_F$  vs  $V_F$ Figure 4. Typical  $I_F$  vs  $V_F$ Figure 5. Typical  $C_i$  vs  $V_R$ 

Figure 6. DC Current Derating Curve

Figure 7. Typical  $Q_{RR}$  vs  $I_F$  at  $T_J = 125\text{ }^{\circ}\text{C}$ Figure 8. Typical  $t_{RR}$  vs  $I_F$  at  $T_J = 125\text{ }^{\circ}\text{C}$




Figure 9. Power Derating Curve




Figure 10. IF (Peak) vs Tc, f = 70 kHz





Figure 11. Normalized Maximum Transient Thermal Impedance

## Dimensional Outline Drawings


TO-220AB



| Dim | Millimeters |       |
|-----|-------------|-------|
|     | MIN         | MAX   |
| A   | 4.32        | 4.70  |
| A1  | 1.11        | 1.38  |
| A2  | 2.59        | 2.79  |
| b   | 0.77        | 1.00  |
| b2  | 1.23        | 1.36  |
| C   | 0.34        | 0.47  |
| D   | 14.71       | 15.75 |
| D1  | 9.05        | 9.25  |
| E   | 9.96        | 10.36 |
| e   | 2.44        | 2.64  |
| e1  | 4.98        | 5.18  |
| L   | 12.70       | 14.22 |
| L1  | —           | 3.90  |
| ØP  | 3.71        | 3.96  |
| Q   | 2.54        | 2.90  |

| Mechanical Mounting Method        | Maximum Torque / Pressure specification                                                     |
|-----------------------------------|---------------------------------------------------------------------------------------------|
| Screw through hole in package tab | 1 Newton Meter (nm) or 8.8 inch-pounds (lb-in)                                              |
| Clamp against package body        | 12.3 kilogram-force per square centimeter (kgf/cm <sup>2</sup> ) or 175 lbf/in <sup>2</sup> |

TO-263AB



| Dim | Millimeters |          |
|-----|-------------|----------|
|     | MIN         | MAX      |
| A   | 4.40        | 4.70     |
| A1  | 0.00        | 0.25     |
| A2  | 2.59        | 2.79     |
| b   | 0.77        | 0.90     |
| b2  | 1.23        | 1.36     |
| c2  | 1.22        | 1.32     |
| D   | 9.05        | 9.25     |
| E   | 10.06       | 10.26    |
| e   | 2.54 BSC    | 2.54 BSC |
| H   | 14.70       | 15.50    |
| L   | 2.00        | 2.60     |
| L1  | 1.17        | 1.40     |
| L2  | —           | 1.75     |
| L3  | 0.25 BSC    | 0.25 BSC |
| L4  | 2.00 BSC    | 2.00 BSC |
| Ø   | 0°          | 8°       |
| Ø1  | 5°          | 9°       |
| Ø2  | 1°          | 5°       |

**Soldering time and temperature:** This product has been designed for use with high-temperature, lead-free solder. The component leads can be subjected to a maximum temperature of 300 °C, for up to 10 seconds. See Application Note AN-303, for more details.

## Ordering Information

| Part Number | Package  | Packing        |
|-------------|----------|----------------|
| LQA30T300C  | TO-220AB | 50 units/tube  |
| LQA30B300C  | TO-263AB | 800 units/reel |

The information contained in this document is subject to change without notice

---

| Revision | Notes           | Date  |
|----------|-----------------|-------|
| 1.0      | Initial Release | 04/13 |

## For the latest updates, visit our website: [www.powerint.com](http://www.powerint.com)

Power Integrations reserves the right to make changes to its products at any time to improve reliability or manufacturability. Power Integrations does not assume any liability arising from the use of any device or circuit described herein. POWER INTEGRATIONS MAKES NO WARRANTY HEREIN AND SPECIFICALLY DISCLAIMS ALL WARRANTIES INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF THIRD PARTY RIGHTS.

### PATENT INFORMATION

The products and applications illustrated herein (including transformer construction and circuits' external to the products) may be covered by one or more U.S. and foreign patents, or potentially by pending U.S. and foreign patent applications assigned to Power Integrations. A complete list of Power Integrations' patents may be found at [www.powerint.com](http://www.powerint.com). Power Integrations grants its customers a license under certain patent rights as set forth at <http://www.powerint.com/ip.htm>.

The PI Logo, TOPSwitch, TinySwitch, LinkSwitch, LYTSwitch, DPA-Switch, PeakSwitch, CAPZero, SENZero, LinkZero, HiperPFS, HiperTFS, HiperLCS, Qspeed, EcoSmart, Clampless, E-Shield, Filterfuse, StackFET, PI Expert and PI FACTS are trademarks of Power Integrations, Inc. Other trademarks are property of their respective companies. ©Copyright 2013 Power Integrations, Inc.

## Power Integrations Worldwide Sales Support Locations

### WORLD HEADQUARTERS

5245 Hellyer Avenue  
San Jose, CA 95138, USA.  
Main: +1-408-414-9200  
Customer Service:  
Phone: +1-408-414-9665  
Fax: +1-408-414-9765  
e-mail: [usasales@powerint.com](mailto:usasales@powerint.com)

### GERMANY

Lindwurmstrasse 114  
80337, Munich  
Germany  
Phone: +49-895-527-39110  
Fax: +49-895-527-39200  
e-mail: [eurosales@powerint.com](mailto:eurosales@powerint.com)

### JAPAN

Kosei Dai-3 Building  
2-12-11, Shin-Yokohama,  
Kohoku-ku, Yokohama-shi,  
Kanagawa 222-0033  
Japan  
Phone: +81-45-471-1021  
Fax: +81-45-471-3717  
e-mail: [japansales@powerint.com](mailto:japansales@powerint.com)

### TAIWAN

5F, No. 318, Nei Hu Rd.,  
Sec. 1  
Nei Hu District  
Taipei 11493, Taiwan R.O.C.  
Phone: +886-2-2659-4570  
Fax: +886-2-2659-4550  
e-mail: [taiwansales@powerint.com](mailto:taiwansales@powerint.com)

### CHINA (SHANGHAI)

Rm 1601/1610, Tower 1,  
Kerry Everbright City  
No. 218 Tianmu Road West,  
Shanghai, P.R.C. 200070  
Phone: +86-21-6354-6323  
Fax: +86-21-6354-6325  
e-mail: [chinasales@powerint.com](mailto:chinasales@powerint.com)

### INDIA

#1, 14<sup>th</sup> Main Road  
Vasanthanagar  
Bangalore-560052  
India  
Phone: +91-80-4113-8020  
Fax: +91-80-4113-8023  
e-mail: [indiasales@powerint.com](mailto:indiasales@powerint.com)

### KOREA

RM 602, 6FL  
Korea City Air Terminal B/D,  
159-6  
Samsung-Dong, Kangnam-Gu,  
Seoul, 135-728 Korea  
Phone: +82-2-2016-6610  
Fax: +82-2-2016-6630  
e-mail: [koreasales@powerint.com](mailto:koreasales@powerint.com)

### EUROPE HQ

1st Floor, St. James's House  
East Street, Farnham  
Surrey GU9 7TJ  
United Kingdom  
Phone: +44 (0) 1252-730-141  
Fax: +44 (0) 1252-727-689  
e-mail: [eurosales@powerint.com](mailto:eurosales@powerint.com)

### CHINA (SHENZHEN)

3rd Floor, Block A,  
Zhongtuo International Business  
Center, No. 1061, Xiang Mei Rd,  
FuTian District, ShenZhen,  
China, 518040  
Phone: +86-755-8379-3243  
Fax: +86-755-8379-5828  
e-mail: [chinasales@powerint.com](mailto:chinasales@powerint.com)

### ITALY

Via Milanese 20, 3<sup>rd</sup> Fl.  
20099 Sesto San Giovanni  
(MI) Italy  
Phone: +39-024-550-8701  
Fax: +39-028-928-6009  
e-mail: [eurosales@powerint.com](mailto:eurosales@powerint.com)

### SINGAPORE

51 Newton Road,  
#19-01/05 Goldhill Plaza  
Singapore, 308900  
Phone: +65-6358-2160  
Fax: +65-6358-2015  
e-mail: [singaporesales@powerint.com](mailto:singaporesales@powerint.com)

### APPLICATIONS HOTLINE

World Wide +1-408-414-9660

### APPLICATIONS FAX

World Wide +1-408-414-9760



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9