20 Series

Vitreous Enamel Conformal Axial Terminal Wirewound, 5% Tolerance Std.

The 20 Series axial terminal resistors are both durable and economical. They have all the electrical attributes of the more expensive 90 Series resistors, including all-welded construction.

They offer the durability of a lead free conformal vitreous enamel coating and are ideal for computer, communications and industrial applications in which cost, quality, and reliability are key considerations.

FEATURES

- Rugged vitreous enamel coating withstands high humidity and temperature cycling.
- Durable construction, recommended for industrial applications where reliability is paramount.
- All-welded construction.
- Flame resistant lead free vitreous enamel coating.
- RoHS compliant; Add "E" suffix to part number to specify.

SERIES SPECIFICATIONS

Series	Wattage	Ohms	Max. Voltage*
21	1	1.0-3.0K	75
22	2	1.0-3.0K	65
23	3	0.1-10K	135
25	5	0.1-28K	330
27	7	0.1-25K	450
20	10	0.1-100K	720

12.5 watt size available on special order

*Maximum Voltage is based on Ohm's Law [$V=\sqrt{(P*R)}$] as limited by the resistance value of specified product

CHARACTERISTICS

Coating	Conformal lead free vitreous enamel
Core	Ceramic.
Terminals	Solder-coated axial. RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu
Derating	Linearly from 100% @ +25°C to 0% @ +350°C
Tolerance	±5% standard; other tolerances available
Power rating	Based on 25°C free air rating (other wattages available)
Overload	Under 7 watts: 5 times rated wattage for 5 seconds; 7 watts and over: 10 times rated wattage for 5 seconds
Temperature coefficient	1 to 9.99 ohms: ±50 ppm/°C; 10 ohms and over: ±30 ppm/°C

DIMENSIONS

(in./mm max.)



Series	Wattage	Length* (max.)	Diam.* (max.)	Lead ga.
21	1	0.421 / 10.7	0.156 / 4.0	24
22	2	0.421 / 10.7	0.219 / 5.6	20
23	3	0.515 / 13.1	0.220 / 5.6	20
25	5	1.015 / 25.8	0.276 / 7.0	20
27	7	1.265 / 32.1	0.394 / 10.0	20
20	10	1.859 / 47.2	0.394 / 10.0	20

*For units below 1Ω, add 15% to body diameter, 10% to body length.

(continued)

20 Series

Vitreous Enamel Conformal Axial Terminal Wirewound, 5% Tolerance Std.

ORDERING INFORMATION

Standard part numbers

Ohmic value	Part No. Prefix ➤ Suffix ▼	Wattage 1 (21J)	2 (22J)	3 (23J)	5 (25J)	7 (27J)	10 (20J)
0.10	R10			✔	✔		✔
0.13	R13			✔	✔		✔
0.15	R15			✔	✔		✔
0.20	R20			✔	✔		✔
0.25	R25			✔	✔		✔
0.30	R30			✔	✔		✔
0.33	R33			✔	✔		✔
0.50	R50			✔	✔		✔
0.75	R75			✔	✔		✔
1	1R0	✔	✔	✔	✔	✔	✔
1.5	1R5	✔	✔	✔	✔	✔	✔
2	2R0	✔	✔	✔	✔	✣	✔
2.2	2R2	✔	✔	✔	✔	✣	✔
3	3R0	✔	✔	✔	✔	✔	✔
4	4R0	✔	✣	✔	✔	✣	✔
5	5R0	✔	✔	✔	✔	✣	✔
7.5	7R5	✔	✔	✔	✔	✣	✔
10	10R	✔	✔	✔	✔	✣	✔
12	12R	✣	✣	✔	✔	✣	✔
15	15R	✔	✣	✔	✣	✔	✔
18	18R	✔	✣	✔	✔	✣	✔
20	20R	✔	✔	✔	✔	✣	✔
22	22R	✔	✔	✔	✔	✣	✔
25	25R	✣	✔	✔	✔	✣	✔
27	27R	✔	✔	✔	✔	✣	✣
30	30R	✔	✔	✔	✔	✣	✔
33	33R	✔	✔	✔	✔	✔	✔
35	35R	✣	✣	✣	✔	✣	✣
39	39R	✔	✔	✔	✣	✣	✔
40	40R	✔	✣	✔	✔	✣	✔
47	47R	✔	✔	✔	✔	✣	✔
50	50R	✔	✔	✔	✔	✔	✔
56	56R	✣	✔	✔	✔	✣	✣
62	62R	✣	✣	✔	✔	✣	✔
68	68R	✔	✔	✔	✔	✣	✔
75	75R	✔	✔	✔	✔	✣	✔
82	82R	✔	✔	✔	✔	✣	✔
100	100	✔	✣	✔	✔	✔	✔
120	120	✔	✔	✔	✔	✣	✔
125	125	✣	✣	✔	✔	✔	✔
150	150	✔	✔	✔	✔	✣	✔
180	180	✔	✔	✔	✔	✣	✔
200	200	✔	✔	✔	✔	✔	✔
220	220	✔	✔	✔	✔	✣	✔
225	225	✣	✣	✣	✣	✣	✣
250	250	✔	✔	✔	✔	✣	✔
270	270	✔	✔	✔	✔	✣	✣
300	300	✔	✔	✔	✔	✣	✔
330	330	✔	✔	✔	✔	✣	✔
350	350	✣	✔	✣	✔	✣	✔
390	390	✔	✣	✔	✣	✣	✣
400	400	✣	✣	✔	✔	✣	✔
450	450	✣	✣	✣	✔	✣	✔
470	470	✔	✔	✔	✔	✣	✔
500	500	✔	✔	✔	✔	✔	✔
560	560	✔	✔	✔	✔	✣	✣
600	600	✔	✔	✔	✔	✣	✔
680	680	✔	✣	✔	✔	✣	✔
750	750	✔	✔	✔	✔	✣	✔
800	800	✔	✣	✔	✔	✣	✣
820	820	✔	✔	✔	✔	✣	✔
900	900	✣	✔	✔	✔	✣	✣
1,000	1K0	✔	✔	✔	✔	✔	✔
1,100	1K1	✣	✣	✔	✔	✣	✔
1,200	1K2	✔	✔	✔	✔	✣	✔
1,500	1K5	✔	✔	✔	✔	✣	✔
1,800	1K8	✔	✔	✔	✣	✣	✣
2,000	2K0	✣	✔	✔	✔	✣	✔
2,200	2K2	✔	✔	✔	✔	✣	✔
2,500	2K5	✔	✔	✔	✔	✣	✔
2,700	2K7	✔	✔	✔	✣	✣	✔
3,000	3K0	✔	✔	✔	✔	✣	✔
3,300	3K3			✔	✔	✣	✣
3,500	3K5			✣	✔	✣	✣
3,900	3K9			✔	✔	✣	✔
4,000	4K0			✔	✔	✣	✔
4,500	4K5			✣	✔	✣	✣
4,700	4K7			✔	✔	✣	✔
5,000	5K0			✔	✔	✔	✔
6,000	6K0			✔	✔	✔	✔
6,800	6K8			✔	✔	✣	✣
7,000	7K0			✔	✔	✣	✣
7,500	7K5			✔	✔	✣	✔
8,000	8K0			✔	✔	✣	✔
9,000	9K0			✔	✣	✣	✣
10,000	10K			✔	✔	✣	✔
12,000	12K				✔	✣	✔
13,000	13K					✣	✔
15,000	15K				✔	✣	✔
17,000	17K					✣	✣
20,000	20K				✔	✔	✔
22,000	22K				✔	✣	✣
25,000	25K				✔	✣	✔
30,000	30K						✔
33,000	33K						✣
35,000	35K						✣
40,000	40K						✔
50,000	50K						✔

✔ = Standard values

✣ = Non-standard values subject to minimum handling charge per item

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.

RoHS Compliant

21JR10E

20 Series	Wattage	Tolerance	Resistance Value
Vitreous Enamel	1 = 1W	J = 5%	R10 = 0.10Ω
Axial Lead	2		1R0 = 1.0Ω
Wirewound	3		10R = 10.0Ω
	5		250 = 250Ω
	7		1K0 = 1,000Ω
	0 = 10W		4K5 = 4,500Ω
			50K = 50,000Ω

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9