SPEJ Compact Momentary Type

Two poles and two contact points, Comfortable momentary operation with click feel

Typical Specifications

Items		Specifications
Rating (max.) (Resistive load)		0.2A 14V DC
Contact resistance (Initial/After operating life)		150mΩ max. / 150mΩ max.
Operating forces		3.5±0.7N
Operating life	Without load	10,000 cycles
	With load	10,000 cycles (0.2A 14V DC)

Product Line

Travel (mm)	Poles	Positions	Minimum order unit (pcs.)		Product No.
			Japan	Export	
1.7	2	2	500	2,000	**SPEJ110100**

Packing Specifications

Taping

Number of packages (pcs.)			Tape width (mm)	Export package measurements (mm)
1 reel	1 case /Japan	1 case /export packing		
500	1,000	2,000	24	404×397×140

Unit:mm

Reel size



Dimensions

Unit:mm

Style



Circuit Diagram

(Viewed from Direction A)



Recommend Pattern

Unit:mm



Refer to P.130 for soldering conditions.

Series			Vertical			
			SPEH	**SPEJ**	**SPPH4**	**SPPH1**
Photo						
Dimensions (mm)	W		6	7	6.5	10
	D		6	7	8.5	10
	H		5	5.95	8.5	
Travel (mm)			—	—	2.2	1.5
Total travel (mm)			1.6	1.7	3	2.5
Number of poles			1	2		
Operating temperature range			−40℃ to +90℃	−40℃ to +85℃	−10℃ to +60℃	
Automotive use			●	●	—	●
Life cycle			★3	★3	★3	★3
Rating (max.) (Resistive load)			50mA 16V DC	0.2A 14V DC	0.1A 30V DC	
Rating (min.) (Resistive load)			10μA 1V DC	—	50μA 3V DC	
Durability	Operating life without load		100,000cycles 400mΩ max.	10,000cycles 150mΩ max.	10,000cycles 100mΩ max.	10,000cycles 40mΩ max.
	Operating life with load (at max. rated load)		100,000cycles 400mΩ max.	10,000cycles 150mΩ max.	10,000cycles 100mΩ max.	10,000cycles 40mΩ max.
Electrical performance	Initial contact resistance		200mΩ max.	150mΩ max.	100mΩ max.	20mΩ max.
	Insulation resistance		100MΩ min. 100V DC	100MΩ min. 500V DC		
	Voltage proof		250V AC for 1minute	500V AC for 1minute		
Mechanical performance	Terminal strength		—	—	5N for 1minute	
	Actuator strength	Operating direction	50N	49N	30N	50N
		Pulling direction	—	—	10N	—
Environmental performance	Cold		-40℃ 1000h	-40℃ 500h	-20℃ 96h	
	Dry heat		90℃ 1000h	85℃ 500h	85℃ 96h	
	Damp heat		60℃, 90 to 95%RH 1000h	60℃, 90 to 95%RH 500h	40℃, 90 to 95%RH 96h	
Page			119	120	121	122

Push Switches Soldering Conditions · · ·

Example of Reflow Soldering Condition

1. Heating method: Double heating method with infrared heater.
2. Temperature measurement: Thermocouple ϕ 0.1 to 0.2 CA (K) or CC (T) at soldering portion (copper foil surface). A heat resisting tape should be used for fixed measurement.
3. Temperature profile



Series (Reflow type)	A (℃) 3s max.	B (℃)	C (s)	D (℃)	E (℃)	F (s)
SPEJ	260	230	40	180	150	120
SPEF						
SPEH						

Notes

1. The condition mentioned above is the temperature on the mounting surface of a PC board. There are cases where the PC board's temperature greatly differs from that of the switch, depending on the PC board's material, size, thickness, etc. The above-stated conditions shall also apply to switch surface temperatures.
2. Soldering conditions differ depending on reflow soldering machines. Prior verification of soldering condition is highly recommended.

Reference for Hand Soldering

Series	Soldering temperature	Soldering time
SPPJ3, SPPJ2, SPUN, SPPH4, SPPH1	350±10℃	3+1/0s
SPED2, SPED4	350±10℃	3±0.5s
SPEJ	350±10℃	4s max.
SPEF	350±5℃	3s max.
SPEH	350℃ max.	3s max.
SPUJ	300±10℃	3+1/0s

Reference for Dip Soldering

(For PC board terminal types)

Series	Items		Dip soldering	
	Preheating temperature	Preheating time	Soldering temperature	Duration of immersion
SPPJ3	100℃ max.	60s max.	260±5℃	5±1s
SPUN	100℃ max.	60s max.	260±5℃	10±1s
SPUJ, SPPH4	—		260±5℃	5±1s
SPPJ2, SPPH1, SPED2, SPED4, SPEF	—		260±5℃	10±1s

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9