## **Surface Mount Schottky Power Rectifier**

#### Plastic SOD-123 Package

This device uses the Schottky Barrier principle with a large area metal-to-silicon power diode. Ideally suited for low voltage, high frequency rectification or as free wheeling and polarity protection diodes in surface mount applications where compact size and weight are critical to the system. This package also provides an easy to work with alternative to leadless 34 package style. Because of its small size, it is ideal for use in portable and battery powered products such as cellular and cordless phones, chargers, notebook computers, printers, PDAs and PCMCIA cards. Typical applications are AC-DC and DC-DC converters, reverse battery protection, and "Oring" of multiple supply voltages and any other application where performance and size are critical.

#### **Features**

- Guardring for Stress Protection
- Low Forward Voltage
- 125°C Operating Junction Temperature
- Epoxy Meets UL 94 V-0 @ 0.125 in
- Package Designed for Optimal Automated Board Assembly
- ESD Rating:
  - ♦ Human Body Model = 3B
  - ◆ Machine Model = C
- NRVB Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free and are RoHS Compliant\*

#### **Mechanical Characteristics**

• Device Marking: L4F

• Polarity Designator: Cathode Band

• Weight: 11.7 mg (approximately)

• Case: Epoxy, Molded

• Finish: All External Surfaces Corrosion Resistant and Terminal Leads are Readily Solderable

• Lead and Mounting Surface Temperature for Soldering Purposes: 260°C Max. for 10 Seconds



#### ON Semiconductor®

http://onsemi.com

# SCHOTTKY BARRIER RECTIFIER 1.0 AMPERES 40 VOLTS



SOD-123FL CASE 498 PLASTIC

#### **MARKING DIAGRAM**



L4F = Specific Device Code

M = Date Code

= Pb-Free Package)

(Note: Microdot may be in either location)

#### **ORDERING INFORMATION**

Device	Package	Shipping <sup>†</sup>		
MBR140SFT1G	SOD-123FL (Pb-Free)	3,000 / Tape & Reel **		
NRVB140SFT1G	SOD-123FL (Pb-Free)	3,000 / Tape & Reel **		
MBR140SFT3G	SOD-123FL (Pb-Free)	10,000 / Tape & Reel ***		
NRVB140SFT3G	SOD-123FL (Pb-Free)	10,000 / Tape & Reel ***		

<sup>\* 8</sup> mm Tape, 7" Reel

<sup>\*</sup>For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

<sup>\*\*\* 8</sup> mm Tape, 13" Reel

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

#### **MAXIMUM RATINGS**

Rating	Symbol	Value	Unit	
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V <sub>RRM</sub> V <sub>RWM</sub> V <sub>R</sub>	40	V	
Average Rectified Forward Current (At Rated V <sub>R</sub> , T <sub>L</sub> = 112°C)	Io	1.0	А	
Peak Repetitive Forward Current (At Rated V <sub>R</sub> , Square Wave, 100 kHz, T <sub>L</sub> = 95°C)	I <sub>FRM</sub>	2.0	А	
Non-Repetitive Peak Surge Current (Non-Repetitive peak surge current, halfwave, single phase, 60 Hz)	I <sub>FSM</sub>	30	А	
Storage Temperature	T <sub>stg</sub>	-55 to 150	°C	
Operating Junction Temperature	TJ	-55 to 125	°C	
Voltage Rate of Change (Rated V <sub>R</sub> , T <sub>J</sub> = 25°C)	dv/dt	10,000	V/μs	

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

#### THERMAL CHARACTERISTICS

Characteristic	Symbol	Value	Unit
Thermal Resistance, Junction-to-Lead (Note 1) Thermal Resistance, Junction-to-Lead (Note 2) Thermal Resistance, Junction-to-Ambient (Note 1) Thermal Resistance, Junction-to-Ambient (Note 2)	R <sub>tjl</sub> R <sub>tjl</sub> R <sub>tja</sub> R <sub>tja</sub>	26 21 325 82	°C/W


<sup>1.</sup> Mounted with minimum recommended pad size, PC Board FR4.

#### **ELECTRICAL CHARACTERISTICS**

Characteristic	Symbol	Value		Unit
Maximum Instantaneous Forward Voltage (Note 3), See Figure 2	V <sub>F</sub>	T <sub>J</sub> = 25°C	T <sub>J</sub> = 85°C	V
$(I_F = 0.1 \text{ A})$ $(I_F = 1.0 \text{ A})$ $(I_F = 3.0 \text{ A})$		0.36 0.55 0.85	0.30 0.515 0.88	
Maximum Instantaneous Reverse Current (Note 3), See Figure 4	I <sub>R</sub>	T <sub>J</sub> = 25°C	T <sub>J</sub> = 85°C	mA
(V <sub>R</sub> = 40 V) (V <sub>R</sub> = 20 V)		0.5 0.15	25 18	

<sup>3.</sup> Pulse Test: Pulse Width  $\leq 250~\mu\text{s},~\text{Duty Cycle} \leq 2\%.$ 


<sup>2.</sup> Mounted with 1 in. copper pad (Cu area 700 mm<sup>2</sup>).



1.0 T<sub>J</sub> = 125°C T<sub>J</sub> = 25°C T<sub>J</sub> = 25°C V<sub>F</sub>, MAXIMUM INSTANTANEOUS FORWARD VOLTAGE (VOLTS)


Figure 1. Typical Forward Voltage

Figure 2. Maximum Forward Voltage



**Figure 3. Typical Reverse Current** 

**Figure 4. Maximum Reverse Current** 






Figure 5. Current Derating

Figure 6. Forward Power Dissipation




Figure 7. Capacitance

Figure 8. Typical Operating Temperature Derating\*

\* Reverse power dissipation and the possibility of thermal runaway must be considered when operating this device under any reverse voltage conditions. Calculations of  $T_J$  therefore must include forward and reverse power effects. The allowable operating  $T_J$  may be calculated from the equation:  $T_J = T_{Jmax} - r(t)(Pf + Pr) \text{ where}$ 

r(t) = thermal impedance under given conditions,

Pf = forward power dissipation, and

Pr = reverse power dissipation

This graph displays the derated allowable  $T_J$  due to reverse bias under DC conditions only and is calculated as  $T_J = T_{Jmax} - r(t)Pr$ , where r(t) = Rthja. For other power applications further calculations must be performed.





Figure 9. Thermal Response

#### PACKAGE DIMENSIONS


#### SOD-123FL **CASE 498 ISSUE B**



- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
- CONTROLLING DIMENSION: MILLIMETER.
  DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH.
- DIMENSIONS D AND J ARE TO BE MEASURED ON FLAT SECTION OF THE LEAD: BETWEEN 0.10 AND 0.25 MM FROM THE LEAD TIP.

		MILLIMETERS			INCHES		
L	DIM	MIN	NOM	MAX	MIN	NOM	MAX
	Α	0.90	0.95	1.00	0.035	0.037	0.039
	A1	0.00	0.05	0.10	0.000	0.002	0.004
	b	0.70	0.90	1.10	0.028	0.035	0.043
	С	0.10	0.15	0.20	0.004	0.006	0.008
	D	1.50	1.65	1.80	0.059	0.065	0.071
	Е	2.50	2.70	2.90	0.098	0.106	0.114
	L	0.55	0.75	0.95	0.022	0.030	0.037
	ΗE	3.40	3.60	3.80	0.134	0.142	0.150
	θ	0°	-	8°	0°	-	8°

#### **SOLDERING FOOTPRINT\***



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and un are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice on semiconductor and are registered readerlands of semiconductor Components industries, Ite (SCILLC) and the series are injected to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

#### **PUBLICATION ORDERING INFORMATION**

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor P.O. Box 5163, Denver, Colorado 80217 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada

Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910 Japan Customer Focus Center

Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

#### **ПОСТАВКА** ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

многоканальный

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

### Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

#### http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

#### Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru\_6 moschip.ru 4 moschip.ru 9