

# NL17SZ125

## Non-Inverting 3-State Buffer

The NL17SZ125 is a high performance non-inverting buffer operating from a 1.65 V to 5.5 V supply.

### Features

- Extremely High Speed:  $t_{PD}$  2.6 ns (typical) at  $V_{CC} = 5.0$  V
- Designed for 1.65 V to 5.5 V  $V_{CC}$  Operation
- Overvoltage Tolerant Inputs and Outputs
- LVTTL Compatible – Interface Capability With 5.0 V TTL Logic with  $V_{CC} = 3.0$  V
- LVCMOS Compatible
- 24 mA Balanced Output Sink and Source Capability
- Near Zero Static Supply Current Substantially Reduces System Power Requirements
- 3-State OE Input is Active-Low
- Replacement for NC7SZ125
- Chip Complexity = 36 FETs
- NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable
- These Devices are Pb-Free and are RoHS Compliant




Figure 1. Pinout (Top View)




Figure 2. Logic Symbol

| PIN ASSIGNMENT |          |
|----------------|----------|
| 1              | OE       |
| 2              | IN A     |
| 3              | GND      |
| 4              | OUT Y    |
| 5              | $V_{CC}$ |




**ON Semiconductor®**

<http://onsemi.com>

### MARKING DIAGRAMS


  
SC-88A (SOT-353)  
DF SUFFIX  
CASE 419A




  
SOT-553  
XV5 SUFFIX  
CASE 463B



  
TSOP-5  
DT SUFFIX  
CASE 483



  
UDFN6  
1.0 x 1.0  
CASE 517BX



M0 = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package

(\*Note: Microdot may be in either location)

\*Date Code orientation and/or position may vary depending upon manufacturing location.

### FUNCTION TABLE

| OE Input | A Input | Y Output |
|----------|---------|----------|
| L        | L       | L        |
| L        | H       | H        |
| H        | X       | Z        |

X = Don't Care

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

## MAXIMUM RATINGS

| Symbol               | Parameter                                                                                                     | Value                  | Units |
|----------------------|---------------------------------------------------------------------------------------------------------------|------------------------|-------|
| V <sub>CC</sub>      | DC Supply Voltage                                                                                             | –0.5 to +7.0           | V     |
| V <sub>IN</sub>      | DC Input Voltage                                                                                              | –0.5 to +7.0           | V     |
| V <sub>OUT</sub>     | DC Output Voltage                                                                                             | –0.5 to +7.0           | V     |
| I <sub>IK</sub>      | DC Input Diode Current                                                                                        | –50                    | mA    |
| I <sub>OK</sub>      | DC Output Diode Current                                                                                       | –50                    | mA    |
| I <sub>OUT</sub>     | DC Output Sink Current                                                                                        | ±50                    | mA    |
| I <sub>CC</sub>      | DC Supply Current per Supply Pin                                                                              | ±100                   | mA    |
| T <sub>STG</sub>     | Storage Temperature Range                                                                                     | –65 to +150            | °C    |
| T <sub>L</sub>       | Lead Temperature, 1 mm from Case for 10 Seconds                                                               | 260                    | °C    |
| T <sub>J</sub>       | Junction Temperature Under Bias                                                                               | +150                   | °C    |
| θ <sub>JA</sub>      | Thermal Resistance (Note 1)<br>SC–88A/SOT–553<br>TSOP–5                                                       | 350<br>230             | °C/W  |
| P <sub>D</sub>       | Power Dissipation in Still Air at 85°C                                                                        | 150                    | mW    |
| MSL                  | Moisture Sensitivity                                                                                          | Level 1                |       |
| F <sub>R</sub>       | Flammability Rating<br>Oxygen Index: 28 to 34                                                                 | UL 94 V–0 @ 0.125 in   |       |
| V <sub>ESD</sub>     | ESD Withstand Voltage<br>Human Body Model (Note 2)<br>Machine Model (Note 3)<br>Charged Device Model (Note 4) | > 2000<br>> 200<br>N/A | V     |
| I <sub>LATCHUP</sub> | Latchup Performance Above V <sub>CC</sub> and Below GND at 125°C (Note 5)                                     | ±100                   | mA    |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.


1. Measured with minimum pad spacing on an FR4 board, using 10 mm–by–1 inch, 2 ounce copper trace with no air flow.
2. Tested to EIA/JESD22–A114–A.
3. Tested to EIA/JESD22–A115–A.
4. Tested to JESD22–C101–A.
5. Tested to EIA/JESD78.

## RECOMMENDED OPERATING CONDITIONS

| Symbol                          | Parameter                                                                                                                                                         | Min              | Max                   | Units |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|-----------------------|-------|
| V <sub>CC</sub>                 | DC Supply Voltage                                                                                                                                                 | 1.65             | 5.5                   | V     |
| V <sub>IN</sub>                 | DC Input Voltage                                                                                                                                                  | 0                | 5.5                   | V     |
| V <sub>OUT</sub>                | DC Output Voltage                                                                                                                                                 | 0                | 5.5                   | V     |
| T <sub>A</sub>                  | Operating Temperature Range                                                                                                                                       | –55              | +125                  | °C    |
| t <sub>r</sub> , t <sub>f</sub> | Input Rise and Fall Time<br>V <sub>CC</sub> = 1.8 V ±0.15 V<br>V <sub>CC</sub> = 2.5 V ±0.2 V<br>V <sub>CC</sub> = 3.0 V ±0.3 V<br>V <sub>CC</sub> = 5.0 V ±0.5 V | 0<br>0<br>0<br>0 | 20<br>20<br>10<br>5.0 | ns/V  |

**DEVICE JUNCTION TEMPERATURE VERSUS  
TIME TO 0.1% BOND FAILURES**

| Junction Temperature °C | Time, Hours | Time, Years |
|-------------------------|-------------|-------------|
| 80                      | 1,032,200   | 117.8       |
| 90                      | 419,300     | 47.9        |
| 100                     | 178,700     | 20.4        |
| 110                     | 79,600      | 9.4         |
| 120                     | 37,000      | 4.2         |
| 130                     | 17,800      | 2.0         |
| 140                     | 8,900       | 1.0         |



**Figure 3. Failure Rate vs. Time Junction Temperature**

**DC ELECTRICAL CHARACTERISTICS**

| Symbol           | Parameter                                                      | V <sub>CC</sub><br>(V)           | T <sub>A</sub> = 25°C                       |                                      |                                             | -55°C ≤ T <sub>A</sub> ≤ 125°C              |                                             | Units | Condition                                                                                                                              |
|------------------|----------------------------------------------------------------|----------------------------------|---------------------------------------------|--------------------------------------|---------------------------------------------|---------------------------------------------|---------------------------------------------|-------|----------------------------------------------------------------------------------------------------------------------------------------|
|                  |                                                                |                                  | Min                                         | Typ                                  | Max                                         | Min                                         | Max                                         |       |                                                                                                                                        |
| V <sub>IH</sub>  | High-Level Input Voltage                                       | 1.65 to 1.95<br>2.3 to 5.5       | 0.75 V <sub>CC</sub><br>0.7 V <sub>CC</sub> |                                      |                                             | 0.75 V <sub>CC</sub><br>0.7 V <sub>CC</sub> |                                             | V     |                                                                                                                                        |
| V <sub>IL</sub>  | Low-Level Input Voltage                                        | 1.65 to 1.95<br>2.3 to 5.5       |                                             |                                      | 0.25 V <sub>CC</sub><br>0.3 V <sub>CC</sub> |                                             | 0.25 V <sub>CC</sub><br>0.3 V <sub>CC</sub> | V     |                                                                                                                                        |
| V <sub>OH</sub>  | High-Level Output Voltage<br>V <sub>IN</sub> = V <sub>IH</sub> | 1.65<br>1.8<br>2.3<br>3.0<br>4.5 | 1.55<br>1.7<br>2.2<br>2.9<br>4.4            | 1.65<br>1.8<br>2.3<br>3.0<br>4.5     |                                             | 1.55<br>1.7<br>2.2<br>2.9<br>4.4            |                                             | V     | I <sub>OH</sub> = -100 μA                                                                                                              |
|                  |                                                                | 1.65<br>2.3<br>3.0<br>3.0<br>4.5 | 1.29<br>1.9<br>2.4<br>2.3<br>3.8            | 1.52<br>2.15<br>2.80<br>2.68<br>4.20 |                                             | 1.29<br>1.9<br>2.4<br>2.3<br>3.8            |                                             | V     | I <sub>OH</sub> = -4 mA<br>I <sub>OH</sub> = -8 mA<br>I <sub>OH</sub> = -16 mA<br>I <sub>OH</sub> = -24 mA<br>I <sub>OH</sub> = -32 mA |
| V <sub>OL</sub>  | Low-Level Output Voltage<br>V <sub>IN</sub> = V <sub>IL</sub>  | 1.65<br>1.8<br>2.3<br>3.0<br>4.5 |                                             | 0.0<br>0.0<br>0.0<br>0.0<br>0.0      | 0.1<br>0.1<br>0.1<br>0.1<br>0.1             |                                             | 0.1<br>0.1<br>0.1<br>0.1<br>0.1             | V     | I <sub>OL</sub> = 100 μA                                                                                                               |
|                  |                                                                | 1.65<br>2.3<br>3.0<br>3.0<br>4.5 |                                             | 0.08<br>0.10<br>0.15<br>0.22<br>0.22 | 0.24<br>0.30<br>0.40<br>0.55<br>0.55        |                                             | 0.24<br>0.30<br>0.40<br>0.55<br>0.55        | V     | I <sub>OL</sub> = 4 mA<br>I <sub>OL</sub> = 8 mA<br>I <sub>OL</sub> = 16 mA<br>I <sub>OL</sub> = 24 mA<br>I <sub>OL</sub> = 32 mA      |
| I <sub>IN</sub>  | Input Leakage Current                                          | 0 to 5.5                         |                                             |                                      | ±0.1                                        |                                             | ±1.0                                        | μA    | V <sub>IN</sub> = 5.5 V or GND                                                                                                         |
| I <sub>OZ</sub>  | 3-State Output Leakage                                         | 1.65 to 5.5                      |                                             |                                      | ±0.5                                        |                                             | ±5.0                                        | μA    | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>0 V ≤ V <sub>OUT</sub> ≤ 5.5 V                                                 |
| I <sub>OFF</sub> | Power Off Leakage Current                                      | 0                                |                                             |                                      | 1.0                                         |                                             | 10                                          | μA    | V <sub>IN</sub> = 5.5 V or<br>V <sub>OUT</sub> = 5.5 V                                                                                 |
| I <sub>CC</sub>  | Quiescent Supply Current                                       | 5.5                              |                                             |                                      | 1.0                                         |                                             | 10                                          | μA    | V <sub>IN</sub> = 5.5 V or GND                                                                                                         |

# NL17SZ125

## AC ELECTRICAL CHARACTERISTICS ( $t_R = t_F = 3.0 \text{ ns}$ )

| Symbol                 | Parameter                                                   | Condition                                                                                           | $V_{CC}$<br>(V) | $T_A = 25^\circ\text{C}$ |     |            | $-55^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$ |            | Units |
|------------------------|-------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-----------------|--------------------------|-----|------------|-----------------------------------------------------|------------|-------|
|                        |                                                             |                                                                                                     |                 | Min                      | Typ | Max        | Min                                                 | Max        |       |
| $t_{PLH}$<br>$t_{PHL}$ | Propagation Delay<br>AN to YN<br>(Figures 4 and 5, Table 1) | $R_L = 1 \text{ M}\Omega$ $C_L = 15 \text{ pF}$                                                     | $1.8 \pm 0.15$  | 2.0                      | 9.0 | 10         | 2.0                                                 | 10.5       | ns    |
|                        |                                                             | $R_L = 1 \text{ M}\Omega$ $C_L = 15 \text{ pF}$                                                     | $2.5 \pm 0.2$   | 1.0                      |     | 7.5        | 1.0                                                 | 8.0        |       |
|                        |                                                             | $R_L = 1 \text{ M}\Omega$ $C_L = 15 \text{ pF}$<br>$R_L = 500 \text{ }\Omega$ $C_L = 50 \text{ pF}$ | $3.3 \pm 0.3$   | 0.8<br>1.2               |     | 5.2<br>5.7 | 0.8<br>1.2                                          | 5.5<br>6.0 |       |
|                        |                                                             | $R_L = 1 \text{ M}\Omega$ $C_L = 15 \text{ pF}$<br>$R_L = 500 \text{ }\Omega$ $C_L = 50 \text{ pF}$ | $5.0 \pm 0.5$   | 0.5<br>0.8               |     | 4.5<br>5.0 | 0.5<br>0.8                                          | 4.8<br>5.3 |       |
| $t_{PZH}$<br>$t_{PZL}$ | Output Enable Time<br>(Figures 6, 7 and 8, Table 1)         | $R_L = 250 \text{ }\Omega$ $C_L = 50 \text{ pF}$                                                    | $1.8 \pm 0.15$  | 2.0                      | 7.6 | 9.5        | 2.0                                                 | 10         | ns    |
|                        |                                                             |                                                                                                     | $2.5 \pm 0.2$   | 1.8                      |     | 8.5        | 1.8                                                 | 9.0        |       |
|                        |                                                             |                                                                                                     | $3.3 \pm 0.3$   | 1.2                      |     | 6.2        | 1.2                                                 | 6.5        |       |
|                        |                                                             |                                                                                                     | $5.0 \pm 0.5$   | 0.8                      |     | 5.5        | 0.8                                                 | 5.8        |       |
| $t_{PHZ}$<br>$t_{PLZ}$ | Output Disable Time<br>(Figures 6, 7 and 8, Table 1)        | $R_L$ and $R_1 = 500 \text{ }\Omega$ $C_L = 50 \text{ pF}$                                          | $1.8 \pm 0.15$  | 2.0                      | 8.0 | 10         | 2.0                                                 | 10.5       | ns    |
|                        |                                                             |                                                                                                     | $2.5 \pm 0.2$   | 1.5                      |     | 8.0        | 1.5                                                 | 8.5        |       |
|                        |                                                             |                                                                                                     | $3.3 \pm 0.3$   | 0.8                      |     | 5.7        | 0.8                                                 | 6.0        |       |
|                        |                                                             |                                                                                                     | $5.0 \pm 0.5$   | 0.3                      |     | 4.7        | 0.3                                                 | 5.0        |       |

## CAPACITIVE CHARACTERISTICS

| Symbol    | Parameter                                 | Condition                                                                                                                                | Typical | Units |
|-----------|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|---------|-------|
| $C_{IN}$  | Input Capacitance                         | $V_{CC} = 5.5 \text{ V}$ , $V_I = 0 \text{ V}$ or $V_{CC}$                                                                               | 2.5     | pF    |
| $C_{OUT}$ | Output Capacitance                        | $V_{CC} = 5.5 \text{ V}$ , $V_I = 0 \text{ V}$ or $V_{CC}$                                                                               | 2.5     | pF    |
| $C_{PD}$  | Power Dissipation Capacitance<br>(Note 6) | 10 MHz, $V_{CC} = 3.3 \text{ V}$ , $V_I = 0 \text{ V}$ or $V_{CC}$<br>10 MHz, $V_{CC} = 5.5 \text{ V}$ , $V_I = 0 \text{ V}$ or $V_{CC}$ | 9<br>11 | pF    |

6.  $C_{PD}$  is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation:  $I_{CC(OPR)} = C_{PD} \cdot V_{CC} \cdot f_{in} + I_{CC}$ .  $C_{PD}$  is used to determine the no-load dynamic power consumption;  $P_D = C_{PD} \cdot V_{CC}^2 \cdot f_{in} + I_{CC} \cdot V_{CC}$ .






Figure 4. Switching Waveform




\*Includes all probe and jig capacitance.  
A 1 MHz square input wave is recommended for propagation delay tests.

Figure 5.  $t_{PLH}$  or  $t_{PHL}$



A 1 MHz square input wave is recommended for propagation delay tests.

Figure 6.  $t_{PZL}$  or  $t_{PLZ}$



A 1 MHz square input wave is recommended for propagation delay tests.

Figure 7.  $t_{PZH}$  or  $t_{PHZ}$




Figure 8. AC Output Enable and Disable Waveform

Table 1. OUTPUT ENABLE AND DISABLE TIMES

$t_R = t_F = 2.5$  ns, 10% to 90%;  $f = 1$  MHz;  $t_W = 500$  ns

| Symbol   | $V_{CC}$                          |                 |                                   |
|----------|-----------------------------------|-----------------|-----------------------------------|
|          | $3.3 \text{ V} \pm 0.3 \text{ V}$ | $2.7 \text{ V}$ | $2.5 \text{ V} \pm 0.2 \text{ V}$ |
| $V_{mi}$ | 1.5 V                             | 1.5 V           | $V_{CC}/2$                        |
| $V_{mo}$ | 1.5 V                             | 1.5 V           | $V_{CC}/2$                        |

## NL17SZ125

### DEVICE ORDERING INFORMATION

| Device           | Package                               | Shipping†          |
|------------------|---------------------------------------|--------------------|
| NL17SZ125DFT2G   | SC-88A (SOT-353)<br>(Pb-Free)         | 3000 / Tape & Reel |
| NLV17SZ125DFT2G* | SC-88A (SOT-353)<br>(Pb-Free)         | 3000 / Tape & Reel |
| NL17SZ125XV5T2G  | SOT-553<br>(Pb-Free)                  | 4000 / Tape & Reel |
| NL17SZ125DTT1G   | TSOP-5<br>(Pb-Free)                   | 3000 / Tape & Reel |
| NL17SZ125CMUTCG  | UDFN6, 1.0 x 1.0 x 0.35P<br>(Pb-Free) | 3000 / Tape & Reel |


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*NLV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable.

# NL17SZ125

## PACKAGE DIMENSIONS

SC-88A (SC-70-5/SOT-353)  
CASE 419A-02  
ISSUE L




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 419A-01 OBSOLETE. NEW STANDARD 419A-02.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | INCHES    |       | MILLIMETERS |      |
|-----|-----------|-------|-------------|------|
|     | MIN       | MAX   | MIN         | MAX  |
| A   | 0.071     | 0.087 | 1.80        | 2.20 |
| B   | 0.045     | 0.053 | 1.15        | 1.35 |
| C   | 0.031     | 0.043 | 0.80        | 1.10 |
| D   | 0.004     | 0.012 | 0.10        | 0.30 |
| G   | 0.026 BSC |       | 0.65 BSC    |      |
| H   | ---       | 0.004 | ---         | 0.10 |
| J   | 0.004     | 0.010 | 0.10        | 0.25 |
| K   | 0.004     | 0.012 | 0.10        | 0.30 |
| N   | 0.008 REF |       | 0.20 REF    |      |
| S   | 0.079     | 0.087 | 2.00        | 2.20 |

### SOLDER FOOTPRINT\*





\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# NL17SZ125

## PACKAGE DIMENSIONS

### SOT-553, 5 LEAD CASE 463B ISSUE B




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.

| DIM            | MILLIMETERS |      |      | INCHES    |       |       |
|----------------|-------------|------|------|-----------|-------|-------|
|                | MIN         | NOM  | MAX  | MIN       | NOM   | MAX   |
| A              | 0.50        | 0.55 | 0.60 | 0.020     | 0.022 | 0.024 |
| b              | 0.17        | 0.22 | 0.27 | 0.007     | 0.009 | 0.011 |
| c              | 0.08        | 0.13 | 0.18 | 0.003     | 0.005 | 0.007 |
| D              | 1.50        | 1.60 | 1.70 | 0.059     | 0.063 | 0.067 |
| E              | 1.10        | 1.20 | 1.30 | 0.043     | 0.047 | 0.051 |
| e              | 0.50 BSC    |      |      | 0.020 BSC |       |       |
| L              | 0.10        | 0.20 | 0.30 | 0.004     | 0.008 | 0.012 |
| H <sub>E</sub> | 1.50        | 1.60 | 1.70 | 0.059     | 0.063 | 0.067 |

### SOLDERING FOOTPRINT\*






\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# NL17SZ125

## PACKAGE DIMENSIONS

### TSOP-5 CASE 483-02 ISSUE H




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.
5. OPTIONAL CONSTRUCTION: AN ADDITIONAL TRIMMED LEAD IS ALLOWED IN THIS LOCATION. TRIMMED LEAD NOT TO EXTEND MORE THAN 0.2 FROM BODY.

| DIM | MILLIMETERS |      |
|-----|-------------|------|
|     | MIN         | MAX  |
| A   | 3.00 BSC    |      |
| B   | 1.50 BSC    |      |
| C   | 0.90        | 1.10 |
| D   | 0.25        | 0.50 |
| G   | 0.95 BSC    |      |
| H   | 0.01        | 0.10 |
| J   | 0.10        | 0.26 |
| K   | 0.20        | 0.60 |
| L   | 1.25        | 1.55 |
| M   | 0°          | 10°  |
| S   | 2.50        | 3.00 |

#### SOLDERING FOOTPRINT\*






\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# NL17SZ125

## PACKAGE DIMENSIONS


### UDFN6, 1x1, 0.35P CASE 517BX ISSUE O



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
  2. CONTROLLING DIMENSION: MILLIMETERS.
  3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.20 MM FROM TERMINAL TIP.
  4. PACKAGE DIMENSIONS EXCLUSIVE OF BURRS AND MOLD FLASH.

| MILLIMETERS |      |      |
|-------------|------|------|
| DIM         | MIN  | MAX  |
| A           | 0.50 | 0.65 |
| A1          | 0.00 | 0.05 |
| A3          | 0.13 | REF  |
| b           | 0.17 | 0.23 |
| D           | 1.00 | BSC  |
| E           | 1.00 | BSC  |
| e           | 0.35 |      |
| L           | 0.20 | 0.40 |
| L1          | ---  | 0.15 |
| L3          | 0.26 | 0.33 |

### RECOMMENDED SOLDERING FOOTPRINT\*



DIMENSION: MILLIMETERS

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada  
Europe, Middle East and Africa Technical Support:  
Phone: 421 33 790 2910  
Japan Customer Focus Center  
Phone: 81-3-5817-1050

ON Semiconductor Website: [www.onsemi.com](http://www.onsemi.com)

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9