

Surface Mount Fuse, 11 x 4.6 mm, Quick-Acting F, 250 VAC, 250 DC



Exemplary part photo depending on  
part no.

IEC 60127-4 · 250 VAC · 250 VDC · Quick-Acting F

See below:

[Approvals and Compliances](#)

### Description

- Directly solderable on printed circuit boards

### Applications

- Primary protection on SMD PCBs

### References

[Packaging Details](#)

Fuse Kit [Fuse Kit OMF](#)

### Weblinks

[pdf data sheet](#), [html datasheet](#), [General Product Information](#), [Packaging details](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

### Technical Data

|                              |                                                                                                                                                                                                                                                       |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated Voltage                | 250 VAC, 250 VDC                                                                                                                                                                                                                                      |
| Rated current                | 0.25 - 4 A                                                                                                                                                                                                                                            |
| Breaking Capacity            | 100 A                                                                                                                                                                                                                                                 |
| Characteristic               | Quick-Acting F                                                                                                                                                                                                                                        |
| Mounting                     | PCB, SMT                                                                                                                                                                                                                                              |
| Admissible Ambient Air Temp. | -55 °C to 125 °C                                                                                                                                                                                                                                      |
| Climatic Category            | 55/125/21 acc. to IEC 60068-1                                                                                                                                                                                                                         |
| Material: Housing            | Thermoplastic, UL 94V-0                                                                                                                                                                                                                               |
| Material: Terminals          | Tin-Plated Copper Alloy                                                                                                                                                                                                                               |
| Unit Weight                  | 0.36 g                                                                                                                                                                                                                                                |
| Storage Conditions           | 0 °C to 60 °C, max. 70% r.h.                                                                                                                                                                                                                          |
| Product Marking              |   , Type, Rated current, Characteristic, Breaking Capacity, Certification marks |

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| Soldering Methods            | Reflow, Wave<br><a href="#">Soldering Profile</a>                       |
| Solderability                | 245 °C / 3 sec acc. to IEC 60068-2-58, Test Td                          |
| Resistance to Soldering Heat | 260 °C / 10 sec acc. to IEC 60068-2-58, Test Td                         |
| Moisture Sensitivity Level   | MSL 1, J-STD-020                                                        |
| Case Resistance              | acc. to EIA/IS-722, Test 4.7<br>>100 MΩ (between leads and body)        |
| Flammability                 | min. UL 94V-1<br>(acc. to EIA/IS-722, Test 4.12)                        |
| Thermal Shock                | MIL-STD-202, Method 107D<br>(200 air-to-air cycles from -55 to +125 °C) |
| Load Humidity Test           | MIL-STD-202, Method 103<br>0.1 x ln @ 0.85 r.H. @ 85 °C                 |
| Moisture Resistance Test     | MIL-STD-202, Method 106<br>(50 cycles in a temp./mister chamber)        |
| Vibration, High Frequency    | MIL-STD-202, Method 204 Condition D                                     |
| Mechanical Shock             | MIL-STD-202, Method 213 Condition A                                     |
| Resistance to Solvents       | MIL-STD-202, Method 215                                                 |
| Terminal Strength            | MIL-STD-202, Method 211A<br>(Deflection of board 1 mm for 1 minute)     |

### Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

## Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type: OMF 250

| Approval Logo                                                                    | Certificates                  | Certification Body | Description                    |
|----------------------------------------------------------------------------------|-------------------------------|--------------------|--------------------------------|
|  | <a href="#">VDE Approvals</a> | VDE                | VDE Certificate Number: 106328 |
|  | <a href="#">UL Approvals</a>  | UL                 | UL File Number: E41599         |

## Product standards

Product standards that are referenced

| Organization                                                                     | Design                | Standard           | Description                                                                                    |
|----------------------------------------------------------------------------------|-----------------------|--------------------|------------------------------------------------------------------------------------------------|
|  | Designed according to | IEC 60127-4/2      | Miniature fuses. Part 4. Universal modular fuse-links for through-hole and surface mount types |
|  | Designed according to | UL 248-14          | Low voltage fuses - Part 14: Additional fuses                                                  |
|  | Designed according to | CSA22.2 No. 248.14 | Low-Voltage Fuses - Part 14: Supplemental Fuses                                                |

## Application standards

Application standards where the product can be used

| Organization                                                                     | Design                         | Standard       | Description                                                                                                          |
|----------------------------------------------------------------------------------|--------------------------------|----------------|----------------------------------------------------------------------------------------------------------------------|
|  | Designed for applications acc. | IEC/UL 62368-1 | IEC 62368-1 includes the basic requirements for safety of audio, video, information technology and office equipment. |



## Compliances

The product complies with following Guide Lines

| Identification                                                                     | Details                                      | Initiator   | Description                                                                                                                                                                                           |
|------------------------------------------------------------------------------------|----------------------------------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <a href="#">CE declaration of conformity</a> | SCHURTER AG | The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008. |
|  | <a href="#">RoHS</a>                         | SCHURTER AG | Directive RoHS 2011/65/EU, Amendment (EU) 2015/863                                                                                                                                                    |
|  | <a href="#">China RoHS</a>                   | SCHURTER AG | The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.                                                                                  |
|  | <a href="#">REACH</a>                        | SCHURTER AG | On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.                               |
|  |                                              | SCHURTER AG | Universal Modular Fuse meets the standard IEC 60127-4                                                                                                                                                 |

## Dimension [mm]

11 mm




Soldering pads

## Pre-Arcing Time

| Rated Current In | 1.25 x In min. | 2.0 x In max. | 10.0 x In min. | 10.0 x In max. |
|------------------|----------------|---------------|----------------|----------------|
| 0.25 A - 4 A     | 60 min         | 120 s         | 1 ms           | 10 ms          |

## Time-Current-Curves



## All Variants

| Rated Current [A] | Rated Voltage [VAC] | Rated Voltage [VDC] | Breaking Capacity | Voltage Drop 1.0 I <sub>n</sub> max. [mV] | Voltage Drop 1.0 I <sub>n</sub> typ. [mV] | Power Dissipation 1.25 I <sub>n</sub> typ. [mW] | Melting I <sup>2</sup> t 10.0 I <sub>n</sub> typ. [A <sup>2</sup> s] |  | Order Number |
|-------------------|---------------------|---------------------|-------------------|-------------------------------------------|-------------------------------------------|-------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|--------------|
| 0.25              | 250                 | 250                 | 1)                | -                                         | 1100                                      | 480                                             | 0.012                                                                | ●                                                                                     | 3403.0010.11 |
| 0.25              | 250                 | 250                 | 1)                | -                                         | 1100                                      | 480                                             | 0.012                                                                | ●                                                                                     | 3403.0010.24 |
| 0.315             | 250                 | 250                 | 1)                | -                                         | 1000                                      | 430                                             | 0.019                                                                | ●                                                                                     | 3403.0011.11 |
| 0.315             | 250                 | 250                 | 1)                | -                                         | 1000                                      | 430                                             | 0.019                                                                | ●                                                                                     | 3403.0011.24 |
| 0.4               | 250                 | 250                 | 2)                | 700                                       | 230                                       | 190                                             | 0.02                                                                 | ● ●                                                                                   | 3403.0012.11 |
| 0.4               | 250                 | 250                 | 2)                | 700                                       | 230                                       | 190                                             | 0.02                                                                 | ● ●                                                                                   | 3403.0012.24 |
| 0.5               | 250                 | 250                 | 1)                | 600                                       | 190                                       | 190                                             | 0.03                                                                 | ● ●                                                                                   | 3403.0013.11 |
| 0.5               | 250                 | 250                 | 1)                | 600                                       | 190                                       | 190                                             | 0.03                                                                 | ● ●                                                                                   | 3403.0013.24 |
| 0.63              | 250                 | 250                 | 1)                | 500                                       | 170                                       | 230                                             | 0.07                                                                 | ● ●                                                                                   | 3403.0014.11 |
| 0.63              | 250                 | 250                 | 1)                | 500                                       | 170                                       | 230                                             | 0.07                                                                 | ● ●                                                                                   | 3403.0014.24 |
| 0.8               | 250                 | 250                 | 1)                | 400                                       | 200                                       | 330                                             | 0.12                                                                 | ● ●                                                                                   | 3403.0015.11 |
| 0.8               | 250                 | 250                 | 1)                | 400                                       | 200                                       | 330                                             | 0.12                                                                 | ● ●                                                                                   | 3403.0015.24 |
| 1                 | 250                 | 250                 | 1)                | 300                                       | 170                                       | 390                                             | 0.23                                                                 | ● ●                                                                                   | 3403.0016.11 |
| 1                 | 250                 | 250                 | 1)                | 300                                       | 170                                       | 390                                             | 0.23                                                                 | ● ●                                                                                   | 3403.0016.24 |
| 1.25              | 250                 | 250                 | 1)                | 300                                       | 150                                       | 390                                             | 0.47                                                                 | ● ●                                                                                   | 3403.0017.11 |
| 1.25              | 250                 | 250                 | 1)                | 300                                       | 150                                       | 390                                             | 0.47                                                                 | ● ●                                                                                   | 3403.0017.24 |
| 1.6               | 250                 | 250                 | 1)                | 300                                       | 150                                       | 490                                             | 0.84                                                                 | ● ●                                                                                   | 3403.0018.11 |
| 1.6               | 250                 | 250                 | 1)                | 300                                       | 150                                       | 490                                             | 0.84                                                                 | ● ●                                                                                   | 3403.0018.24 |
| 2                 | 250                 | 250                 | 1)                | 300                                       | 140                                       | 600                                             | 1.4                                                                  | ● ●                                                                                   | 3403.0019.11 |
| 2                 | 250                 | 250                 | 1)                | 300                                       | 140                                       | 600                                             | 1.4                                                                  | ● ●                                                                                   | 3403.0019.24 |
| 2.5               | 250                 | 250                 | 1)                | 300                                       | 130                                       | 670                                             | 2.6                                                                  | ● ●                                                                                   | 3403.0020.11 |
| 2.5               | 250                 | 250                 | 1)                | 300                                       | 130                                       | 670                                             | 2.6                                                                  | ● ●                                                                                   | 3403.0020.24 |
| 3.15              | 250                 | 250                 | 1)                | 300                                       | 130                                       | 870                                             | 4.8                                                                  | ● ●                                                                                   | 3403.0021.11 |
| 3.15              | 250                 | 250                 | 1)                | 300                                       | 130                                       | 870                                             | 4.8                                                                  | ● ●                                                                                   | 3403.0021.24 |
| 4                 | 250                 | 250                 | 1)                | 300                                       | 100                                       | 950                                             | 8.6                                                                  | ● ●                                                                                   | 3403.0022.11 |
| 4                 | 250                 | 250                 | 1)                | 300                                       | 100                                       | 950                                             | 8.6                                                                  | ● ●                                                                                   | 3403.0022.24 |

Most Popular.

Availability for all products can be searched real-time: <https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

| Rated Cur-<br>rent [A] | Rated Vol-<br>tage [VAC] | Rated Vol-<br>tage [VDC] | Breaking<br>Capacity | Voltage Drop<br>1.0 I <sub>n</sub> max.<br>[mV] | Voltage Drop<br>1.0 I <sub>n</sub> typ.<br>[mV] | Power Dissi-<br>pation 1.25 I <sub>n</sub><br>typ. [mW] | Melting I <sup>2</sup> t<br>10.0 I <sub>n</sub> typ.<br>[A²s] |  | Order Number |
|------------------------|--------------------------|--------------------------|----------------------|-------------------------------------------------|-------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------|
|------------------------|--------------------------|--------------------------|----------------------|-------------------------------------------------|-------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------|

- 1) 100 A @ 250 VAC/DC
- 2) 100 A @ 250 VAC/DC / 50 A @ 400 VDC

|                |           |                                     |
|----------------|-----------|-------------------------------------|
| Packaging Unit | .xx = .11 | Plastic Bag (100 pcs.)              |
|                | .xx = .24 | Blister Tape 33 cm Reel (2000 pcs.) |

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9