
FHX04LG, 05LG, 06LG

Super Low Noise HEMT

FEATURES

- Low Noise Figure: 0.75dB (Typ.)@f=12GHz (FHX04)
- High Associated Gain: 10.5dB (Typ.)@f=12GHz
- Lg ≤ 0.25µm, Wg = 200µm
- Gold Gate Metallization for High Reliability
- Cost Effective Ceramic Microstrip (SMT) Package
- Tape and Reel Packaging Available



DESCRIPTION

The FHX04LG, FHX05LG, FHX06LG is a High Electron Mobility Transistor(HEMT) intended for general purpose, low noise and high gain amplifiers in the 2-18GHz frequency range.The devices are packaged in cost effective, low parasitic, hermetically sealed metal-ceramic package for high volume telecommunication, TVRO, VSAT or other low noise applications.

Fujitsu's stringent Quality Assurance Program assures the highest reliability and consistent performance.

ABSOLUTE MAXIMUM RATING (Ambient Temperature Ta=25°C)

Item	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	3.5	V
Gate-Source Voltage	V_{GS}	-3.0	V
Total Power Dissipation	P_{t}*	180	mW
Storage Temperature	T_{stg}	-65 to +175	°C
Channel Temperature	T_{ch}	175	°C

***Note:** Mounted on Al_2O_3 board (30 x 30 x 0.65mm)

Fujitsu recommends the following conditions for the reliable operation of GaAs FETs:

1. The drain-source operating voltage (V_{DS}) should not exceed 2 volts.
2. The forward and reverse gate currents should not exceed 0.2 and -0.05 mA respectively with gate resistance of 4000Ω.
3. The operating channel temperature (T_{ch}) should not exceed 80°C.

ELECTRICAL CHARACTERISTICS (Ambient Temperature Ta=25°C)


Item		Symbol	Condition	Limit			Unit
				Min.	Typ.	Max.	
Saturated Drain Current		I_{DSS}	V_{DS} = 2V, V_{GS} = 0V	15	30	60	mA
Transconductance		g_m	V_{DS} = 2V, I_{DS} =10mA	35	45	-	mS
Pinch-off Voltage		V_p	V_{DS} = 2V, I_{DS} =1mA	-0.2	-0.7	-1.5	V
Gate Source Breakdown Voltage		V_{GSO}	I_{GS} = -10µA	-3.0	-	-	V
Noise Figure	FHX04LG	NF	V_{DS} = 2V, I_{DS} = 10mA, f = 12GHz	-	0.75	0.85	dB
Associated Gain	FHX04LG	G_{as}		9.5	10.5	-	dB
Noise Figure	FHX05LG	NF		-	0.9	1.1	dB
Associated Gain	FHX05LG	G_{as}		9.5	10.5	-	dB
Noise Figure	FHX06LG	NF		-	1.1	1.35	dB
Associated Gain	FHX06LG	G_{as}		9.5	10.5	-	dB
Thermal Resistance		R_{th}	Channel to Case	-	300	400	°C/W

AVAILABLE CASE STYLES: LG


Note: RF parameters are measured on a sample basis as follows:

Lot qty.			Sample qty.	Accept/Reject
1200	or	less	125	(0,1)
1201	to	3200	200	(0,1)
3201	to	10000	315	(1,2)
10001	or	over	500	(1,2)

POWER DERATING CURVE




DRAIN CURRENT vs. DRAIN-SOURCE VOLTAGE




NF & Gas vs. FREQUENCY

FHX04LG




NF & Gas vs. I_{DS}

FHX04LG




NF & Gas vs. TEMPERATURE


FHX04LG



OUTPUT POWER vs. INPUT POWER




TYPICAL NOISE FIGURE CIRCLE



f=12GHz
V_{DS}=2V
I_{DS}=10mA

Γopt=0.72∠152°
Rn/50=0.04
NFmin=0.75dB

Ga(max) AND $|S_{21}|$ vs. FREQUENCY
FHX04LG




NOISE PARAMETERS
FHX04LG
V_{DS}=2V, I_{DS}=10MA

Freq. (GHz)	Γopt (MAG)	Γopt (ANG)	NFmin (dB)	Rn/50
2.0	0.99	29.0	0.33	0.43
4.0	0.97	53.0	0.35	0.30
6.0	0.93	77.0	0.45	0.20
8.0	0.87	101.0	0.55	0.12
10.0	0.80	127.0	0.66	0.07
12.0	0.72	152.0	0.75	0.04
14.0	0.63	178.0	0.88	0.03
16.0	0.53	-156.0	1.05	0.05
18.0	0.42	-129.0	1.30	0.09

FHX04LG, 05LG, 06LG

Super Low Noise HEMT



S-PARAMETERS
FHX04LG
V_{DS} = 2V, I_{DS} = 10mA


FREQUENCY	S11		S21		S12		S22	
(GHZ)	MAG	ANG	MAG	ANG	MAG	ANG	MAG	ANG
1.0	0.990	-19.3	4.232	162.1	0.016	75.1	0.576	-14.3
2.0	0.965	-37.5	4.115	144.1	0.030	64.8	0.563	-28.1
3.0	0.928	-55.2	3.923	127.4	0.042	53.3	0.546	-41.2
4.0	0.886	-72.1	3.737	110.9	0.052	41.9	0.525	-54.4
5.0	0.844	-88.3	3.518	95.6	0.059	32.2	0.505	-67.6
6.0	0.804	-103.4	3.302	80.8	0.063	23.9	0.489	-80.7
7.0	0.771	-117.4	3.090	66.4	0.066	16.6	0.484	-93.0
8.0	0.741	-129.6	2.876	53.1	0.065	11.5	0.487	-104.5
9.0	0.717	-140.3	2.703	40.7	0.066	4.9	0.497	-115.1
10.0	0.695	-150.8	2.592	28.6	0.065	-0.3	0.503	-124.9
11.0	0.675	-161.2	2.476	16.4	0.064	-3.0	0.517	-135.7
12.0	0.650	-171.5	2.374	4.2	0.064	-6.4	0.534	-145.8
13.0	0.630	178.9	2.277	-7.8	0.063	-9.3	0.552	-156.1
14.0	0.607	170.2	2.176	-19.1	0.064	-12.5	0.585	-164.6
15.0	0.585	161.8	2.144	-30.7	0.065	-16.4	0.617	-171.7
16.0	0.557	151.8	2.151	-43.2	0.066	-22.2	0.642	177.8
17.0	0.522	140.9	2.142	-56.9	0.067	-29.4	0.673	169.5
18.0	0.480	128.4	2.136	-71.2	0.068	-39.2	0.694	159.7

Download S-Parameters, click here

FUJITSU

Case Style "LG"

Metal-Ceramic Hermetic Package



1. **Gate**
2. **Source**
3. **Drain**
4. **Source**

Unit: mm(inches)

For further information please contact:

FUJITSU COMPOUND SEMICONDUCTOR, INC.
2355 Zanker Rd.
San Jose, CA 95131-1138, U.S.A.
Phone: (408) 232-9500
FAX: (408) 428-9111
www.fcsi.fujitsu.com

FUJITSU MICROELECTRONICS EUROPE, GmbH
Quantum Devices Division
Network House
Norreys Drive
Maidenhead, Berkshire SL6 4FJ
Phone:+44 (0)1628 504800
FAX:+44 (0)1628 504888

CAUTION

Fujitsu Compound Semiconductor Products contain **gallium arsenide (GaAs)** which can be hazardous to the human body and the environment. For safety, observe the following procedures:

- **Do not put these products into the mouth.**
- **Do not alter the form of this product into a gas, powder, or liquid through burning, crushing, or chemical processing as these by-products are dangerous to the human body if inhaled, ingested, or swallowed.**
- **Observe government laws and company regulations when discarding this product. This product must be discarded in accordance with methods specified by applicable hazardous waste procedures.**

Fujitsu Limited reserves the right to change products and specifications without notice.
The information does not convey any license under rights of Fujitsu Limited or others.

© 1998 FUJITSU COMPOUND SEMICONDUCTOR, INC.

Printed in U.S.A. FCSI0598M200

FUJITSU

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9