

Type CFR Series

Key Features

- Low cost, combined with high reliability, make these components suitable for use in most types of circuits, including audio, communications, measurement and computer applications.
- Premium quality carbon film resistors whose ceramic core has a high alumina content offering power to size ratios not normally associated with carbon film product.
- Available in 5 power ratings from 1 ohm to 10 Mohm. The smallest case size (CFR16) has a full 0.25 W power rating.



The resistive element comprises a thin film of carbon, deposited onto a high thermal conductivity ceramic core. Metal end caps are force fitted to the element prior to spiralling to value. Tinned copper lead wires are welded to the end caps and the components are then coated. One coat of phenolic resin is followed by three coats of epoxy resin. All resistors are tested for value and tolerance.

Characteristics - Electrical

| | CFR16 | CFR25 | CFR50 | CFR100 | CFR200 |
|--|------------|------------|-------------|------------|------------|
| Rated Power @ 70 °C (W) | 0.25 | 0.33 | 0.5 | 1 | 2 |
| Resistance Range (Ohms) | | | | | |
| Min | 1R0 | 1R0 | 1R0 | 1R0 | 1R0 |
| Max | 4M7 | 10M | 10M | 10M | 10M |
| Tolerance (%) | | | 2 | 5 | |
| Code letter | | | G | J | |
| Temp. Coefficient (ppm/°C) | | | | | |
| up to 10R | ±350 | ±350 | ±350 | ±350 | ±350 |
| 11R - 99K | 0 to -450 | 0 to -450 | 0 to -450 | 0 to -450 | 0 to -450 |
| 100K - 1M0 | 0 to -700 | 0 to -700 | 0 to -700 | 0 to -700 | 0 to -700 |
| 1M1 - 10M | 0 to -1500 | 0 to -1500 | 0 to -1500 | 0 to -1500 | 0 to -1500 |
| Selection Series | | | E24 | | |
| Limiting Element Voltage (V) | 200 | 250 | 350 | 500 | 500 |
| Max Overload Voltage¹ (V) | 400 | 500 | 700 | 1000 | 1000 |
| Max Intermittent Overload Voltage² (V) | 500 | 700 | 750 | 750 | 750 |
| Operating Temp. Range (°C) | | | -55 to +155 | | |
| Climatic Category (°C) | | | 55/155/56 | | |
| Dielectric Strength (V) | 400 | 500 | 700 | 1000 | 1000 |
| Insulation Resistance (Mohms) | | | 1000 | | |

¹Maximum Overload Voltage is 2.5 times rated voltage up to the specified voltage for 5 seconds.

²Maximum Intermittent Overload Voltage is 4 times rated voltage up to the specified voltage for 1 second ON and 25 seconds OFF. >100R ONLY

Type CFR Series

Dimensions



| Style | L* max. | D max. | d ± 0.05 | l |
|--------|---------|--------|--------------|------------|
| CFR16 | 3.5 | 1.85 | 0.45 | 28 \pm 3 |
| CFR25 | 6.8 | 2.5 | 0.54 | 28 \pm 3 |
| CFR50 | 9.0 | 3.0 | 0.54 | 28 \pm 3 |
| CFR100 | 12.0 | 5.0 | 0.70 | 25 \pm 3 |
| CFR200 | 16.0 | 5.5 | 0.70 | 28 \pm 3 |

* Length is measured in accordance with IEC 294

Derating Curve



Surface Temperature Rise vs Load



Marking

The resistors are marked with a four colour band code in accordance with IEC 62 on greyish green base color.

Mounting

The resistors are suitable for processing on automatic insertion equipment and cutting and bending machines.

Packaging

Carbon film resistors are normally supplied taped in 'ammo' boxes. Other styles may be supplied on request. All tape specifications are in accordance with IEC 286-1.

| Type | Box Quantity | Std. Tape Spacing | Component Spacing |
|--------|--------------|-------------------|-------------------|
| CFR16 | 5000 | 52 | 5 |
| CFR25 | 4000 | 52 | 5 |
| CFR50 | 3000 | 52 | 5 |
| CFR100 | 1000 | 52 | 10 |
| CFR200 | 500 | 64 | 10 |

Type CFR Series

Performance Characteristics

The evaluation of the performance characteristics is carried out with reference to IECQ specifications QC 400 000 and QC 400 100.

| TEST REF | Long Term Tests $\pm(5\% + 0.1 \text{ ohm})$ |
|----------|--|
| 4.23 | Climatic sequence |
| 4.24 | Damp heat, steady state |
| 4.25.1 | Endurance at 70°C |
| 4.25.3 | Endurance at 155°C |
| TEST REF | Short Term Tests $\pm(1\% + 0.05 \text{ ohm})$ |
| 4.13 | Overload |
| 4.16 | Robustness of terminations |
| 4.18 | Resistance to soldering heat |
| 4.19 | Rapid change of temperature |
| 4.22 | Vibration |

How to Order

| CFR | 16 | J | 100R |
|----------------------------|---|----------------------|--|
| Common Part | Size | Tolerance | Value |
| CFR - Carbon Film Resistor | 16 - 0.25 W 25 - 0.33 W 50 - 0.50 W 100 - 1.00 W 200 - 2.00 W | G - 2% J - 5% | 1 ohm (1 ohms) 1R0 1K ohm (1000 ohms) 1K0 100K ohm (100000 ohms) 100K 1M ohm (1000000 ohms) 1M0 |

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9