PANDUIT
building a smarter, unified business foundation
Connect. Manage. Automate.

# Material & Color Availability Chart

## CABLE TIES

### Available Styles

- Pan-Ty® Cable Ties - Clamp Ties, Marker and Flag Ties, Push Mount Ties, Lashing Ties, Releasable Ties

- Super-Grip® Cable Ties

- Dome-Top® Barb Ty Cable Ties - Clamp Ties, Marker and Flag Ties, Push Mount Ties, Dura-Ty™ Cable Ties

- Parallel-Entry Ties:
  Contour-Ty™ Cable Ties,
  Hyper-V™ In-Line Cable Ties,
  Belt-Ty™ In-Line Cable Ties,
  IN-LINE Cable Ties),
  Elastomeric Cable Ties

- Hook and Loop Cable Ties:
  Tak-Ty® Cable Ties (Cinch Ties, 15' & 75' Rolls, Strip Ties, Loop Ties, UL Listed Strip & Loop Ties, Stacked Strips)
  Tak-Tape™ Rolls
  Ultra-Cinch™ Cable Ties

- Sta-Strap® Cable Ties - Clamp Ties, Marker Ties

- Specialty Ties - Cable Marker Strap, Double Hose Clamp, Double Loop, Triple Loop, Locking Stud Mounted, Releasable Stud Mounted Ladder Ties, Bow-Ty, Chassis/Panel Mount Ties

---

## CONTACTS

**Customer Service** Phone: 800-777-3300 • Fax: 708-532-1811 • Email: info@panduit.com • Website: www.panduit.com

**Revised 2010-10-06**

## Part Number System for Pan-Ty® Cable Ties

**PLT** **2** **S** **–** **C**

**Type**

PLT = Locking Tie
PRT = Releasable Tie
PLC = Locking Clamp
PLF = Locking Flag
PLM = Locking Marker
PLP = Locking Push Mount
PLWP = Locking Wing Push Mount
PRLWP = Releasable Ladder Wing Push Mt.
PRWP = Releasable Wing Push Mount
PLUP = Locking Umbrella Push Mount

**Size**

Approx. Maximum Bundle Dia. (In)

**Cross Section**

SM = Subminiature
M = Miniature
I = Intermediate
S = Standard
LH = Light-Heavy
H = Heavy
EH = Extra-Heavy

**Screw Hole Size**
(Clamp Ties Only)

– S4 = #4(M2.5)
– S6 = #6 (M3)
– S8 = #8 (M4)
– S10 = #10 (M5)
– S25 = 1/4 (M6)

**Package Size**

Q = 25
L = 50
C = 100
TL = 250
D = 500
M = 1000
VMR = 2 reels/2500 ea
XMR = 2 reels/5000 ea

**Mat'l / Color**

See below

## Material and Color Chart

| Material | Color | Panduit Suffix |
|---|---|---|
| Nylon 6.6 | Natural | ✓ |
| Weather Resistant Nylon 6.6 | Black | 0 |
| Weather Resistant Nylon 6.6 (meets Mil. Spec.) | Black | 00 |
| Nylon 6.6 | Brown | 1 |
| Nylon 6.6 | Red | 2 |
| Nylon 6.6 | Orange | 3 |
| Nylon 6.6 | Yellow | 4Y |
| Nylon 6.6 | Green | 5 |
| Nylon 6.6 | Blue | 6 |
| Nylon 6.6 | Purple | 7 |
| Nylon 6.6 | Gray | 8 |
| Nylon 6.6 | White | 10 |
| Nylon 6.6 | Telephone Gray | 14 |
| Nylon 6.6 | Black | 20 |
| Heat Stabilized Nylon 6.6 | Black | 30 |

| Material | Color | Panduit Suffix |
|---|---|---|
| Heat Stabilized Nylon 6.6 | Natural | 39 |
| Nylon 6.6 | Fluorescent Orange | 53 |
| Nylon 6.6 | Fluorescent Yellow | 54 |
| Nylon 6.6 | Fluorescent Green | 55 |
| Nylon 6.6 | Fluorescent Pink | 59 |
| Flame Retardant Nylon 6.6 | Black | 60 |
| Flame Retardant Nylon 6.6 | Natural (Ivory) | 69 |
| PEEK (Polyetheretherketone) | Translucent Brown | 71 |
| TEFZEL▪ | Aqua Blue | 76 |
| Metal Detectable | Blue | 86 |
| Weather Resistant Polypropylene | Black | 100 |
| Polypropylene | Green | 109 |
| Nylon 12 | Black | 120 |
| Heat Stabilized Weather Resistant Nylon 6.6 | Black | 300 |
| HALAR▲ | Maroon | 702Y |

✓ Denotes Panduit Natural Nylon 6.6 (no suffix).
▪TEFZEL is a registered trademark of E. I. du Pont de Nemours and Company.
▲HALAR is a registered trademark of Solvay Solexis, Inc.

## Part Number Availability List

| Standard Packaging | | | Bulk Packaging | | |
|---|---|---|---|---|---|
| Part Number | Natural Nylon 6.6 | Material/Color Suffix | Part Number | Natural Nylon 6.6 | Material/Color Suffix |
| PLC1M-S4-C | ✓ | 0 | PLC1M-S4-M | ✓ | 0, 30 |
| PLC1.5I-S8-C | ✓ | 0 | PLC1.5I-S8-M | ✓ | 0, 30 |
| PLC2S-S6-C | ✓ | 0 | PLC2S-S6-M | ✓ | 0 |
| PLC2S-S10-C | ✓ | 0, 14 | PLC2S-S10-M | ✓ | 0, 20, 30 |
| PLC3S-S10-C | ✓ | 0 | PLC3S-S10-M | ✓ | 0 |
| PLC4S-S10-C | ✓ | 0 | PLC4S-S10-M | ✓ | 0, 30 |
| PLC2H-S25-L | ✓ | | PLC2H-S25-TL | ✓ | 0, 30 |
| PLC4H-S25-L | ✓ | 0 | PLC4H-S25-TL | ✓ | 0, 30 |
| PLF1M-C | ✓ | 0 | PLF1M-M | ✓ | 0, 2, 3, 4Y, 6, 10, 69 |
| PLF1MA-C | ✓ | 3, 4Y | PLF1MA-M | ✓ | 0, 2, 3, 4Y, 5, 6, 10 |
| PLF1MB-C | ✓ | | PLF1MB-M | ✓ | |
| | | | PLF1MC-M | ✓ | 3 |
| PLM1M-C | ✓ | 0 | PLM1M-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 69 |
| PLM2M-C | ✓ | | PLM2M-M | ✓ | 0, 4Y, 6 |
| PLM2S-C | ✓ | 0, 4Y | PLM2S-D | ✓ | 0, 2, 3, 4Y, 5, 6, 8 |
| PLM4S-C | ✓ | | PLM4S-D | ✓ | 0, 2, 4Y, 6 |
| PL2M2S-L | ✓ | 0 | PL2M2S-D | ✓ | 0, 4Y, 10 |

| Standard Packaging | | | Bulk Packaging | | |
|---|---|---|---|---|---|
| **Part Number** | **Natural Nylon 6.6** | **Material/Color Suffix** | **Part Number** | **Natural Nylon 6.6** | **Material/Color Suffix** |
| PL3M2S-L | ✓ | | PL3M2S-D | ✓ | 0, 4Y |
| PLP1.5I-C | ✓ | | PLP1.5I-M | ✓ | 0, 30 |
| | | | PLP1S-M | ✓ | 0, 30 |
| | | | PLP1.5S-M | ✓ | |
| PLP2S-C | ✓ | | PLP2S-M | ✓ | 0, 30 |
| PLT.6SM-C | ✓ | 0 | PLT.6SM-M | ✓ | 0, 30 |
| PLT.7M-C | ✓ | | PLT.7M-M | ✓ | 0, 30 |
| PLT1M-C | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 14, 30, 76, 86, 186, 702Y | PLT1M-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 14, 20, 30, 53, 54, 55, 59, 60, 69, 76, 100, 109, 300, 702Y |
| | | | PLT1M-XMR | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 30 |
| PLT1.5M-C | ✓ | 0 | PLT1.5M-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 14, 20, 30 |
| | | | PLT1.5M-XMR | ✓ | 0, 00, 30 |
| PLT2M-C | ✓ | 0 | PLT2M-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30, 69 |
| PLT1.5I-C | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30 | PLT1.5I-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30, 69, 100, 109, 120, 300 |
| PLT2I-C | ✓ | 0, 14, 30, 76, 86, 186 | PLT2I-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 14, 20, 30, 53, 54, 55, 59, 69, 76, 300 |
| PLT2.5I-C | ✓ | 0 | PLT2.5I-M | ✓ | 0, 20 |
| PLT3I-C | ✓ | 0, 14 | PLT3I-M | ✓ | 0, 2, 3, 4Y, 5, 6, 8, 10, 14, 20, 30 |
| PLT4I-C | ✓ | 0, 14 | PLT4I-M | ✓ | 0, 2, 5, 6, 14, 20, 30 |
| PLT1S-C | ✓ | 0 | PLT1S-M | ✓ | 0, 30, 38, 300 |
| PLT1.5S-C | ✓ | 0 | PLT1.5S-M | ✓ | 0, 30 |
| PLT2S-C | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30, 71, 76, 86, 186, 702Y | PLT2S-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30, 38, 39, 53, 54, 55, 59, 60, 69, 71, 76, 100, 109, 120, 300, 702Y |
| | | | PLT2S-VMR | ✓ | 0, 30 |
| PLT2.5S-C | ✓ | 0 | PLT2.5S-M | ✓ | 0, 30 |
| PLT3S-C | ✓ | 0, 00, 2, 20, 30, 76, 86, 186, 702Y | PLT3S-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30, 53, 54, 55, 59, 76, 100, 109, 702Y |
| | | | PLT3S-VMR | ✓ | 30 |
| PLT4S-C | ✓ | 0, 00, 2, 3, 4Y, 5, 6, 8, 20, 30, 76, 86, 186 | PLT4S-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 14, 20, 30, 69, 76, 100, 109, 120, 300 |
| PLT4.5S-C | ✓ | 0 | PLT4.5S-M | ✓ | 0 |
| PLT5S-C | ✓ | 0 | PLT5S-M | ✓ | 0, 2, 3, 4Y, 5, 6, 8, 30 |
| PLT6LH-L | ✓ | 0 | PLT6LH-C | ✓ | 0 |
| PLT7LH-L | ✓ | 0 | PLT7LH-C | ✓ | 0, 30 |
| PLT8LH-L | ✓ | 0 | PLT8LH-C | ✓ | 0, 120 |
| PLT8LH-Q | | 0 | | | |
| PLT9LH-L | ✓ | 0 | PLT9LH-C | ✓ | 0, 30 |
| PLT10LH-L | ✓ | | PLT10LH-C | ✓ | |
| PLT2H-L | ✓ | 0 | PLT2H-TL | ✓ | 0, 2, 4Y, 6, 30, 100, 109, 300 |
| PLT2.5H-L | ✓ | 0 | PLT2.5H-TL | ✓ | 0 |
| PLT3H-L | ✓ | 0, 76, 86, 186 | PLT3H-TL | ✓ | 0, 30, 76, 100, 109 |
| PLT4H-L | ✓ | 0, 00, 76, 86, 186 | PLT4H-TL | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 10, 20, 30, 69, 76, 100, 109, 120, 300 |
| PLT4H-C | ✓ | 0 | | | |
| PLT5H-L | ✓ | 0 | PLT5H-C | ✓ | 0, 30 |
| PLT6H-L | ✓ | 0 | PLT6H-C | ✓ | 0, 30 |
| PLT8H-L | ✓ | 0 | PLT8H-C | ✓ | 0, 00, 30 |
| PLT8H-L | ✓ | 0 | | | |
| PLT13H-Q | ✓ | 0 | PLT13H-C | ✓ | 0, 3 |
| PLT2EH-Q | | 0 | PLT2EH-C | ✓ | 0 |
| | | | PLT3EH-NB-C | | 0 |
| PLT5EH-Q | ✓ | 0 | PLT5EH-C | ✓ | 0 |
| | | | PLT5EH-NB-C | | 0 |
| PLT6EH-Q | ✓ | 0 | PLT6EH-C | ✓ | 0 |
| | | | PLT6EH-NB-C | | 0 |
| PLT8EH-Q | | 0 | PLT8EH-C | ✓ | 0 |
| PLT10EH-Q | | 0 | PLT10EH-C | ✓ | 0 |
| PLT12EH-Q | | 0 | PLT12EH-C | ✓ | 0 |

| Standard Packaging | | | Bulk Packaging | | |
|---|---|---|---|---|---|
| **Part Number** | **Natural Nylon 6.6** | **Material/Color Suffix** | **Part Number** | **Natural Nylon 6.6** | **Material/Color Suffix** |
| | | | PLUP40S-D | | 30 |
| | | | PLUP40SE-D | ✓ | 30 |
| PLWP1M-C | ✓ | | PLWP1M-D | ✓ | 0, 30 |
| PLWP1.5I-C | ✓ | | PLWP1.5I-D | ✓ | 30 |
| PLWP1S-C | ✓ | 0 | PLWP1S-D | ✓ | 0, 20, 30 |
| | | | PLWP1SA-D | ✓ | |
| | | | PLWP1SB-D | ✓ | |
| | | | PLWP1.5S-D | ✓ | 30 |
| | | | PLWP1.5SA-D | ✓ | |
| PLWP2S-C | ✓ | 0 | PLWP2S-D | ✓ | 0, 30 |
| | | | PLWP2SA-D | ✓ | |
| | | | PLWP2SB-D | ✓ | |
| | | | PLWP2H-TL | ✓ | 0, 30 |
| | | | PLWP3H-TL | ✓ | 0 |
| | | | PLWP30SC-D | | 30 |
| | | | PLWP40SC-D | | 30 |
| | | | PLWP40SD-D | | 30 |
| | | | PLWP50SC-D | | 30 |
| | | | PLWP50SE-D | | 30 |
| | | | PRLWP30S-D | | 30 |
| | | | PRLWP50S-D | | 30 |
| PRT1S-C | ✓ | 0 | PRT1S-M | ✓ | 0 |
| PRT1.5S-C | ✓ | 0 | PRT1.5S-M | ✓ | 0, 30 |
| PRT2S-C | ✓ | 0 | PRT2S-M | ✓ | 0, 2, 3, 4Y, 6, 7 |
| PRT3S-C | ✓ | 0 | PRT3S-M | ✓ | 0 |
| PRT4S-C | ✓ | 0 | PRT4S-M | ✓ | 0, 2, 3, 4Y, 6 |
| PRT2H-L | ✓ | 0 | PRT2H-TL | ✓ | 0 |
| PRT3H-L | ✓ | 0 | PRT3H-TL | ✓ | 0 |
| PRT4H-L | ✓ | 0 | PRT4H-TL | ✓ | 0 |
| PRT2EH-Q | | 0 | PRT2EH-C | ✓ | 0, 100 |
| PRT5EH-Q | ✓ | 0 | PRT5EH-C | ✓ | 0, 100 |
| PRT6EH-Q | ✓ | 0 | PRT6EH-C | ✓ | 0, 100 |
| PRT8EH-Q | | 0 | PRT8EH-C | ✓ | 0, 100 |
| PRT10EH-Q | | 0 | PRT10EH-C | ✓ | 0 |
| PRT12EH-Q | | 0 | PRT12EH-C | ✓ | 0 |
| PRWP1S-C | ✓ | | PRWP1S-D | ✓ | 0 |
| | | | PRWP1SA-D | ✓ | |
| | | | PRWP1SB-D | ✓ | |
| | | | PRWP1.5S-D | ✓ | 0, 20, 30 |
| | | | PRWP2S-D | ✓ | 0 |
| | | | PRWP2H-TL | ✓ | |

## Part Number System for Super-Grip® Cable Ties

| SG | 200 | S | – | C |
|---|---|---|---|---|
| **Type** | **Size** | **Cross Section** | **Package Size** | **Material / Color** |
| SG = Locking Tie | Approx. Length (mm) | M = Miniature<br>I = Intermediate<br>S = Standard<br>LH = Light-Heavy<br>H = Heavy | L = 50<br>C = 100<br>TL = 250<br>M = 1000 | See below |

## Material and Color Chart

| Material | Color | Panduit Suffix |
|---|---|---|
| Nylon 6.6 | Natural | ✓ |
| Weather Resistant Nylon 6.6 | Black | 0 |
| Heat Stabilized Nylon 6.6 | Black | 30 |

✓ Denotes Panduit Natural Nylon 6.6 (no suffix).

## Part Number Availability List

| Standard Packaging | | | Bulk Packaging | | |
|---|---|---|---|---|---|
| Part Number | Natural Nylon 6.6 | Material/Color Suffix | Part Number | Natural Nylon 6.6 | Material/Color Suffix |
| SG100M-C | ✓ | 0 | SG100M-M | ✓ | 0 |
| SG150I-C | ✓ | 0 | SG150I-M | ✓ | 0 |
| SG200S-C | ✓ | 0 | SG200S-M | ✓ | 0, 30 |
| SG250S-C | ✓ | 0 | | | |
| SG300S-C | ✓ | 0 | SG300S-M | ✓ | 0, 30 |
| SG370S-C | ✓ | 0 | SG370S-M | ✓ | 0 |
| SG350LH-L | ✓ | 0 | SG350LH-TL | ✓ | 0, 30 |
| SG450H-L | ✓ | 0 | SG450H-C | ✓ | 0 |

## Part Number System for Dome-Top® Barb Ty & Dura-Ty™ Cable Ties

| BT | 2 | S | — | C | |
|---|---|---|---|---|---|
| **Type** | **Size** | **Cross Section** | **Screw Hole Size** (Clamp Ties Only) | **Package Size** | **Material / Color** |
| BT = Locking Tie<br>BC = Clamp Tie<br>BF = Flag Tie<br>BM = Marker Tie<br>BP = Push Mount Tie<br>BW = Wing Push Mount Tie<br>DT = Locking Tie | Approx. Maximum Bundle Dia. (In) | M = Miniature<br>I = Intermediate<br>S = Standard<br>LH = Light-Heavy<br>H = Heavy<br>EH = Extra-Heavy | —S4 = #4 (M2.5)<br>—S6 = #6 (M3)<br>—S8 = #8 (M4)<br>—S10 = #10 (M5)<br>—S25 = 1/4 (M6) | Q = 25<br>L = 50<br>C = 100<br>TL = 250<br>D = 500<br>M = 1000<br>LR = 50' Reel | See below |

## Material and Color Chart

| Material | Color | Panduit Suffix |
|---|---|---|
| Nylon 6.6 | Natural | ✓ |
| Weather Resistant Nylon 6.6 | Black | 0 |
| Nylon 6.6 | Brown | 1 |
| Nylon 6.6 | Red | 2 |
| Nylon 6.6 | Orange | 3 |
| Nylon 6.6 | Yellow | 4Y |
| Nylon 6.6 | Green | 5 |
| Nylon 6.6 | Blue | 6 |
| Nylon 6.6 | Purple | 7 |

| Material | Color | Panduit Suffix |
|---|---|---|
| Nylon 6.6 | Gray | 8 |
| Nylon 6.6 | White | 10 |
| Nylon 6.6 | Telephone Gray | 14 |
| Nylon 6.6 | Black | 20 |
| Heat Stabilized Nylon 6.6 | Black | 30 |
| Heat Stabilized Nylon 6.6 | Natural | 39 |
| Flame Retardant Nylon 6.6 | Natural (Ivory) | 69 |
| Weather Resistant Acetal | Black | * |
| Heat Stabilized Weather Resistant Nylon 6.6 | Black | 300 |

✓ Denotes Panduit Natural Nylon 6.6 (no suffix).
* Denotes Dura-Ty™ Weather Resistant Acetal material (no suffix).

## Part Number Availability List

| Standard Packaging | | | Bulk Packaging | | |
|---|---|---|---|---|---|
| **Part Number** | **Natural Nylon 6.6** | **Material/Color Suffix** | **Part Number** | **Natural Nylon 6.6** | **Material/Color Suffix** |
| | | | BC1M-S4-M | ✓ | 0 |
| | | | BC2M-S4-M | ✓ | 0 |
| | | | BC1.5I-S8-M | ✓ | 0 |
| BC2S-S10-C | ✓ | 0 | BC2S-S10-D | ✓ | 0 |
| | | | BC3S-S10-D | ✓ | 0 |
| BC4S-S10-C | ✓ | 0 | BC4S-S10-D | ✓ | 0, 30 |
| BC4LH-S25-L | ✓ | 0 | BC4LH-S25-TL | ✓ | 0 |
| BF1M-C | ✓ | | BF1M-M | ✓ | 0 |
| BF2M-C | ✓ | | BF2M-M | ✓ | 0 |
| BM1M-C | ✓ | | BM1M-M | ✓ | 0 |
| BM2M-C | ✓ | | BM2M-M | ✓ | 0 |
| BM2S-C | ✓ | | BM2S-D | ✓ | 0 |
| BM4S-C | ✓ | | BM4S-D | ✓ | 0 |
| | | | BP2S-D | | 0 |
| BT1M-C | ✓ | 0, 30 | BT1M-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 30, 39, 69, 300 |
| | | | BT1M-XMR | ✓ | 0, 30 |
| BT1.5M-C | ✓ | 0 | BT1.5M-M | ✓ | 0, 30, 69 |
| | | | BT1.5M-XMR | ✓ | 0, 30, 69 |
| BT2M-C | ✓ | 0 | BT2M-M | ✓ | 0, 2, 3, 4Y, 5, 6, 8, 30 |
| BT4M-C | ✓ | 0 | BT4M-M | ✓ | 0 |
| BT1.5I-C | ✓ | 0 | BT1.5I-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 30, 39 |
| BT2I-C | ✓ | 0 | BT2I-M | ✓ | 0, 30, 69, 300 |
| BT3I-C | ✓ | 0 | BT3I-M | ✓ | 0, 14, 30 |

| Standard Packaging | | | Bulk Packaging | | |
|---|---|---|---|---|---|
| **Part Number** | **Natural Nylon 6.6** | **Material/Color Suffix** | **Part Number** | **Natural Nylon 6.6** | **Material/Color Suffix** |
| BT4I-C | ✓ | 0 | BT4I-M | ✓ | 0, 14 |
| BT2S-C | ✓ | 0 | BT2S-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30, 39, 69, 300 |
| BT3S-C | ✓ | 0, 2 | BT3S-M | ✓ | 0, 30, 39, 69, 300 |
| BT4S-C | ✓ | 0 | BT4S-M | ✓ | 0, 2, 3, 4Y, 5, 6, 7, 8, 10, 30, 39, 300 |
| BT2LH-L | ✓ | 0 | BT2LH-TL | ✓ | 0, 300 |
| BT3LH-L | ✓ | 0 | BT3LH-TL | ✓ | 0 |
| BT4LH-L | ✓ | 0 | BT4LH-TL | ✓ | 0, 30, 39, 69, 300 |
| BT5LH-L | ✓ | 0 | BT5LH-C | ✓ | 0, 300 |
| BT6LH-L | ✓ | 0 | BT6LH-C | ✓ | 0, 69, 300 |
| BT7LH-L | ✓ | 0 | BT7LH-C | ✓ | 0 |
| BT8LH-L | ✓ | 0 | BT8LH-C | ✓ | 0, 300 |
| BT9LH-L | ✓ | 0 | BT9LH-C | ✓ | 0, 300 |
| | | | BW1.5I-D | ✓ | |
| | | | BW2S-D | ✓ | 0 |
| | | | B2M2S-D | ✓ | 0 |
| | | | B3M2S-TL | ✓ | 0 |
| | | | B4M2S-TL | ✓ | 0 |
| DTHEH-Q0 | | * | | | |
| DTHH-Q0 | | * | | | |
| DTKEH-0 | | * | | | |
| DTKH-0 | | * | | | |
| DTREH-LR0 | | * | | | |
| DTRH-LR0 | | * | | | |
| DT4EH-L0 | | * | | | |
| DT8EH-Q0 | | * | | | |
| DT14EH-L0 | | * | DT14EH-C0 | | * |
| DT15EH-L0 | | * | | | |
| DT28EH-C0 | | * | | | |
| DT44EH-C0 | | * | | | |

## Part Number System for Contour-Ty® and Belt-Ty™ Cable Ties

| CBR | 2 | S | — | M | |
|---|---|---|---|---|---|
| **Type** | **Size** | **Cross Section** | | **Package Size** | **Material/Color** |
| CBR = Locking Tie<br>ILT = Locking Tie | Approx. Maximum Bundle Dia. (In) | M = Miniature<br>I = Intermediate<br>S = Standard<br>HS = Heavy-Standard<br>LH = Light-Heavy | | C = 100<br>TL = 250<br>D = 500<br>M = 1000 | See below |

## Part Number System for IN-LINE and Hyper-V™ Cable Ties

| IT | 9 | 100 | — | C | |
|---|---|---|---|---|---|
| **Type** | **Width** | **Size** | | **Package Size** | **Material/Color** |
| HV = Locking Tie<br>IT = Locking Tie | Approx. Width (mm) | Approx. Max. Bundle Dia. (mm) | | C = 100 | See below |

## Part Number System for Elastomeric Cable Ties

| ERT | 2 | M | — | C | |
|---|---|---|---|---|---|
| **Type** | **Size** | **Cross Section** | | **Package Size** | **Material/Color** |
| ERT = Elastomeric Releasable Tie | Approx. Max. Bundle Dia. (In) | M = Miniature | | C = 100 | See below |

## Material and Color Chart

| Material | Color | Panduit Suffix |
|---|---|---|
| Nylon 6.6 | Natural | ✓ |
| Weather Resistant Nylon 6.6 | Black | 0 |
| Nylon 6.6 | Brown | 1 |
| Nylon 6.6 | Red | 2 |
| Nylon 6.6 | Orange | 3 |
| Nylon 6.6 | Yellow | 4Y |
| Nylon 6.6 | Green | 5 |
| Nylon 6.6 | Blue | 6 |
| Nylon 6.6 | Purple | 7 |
| Nylon 6.6 | Gray | 8 |
| Nylon 6.6 | White | 10 |
| TPU | Black | 20 |
| Heat Stabilized Nylon 6.6 | Black | 30 |
| Heat Stabilized Nylon 6.6 | Natural | 39 |
| Flame Retardant Nylon 6.6 | Natural (Ivory) | 69 |

| Material | Color | Panduit Suffix |
|---|---|---|
| Nylon 6.6 | Ultraviolet Red | UV2 |
| Nylon 6.6 | Ultraviolet Bright Red | UV2A |
| Nylon 6.6 | Ultraviolet Yellow | UV4Y |
| Nylon 6.6 | Ultraviolet Butterscotch | UV4A |
| Nylon 6.6 | Ultraviolet Green | UV5A |
| Nylon 6.6 | Ultraviolet Hunter Green | UV5B |
| Nylon 6.6 | Ultraviolet Dark Blue | UV6 |
| Nylon 6.6 | Ultraviolet Light Blue | UV6A |
| Nylon 6.6 | Ultraviolet Cobalt Blue | UV6B |
| Nylon 6.6 | Ultraviolet Purple | UV7A |
| Nylon 6.6 | Ultraviolet Gray | UV8 |
| Nylon 6.6 | Ultraviolet Teal | UV11 |
| Nylon 6.6 | Ultraviolet Magenta | UV16B |
| Nylon 6.6 | Ultraviolet Tan | UV18 |

✓ Denotes Panduit Natural Nylon 6.6 (no suffix).

## Part Number Availability List

| Standard Packaging | | | Bulk Packaging | | |
|---|---|---|---|---|---|
| **Part Number** | **Natural Nylon 6.6** | **Material/Color Suffix** | **Part Number** | **Natural Nylon 6.6** | **Material/Color Suffix** |
| | | | CBR1M-M | ✓ | 0, 30 |
| | | | CBR1.5M-M | ✓ | 0 |
| | | | CBR2M-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 10 |
| | | | CBR1.5I-M | ✓ | 0, 30 |
| | | | CBR3I-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10 |
| | | | CBR4I-M | ✓ | 0 |
| | | | CBR2S-M | ✓ | 0, 30, 39 |
| | | | CBR3S-M | ✓ | 0, 30, 69 |
| | | | CBR4S-M | ✓ | 0, 30 |
| | | | CBR2HS-D | ✓ | 0 |
| | | | CBR4LH-TL | ✓ | 0, 30 |
| | | | CBR6LH-C | ✓ | 0, 30 |
| | | | ERT2M-C | | 20 |
| | | | ERT3M-C | | 20 |
| | | | ERT4.5M-C | | 20 |
| | | | HV965-C | | 0 |
| | | | HV9100-C | | 0 |
| | | | HV9150-C | | 0 |
| | | | HV9250-C | | 0 |
| ILT2S-C | ✓ | 0 | ILT2S-M | ✓ | 0 |
| ILT3S-C | ✓ | 0 | ILT3S-M | ✓ | 0 |
| ILT4S-C | ✓ | 0 | ILT4S-M | ✓ | 0 |
| | | | ILT4LH-TL | ✓ | 0 |
| | | | ILT6LH-C | ✓ | 0 |
| | | | IT940-C | | 0 |
| | | | IT965-C | | 0 |
| | | | IT9100-C | | 0, UV2,4Y,6,6A,7A,8,16B |
| | | | IT9115-C | | 0, UV2,2A,4Y,4A,5A,5B, 6,6A,6B,7A, 8,11,16B, 18 |

## Part Number System for Sta-Strap® Cable Ties

**SST 1 M — C**

| Type | Size | Cross Section | Screw Hole Size (Clamp Ties Only) | Package Size | Material/Color |
|---|---|---|---|---|---|
| SST = Locking Tie<br>SSC = Clamp Tie<br>SSM = Marker Tie | Approx. Maximum Bundle Dia. (In) | M = Miniature<br>I = Intermediate<br>S = Standard<br>H = Heavy<br>HH = Heavy Head | —S6 = #6 (M3)<br>—S10 = #10 (M5)<br>—S25 = ¼ (M6) | L = 50<br>C = 100<br>D = 500<br>M = 1000 | See below |

## Material and Color Chart

| Material | Color | Panduit Suffix |
|---|---|---|
| Nylon 6.6 | Natural | ✓ |
| Weather Resistant Nylon 6.6 | Black | 0 |
| Nylon 6.6 | Red | 2 |

| Material | Color | Panduit Suffix |
|---|---|---|
| Nylon 6.6 | Black | 20 |
| Heat Stabilized Nylon 6.6 | Black | 30 |

✓ Denotes Panduit Natural Nylon 6.6 (no suffix).

## Part Number Availability List

| Standard Packaging | | | Bulk Packaging | | |
|---|---|---|---|---|---|
| Part Number | Natural Nylon 6.6 | Material/Color Suffix | Part Number | Natural Nylon 6.6 | Material/Color Suffix |
| SSC2S-S6-C | ✓ | | SSC2S-S6-M | ✓ | 0 |
| SSC2S-S10-C | ✓ | | SSC2S-S10-M | ✓ | 0, 30 |
| SSC4S-S10-C | ✓ | | SSC4S-S10-M | ✓ | 0 |
| SSC4H-S25-L | ✓ | | SSC4H-S25-D | ✓ | 0 |
| SSM2S-C | ✓ | | SSM2S-D | ✓ | 0 |
| | | | SSM4S-D | ✓ | |
| SST1M-C | ✓ | 0 | SST1M-M | ✓ | 0, 20, 30 |
| SST1.5M-C | ✓ | | SST1.5M-M | ✓ | 0, 20, 30 |
| SST1.5I-C | ✓ | | SST1.5I-M | ✓ | 0 |
| SST2I-C | ✓ | | SST2I-M | ✓ | 0 |
| SST3I-C | ✓ | 0 | SST3I-M | ✓ | 0 |
| SST4I-C | ✓ | | SST4I-M | ✓ | 0 |
| | | | SST1.5S-M | ✓ | 0 |
| SST2S-C | ✓ | 0 | SST2S-M | ✓ | 0, 20, 30 |
| SST3S-C | ✓ | 0 | SST3S-M | ✓ | 0, 20, 30 |
| SST4S-C | ✓ | 0 | SST4S-M | ✓ | 0, 2, 30 |
| | | | SST2H-D | ✓ | 0 |
| | | | SST2HH-D | | 30 |
| SST4H-L | ✓ | 0 | SST4H-D | ✓ | 0, 30 |
| | | | SST4HH-D | | 30 |
| SST8H-L | ✓ | 0 | SST8H-D | ✓ | 0, 30 |

## Part Number System for Specialty Cable Ties

| PLST | 4 | H | S25 | – | TL | 300 |
|---|---|---|---|---|---|---|

**Type**

CM4S = Cable Marker Strap
PLB = Locking Bow Tie
PL3B = Triple Loop Tie
DHC = Double Hose Clamp
PLST = Locking Stud Mounted Tie
PRST = Releasable Stud Mount Ladder Style
SSB = Sta-Strap® Bow-Ty™ Tie
SSPM = Sta-Strap® Panel Mount

**Size**

Approx. Maximum Bundle Dia. (In)

**Cross Section**

S = Standard
H = Heavy
EH = Extra-Heavy

**Stud Size**

–S25 = M6
–SC = 5mm
–S14 = 5mm

**Package Size**

L = 50
C = 100
TL = 250
D = 500
M = 1000

**Material/ Color**

See below

## Material and Color Chart

| Material | Color | Panduit Suffix |
|---|---|---|
| Nylon 6.6 | Natural | ✓ |
| Weather Resistant Nylon 6.6 | Black | 0 |
| Nylon 6.6 | Red | 2 |
| Nylon 6.6 | Gray | 8 |

| Material | Color | Panduit Suffix |
|---|---|---|
| Heat Stabilized Nylon 6.6 | Black | 30 |
| Heat Stabilized Weather Resistant Nylon 6.6 | Black | 300 |

✓ Denotes Panduit Natural Nylon 6.6 (no suffix).

## Part Number Availability List

| Standard Packaging | | | Bulk Packaging | | |
|---|---|---|---|---|---|
| Part Number | Natural Nylon 6.6 | Material/Color Suffix | Part Number | Natural Nylon 6.6 | Material/Color Suffix |
| CM4S-L | | 2, 8 | | | |
| | | | DHC1.12X1.75-D | | 0 |
| PLB2S-C | ✓ | 0 | PLB2S-M | ✓ | 0, 30 |
| PLB3S-C | ✓ | 0 | PLB3S-M | ✓ | 0, 30 |
| PLB4S-C | ✓ | | PLB4S-M | ✓ | 0, 30, 39 |
| | | | PLB4H-TL | ✓ | 0, 30, 39 |
| | | | PLB5EH-C | | 0 |
| | | | PL3B5EH-C | | 0 |
| | | | PLST4HS25-TL | | 300 |
| | | | PLST30SC-D | | 30 |
| | | | PLST50SC-D | | 30 |
| | | | PRST30S-S14-M | | 30 |
| | | | PRST40SC-D | | 30 |
| SSB2S-C | ✓ | | SSB2S-M | ✓ | 0, 30 |
| SSPM2.5H-L | | 300 | SSPM2.5H-TL | | 300 |
| SSPM2.5HP-L | | 300 | SSPM2.5HP-TL | | 300 |
| SSPM4H-L | | 300 | SSPM4H-TL | | 300 |
| SSPM4HP-L | | 300 | SSPM4HP-TL | | 300 |
| | | | SSPM4HLP-TL | | 300 |

## Part Number System for Tak-Ty® Hook & Loop Cable Ties

| HLT | 2 | I | – | X | 0 |
|---|---|---|---|---|---|
| **Type** | **Size** | **Cross Section** | | **Package Size** | **Color** |
| HL = Hook and Loop<br>HLB = Hook and Loop Brick Pack<br>HLC = HL Cinch Tie<br>HLM = HL Miniature<br>HLT = HL Loop Tie<br>HLTP = HL Loop Tie Plenum-Rated<br>HLS = HL Strip Tie<br>HLSP = HL Strip Tie Plenum-Rated<br>TTS = Tak-Tape™ Roll | Approx. Maximum Bundle Dia. (In) | I = Intermediate<br>S = Standard | | C = 100<br>X = 10<br>15R = 15' Roll<br>20R = 20' Roll<br>35R3 = 35' Rolls (3)<br>35RX = 35' Rolls (10)<br>75R = 75' Roll | See below |

## Part Number System for Ultra-Cinch™ Hook & Loop Cable Ties

| UGCT | E | 3 | S | – | X | 0 |
|---|---|---|---|---|---|---|
| **Type** | **Mount** | **Size** | **Cross Section** | | **Package Size** | **Color** |
| UCT = Cinch Tie<br>UGCT = Grommet Cinch Tie | E = End Mount<br>C = Center Mount | Approx. Maximum Bundle Dia. (In) | I = Intermediate<br>S = Standard | | X = 10 | See below |

## Color Chart

| Color | Panduit Suffix |
|---|---|
| Black | 0 |
| Red | 2 |
| Orange | 3 |
| Yellow | 4 |
| Green | 5 |

| Color | Panduit Suffix |
|---|---|
| Blue | 6 |
| Gray | 8 |
| White | 10 |
| Maroon | 12 |

## Part Number Availability List

| Standard Packaging | |
|---|---|
| **Part Number** | **Color Suffix** |
| HLB2S-C | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLC3S-X | 0 |
| HLC5S-X | 0 |
| HLM-15R | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLS-15R | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLS-75R | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLS1.5S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLS3S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLS5S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLSP1.5S-X | 0, 12 |
| HLSP3S-X | 0, 12 |
| HLSP5S-X | 0, 12 |
| HLT2I-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLT3I-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLTP2I-X | 0, 12 |
| HLTP3I-X | 0, 12 |
| HLWM1.5S-X | 0 |
| HLWM3S-X | 0 |
| TTS-20R | 0 |
| TTS-35RX | 0 |
| TTS-35R3 | 0 |
| UCT3S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| UCT5S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| UGCTC3S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| UGCTC5S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| UGCTE3S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| UGCTE5S-X | 0, 2, 3, 4, 5, 6, 8, 10 |

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

**Данный компонент на территории Российской Федерации**

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

**Офис по работе с юридическими лицами:**

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9