


GLOBAL PERFORMANCE SWITCHERS

Features:

- Industry's smallest 25 W switcher
- 2.50 x 4.25 x 0.86"
- Conducted EMI exceeds FCC Class B and CISPR 22 Class B (Commercial models) and CISPR 11 Class B (Medical models)
- Overvoltage protection standard
- Commercial Approved to UL1950, CSA-C22.2 No.950, EN60950
- Medical Approved to UL2601-1, IEC60601-1 EN60601-1 and CSA-C22.2 No. 601-1
- RoHS Compliant (G suffix)
- CE marked to LVD

CONDOR
DC Power Supplies



SPECIFICATIONS

Ac Input 90-264 Vac, 47-63 Hz single phase.	Inrush Current Inrush is limited by internal thermistor. The inrush at 230 Vac, averaged over the first ac half-cycle under cold start conditions will not exceed 32 A.															
Input Current Maximum input current at minimum 120 Vac, 60 Hz with full rated output load is 0.6 A.	Temperature Coefficient 0.03%/°C typical on all outputs.															
Hold-up Time 15 ms minimum from loss of ac input at full load, nominal line (120 Vac).	Environmental Designed for 0 to 50°C operation at full rated output power; derate output current and total output power by 2.5% per °C between 50 - 70°C. See Environmental and Packaging Specifications on next page.															
Output Power Normal continuous output power is 25 W, 28 W peak for 60 sec. maximum duration, 10% duty cycle. Factory set to begin power limiting at approximately 30 W.	EMI/EMC Compliance All models include built-in EMI filtering to meet the following emissions requirements:															
Output Regulation Regulation from initial setpoint measured by changing load from 5% load to 50% load or 50% load to full load in either direction. Initial setpoint tolerance is measured at 50% load. A minimum load of 5% of the output current on the +5.1 V output (125 mA) is required to maintain proper regulation.	<table><tr><th>EMI SPECIFICATIONS</th><th>COMPLIANCE LEVEL</th></tr><tr><td>Conducted Emissions GSC25 Conducted Emissions GSM25 Static Discharge RF Field Susceptibility Fast Transients/Bursts Surge Susceptibility</td><td>EN55022 Class B; FCC Class B EN55011 Class B; FCC Class B EN61000-4-2, 6 kV contact, 8 kV air EN61000-4-3, 3 V/meter EN61000-4-4, 2 kV, 5 kHz EN61000-4-5, 1 kV diff., 2 kV com.</td></tr></table>	EMI SPECIFICATIONS	COMPLIANCE LEVEL	Conducted Emissions GSC25 Conducted Emissions GSM25 Static Discharge RF Field Susceptibility Fast Transients/Bursts Surge Susceptibility	EN55022 Class B; FCC Class B EN55011 Class B; FCC Class B EN61000-4-2, 6 kV contact, 8 kV air EN61000-4-3, 3 V/meter EN61000-4-4, 2 kV, 5 kHz EN61000-4-5, 1 kV diff., 2 kV com.											
EMI SPECIFICATIONS	COMPLIANCE LEVEL															
Conducted Emissions GSC25 Conducted Emissions GSM25 Static Discharge RF Field Susceptibility Fast Transients/Bursts Surge Susceptibility	EN55022 Class B; FCC Class B EN55011 Class B; FCC Class B EN61000-4-2, 6 kV contact, 8 kV air EN61000-4-3, 3 V/meter EN61000-4-4, 2 kV, 5 kHz EN61000-4-5, 1 kV diff., 2 kV com.															
Overload Protection Fully protected against short circuit and output overload. Short circuit protection is cycling type power limit	Commercial Safety: Condor D.C. Power Supplies, Inc. declares under our sole responsibility that all GSC models are in conformity with the applicable requirements of EN60950 following the provisions of the Low Voltage Directive 73/23/EEC. All GSC models are approved to UL1950, CSA-C22.2 No.950, EN60950.															
Output Noise 0.5% rms, 1% pk-pk, 20 MHz bandwidth, differential mode. Measured with scope probe directly across output terminals of the power supply with load terminated with 0.1 uF capacitor.	GSM25 Medical Model Earth Leakage Current Leakage current measured in the Gnd wire connection when measured per UL2601-1 or IEC60601-1 is as follows:															
Transient Response Main output: 750 μs typical response time for return to within 0.5% of final value for a 50% load step within the regulation limits of minimum and maximum load, ΔI/Δt <0.2 A/μs. Maximum voltage deviation is 3.5%. Startup/shut-down overshoot less than 2%.	<table><tr><th>Model</th><th>Normal Leakage</th><th>Fault Leakage</th><th>Test Voltage</th><th>Test Method</th></tr><tr><td>GSM25</td><td>50 μA</td><td>78 μA</td><td>132 Vca/60 Hz</td><td>UL2601-1</td></tr><tr><td>GSM25</td><td>94 μA</td><td>150 μA</td><td>264 Vca/50 Hz</td><td>IEC60601-1</td></tr></table>	Model	Normal Leakage	Fault Leakage	Test Voltage	Test Method	GSM25	50 μA	78 μA	132 Vca/60 Hz	UL2601-1	GSM25	94 μA	150 μA	264 Vca/50 Hz	IEC60601-1
Model	Normal Leakage	Fault Leakage	Test Voltage	Test Method												
GSM25	50 μA	78 μA	132 Vca/60 Hz	UL2601-1												
GSM25	94 μA	150 μA	264 Vca/50 Hz	IEC60601-1												
Overvoltage Protection Built in with firing point set per ratings table. OVP firing reduces voltage to less than 50% of nominal voltage in 50 ms.	Medical Safety Condor D.C. Power Supplies, Inc. declares under our sole responsibility that all GSM models are in conformity with the applicable requirements of UL2601-1 Patient Care Equipment, CSA-C22.2 No.601.1, IEC60601-1, EN 60601-1.															
Voltage Adjustment Factory set with fixed resistors to maximize reliability.																
Efficiency 70% minimum at full rated load, nominal input voltage.																
Input Protection Internal ac fuse provided on all units.																

All specifications are typical at nominal input, full load at 25°C unless otherwise stated

Commercial Model	Medical Model	Output No.	Output	Current	Load Regulation	Initial Setpoint Tolerance	OVP Setting	Ripple and Noise	Notes
GSC25A	GSM25A	1	+ 5.1 V	2.5 A	1%	1%	6.2 ± 0.6 V	1%	A
		2	+12 V	1.5 A	4%	3%		1%	A
		3	- 12 V	0.2 A	1%	4%		1%	B
GSC25B	GSM25B	1	+ 5 V	2.5 A	1%	1%	6.2 ± 0.6 V	1%	A
		2	+15 V	1.5 A	4%	3%		1%	A
		3	- 15 V	0.2 A	1%	4%		1%	B
GSC25D	GSM25D	1	+5.1 V	2.5 A	1%	1%	6.2 ± 0.6 V	1%	A
		2	+24 V	1.0 A	4%	3%		1%	A
		3	-12 V	0.2 A	1%	4%		1%	B

A. To maintain proper regulation on output 2, +5.1 V current must be at least 1/4 and not greater than 5 times V2 current. V1 must be adjusted within 1% of 5.1 V to maintain full load regulation on V2.

B. Thermal foldback type current limit

C. Add "G" suffix to model number for RoHS compliant model.

GSC25/GSM25 MECHANICAL SPECIFICATIONS

INPUT: J1

AMP P/N: 640445-3

W/CENTER PIN REMOVED: 0.156 CTR HEADER

PIN 1 AC LINE
PIN 2 AC NEUTRAL

GND

0.250 FASTON TAB

OUTPUT: J2

AMP P/N: 640445-6

0.156 CTR HEADER

PIN #	OUTPUT
1	OUTPUT #2
2	OUTPUT #1
3	OUTPUT #1
4	COMMON
5	COMMON
6	OUTPUT #3

MATING CONNECTOR AMP P/N'S


	HOUSING	CONTACT
INPUT J1	640250-3	770476-1
OUTPUT J2	640250-6	770476-1

NOTE: 5A MAXIMUM RECOMMENDED CURRENT PER CONNECTOR PIN.

TOLERANCES:

X.XX ± 0.030 (0.76MM)

X.XXX ± 0.010 (0.25MM)



ENVIRONMENTAL SPECIFICATIONS	OPERATING	NON-OPERATING
Temperature (A)	See individual specs.	-40 to +85°C
Humidity (A)	0 to 95% RH	0 to 95% RH
Shock (B)	20 g _{pk}	40 g _{pk}
Altitude	-500 to 10,000 ft	-500 to 40,000 ft
Vibration (C)	1.5 g _{rms} 0.003 g ² /Hz	5 g _{rms} 0.026 g ² /Hz

A. Units should be allowed to warm up/operate under non-condensing conditions before application of power.

B. Shock testing—half-sinusoidal, 10 ± 3 ms duration, ± direction, 3 orthogonal axes, total 6 shocks.

C. Random vibration—10 to 2000Hz, 6dB/octave roll-off from 350 to 2000Hz, 3 orthogonal axes. Tested for 10 min./axis operating and 1 hr./axis non-operating.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9