

## DATA SHEET

# SE5005L: 5 GHz Power Amplifier with Power Detector

## Applications


- DSSS 5 GHz WLAN (IEEE802.11a)
- Access points
- PCMCIA cards
- PC cards

## Features

- 5 GHz matched +18 dBm PA
- Integrated PA enable pin ( $V_{EN}$ )
- Buffered, temperature-compensated power detector
- High and low linearity modes
- 3% EVM, @ +18 dBm, 64 QAM, 54 Mbps
- +30 dB typical gain
- DC blocked
- QFN (16-pin, 3.0 mm x 3.0 mm x 0.9 mm) package (MSL1 @ 260 °C per JEDEC J-STD-020)



Skyworks Green™ products are compliant with all applicable legislation and are halogen-free. For additional information, refer to *Skyworks Definition of Green™*, document number SQ04-0074.



*Note: The RF I/Os are DC blocked.*

K111

**Figure 1. SE5005L Block Diagram**

## Description

The SE5005L is a 5 GHz Power Amplifier (PA) that offers high linear power for wireless LAN applications.

The SE5005L offers a high level of integration for a simplified design, which provides quicker time-to-market and higher application board production yield. The SE5005L integrates all matching elements, a 3.8 GHz notch filter, and a temperature-compensated, load-insensitive power detector with +20 dB of dynamic range.

For wireless LAN applications, the SE5005L meets the requirements of IEEE 802.11a and delivers approximately +18 dBm of linear output power. The SE5005L also features a linearity mode-control function to reduce current consumption at low power.

The SE5005L integrates the reference voltage generator, which allows for a true Complementary Metal Oxide Semiconductor (CMOS) compatible digital enable (EN) function to turn the PA on and off.

A functional block diagram is shown in Figure 1. The pin configuration and package are shown in Figure 2. Signal pin assignments and functional pin descriptions are provided in Table 1.




Figure 2. SE5005L Pinout  
(Top View)

Table 1. SE5005L Signal Descriptions

| Pin # | Name | Description                    | Pin # | Name    | Description                   |
|-------|------|--------------------------------|-------|---------|-------------------------------|
| 1     | VCC2 | Bias and driver supply voltage | 9     | GND     | Ground                        |
| 2     | EN   | PA enable                      | 10    | GND     | Ground                        |
| 3     | GND  | Ground                         | 11    | GND     | Ground                        |
| 4     | RFIN | TX RF input signal             | 12    | RFOUT   | 5 GHz antenna output          |
| 5     | GND  | Ground                         | 13    | GND     | Ground                        |
| 6     | GND  | Ground                         | 14    | DET     | Power detector output         |
| 7     | GND  | Ground                         | 15    | H/L Lin | High to low linearity control |
| 8     | GND  | Ground                         | 16    | VCC1    | Power stage supply voltage    |

**Table 2. SE5005L Absolute Maximum Ratings**

| Parameter                                                                  | Symbol             | Minimum | Maximum | Units |
|----------------------------------------------------------------------------|--------------------|---------|---------|-------|
| Supply voltage on VCC1 and VCC2 pins                                       | V <sub>CC</sub>    | −0.3    | 4.2     | V     |
| DC input on Enable                                                         | EN                 | −0.3    | 3.6     | V     |
| RF input power, RF_OUT into 50 $\Omega$ match                              | RFIN               |         | +12     | dBm   |
| Storage temperature range                                                  | T <sub>STG</sub>   | −40     | 150     | °C    |
| Electrostatic discharge—Human Body Model (HBM), JEDEC JESD22-A114 all pins | ESD <sub>HBM</sub> |         | 350     | V     |

**Note:** Exposure to maximum rating conditions for extended periods may reduce device reliability. There is no damage to device with only one parameter set at the limit and all other parameters set at or below their nominal value. Exceeding any of the limits listed here may result in permanent damage to the device.

---

**CAUTION:** Although this device is designed to be as robust as possible, Electrostatic Discharge (ESD) can damage this device. This device must be protected at all times from ESD. Static charges may easily produce potentials of several kilovolts on the human body or equipment, which can discharge without detection. Industry-standard ESD precautions should be used at all times.

---

**Table 3. Recommended Operating Conditions**

| Parameter                            | Symbol          | Minimum | Maximum | Units |
|--------------------------------------|-----------------|---------|---------|-------|
| Supply voltage on VCC1 and VCC2 pins | V <sub>CC</sub> | 3.0     | 3.6     | V     |
| Ambient Temperature                  | T <sub>A</sub>  | −40     | 85      | °C    |

## Electrical and Mechanical Specifications

The absolute maximum ratings of the SE5005L are provided in Table 2. The recommended operating conditions are specified in Table 3, and electrical specifications are provided in Tables 4 and 5.

The state of the SE5005L is determined by the logic provided in Table 6.

**Table 4. SE5005L Electrical Specifications: Transmit (Tx) AC Characteristics (Note 1)****(V<sub>CC</sub> = V<sub>EN</sub> = C<sub>0</sub> = H/L Lin = 3.3 V, T<sub>A</sub> = +25 °C, as Measured on Skyworks SE5005L-EK1 Evaluation Board, Unless Otherwise Noted)**

| Parameter                                                                                                     | Symbol                                                             | Test Condition                                                                                                                                                               | Min.                                                           | Typ.                                                     | Max.                              | Units   |
|---------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|----------------------------------------------------------|-----------------------------------|---------|
| Frequency range                                                                                               | f                                                                  |                                                                                                                                                                              | 5.15                                                           |                                                          | 5.75                              | GHz     |
| Output power, 802.11a, 64 QAM:<br>High linearity mode H/L Lin = 3.3 V<br><br>Low linearity mode H/L Lin = 0 V | P <sub>OUT</sub>                                                   | EVM = 3%<br>EVM < 2.2%<br>MCS0, HT20, mask compliant<br>MCS0, HT40, mask compliant<br><br>EVM = 3%<br>EVM < 2.2%<br>MCS0, HT20, mask compliant<br>MCS0, HT40, mask compliant |                                                                | +18<br>+16<br>+22<br>+21<br><br>+17<br>+15<br>+20<br>+19 | 0                                 | dBm     |
| Output 1dB compression point                                                                                  | P1dB                                                               | No modulation                                                                                                                                                                |                                                                | +27<br>+23                                               |                                   | dBm     |
| Input return loss                                                                                             | S <sub>11</sub>                                                    | P <sub>IN</sub> = -25 dBm                                                                                                                                                    | +22                                                            | +25                                                      |                                   | dBm     |
| Gain:<br>Small signal<br><br>Small signal variation<br><br>Out of band                                        | S <sub>21</sub><br><br>ΔS <sub>21</sub><br><br>S <sub>21_3.8</sub> | P <sub>IN</sub> = -25dBm<br>High linearity mode<br>Low linearity mode<br>Gain variation over single 40 MHz channel<br>Gain variation over band<br>Gain at 3.8 GHz            | +10<br>+27<br>+23<br><br>-1.5                                  | +14                                                      | +34<br>+32<br>+0.5<br>+1.5<br>+10 | dB      |
| Harmonic                                                                                                      | 2f<br>3f                                                           | P <sub>OUT</sub> = +18 dBm, OFDM                                                                                                                                             |                                                                | -50<br>-60                                               | -42<br>-42                        | dBm/MHz |
| Rise and fall time                                                                                            | t <sub>r</sub> , t <sub>f</sub>                                    |                                                                                                                                                                              |                                                                | 0.5                                                      |                                   | μs      |
| Stability                                                                                                     | STAB                                                               | P <sub>OUT</sub> = +18 dBm, 54 Mbps, 64 QAM, VSWR = 6:1, all phases                                                                                                          | All non-harmonically related outputs less than -50 dBc/100 kHz |                                                          |                                   |         |
| Ruggedness—tolerance to output load mismatching                                                               | RU                                                                 | P <sub>IN</sub> = +12 dBm, CW, VSWR = 6:1, all phases                                                                                                                        | No damage                                                      |                                                          |                                   |         |
| Robustness tolerance to input power                                                                           |                                                                    | P <sub>IN</sub> = +12 dBm, CW, VSWR = 6:1, all phases                                                                                                                        | No damage                                                      |                                                          |                                   |         |

**Note 1:** Performance is guaranteed only under the conditions listed in the above Table.**Table 5. SE5005L Power Detector Characteristics (Note 1)****(V<sub>CC</sub> = V<sub>EN</sub> = 3.3 V, f = 5.4 GHz, T<sub>A</sub> = +25 °C, as Measured on Skyworks SE2432L-EK1 Evaluation Board, Unless Otherwise Noted)**

| Parameter                     | Symbol                                                        | Test Condition                                                                        | Minimum              | Typical | Maximum             | Units |
|-------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------|---------|---------------------|-------|
| P <sub>OUT</sub> detect range | PDR                                                           |                                                                                       | 0                    |         | P1dB                | dBm   |
| Detector voltage              | VDET <sub>22</sub><br>VDET <sub>16</sub><br>VDET <sub>2</sub> | P <sub>OUT</sub> = +22 dBm<br>P <sub>OUT</sub> = +16 dBm<br>P <sub>OUT</sub> = +2 dBm | 0.80<br>0.55<br>0.25 |         | 1.0<br>0.60<br>0.35 | V     |
| Output impedance              | PDZ <sub>OUT</sub>                                            |                                                                                       |                      | 5       |                     | kΩ    |

**Note 1:** Performance is guaranteed only under the conditions listed in the above Table.




Figure 3. SE5005L Power Detector Sweep over Temperature and Frequency




Figure 4. SE5005L Power Detector Accuracy at 2:1 Mismatch

**Table 6. SE5005L Logic Control Characteristics****(V<sub>CC</sub> = V<sub>EN</sub> = 3.3 V, T<sub>A</sub> = +25 °C, as Measured on Skyworks SE5005L-EV1 Evaluation Board, Unless Otherwise Noted)**

| Parameter                                   | Symbol                               | Test Condition                                                                                                                                                                                                                                       | Minimum      | Typical           | Maximum      | Units          |
|---------------------------------------------|--------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------------------|--------------|----------------|
| Supply current                              | ICC-802.11a                          | P <sub>OUT</sub> = +18 dBm, 54 Mbps, 64 QAM, H/L Lin = 3.3V (high linearity mode)<br>P <sub>OUT</sub> = +14 dBm, 54 Mbps, 64 QAM, H/L Lin = 0V (low linearity mode)<br>P <sub>OUT</sub> = +5 dBm, 54 Mbps, 64 QAM, H/L Lin = 0V (low linearity mode) |              | 195<br>140<br>108 |              | mA<br>mA<br>mA |
|                                             | I <sub>OFF</sub>                     | V <sub>EN</sub> = 0 V, No RF                                                                                                                                                                                                                         |              | 0.5               |              | μA             |
| Logic voltage:<br>High<br>Low               | V <sub>ENH</sub><br>V <sub>ENL</sub> |                                                                                                                                                                                                                                                      | +2.8<br>−0.3 |                   | +3.6<br>+0.3 | V<br>V         |
| Input current logic voltage:<br>High<br>Low | I <sub>ENH</sub><br>I <sub>ENL</sub> |                                                                                                                                                                                                                                                      |              | <1                | 400          | μA<br>μA       |

## Package Dimensions


Branding information is shown in Figure 5. Package dimensions are shown in Figure 6, the recommended land and solder pattern is shown in Figure 7, and tape and reel dimensions are provided in Figure 5.

The SE5005L is rated to Moisture Sensitivity Level 1 (MSL1) at 260 °C, and can be used for lead or lead-free soldering. For additional information, refer to the Skyworks Application Note, *Solder Reflow Information* (Document Number 200164).


Care must be taken when attaching this product, whether it is done manually or in a production solder reflow environment. Production quantities of this product are shipped in a standard tape and reel format.

## Package and Handling Information


Instructions on the shipping container label regarding exposure to moisture after the container seal is broken must be followed. Otherwise, problems related to moisture absorption may occur when the part is subjected to high temperatures during solder assembly.



**Figure 5. SE5005L Typical Part Marking  
(Top View)**




1. All measurements are in millimeters.
2. Dimensioning and tolerancing according to ASME Y14.5M-1994.  
Unless otherwise specified the following values apply:  
Decimal Tolerance:      Angular Tolerance:  
X.X (1 place) ± 0.1 mm      ±0.5°  
X.XX (2 places) ± 0.05 mm  
X.XXX (3 places) ± 0.025 mm
3. Coplanarity applies to the exposed heat sink slug as well as the terminals.
4. Dimension applies to metalized terminal. If terminal has a radius, dimension should be measured in that radius area.
5. Unless specified, dimensions are symmetrical about center lines.



S3396

Figure 6. SE5005L Package Dimensions



**NOTES:**

1. Via hole recommendations:  
0.025 mm Cu via wall plating (minimum),  
soldermask on the farside should tent  
or plug via holes.
2. Soldermask recommendations:  
Contact board fabricator for recommended  
soldermask offset and tolerance.
3. Stencil recommendations:  
0.125 mm stencil thickness, laser cut apertures,  
trapezoidal walls, and rounded corners offer  
better paste release.

Dimension and tolerancing according to ASME Y14.5M-1994.  
Unless specified, dimensions are symmetrical about center lines.  
All dimensions are in millimeters.

S3397

**Figure 7. SE5005L Recommended Land and Solder Pattern**



## Ordering Information

| Model Name                                         | Manufacturing Part Number | Evaluation Board Part Number |
|----------------------------------------------------|---------------------------|------------------------------|
| SE5005L: 5 GHz Power Amplifier with Power Detector | SE5005L                   | SE5005L-EK1                  |

Copyright © 2012, 2013 Skyworks Solutions, Inc. All Rights Reserved.

Information in this document is provided in connection with Skyworks Solutions, Inc. ("Skyworks") products or services. These materials, including the information contained herein, are provided by Skyworks as a service to its customers and may be used for informational purposes only by the customer. Skyworks assumes no responsibility for errors or omissions in these materials or the information contained herein. Skyworks may change its documentation, products, services, specifications or product descriptions at any time, without notice. Skyworks makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of Skyworks products, information or materials, except as may be provided in Skyworks Terms and Conditions of Sale.

THE MATERIALS, PRODUCTS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT; ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Skyworks products are not intended for use in medical, lifesaving or life-sustaining applications, or other equipment in which the failure of the Skyworks products could lead to personal injury, death, physical or environmental damage. Skyworks customers using or selling Skyworks products for use in such applications do so at their own risk and agree to fully indemnify Skyworks for any damages resulting from such improper use or sale.

Customers are responsible for their products and applications using Skyworks products, which may deviate from published specifications as a result of design defects, errors, or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Skyworks assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Skyworks products outside of stated published specifications or parameters.

Skyworks, the Skyworks symbol, and "Breakthrough Simplicity" are trademarks or registered trademarks of Skyworks Solutions, Inc., in the United States and other countries. Third-party brands and names are for identification purposes only, and are the property of their respective owners. Additional information, including relevant terms and conditions, posted at [www.skyworksinc.com](http://www.skyworksinc.com), are incorporated by reference.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9