


**a**

# Low Voltage 1.2 V to 5.5 V, Bidirectional, Logic Level Translators

## Preliminary Technical Data

**ADG3304****FEATURES****Bidirectional Level Translation****Operates from 1.2 V to 5.5 V****12 Bump WLCSP package and 14-lead TSSOP****Low Quiescent Current <5 $\mu$ A****APPLICATIONS****SPI™, Microwire™ and I<sup>2</sup>C™ Translation****Low Voltage ASIC level Translation****Smart Card Readers****Cell Phones & Cell-Phone Cradles****Portable Communication Devices****Telecommunications Equipment****Network Switches and Routers****Storage Systems (SAN/NAS)****Computing/Server Applications****GPS****Portable POS Systems****Low Cost Serial Interfaces****FUNCTIONAL BLOCK DIAGRAM****GENERAL DESCRIPTION**

The ADG3304 is a 4-Channel bidirectional level translator. Its function is to provide level shifting in a multi-voltage system. The voltage applied to  $V_{CCA}$  sets up the logic levels on the A side of the device, while  $V_{CCY}$  sets the levels on the Y side. In this way, signals applied to the  $V_{CCA}$  side of the device appear as  $V_{CCY}$  compatible logic on the other side of the device and vice versa as the device is designed to handle bidirectional signals. The device is guaranteed for operation over the supply range 1.2 V to 5.5 V.

These devices are suited to applications like data transfer between a low voltage DSP/Controller and a higher voltage device. Other applications include high end consumer products where constant changes to the chipset designs result in multiple supply levels in the application.

$V_{CCY}$  operates from +1.65 to 5.5 V while  $V_{CCA}$  from +1.2 to  $V_{CCY}$ .  $V_{CCA}$  must always operate from a supply that is lower than  $V_{CCY}$ . When the device Enable pin (EN) is pulled low, the Ax and Yx inputs/outputs are tri-stated. The EN pin is driven high for normal operation. EN pin is referred to  $V_{CCA}$  voltage.

**PRODUCT HIGHLIGHTS**

1. Bidirectional Level Translation.
2. The ADG3304 is fully guaranteed from 1.2 V to 5.5 V supply range.
3. 14 lead TSSOP and 12 lead WLCSP package.

REV. PrC Feb 2004

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.  
Tel: 781/329-4700 World Wide Web Site: <http://www.analog.com>  
Fax: 781/326-8703 Analog Devices, Inc., 2004

# PRELIMINARY TECHNICAL DATA

## ADG3304—SPECIFICATIONS<sup>1</sup>

( $V_{CCY} = +1.65$  to  $5.5$  V,  $V_{CCA} = +1.1$  to  $V_{CCY}$ , GND = 0 V, All specifications  $T_{MIN}$  to  $T_{MAX}$  unless otherwise noted)

| Parameter                                                                       | Symbol       | Conditions                                      | Min             | Typ <sup>2</sup> | Max     | Units   |
|---------------------------------------------------------------------------------|--------------|-------------------------------------------------|-----------------|------------------|---------|---------|
| <b>LOGIC INPUTS/OUTPUTS</b>                                                     |              |                                                 |                 |                  |         |         |
| Input High Voltage                                                              | $V_{IH}$     |                                                 | $V_{CCY} - 0.4$ |                  |         | V       |
| Input Low Voltage                                                               | $V_{IL}$     |                                                 | $V_{CCA} - 0.4$ |                  | 0.4     | V       |
| Output High Voltage                                                             | $V_{OH}$     | $I_{OH} = 20 \mu A$ ,                           | $V_{CCY} - 0.4$ |                  | 0.4     | V       |
| Output Low Voltage                                                              | $V_{OL}$     | $I_{OH} = 20 \mu A$ ,<br>$I_{OL} = 20 \mu A$ ,  | $V_{CCA} - 0.4$ |                  | 0.4     | V       |
| Input Leakage Current                                                           | $I_I$        | $0 \leq V_{IN} \leq 3.6$ V                      |                 |                  | $\pm 1$ | $\mu A$ |
| Output Leakage Current                                                          | $I_O$        | $0 \leq V_{IN} \leq 3.6$ V                      |                 |                  | $\pm 1$ | $\mu A$ |
| Input Capacitance <sup>3</sup>                                                  | $C_{IN}$     | $f = 1$ MHz, $V_{A/Y} = V_{CCA/Y}$ or GND       |                 | 5                |         | pF      |
| Output Capacitance <sup>3</sup>                                                 | $C_O$        | $f = 1$ MHz, $V_{A/Y} = V_{CCY/A}$ or GND       |                 | 5                |         | pF      |
| <b>SWITCHING CHARACTERISTICS<sup>3</sup></b>                                    |              |                                                 |                 |                  |         |         |
| <b><math>3.3V \pm 0.3V \leq V_{CCA} \leq V_{CCY} \leq 5V \pm 0.5V</math></b>    |              |                                                 |                 |                  |         |         |
| Propagation Delay, $t_{PD}$                                                     | Y - A        | $R_S = 50\Omega$ , $C_A = 15$ pF                |                 |                  | 5       | ns      |
|                                                                                 | A - Y        | $R_S = 50\Omega$ , $C_Y = 50$ pF                |                 |                  | 5       | ns      |
| Rise Time                                                                       | $t_{R_Y}$    | $R_S = 50\Omega$ , $C_Y = 50$ pF                |                 |                  | 5       | ns      |
| Fall Time                                                                       | $t_{F_Y}$    | $R_S = 50\Omega$ , $C_Y = 50$ pF                |                 |                  | 5       | ns      |
| Rise Time                                                                       | $t_{R_A}$    | $R_S = 50\Omega$ , $C_A = 15$ pF                |                 |                  | 5       | ns      |
| Fall Time                                                                       | $t_{F_A}$    | $R_S = 50\Omega$ , $C_A = 15$ pF                |                 |                  | 5       | ns      |
| Maximum Data Rate                                                               |              | $R_S = 50\Omega$ , $C_Y = 50$ pF, $C_A = 15$ pF | 40              |                  |         | Mbps    |
| Channel To Channel Skew                                                         | $t_{SKEW}$   | $R_S = 50\Omega$ , $C_Y = 50$ pF, $C_A = 15$ pF |                 |                  | tbd     | ns      |
| Part To Part Skew                                                               | $t_{PPSKEW}$ | $R_S = 50\Omega$ , $C_Y = 50$ pF, $C_A = 15$ pF |                 |                  | tbd     | ns      |
| <b><math>1.8V \pm 0.15V \leq V_{CCA} \leq V_{CCY} \leq 3.3V \pm 0.3V</math></b> |              |                                                 |                 |                  |         |         |
| Propagation Delay, $t_{PD}$                                                     | Y - A        | $R_S = 50\Omega$ , $C_A = 15$ pF                |                 |                  | 10      | ns      |
|                                                                                 | A - Y        | $R_S = 50\Omega$ , $C_Y = 50$ pF                |                 |                  | 15      | ns      |
| Rise Time                                                                       | $t_{R_Y}$    | $R_S = 50\Omega$ , $C_Y = 50$ pF                |                 |                  | 10      | ns      |
| Fall Time                                                                       | $t_{F_Y}$    | $R_S = 50\Omega$ , $C_Y = 50$ pF                |                 |                  | 10      | ns      |
| Rise Time                                                                       | $t_{R_A}$    | $R_S = 50\Omega$ , $C_A = 15$ pF                |                 |                  | 10      | ns      |
| Fall Time                                                                       | $t_{F_A}$    | $R_S = 50\Omega$ , $C_A = 15$ pF                |                 |                  | 10      | ns      |
| Maximum Data Rate                                                               |              | $R_S = 50\Omega$ , $C_Y = 50$ pF, $C_A = 15$ pF | 35              |                  |         | Mbps    |
| Channel To Channel Skew                                                         | $t_{SKEW}$   | $R_S = 50\Omega$ , $C_Y = 50$ pF, $C_A = 15$ pF |                 |                  | 5       | ns      |
| <b><math>1.2V \pm 0.1V \leq V_{CCA} \leq V_{CCY} \leq 3.3V \pm 0.3V</math></b>  |              |                                                 |                 |                  |         |         |
| Propagation Delay, $t_{PD}$                                                     | Y - A        | $R_S = 50\Omega$ , $C_A = 15$ pF                |                 |                  | 20      | ns      |
|                                                                                 | A - Y        | $R_S = 50\Omega$ , $C_Y = 50$ pF                |                 |                  | 20      | ns      |
| Rise Time                                                                       | $t_{R_Y}$    | $R_S = 50\Omega$ , $C_Y = 50$ pF                |                 |                  | 15      | ns      |
| Fall Time                                                                       | $t_{F_Y}$    | $R_S = 50\Omega$ , $C_Y = 50$ pF                |                 |                  | 15      | ns      |
| Rise Time                                                                       | $t_{R_A}$    | $R_S = 50\Omega$ , $C_A = 15$ pF                |                 |                  | 15      | ns      |
| Fall Time                                                                       | $t_{F_A}$    | $R_S = 50\Omega$ , $C_A = 15$ pF                |                 |                  | 15      | ns      |
| Maximum Data Rate                                                               |              | $R_S = 50\Omega$ , $C_Y = 50$ pF, $C_A = 15$ pF |                 | 20               |         | Mbps    |
| Channel To Channel Skew                                                         | $t_{SKEW}$   | $R_S = 50\Omega$ , $C_Y = 50$ pF, $C_A = 15$ pF |                 |                  | 5       | ns      |
| <b><math>2.5V \pm 0.2V \leq V_{CCA} \leq V_{CCY} \leq 3.3V \pm 0.3V</math></b>  |              |                                                 |                 |                  |         |         |
| Propagation Delay, $t_{PD}$                                                     | Y - A        | $R_S = 50\Omega$ , $C_A = 15$ pF                |                 |                  | 8.5     | ns      |
|                                                                                 | A - Y        | $R_S = 50\Omega$ , $C_Y = 50$ pF                |                 |                  | 8.5     | ns      |
| Rise Time                                                                       | $t_{R_Y}$    | $R_S = 50\Omega$ , $C_Y = 50$ pF                |                 |                  | 8.5     | ns      |
| Fall Time                                                                       | $t_{F_Y}$    | $R_S = 50\Omega$ , $C_Y = 50$ pF                |                 |                  | 8.5     | ns      |
| Rise Time                                                                       | $t_{R_A}$    | $R_S = 50\Omega$ , $C_A = 15$ pF                |                 |                  | 8.5     | ns      |
| Fall Time                                                                       | $t_{F_A}$    | $R_S = 50\Omega$ , $C_A = 15$ pF                |                 |                  | 8.5     | ns      |
| Maximum Data Rate                                                               |              | $R_S = 50\Omega$ , $C_Y = 50$ pF, $C_A = 15$ pF | 40              |                  |         | Mbps    |
| Channel To Channel Skew                                                         | $t_{SKEW}$   | $R_S = 50\Omega$ , $C_Y = 50$ pF, $C_A = 15$ pF |                 |                  | 10      | ns      |
| <b>POWER REQUIREMENTS</b>                                                       |              |                                                 |                 |                  |         |         |
| Power Supply Voltages                                                           | $V_{CCY}$    |                                                 | 1.65            |                  | 5.5     | V       |
|                                                                                 | $V_{CCA}$    |                                                 | 1.1             |                  | 5.5     | V       |
| Quiescent Power Supply Current                                                  | $I_{CCY}$    | Digital Inputs = 0 V or $V_{CCY}$               |                 |                  | 5       | $\mu A$ |
|                                                                                 | $I_{CCA}$    | Digital Inputs = 0 V or $V_{CCA}$               |                 |                  | 5       | $\mu A$ |

### NOTES

<sup>1</sup>Temperature range is as follows: B Version:  $-40^\circ C$  to  $+85^\circ C$ .

<sup>2</sup>All typical vlaues are at  $T_A = +25^\circ C$  unless otherwise stated.

<sup>3</sup>Guaranteed by design, not subject to production test.

Specifications subject to change without notice.

### ABSOLUTE MAXIMUM RATINGS<sup>1</sup>

(T<sub>A</sub> = 25°C unless otherwise noted)

V<sub>CCY</sub> to GND ..... -0.3 V to +7 V

V<sub>CCA</sub> to GND ..... -0.3 V to +7 V

Digital Inputs (A) ..... -0.3 V to (V<sub>CCA</sub> + 0.3V)

Digital Inputs (Y) ..... -0.3 V to (V<sub>CCY</sub> + 0.3V)

EN to GND ..... -0.3 V to +7 V

Operating Temperature Range

Industrial (B Version) ..... -40°C to +85°C

Storage Temperature Range ..... -65°C to +150°C

Junction Temperature ..... 150°C

14 Lead TSSOP

θ<sub>JA</sub> Thermal Impedance ..... 150°C/W


Lead Temperature, Soldering (10seconds) ..... 300°C

IR Reflow, Peak Temperature (<20 seconds) ... +235°C


### NOTES

<sup>1</sup>Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those listed in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability. Only one absolute maximum rating may be applied at any one time.

### Pin Configuration 14 Lead TSSOP (RU-14)



### 12 Lead WLCSP (CB-12)



### ORDERING GUIDE

| Model      | Temperature Range | Package Description | Package Option |
|------------|-------------------|---------------------|----------------|
| ADG3304BRU | -40°C to +85°C    | TSSOP               | RU-14          |
| ADG3304BCB | -40°C to +85°C    | WLCSP               | CB-12          |


### CAUTION

ESD (electrostatic discharge) sensitive device. Electrostatic charges as high as 4000 V readily accumulate on the human body and test equipment and can discharge without detection. Although the ADG3304 features proprietary ESD protection circuitry, permanent damage may occur on devices subjected to high energy electrostatic discharges. Therefore, proper ESD precautions are recommended to avoid performance degradation or loss of functionality.



The ADG3304 level translator allows the required level shifting necessary for data transfer in a system where multiple voltages are used. The device requires two supplies,  $V_{CCA}$  and  $V_{CCY}$ . These supplies set the logic levels on each side of the device. The device translates data present on the  $V_A$  side of the device to the higher voltage level at the  $V_Y$  side of the device. Similarly, as the device is capable of bidirectional translation, data applied to the  $V_Y$  side will be translated to the voltage referenced to  $V_A$ .

The forward channel consists of a string of inverters and a level translator, while the reverse channel consists simply of inverters. A level translator is not required in the reverse path (Y-A) as the supply voltage  $V_{CCY}$  must always be greater than or equal to  $V_{CCA}$ . A current limiting resistor is used in series with each channel to prevent any contention issues, see figure 1.



As the driven side has to drive a load capacitance through this 6k resistance, one shot generators are used to drive large mos devices in the output stage to help speed up the rate of switching. The output stage is inactive and three state except when transistions are present on either side of the translator. When this happens the one shot fires turning on the output stage and driving the load capacitance faster than if it were driven through the resistor. As the device is bi-directional, both input stages will be active during this period. While this design gives maximum speed from the device, it can result in some current driving back into the source driving the input of the translator.


## Enable Operation

When pulled low, the EN input allows the user to tri-state both sides (A and Y) of the level translator. EN pin is referred to  $V_{CCA}$  voltage.


### OUTLINE DIMENSIONS

Dimensions shown in inches and (mm).

#### 14-Lead TSSOP (RU-14)



#### 12-Lead WLCSP (CB-12)



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9