

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0740571007](#)
Status: **Active**
Overview: [vhdm](#)
Description: 2.00mm (.079") Pitch VHDM® Board-to-Board Backplane Header, Vertical, 6-Row, Open Signal Module, 60 Circuits, 10 Columns, Pin Length 6.25mm (.246"), 1.27µm (50µ") Gold (Au) Plating

Documents:

[3D Model](#) [RoHS Certificate of Compliance \(PDF\)](#)
[Drawing \(PDF\)](#)

Agency Certification


UL E29179

General

Product Family Backplane Connectors
Series [74057](#)
Application Backplane
Application Tooling Documents Tooling Manual
Comments Open Header
Component Type PCB Header
Overview [vhdm](#)
Product Name VHDM®
Style N/A

Physical

Circuits (Loaded) 60
Circuits (maximum) 60
Color - Resin Black
Durability (mating cycles max) 200
First Mate / Last Break No
Flammability 94V-0
Guide to Mating Part No
Keying to Mating Part None
Material - Metal Beryllium Copper, High Performance Alloy (HPA)
Material - Plating Mating Gold
Material - Plating Termination Tin-Lead
Material - Resin High Temperature Thermoplastic
Number of Columns N/A
Number of Pairs Open Pin Field
Number of Rows 6
Orientation Vertical
PC Tail Length (in) 0.098 In
PC Tail Length (mm) 2.50 mm
PCB Locator No
PCB Retention None
PCB Thickness Recommended (in) 0.071 In
PCB Thickness Recommended (mm) 1.80 mm
Packaging Type Tube
Pitch - Mating Interface (in) 0.079 In
Pitch - Mating Interface (mm) 2.00 mm
Pitch - Term. Interface (in) 0.079 In
Pitch - Term. Interface (mm) 2.00 mm
Plating min: Mating (µin) 50
Plating min: Mating (µm) 1.25



Series

image - Reference only

EU RoHS
RoHS Compliant by Exemption
REACH SVHC
Contains SVHC: No
Halogen-Free
Status
Halogen-Free

China RoHS

Pb

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[74057Series](#)

Mates With
[74030](#) VHDM® Board-to-Board Daughtercard Receptacle

Application Tooling | FAQ
Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.
Global

Description	Product #
Flat Rock Tooling for Pneumatic Press	0622013700
VHDM® Insertion Module for Advanced Mate Signal Header, 6 Row by 11 Wide, 20.00mm (.787")	0622011101
VHDM® Signal Pin Inserter Repair Tool	0622015700

Plating min: Termination (µin)	30
Plating min: Termination (µm)	0.75
Polarized to PCB	Yes
Stackable	Yes
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	105°C
Termination Interface: Style	Through Hole - Compliant Pin

Electrical

Current - Maximum per Contact	1A
Data Rate	3.125 Gbps
Real Signals (per 25mm)	75
Shield Type	Ground Plane Shield
Shielded	Yes
Voltage - Maximum	120V AC (RMS)/DC

Material Info

Reference - Drawing Numbers



Packaging Specification	PK-74057-003
Sales Drawing	SD-74057-002

VHDM and Very High Density Metric are trademarks of Amphenol Corporation

VHDM® 6 Row Pin and Shield Repair Tool	0622015800
VHDM® 6 Row Shield Extraction Tool	0622016000
VHDM® Insertion Module for Advanced Mate Signal Header, 6 Row by 10 Wide, 20.00mm (.787")	0622020203
VHDM® Insertion Module for Advanced Mate Signal Header, 6 Row by 10 Wide, 20.00mm (.787")	0622020207



This document was generated on 05/19/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION




NOTES:

1. MATERIALS:
HOUSING - LIQUID CRYSTAL POLYMER (LCP),
GLASS-FILLED, UL 94V-0, COLOR: BLACK
SIGNAL PIN & SHIELD - COPPER ALLOY
2. FINISHES:
CONTACT AREA: SELECTIVE GOLD (Au)
PCB TAILS: SELECTIVE TIN/LEAD (Sn/Pb)
OR SELECTIVE MATTE TIN (Sn)
NICKEL (Ni) OVERALL.
3. THIS PART CONFORMS TO MOLEX PRODUCT
SPECIFICATION PS-74031-999
4. FOR MIXED CONTACT LENGTHS CONSULT
MOLEX FOR AVAILABILITY
5. FOR SPECIFIC MATERIAL NUMBERS & MATING
INFORMATION REFER TO SHEET 2
6. PACKAGE PER PK-74057-003
7. EITHER MARK PART WITH PART NUMBER & DATE
CODE APPROXIMATELY WHERE SHOWN OR PLACE
LABEL ON THE TUBE.





ADDED 15 COLUMN EC NO: UCP2006-1491 DRWNG: JONI AK 2006/01/19 CHKD: JONI AK 2006/01/19 APPR: CB IXLER 2006/01/23	QUALITY SYMBOLS ▽=0 ▽=0	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 2.5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION			
				mm	INCH	DRAWN BY MWANG	DATE 1998/11/09	TITLE VHDM 6 ROW OPEN END BACKPLANE SALES ASSEMBLY				
			4 PLACES	± ---	± ---	CHECKED BY JLAURX	DATE 1998/11/09					
			3 PLACES	± ---	± ---	APPROVED BY CB IXLER	DATE 1998/11/09					MOLEX MOLEX INCORPORATED
			2 PLACES	± ---	± ---	ANGULAR ±1/2°		MATERIAL NO. SEE SHEET 3	DOCUMENT NO. SD-74057-002	SHEET NO. 1 OF 3		
			1 PLACE	± ---	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS						
							SIZE B	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				

SIGNAL COLUMN
DAUGHTERCARD
CONNECTOR SIDE



0.41 OFFSET
SIGNAL TO SIGNAL

SHIELD
SIGNAL




ROW A

12.36

0.66
TOP DAUGHTERCARD
PCB TO $\varnothing$ ROW A

ROW A



MATERIAL NUMBER ASSIGNMENT

74057-*** ** SEE TABLES (SHEET 3)

NUMBER OF COLUMNS/PLATING
10 = 10 COLUMN TIN/LEAD
15 = 15 COLUMN TIN/LEAD
25 = 25 COLUMN TIN/LEAD
90 = 10 COLUMN MATTE TIN
95 = 15 COLUMN MATTE TIN
85 = 25 COLUMN MATTE TIN

ADDED 15 COLUMN EC NO: UCP2006-1491 DRWN: JONI AK 2006/01/19 CHKD: JONI AK 2006/01/19 APPR: CBIXLER 2006/01/23 K	QUALITY SYMBOLS ▽=0 ▽=0	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
				mm	INCH	DRAWN BY MWANG	DATE 1998/11/09	TITLE VHDM 6 ROW OPEN END BACKPLANE SALES ASSEMBLY MOLEX MOLEX INCORPORATED	
			4 PLACES	± ---	± ---	CHECKED BY JLAURX	DATE 1998/11/09		
			3 PLACES	± ---	± ---				
			2 PLACES	± ---	± ---				
			1 PLACE	± ---	± ---	APPROVED BY CBIXLER	DATE 1998/11/09		
			ANGULAR ±1/2°		MATERIAL NO. SEE SHEET 3		DOCUMENT NO. SD-74057-002	SHEET NO. 2 OF 3	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							

	10	9	8	7	6	5	4	3	2	1																																																																																																																																																																																																																																																																																	
F	<table><tr><th>PART NUMBER</th><th>COLUMN</th><th>NUMBER OF SIGNAL</th><th>OF PIN</th><th>NUMBER OF SHIELD</th><th>A</th><th>B</th><th>M</th><th>Au (um) THICKNESS</th></tr><tr><td>74057-1001</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">4.75</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-1006</td><td>1.27</td></tr><tr><td>74057-1501</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-1506</td><td>1.27</td></tr><tr><td>74057-2501</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-2501</td><td>1.27</td></tr><tr><td>74057-1002</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">6.25</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-1007</td><td>1.27</td></tr><tr><td>74057-1502</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-1507</td><td>1.27</td></tr><tr><td>74057-2502</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-2507</td><td>1.27</td></tr><tr><td>74057-1003</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">4.25</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-1008</td><td>1.27</td></tr><tr><td>74057-1503</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-1508</td><td>1.27</td></tr><tr><td>74057-2503</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-2508</td><td>1.27</td></tr><tr><td>74057-1004</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">5.15</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-1009</td><td>1.27</td></tr><tr><td>74057-1504</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-1509</td><td>1.27</td></tr><tr><td>74057-2504</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-2509</td><td>1.27</td></tr></table>								PART NUMBER	COLUMN	NUMBER OF SIGNAL	OF PIN	NUMBER OF SHIELD	A	B	M	Au (um) THICKNESS	74057-1001	10	60	10	20.00	18.00	4.75		0.76	74057-1006	1.27	74057-1501	15	90	15	30.00	28.00		0.76	74057-1506	1.27	74057-2501	25	150	25	50.00	48.00		0.76	74057-2501	1.27	74057-1002	10	60	10	20.00	18.00	6.25		0.76	74057-1007	1.27	74057-1502	15	90	15	30.00	28.00		0.76	74057-1507	1.27	74057-2502	25	150	25	50.00	48.00		0.76	74057-2507	1.27	74057-1003	10	60	10	20.00	18.00	4.25		0.76	74057-1008	1.27	74057-1503	15	90	15	30.00	28.00		0.76	74057-1508	1.27	74057-2503	25	150	25	50.00	48.00		0.76	74057-2508	1.27	74057-1004	10	60	10	20.00	18.00	5.15		0.76	74057-1009	1.27	74057-1504	15	90	15	30.00	28.00		0.76	74057-1509	1.27	74057-2504	25	150	25	50.00	48.00		0.76	74057-2509	1.27	<table><tr><th>PART NUMBER</th><th>COLUMN</th><th>NUMBER OF SIGNAL</th><th>OF PIN</th><th>NUMBER OF SHIELD</th><th>A</th><th>B</th><th>M</th><th>Au (um) THICKNESS</th></tr><tr><td>74057-9001</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">4.75</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-9006</td><td>1.27</td></tr><tr><td>74057-9501</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-9506</td><td>1.27</td></tr><tr><td>74057-8501</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-8501</td><td>1.27</td></tr><tr><td>74057-9002</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">6.25</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-9007</td><td>1.27</td></tr><tr><td>74057-9502</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-9507</td><td>1.27</td></tr><tr><td>74057-8502</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-8507</td><td>1.27</td></tr><tr><td>74057-9003</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">4.25</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-9008</td><td>1.27</td></tr><tr><td>74057-9503</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-9508</td><td>1.27</td></tr><tr><td>74057-8503</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-8508</td><td>1.27</td></tr><tr><td>74057-9004</td><td rowspan="2">10</td><td rowspan="2">60</td><td rowspan="2">10</td><td rowspan="2">20.00</td><td rowspan="2">18.00</td><td rowspan="6">5.15</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-9009</td><td>1.27</td></tr><tr><td>74057-9504</td><td rowspan="2">15</td><td rowspan="2">90</td><td rowspan="2">15</td><td rowspan="2">30.00</td><td rowspan="2">28.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-9509</td><td>1.27</td></tr><tr><td>74057-8504</td><td rowspan="2">25</td><td rowspan="2">150</td><td rowspan="2">25</td><td rowspan="2">50.00</td><td rowspan="2">48.00</td><td rowspan="2"></td><td>0.76</td></tr><tr><td>74057-8509</td><td>1.27</td></tr></table>								PART NUMBER	COLUMN	NUMBER OF SIGNAL	OF PIN	NUMBER OF SHIELD	A	B	M	Au (um) THICKNESS	74057-9001	10	60	10	20.00	18.00	4.75		0.76	74057-9006	1.27	74057-9501	15	90	15	30.00	28.00		0.76	74057-9506	1.27	74057-8501	25	150	25	50.00	48.00		0.76	74057-8501	1.27	74057-9002	10	60	10	20.00	18.00	6.25		0.76	74057-9007	1.27	74057-9502	15	90	15	30.00	28.00		0.76	74057-9507	1.27	74057-8502	25	150	25	50.00	48.00		0.76	74057-8507	1.27	74057-9003	10	60	10	20.00	18.00	4.25		0.76	74057-9008	1.27	74057-9503	15	90	15	30.00	28.00		0.76	74057-9508	1.27	74057-8503	25	150	25	50.00	48.00		0.76	74057-8508	1.27	74057-9004	10	60	10	20.00	18.00	5.15		0.76	74057-9009	1.27	74057-9504	15	90	15	30.00	28.00		0.76	74057-9509	1.27	74057-8504	25	150	25	50.00	48.00		0.76	74057-8509	1.27	
PART NUMBER	COLUMN	NUMBER OF SIGNAL	OF PIN	NUMBER OF SHIELD	A	B	M	Au (um) THICKNESS																																																																																																																																																																																																																																																																																			
74057-1001	10	60	10	20.00	18.00	4.75		0.76																																																																																																																																																																																																																																																																																			
74057-1006								1.27																																																																																																																																																																																																																																																																																			
74057-1501	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																																			
74057-1506								1.27																																																																																																																																																																																																																																																																																			
74057-2501	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																																			
74057-2501								1.27																																																																																																																																																																																																																																																																																			
74057-1002	10	60	10	20.00	18.00	6.25		0.76																																																																																																																																																																																																																																																																																			
74057-1007								1.27																																																																																																																																																																																																																																																																																			
74057-1502	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																																			
74057-1507								1.27																																																																																																																																																																																																																																																																																			
74057-2502	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																																			
74057-2507								1.27																																																																																																																																																																																																																																																																																			
74057-1003	10	60	10	20.00	18.00	4.25		0.76																																																																																																																																																																																																																																																																																			
74057-1008								1.27																																																																																																																																																																																																																																																																																			
74057-1503	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																																			
74057-1508								1.27																																																																																																																																																																																																																																																																																			
74057-2503	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																																			
74057-2508								1.27																																																																																																																																																																																																																																																																																			
74057-1004	10	60	10	20.00	18.00	5.15		0.76																																																																																																																																																																																																																																																																																			
74057-1009								1.27																																																																																																																																																																																																																																																																																			
74057-1504	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																																			
74057-1509								1.27																																																																																																																																																																																																																																																																																			
74057-2504	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																																			
74057-2509								1.27																																																																																																																																																																																																																																																																																			
PART NUMBER	COLUMN	NUMBER OF SIGNAL	OF PIN	NUMBER OF SHIELD	A	B	M	Au (um) THICKNESS																																																																																																																																																																																																																																																																																			
74057-9001	10	60	10	20.00	18.00	4.75		0.76																																																																																																																																																																																																																																																																																			
74057-9006								1.27																																																																																																																																																																																																																																																																																			
74057-9501	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																																			
74057-9506								1.27																																																																																																																																																																																																																																																																																			
74057-8501	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																																			
74057-8501								1.27																																																																																																																																																																																																																																																																																			
74057-9002	10	60	10	20.00	18.00	6.25		0.76																																																																																																																																																																																																																																																																																			
74057-9007								1.27																																																																																																																																																																																																																																																																																			
74057-9502	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																																			
74057-9507								1.27																																																																																																																																																																																																																																																																																			
74057-8502	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																																			
74057-8507								1.27																																																																																																																																																																																																																																																																																			
74057-9003	10	60	10	20.00	18.00	4.25		0.76																																																																																																																																																																																																																																																																																			
74057-9008								1.27																																																																																																																																																																																																																																																																																			
74057-9503	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																																			
74057-9508								1.27																																																																																																																																																																																																																																																																																			
74057-8503	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																																			
74057-8508								1.27																																																																																																																																																																																																																																																																																			
74057-9004	10	60	10	20.00	18.00	5.15		0.76																																																																																																																																																																																																																																																																																			
74057-9009								1.27																																																																																																																																																																																																																																																																																			
74057-9504	15	90	15	30.00	28.00			0.76																																																																																																																																																																																																																																																																																			
74057-9509								1.27																																																																																																																																																																																																																																																																																			
74057-8504	25	150	25	50.00	48.00			0.76																																																																																																																																																																																																																																																																																			
74057-8509								1.27																																																																																																																																																																																																																																																																																			
E											E																																																																																																																																																																																																																																																																																
D											D																																																																																																																																																																																																																																																																																
C											C																																																																																																																																																																																																																																																																																
B	TIN/LEAD CHART											LEAD FREE CHART											B																																																																																																																																																																																																																																																																				
A	ADDED 15 COLUMN EC NO: UCP2006-1491 DRWN: JONI AK 2006/01/19 CHKD: JONI AK 2006/01/19 APPR: CBI XLER 2006/01/23 REV											QUALITY SYMBOLS ▽=0 ▽=0											GENERAL TOLERANCES (UNLESS SPECIFIED) <table><tr><td></td><td>mm</td><td>INCH</td></tr><tr><td>4 PLACES</td><td>±---</td><td>±---</td></tr><tr><td>3 PLACES</td><td>±---</td><td>±---</td></tr><tr><td>2 PLACES</td><td>±---</td><td>±---</td></tr><tr><td>1 PLACE</td><td>±---</td><td>±---</td></tr></table> ANGULAR ±1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS												mm	INCH	4 PLACES	±---	±---	3 PLACES	±---	±---	2 PLACES	±---	±---	1 PLACE	±---	±---	DIMENSION STYLE MM ONLY <table><tr><td>DRAWN BY</td><td>DATE</td></tr><tr><td>J JONI AK</td><td>2006/01/10</td></tr><tr><td>CHECKED BY</td><td>DATE</td></tr><tr><td>J JONI AK</td><td>2006/01/10</td></tr><tr><td>APPROVED BY</td><td>DATE</td></tr><tr><td>J JONI AK</td><td>2006/01/10</td></tr></table> MATERIAL NO. SEE CHARTS SIZE B											DRAWN BY	DATE	J JONI AK	2006/01/10	CHECKED BY	DATE	J JONI AK	2006/01/10	APPROVED BY	DATE	J JONI AK	2006/01/10	SCALE --- DESIGN UNITS METRIC THIRD ANGLE PROJECTION VHDM 6 ROW OPEN END BACKPLANE SALES ASSEMBLY MOLEX MOLEX INCORPORATED DOCUMENT NO. SD-74057-002 SHEET NO. 3 OF 3 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											A																																																																																																																																																																																																								
	mm	INCH																																																																																																																																																																																																																																																																																									
4 PLACES	±---	±---																																																																																																																																																																																																																																																																																									
3 PLACES	±---	±---																																																																																																																																																																																																																																																																																									
2 PLACES	±---	±---																																																																																																																																																																																																																																																																																									
1 PLACE	±---	±---																																																																																																																																																																																																																																																																																									
DRAWN BY	DATE																																																																																																																																																																																																																																																																																										
J JONI AK	2006/01/10																																																																																																																																																																																																																																																																																										
CHECKED BY	DATE																																																																																																																																																																																																																																																																																										
J JONI AK	2006/01/10																																																																																																																																																																																																																																																																																										
APPROVED BY	DATE																																																																																																																																																																																																																																																																																										
J JONI AK	2006/01/10																																																																																																																																																																																																																																																																																										
	10	9	8	7	6	5	4	3	2	1																																																																																																																																																																																																																																																																																	
ib_frame_B_P_ME_T																																																																																																																																																																																																																																																																																											
Rev. D 2004/04/02																																																																																																																																																																																																																																																																																											

TIN/LEAD CHART

LEAD FREE CHART

ADDED 15 COLUMN

EC NO: UCP2006-1491

DRWN: JJONIAK 2006/01/19

CHKD: JJONIAK 2006/01/19

APPR: CBI XLER 2006/01/23

REV

QUALITY SYMBOLS

▽=0

▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± ---
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---

ANGULAR ±1/2°

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE

MM ONLY

DRAWN BY	DATE
JJONIAK	2006/01/10
CHECKED BY	DATE
JJONIAK	2006/01/10
APPROVED BY	DATE
JJONIAK	2006/01/10

MATERIAL NO.

SEE CHARTS

SIZE

B

SCALE

TITLE

VHDM 6 ROW
OPEN END BACKPLANE
SALES ASSEMBLY

MOLEX INCORPORATED

DOCUMENT NO.

SD-74057-002

SHEET NO.

3 OF 3

DESIGN UNITS

METRIC

THIRD ANGLE
PROJECTION

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9