

Chip beads  
For power line  
MPZ series



# MPZ0402 type



## FEATURES

- Noise reduction solution for power line.
- Compared to the MMZ series, has low direct current resistance for compatibility with large currents, optimal for low power consumption.
- Performs well even in signal lines where low direct current resistance is required.
- Operating temperature range: -55 to +125°C

## APPLICATION

- Noise removal for mobile devices such as smartphones and tablet terminals, and various modules.
- Noise removal for PCs and recorders, household appliances such as STBs, smart grids, and industrial equipment.

## PART NUMBER CONSTRUCTION

| MPZ         | 0402                               | S             | 100                        | C                   | T               | 000           |
|-------------|------------------------------------|---------------|----------------------------|---------------------|-----------------|---------------|
| Series name | LxWxT dimensions<br>0.4x0.2x0.2 mm | Material name | Impedance<br>(Ω) at 100MHz | Characteristic type | Packaging style | Internal code |

## CHARACTERISTICS SPECIFICATION TABLE

| Impedance<br>[100MHz]<br>(Ω) | Tolerance | DC resistance<br>(Ω) | Rated current*<br>(A) | Part No.                                                             |
|------------------------------|-----------|----------------------|-----------------------|----------------------------------------------------------------------|
| 10                           | ±5Ω       | 0.05                 | 1.10                  | <a href="#">MPZ0402S100CT000</a><br><a href="#">MPZ0402S100CTF0W</a> |
| 22                           | ±25%      | 0.15                 | 0.75                  | <a href="#">MPZ0402S220CT000</a><br><a href="#">MPZ0402S220CTF0W</a> |
| 33                           | ±25%      | 0.2                  | 0.55                  | <a href="#">MPZ0402S330CT000</a><br><a href="#">MPZ0402S330CTF0W</a> |



\* Please refer to the graph of rated current vs. temperature characteristics (derating) about the rating current at 85°C or more in temperature of the product.

### Measurement equipment

| Measurement item | Product No.   | Manufacturer          |
|------------------|---------------|-----------------------|
| Impedance        | E4991A+16196D | Keysight Technologies |
| DC resistance    | Type-7556     | Yokogawa              |

\* Equivalent measurement equipment may be used.


### Rated current vs. temperature characteristics (derating)



# MPZ0402 type


## Z VS. FREQUENCY CHARACTERISTICS (BY SERIES)

### MPZ0402 series




## Z, X, R VS. FREQUENCY CHARACTERISTICS


### MPZ0402S100CT



### MPZ0402S220CT




### MPZ0402S330CT




# MPZ0402 type

## SHAPE & DIMENSIONS




Dimensions in mm

## RECOMMENDED LAND PATTERN



Dimensions in mm


## RECOMMENDED REFLOW PROFILE



# MPZ0402 type

## PACKAGING STYLE


### REEL DIMENSIONS





| Type          | Package specifications | A        | W1            | W2       | N       |
|---------------|------------------------|----------|---------------|----------|---------|
| MPZ0402**T000 | Paper carrier (W8P2)   | ø180±2.0 | 8.4+2.0, -0.0 | 14.4max. | ø60min. |
| MPZ0402**TF0W | Plastic carrier (W4P1) | ø178±2.0 | 5.0±1.0       | —        | ø60±2.0 |

### TAPE DIMENSIONS

#### Paper carrier (W8P2)



#### Plastic carrier (W4P1)



### PACKAGE QUANTITY

|                  |                                         |                 |
|------------------|-----------------------------------------|-----------------|
| Package quantity | MPZ0402**T000<br>(W8P2 Paper carrier)   | 20,000 pcs/reel |
|                  | MPZ0402**TF0W<br>(W4P1 Plastic carrier) | 40,000 pcs/reel |

## TEMPERATURE RANGE, INDIVIDUAL WEIGHT

| Type                                    | Operating temperature range | Storage temperature range* | Individual weight |
|-----------------------------------------|-----------------------------|----------------------------|-------------------|
| MPZ0402**T000<br>(W8P2 Paper carrier)   | -55 to +125 °C              | -55 to +125 °C             | 0.08 mg           |
| MPZ0402**TF0W<br>(W4P1 Plastic carrier) | -55 to +125 °C              | -55 to +125 °C             | 0.08 mg           |

\* The storage temperature range is for after the assembly.

## REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

### SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using this products.

#### REMINDERS

- The storage period is within 12 months. Be sure to follow the storage conditions (temperature: 5 to 40°C, humidity: 10 to 75% RH or less).  
If the storage period elapses, the soldering of the terminal electrodes may deteriorate.
- Do not use or store in locations where there are conditions such as gas corrosion (salt, acid, alkali, etc.).
- Before soldering, be sure to preheat components.  
The preheating temperature should be set so that the temperature difference between the solder temperature and chip temperature does not exceed 150°C.
- Soldering corrections after mounting should be within the range of the conditions determined in the specifications.  
If overheated, a short circuit, performance deterioration, or lifespan shortening may occur.
- When embedding a printed circuit board where a chip is mounted to a set, be sure that residual stress is not given to the chip due to the overall distortion of the printed circuit board and partial distortion such as at screw tightening portions.
- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- Carefully lay out the coil for the circuit board design of the non-magnetic shield type.  
A malfunction may occur due to magnetic interference.
- Use a wrist band to discharge static electricity in your body through the grounding wire.
- Do not expose the products to magnets or magnetic fields.
- Do not use for a purpose outside of the contents regulated in the delivery specifications.
- The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.  
The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.  
If you intend to use the products in the applications listed below or if you have special requirements exceeding the range or conditions set forth in the each catalog, please contact us.

- (1) Aerospace/aviation equipment
- (2) Transportation equipment (cars, electric trains, ships, etc.)
- (3) Medical equipment
- (4) Power-generation control equipment
- (5) Atomic energy-related equipment
- (6) Seabed equipment
- (7) Transportation control equipment

- (8) Public information-processing equipment
- (9) Military equipment
- (10) Electric heating apparatus, burning equipment
- (11) Disaster prevention/crime prevention equipment
- (12) Safety equipment
- (13) Other applications that are not considered general-purpose applications

When designing your equipment even for general-purpose applications, you are kindly requested to take into consideration securing protection circuit/device or providing backup circuits in your equipment.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9