



Features

- High resistance to heat and humidity
- Resistance to mechanical shock and pressure
- Accurate dimensions for automatic surface mounting
- Wide impedance range

Applications

- Power supply lines
- IC power lines
- Signal lines

MG, MU, MZ Series High Impedance Chip Ferrite Beads

Electrical Specifications

Model Number	Impedance (Ω) at 100 MHz	RDC (Ω) Max.	IDC (mA) Max.
MU3261-300Y	30 $\pm$ 25 %	0.20	500
MU3261-600Y	60 $\pm$ 25 %	0.20	400
MU3261-750Y	75 $\pm$ 25 %	0.20	400
MU3261-101Y	100 $\pm$ 25 %	0.15	500
MU3261-121Y	120 $\pm$ 25 %	0.15	900
MG3261-151Y	150 $\pm$ 25 %	0.30	300
MU3261-221Y	220 $\pm$ 25 %	0.35	700
MG3261-301Y	300 $\pm$ 25 %	0.30	300
MU3261-301Y	300 $\pm$ 25 %	0.30	300
MU3261-471Y	470 $\pm$ 25 %	0.35	400
MU3261-601Y	600 $\pm$ 25 %	0.30	200
MZ3261-601Y	600 $\pm$ 25 %	0.30	200
MU3261-801Y	800 $\pm$ 25 %	0.60	300
MU3261-102Y	1000 $\pm$ 25 %	0.60	100
MU3261-122Y	1200 $\pm$ 25 % (at 50 MHz)	0.50	100
MU3261-152Y	1500 $\pm$ 25 % (at 50 MHz)	0.70	300
MU3261-202Y	2000 $\pm$ 25 % (at 30 MHz)	0.60	100
MG2029-100Y	10 $\pm$ 25 %	0.20	400
MG2029-300Y	30 $\pm$ 25 %	0.10	400
MG2029-400Y	40 $\pm$ 25 %	0.20	300
MU2029-600Y	60 $\pm$ 25 %	0.10	900
MG2029-800Y	80 $\pm$ 25 %	0.20	300
MG2029-101Y	100 $\pm$ 25 %	0.20	400
MG2029-121Y	120 $\pm$ 25 %	0.25	300
MU2029-151Y	150 $\pm$ 25 %	0.20	800
MU2029-221Y	220 $\pm$ 25 %	0.30	500
MU2029-301Y	300 $\pm$ 25 %	0.30	500
MU2029-471Y	470 $\pm$ 25 %	0.35	700
MZ2029-601Y	600 $\pm$ 25 %	0.40	100
MZ2029-601T	600 $\pm$ 25 %	0.40	200
MZ2029-102Y	1000 $\pm$ 25 %	0.45	100
MG1608-300Y	30 $\pm$ 25 %	0.20	200
MG1608-400Y	40 $\pm$ 25 %	0.30	300
MU1608-600Y	60 $\pm$ 25 %	0.20	700
MG1608-800Y	80 $\pm$ 25 %	0.30	300
MG1608-101Y	100 $\pm$ 25 %	0.25	200
MG1608-121Y	120 $\pm$ 25 %	0.30	200
MU1608-151Y	150 $\pm$ 25 %	0.25	600
MU1608-221Y	220 $\pm$ 25 %	0.30	200
MU1608-301Y	300 $\pm$ 25 %	0.35	150
MU1608-471Y	470 $\pm$ 25 %	0.45	350
MZ1608-601Y	600 $\pm$ 25 %	0.45	100
MZ1608-102Y	1000 $\pm$ 25 %	0.60	100
MU1005-100Y	10 $\pm$ 25 %	0.10	500
MU1005-300Y	30 $\pm$ 25 %	0.20	300
MU1005-600Y	60 $\pm$ 25 %	0.25	300
MU1005-121Y	120 $\pm$ 25 %	0.30	100
MU1005-151Y	150 $\pm$ 25 %	0.30	100
MU1005-221Y	220 $\pm$ 25 %	0.40	100
MU1005-241Y	240 $\pm$ 25 %	0.60	100
MU1005-301Y	300 $\pm$ 25 %	0.50	100
MU1005-471Y	470 $\pm$ 25 %	0.65	100
MU1005-601Y	600 $\pm$ 25 %	0.80	80
MU1005-102Y	1000 $\pm$ 25 %	1.20	80

General Specifications

Operating Temperature-55 °C to +125 °C
Storage Temperature ..-55 °C to +125 °C
Storage Condition+40 °C max. at 70 % RH
Reflow Soldering 230 °C, 50 seconds max.
Resistance to Soldering Heat 260 °C, 5 seconds
Rated Current Based on max. temperature rise of +40 °C
Terminal Strength
(Force "F" applied for 30 seconds)
3261 Series 1.0 F (Kg)
2029 Series 0.6 F (Kg)
1608 Series 0.5 F (Kg)

Materials


Core Material Ferrite
Internal Conductor Ag or Ag/Pd
Terminal Ag/Ni/Sn

MG, MU, MZ Series High Impedance Chip Ferrite Beads


BOURNS®

Electrical Specifications (continued)


MU 3261- 300Y




MU 3261- 600Y




MU 3261- 750Y




MU 3261- 101Y




MU 3261- 121Y




MG 3261- 151Y




MU 3261- 221Y



MG 3261- 301Y



MU 3261- 301Y




Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

MG, MU, MZ Series High Impedance Chip Ferrite Beads


BOURNS®

Electrical Specifications (continued)


MU 3261- 471Y




MU 3261- 601Y




MZ 3261- 601Y




MU 3261- 801Y




MU 3261- 102Y




MU 3261- 122Y




MU 3261- 152Y



MU 3261- 202Y



MG 2029- 100Y




Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

MG, MU, MZ Series High Impedance Chip Ferrite Beads


BOURNS®

Electrical Specifications (continued)


MG 2029- 300Y




MG 2029- 400Y




MU 2029- 600Y




MG 2029- 800Y




MG 2029- 101Y




MG 2029- 121Y




MU 2029- 151Y



MU 2029- 221Y



MU 2029- 301Y




Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

MG, MU, MZ Series High Impedance Chip Ferrite Beads


BOURNS®

Electrical Specifications (continued)


MU 2029- 471Y




MZ 2029- 601Y




MZ 2029- 102Y




MG 2029- 152Y




MG 2029- 202Y




MU 1608- 300Y




MG 1608- 400Y



MU 1608- 600Y



MG 1608- 800Y




Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

MG, MU, MZ Series High Impedance Chip Ferrite Beads


BOURNS®

Electrical Specifications (continued)


MU 1608- 101Y




MG 1608- 121Y




MU 1608- 151Y




MU 1608- 221Y




MU 1608- 301Y




MU 1608- 471Y




MZ 1608- 601Y



MZ 1608- 102Y



MG 1608- 152Y




MG, MU, MZ Series High Impedance Chip Ferrite Beads


BOURNS®

Electrical Specifications (continued)


MZ 1608- 222Y




MU 1005- 100Y




MU 1005- 300Y




MU 1005- 600Y




MU 1005- 121Y




MU 1005- 151Y




MU 1005- 221Y



MU 1005- 241Y



MU 1005- 301Y




Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications.

MG, MU, MZ Series High Impedance Chip Ferrite Beads


BOURNS®

Electrical Specifications (continued)


MU 1005- 471Y




MU 1005- 601Y




MU 1005- 102Y



Product Dimensions



Recommended Land Pattern




Series	A	B	C	D	G	H	I
3261	$\frac{3.2 \pm 0.2}{(.126 \pm .008)}$	$\frac{1.6 \pm 0.2}{(.063 \pm .008)}$	$\frac{1.1 \pm 0.2}{(.043 \pm .008)}$	$\frac{0.5 \pm 0.2}{(.020 \pm .008)}$	$\frac{2.0}{(.079)}$	$\frac{1.4}{(.053)}$	$\frac{1.1}{(.043)}$
2029	$\frac{2.0 \pm 0.2}{(.079 \pm .008)}$	$\frac{1.2 \pm 0.2}{(.047 \pm .008)}$	$\frac{0.9 \pm 0.2}{(.035 \pm .008)}$	$\frac{0.5 \pm 0.2}{(.020 \pm .008)}$	$\frac{1.0}{(.040)}$	$\frac{1.0}{(.040)}$	$\frac{1.0}{(.040)}$
1608	$\frac{1.6 \pm 0.2}{(.063 \pm .008)}$	$\frac{0.8 \pm 0.2}{(.031 \pm .008)}$	$\frac{0.8 \pm 0.2}{(.031 \pm .008)}$	$\frac{0.5 \pm 0.2}{(.020 \pm .008)}$	$\frac{0.7}{(.028)}$	$\frac{0.7}{(.028)}$	$\frac{0.7}{(.028)}$
1005	$\frac{1.0 \pm 0.10}{(.04 \pm .004)}$	$\frac{0.50 \pm 0.10}{(.02 \pm .004)}$	$\frac{0.50 \pm 0.10}{(.02 \pm .004)}$	$\frac{0.25 \pm 0.10}{(.01 \pm .004)}$	$\frac{0.5}{(.02)}$	$\frac{0.55}{(.022)}$	$\frac{0.7}{(.028)}$

MG, MU, MZ Series High Impedance Chip Ferrite Beads


BOURNS®

Reel Dimensions




Series	Pcs. per Reel	Gross Weight (g)	D	G	T
3261	3,000	150	$\frac{8.0}{(.315)}$	$\frac{10.0 +0}{(.394 +0)}$	$\frac{12.5}{(.492)}$
2029	4,000	120			
1608	4,000	90			
1005	10,000	135			

Equivalent Circuit



Recommended Soldering



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9