

Technical Data Sheet

RRC-SCC-EZP – Battery Charger



5 Watt Desktop Battery Charger for Varta EasyPack batteries S, L, XL and PLUS

Features:

- Single bay charger
- For the standard Varta EasyPack batteries S, L, XL and PLUS
- Simple operation – Plug and Play
- External wall plug power supply for worldwide use

Applications:

- Charging station for VARTA EasyPack battery packs for mobile devices used in industry and customer areas

Specification RRC-SCC-EZP

Input	
Voltage	5V nom.
Current	1000mA nom.
Power	5W

Output	
Voltage	4.2VDC
Volt. tolerance ⁽¹⁾	±1 % max.
Current max.	1A max. for EZPack L, XL, PLUS 0.5A max. for the EZPack S
Protection	Short circuit Battery over/under temperature Charger over temperature Charge timer

Environmental	
Cooling	convection cooled
Temperature	Operating: 0°C to 40°C Non-operating -10°C to 70°C
Pressure & Altitude	Operating: 1060hPa to 795hPa -382m to 2000m Non-operating: 1060hPa to 572hPa -382m to 4570m
Humidity	5% to 95% r.H., non-condensing

General	
Indicator	Multi-color LED (green, red, orange)
Battery types	EZPack S, EZPack L, EZPack XL, EZPack PLUS
Energy Efficiency	CEC, DoE
Green procurement	RoHS 2011/65/EU WEEE 2012/19/EU

LED Indications	
Orange light	The inserted battery is currently being charged.
Green light	The battery is charged and can be removed for use.
Red blinking	Battery detection phase
Red light	No battery inserted, battery over/under temperature-, charger over temperature-, battery over voltage-, battery charge timer time-out-error or input voltage too low

Charger Mechanical Details	
Housing dimensions (LxWxH)	46.7 x 101.4 x 12.5mm
Weight	26g (without power supply)

Notes:

1. Total regulation tolerance includes initial set accuracy, line and load regulation

Technical Data Sheet

RRC-SCC-EZP – Battery Charger



Safety & EMC			In combination with the specified external AC/DC power supply
Regulatory approvals	Europe	CE	
Electromagnetic Emissions	Europe	EN55032 class B + CISPR32 class B	
	USA	FCC15 class B	
Electromagnetic Immunity	ESD immunity	EN/IEC61000-4-2	
	Electromagnetic field immunity	EN/IEC61000-4-3	
	EFT / Burst	EN/IEC61000-4-4	
	Surge	EN/IEC61000-4-5	
	Conducted Immunity	EN/IEC61000-4-6	
	Magnetic Fields	EN/IEC61000-4-8 + -4-11	

Specification external AC/DC power supply

Input		Output	
Voltage range	100 - 240VAC	Voltage	5VDC $\pm$ 0.25V
Current	0.35A max.	Power	5W max.
Stand by power	< 0.1W @115VAC and 230 VAC	Current range	0 - 1A
		Protection	Over voltage, over current, Short circuit

Environmental		General	
Temperature	Operating: -10°C to 40°C Storage: -20°C to 70°C	Efficiency	California's Energy Efficiency Level VI
Humidity	Operating: 10% to 90% Storage: 5% to 95%	Lifetime	30000 hours min (acc. to MIL-HDBK-217F)
		Ripple & Noise	120mV max.
		Green procurement	RoHS2011/65/EU

Power Supply Mechanical Details	
Standard output connector	USB Micro 5pin
Standard input connector	Wall mount type EU, USA, AUS and UK
Housing dimensions (LxWxH)	54.8 x 29.45 x 44.9mm (without wall-mount plug)
Weight	45g $\pm$ 10g

Safety & EMC & Approvals		
Approvals	Europe	CE
	International	CB
	USA/Canada	cETLus
	Australia	SAA

Germany/Headquarters	USA	Hong Kong	China
RRC power solutions GmbH Technologiepark 1 D-66424 Homburg / Saar	RRC power solutions Inc. 18340 Yorba Linda Blvd., Suite 107-437 Yorba Linda, CA 92886-4104	RRC power solutions Ltd. S-V,6/F, Valiant Industrial Centre 2-12 Au Pui Wan Street Fo Tan, N.T., Hong Kong	RRC power solutions Ltd. Room 520, Yuanlin Building, Aiguo Road No. 3066, Luohu District, Shenzhen 518021
Tel.: +49 6841 98090 Fax: +49 6841 9809280 Email: sales@rrc-ps.de Web: www.rrc-ps.de	Tel.: +1 714 777 3604 Fax: +1 714 777 3658 Email: usa@rrc-ps.com Web: www.rrc-ps.com	Tel.: +852 2376 0106 Fax: +852 2375 0107 Email: hkrrc@rrc-ps.cn Web: www.rrc-ps.com	Tel.: +86 755 8374 1908 Fax: +86 755 8374 1861 Email: hkrrc@rrc-ps.cn Web: www.rrc-ps.com

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9