

Series: SMD Helical Antenna

Description: 860-930MHz Embedded Helical Antenna

PART NUMBER: W3136



Features:

- 860-930MHz
- Impedance 50 Ohm
- Plastic support helical antenna
- Length 29.5mm,
- Gain 2dBi
- SMD Mounting on PCB
- RoHS Compliant


Applications:

- 868MHz and 915MHz ISM Band Systems
- IoT systems
- Metering, Automation
- Security, surveillance
- · Remote controls, toys

All dimensions are in mm / inches

Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



For more information: Pulse Worldwide Headquarters

15255 Innovation Drive #100 San Diego, CA 92128 USA Tel:1-858-674-8100 Pulse/Larsen Antennas 18110 SE 34th St Bldg 2 Suite 250 Vancouver, WA 98683 USA Tel: 1-360-944-7551 Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0 Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



1





Series: SMD Helical Antenna

PART NUMBER: W3136

ELECTRICAL SPECIFICATIONS

| Antenna Type | Helical monopole |
|--------------------|------------------|
| Frequency | 860-930MHz |
| Nominal Impedance | 50 Ω |
| VSWR | Max 2.5 |
| Radiation Pattern | Omni |
| Gain | 2 dBi |
| Efficiency | 65% |
| Polarization | Linear |
| Power Withstanding | 2W |
| | |

| MECHANICAL SPECIFICATIONS | | | | | |
|------------------------------|-------------------------|--|--|--|--|
| Overall Length | 29.5mm | | | | |
| Weight | 2.52g | | | | |
| Antenna Color / Material | White | | | | |
| Fix system | SMD+Glue | | | | |
| Recommended Glue | Resinlab EP1320LV Black | | | | |
| Solder Paste Thickness | Min 0.15mm | | | | |
| MSL | 3 | | | | |
| ENVIRONMENTAL SPECIFICATIONS | | | | | |
| Operating Temperature | -40° C~+85° C | | | | |
| Storage Temperature | -40° C~+85° C | | | | |
| RoHS Compliant | Yes | | | | |

OTHER SPECIFICATIONS

Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION




2





Series: SMD Helical Antenna

PART NUMBER: W3136



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

ROHS 3






Series: SMD Helical Antenna

PART NUMBER: W3136

FIX SYSTEM RECOMMENDATION

Fix system

- 1. SMD process
- 2. Solder paste thickness: minimum 0.15mm
- 3. Glue is required, Recommended Glue: Resinlab EP1320LV Black, usage and position see below recommended area.



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION








Description: 860-930MHz Embedded Helical Antenna

PART NUMBER: W3136

FIX SYSTEM RECOMMENDATION

Fix system

1. Glue position on PCB for recommendation



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION




5



Description: 860-930MHz Embedded Helical Antenna

Series: SMD Helical Antenna

PART NUMBER: W3136



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



6




Series: SMD Helical Antenna

Description: 860-930MHz Embedded Helical Antenna

PART NUMBER: W3136

TEST SETUP

PWB Layout for W3136 SMD Helical Antenna



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION








Series: SMD Helical Antenna

Description: 860-930MHz Embedded Helical Antenna

PART NUMBER: W3136

TEST SETUP

PWB ground clearance area (Top):40x9.5mm PWB ground clearance area (Bottom):40x9.5mm



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



Pulse LARSEN Antennas


Series: SMD Helical Antenna

Description: 860-930MHz Embedded Helical Antenna

PART NUMBER: W3136

TEST SETUP

PWB Pad dimension in top copper



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



9






Series: SMD Helical Antenna


Description: 860-930MHz Embedded Helical Antenna

PART NUMBER: W3136

TEST SETUP

PWB Layout, Pulse PWB size:121x40mm, Thickness 1.0mm, other size boards can be used depending on customer size.





Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION






Series: SMD Helical Antenna

Description: 860-930MHz Embedded Helical Antenna

PART NUMBER: W3136

TEST SETUP

PWB Layout, Pulse PWB size:121x40mm, Thickness 1.0mm, other size boards can be used depending on customer size.



Note : Exact matching and tuning components value depend on application , board size ,cover etc.



In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

Issue: 1943




Series: SMD Helical Antenna

Description: 860-930MHz Embedded Helical Antenna

PART NUMBER: W3136

CHARTS

Measured on the 121x40mm test board with tuning and matching circuit



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

ROHS 12






Series: SMD Helical Antenna

PART NUMBER: W3136

TEST SETUP

Measured on the 121x40mm test board with tuning and matching circuit.

Test in PSU China Chamber.



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION






Description: 860-930MHz Embedded Helical Antenna

Series: SMD Helical Antenna

PART NUMBER: W3136

CHARTS



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

ROHS 14




Description: 860-930MHz Embedded Helical Antenna

Series: SMD Helical Antenna

PART NUMBER: W3136

CHARTS



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION

ROHS 15




Series: SMD Helical Antenna

Description: 860-930MHz Embedded Helical Antenna

PART NUMBER: W3136

CHARTS

Typical radiation pattern in free space



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION






Series: SMD Helical Antenna

Description: 860-930MHz Embedded Helical Antenna

PART NUMBER: W3136

CHARTS

Typical radiation pattern in free space



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



17




Series: SMD Helical Antenna

Description: 860-930MHz Embedded Helical Antenna

PART NUMBER: W3136

CHARTS

Typical radiation pattern in free space



Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION





Series: SMD Helical Antenna

Description: 860-930MHz Embedded Helical Antenna

PART NUMBER: W3136

Recommendation for reflow soldering process

Printing stencil thickness 0,15 - 0,25 mm is recommended for the solder paste. The maximum soldering temperature should not exceed 260°C. The temperature profile recommendations for reflow soldering process is presented in the Figures 1 and 2. The reflow profile presented in figure 1 describes minimum reflow temperatures. The reflow profile presented in figure 2 describes maximum reflow temperatures. located at the center of the coverage area.

| | Method of heat transfer | Controlled hot air convection |
|---|--|-------------------------------|
| 1 | Average temperature gradient in preheating | 2.5 °C/s |
| 2 | Soak time | 2-3 minutes |
| 3 | Max temperature gradient in reflow | 3 °C/s |
| 4 | Time above 217 °C | Max 30 sec |
| 5 | Peak temperature in reflow | 230 °C for 10 seconds |
| 6 | Temperature gradient in cooling | Max -5 °C/s |




Figure 1. Minimum temperature profile recommendation for reflow soldering process

Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION





Series: SMD Helical Antenna

PART NUMBER: W3136

Recommendation for reflow soldering process

| | Method of heat transfer | Controlled hot air convection |
|---|--|-------------------------------|
| 1 | Average temperature gradient in preheating | 2.5 °C/s |
| 2 | Soak time | 2-3 minutes |
| 3 | Max temperature gradient in reflow | 3 °C/s |
| 4 | Time above 217 °C | Max 60 sec |
| Б | Time above 230 °C | Max 50 sec |
| 6 | Time above 250 °C | Max 10 sec |
| 7 | Peak temperature in reflow | 260 ℃ for 5 seconds |
| 8 | Temperature gradient in cooling | Max -5 °C/s |




Figure 2. Maximum temperature profile recommendation for reflow soldering process

Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION


ROHS 20



Series: SMD Helical Antenna

PART NUMBER: W3136

PACKAGING



Reel Size: 330MM[13INCH] Total 2 PCS Reel In Package Box Package Box Size:350x350x120mm

Issue: 1943

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION







Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.З, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж: moschip.ru moschip.ru_4

moschip.ru_6 moschip.ru_9