

# E3ZM-B

## Excellent PET Bottle Detection

- New detection method that is independent of bottle shape, position, and contents.
- Automatic compensation against effects of contamination and temperature (except E3ZM-B□T).
- Product lineup includes models with adjuster (E3ZM-B□T).
- Detects transparent objects made by PET, resin, and glass.



Refer to *Safety Precautions* on page 10.


## Features

**Industry Top** P-opaquisting and a Coaxial Optical System Eliminate Dependence on the Bottle's Shape, Position, Transparency, and Contents.

**P-opaquisting: Polarization-opaquisting**

**Patented** (Refer to page 9 for a technical description.)

The E3ZM-B more than triples conventional detection performance, with outstanding stability.



\*Depending on the shape and position of the PET bottle.

**Industry Top** AC<sup>3</sup> Function Automatically Compensates Effects of Soiling and Temperature

**AC<sup>3</sup>: Auto Compensation Control for Contamination**

**Patented** (Refer to page 9 for a technical description.)

Parameters require resetting when static electricity causes dust to adhere to the surface of the Sensor or Reflector, or when the light emission power drops due to temperature- or time-related changes. Original OMRON light emission control technology greatly reduces the resetting work involved.



Initial Condition . . . Contamination . . . Auto Compensation

## Teaching with No Workpiece Required -- Quick and Easy Setting

There is no need for delicate sensitivity adjustments. Simply adjust the optical axes of the Sensor and Reflector, then press the Teaching button twice. This high-reliability design eliminates worries about variations in the sensitivity settings of different operators.




## Industry Top IP69K Degree of Protection with an SUS316L Housing

The housing is constructed of corrosion-resistant SUS316L, and the display cover is PES (polyethersulfone). Both materials are highly resistant to the effects of detergents and disinfectants. IP69K degree of protection also allows the E3ZM-B to withstand washing with high-temperature, high-pressure water. This makes the E3ZM-B well suited to use in sites requiring a high level of hygiene.



## A Wide Ambient Temperature Range of -40 to 60°C

This wide temperature range meets the needs of the many and diverse applications in the beverage industry.



## Applications





**Detecting Plastic Bottles**

### Precautions for Correct Use

The E3ZM-B□1/-B□6 are not applicable for detecting transparent objects that exhibit no birefringence, such as glass bottles. Transparent objects made of resin also exhibit little birefringence, and cannot be detected with complete stability. Check the detection stability of objects such as these prior to actual operation.

## Ordering Information

Sensors [Refer to *Dimensions* on page 12.]
 Red light

| Sensing method                    | Appearance  | Sensitivity adjustment | Connection method      | Sensing distance  | Model             |                  |                |               |
|-----------------------------------|---|------------------------|------------------------|---|-------------------|------------------|----------------|---------------|
|                                   |   |                        |                        |   | Special reflector | NPN output       | PNP output     |               |
| Retroreflective with MSR function |  | Teaching type          | Pre-wired (2 m) *2     |  | Order separately  | E3ZM-B61 2M      | E3ZM-B81 2M    |               |
|                                   |   |                        | Connector (M8, 4 pins) |   |                   | E3ZM-B66         | E3ZM-B86       |               |
|                                   |   |                        | Pre-wired (2 m) *2     |   |                   | Included         | E3ZM-B61-C 2M  | E3ZM-B81-C 2M |
|                                   |   |                        | Connector (M8, 4 pins) |   |                   |                  | E3ZM-B66-C     | E3ZM-B86-C    |
|                                   |   |                        | Pre-wired (2 m)        |   |                   | Order separately | E3ZM-B61T 2M   | E3ZM-B81T 2M  |
|                                   |   |                        | Connector (M8, 4 pins) |   |                   |                  | E3ZM-B66T      | E3ZM-B86T     |
|                                   |   | One-turn adjuster type | Pre-wired (2 m)        |   | Included          | E3ZM-B61T-C 2M   | E3ZM-B81T-C 2M |               |
|                                   |   |                        | Connector (M8, 4 pins) |   |                   | E3ZM-B66T-C      | E3ZM-B86T-C    |               |




\*1. Values in parentheses indicate the minimum required distance between the Sensor and Reflector.

\*2. Models with a 5-m pre-wired cable are also available. When ordering, add the cable length to the end of the model number (e.g., E3ZM-B61 5M).

## Accessories

Special Retroreflective Reflector (A Reflector is provided depending on the model number. Check the model number in the remarks column.)

[Refer to *Dimensions* on page 12.]










| Name                         | Model    | Sensing distance (rated)  |                      | Quantity | Remarks   |
|------------------------------|----------|---|----------------------|----------|---|
|                              |          | E3ZM-B□□1(T)/-B□□6(T)   |                      |          |   |
| Special Polarizing Reflector | E39-RP1  |  | 500 mm<br>[100 mm] * | 1        | A Reflector is provided with the E3ZM-B□□□(T)-C. A Reflector is not provided with the Sensor. |
|                              | E39-RSP1 |  | 250 mm<br>[0 mm] *   | 1        | A Reflector is not provided with the Sensor. The MSR function is enabled.                     |
|                              | E39-RP37 |  | 250 mm<br>[0 mm] *   | 1        | A Reflector is not provided with the Sensor. The MSR function is enabled.                     |

Note: Previous OMRON Retroreflective Reflectors (E39-R1/-R1S/-R2/-R3/-R9/-R10/-R1K/-RS1/-RS2/-RS3, etc.) cannot be used with the E3ZM-B.

\*Values in parentheses indicate the minimum required distance between the Sensor and Reflector.

**Mounting Brackets** A Mounting Bracket is not provided with the Sensor. Order a Mounting Bracket separately if required.



[Refer to *Dimensions* on E39-L/F39-L/E39-S/E39-R, E39-L□.]

| Appearance   | Model                       | Quantity | Remarks                               | Appearance   | Model                       | Quantity | Remarks  |
|--|-----------------------------|----------|---------------------------------------|--|-----------------------------|----------|--|
|   | <b>E39-L153</b><br>(SUS304) | 1        | Mounting Brackets                     |   | <b>E39-L98</b><br>(SUS304)  | 1        | Metal Protective Cover Bracket *   |
|   | <b>E39-L104</b><br>(SUS304) | 1        |                                       |   | <b>E39-L150</b><br>(SUS304) | 1 set    | (Sensor adjuster)<br>Easily mounted to the aluminum frame rails of conveyors and easily adjusted.<br>For vertical angle adjustment |
|   | <b>E39-L43</b><br>(SUS304)  | 1        | Horizontal Mounting Bracket *         |   | <b>E39-L151</b><br>(SUS304) | 1 set    | Easily mounted to the aluminum frame rails of conveyors and easily adjusted.<br>For vertical angle adjustment                      |
|   | <b>E39-L142</b><br>(SUS304) | 1        | Horizontal Protective Cover Bracket * |  |                             |          |  |
|  | <b>E39-L44</b><br>(SUS304)  | 1        | Rear Mounting Bracket                 |  | <b>E39-L144</b><br>(SUS304) | 1        | Compact Protective Cover Bracket *   |

\*Cannot be used for Standard Connector models.

**Sensor I/O Connectors** (Models for Connectors: A Connector is not provided with the Sensor. Be sure to order a Connector separately.)

[Refer to *Dimensions* on XS3.]

| Size        | Specifications | Appearance   | Cable | Model  |                        |
|-------------|----------------|--|-------|--------|------------------------|
| M8 (4 pins) | Standard       | Straight *1     | 2 m   | 4-wire | <b>XS3F-E421-402-A</b> |
|             |                |  | 5 m   |        | <b>XS3F-E421-405-A</b> |
|             |                | L-shaped *1 *2  | 2 m   |        | <b>XS3F-E422-402-A</b> |
|             |                |  | 5 m   |        | <b>XS3F-E422-405-A</b> |

Note: The outer cover of the cable is made of PVC (polyvinyl chloride), the nut is made of SUS316L stainless steel, and the degree of protection is IP67 (IEC 60529).

When high-pressure washing will be used, select an I/O Connector that has IP69K degree of protection.

\*1. The connector will not rotate after connecting.

\*2. The cable is fixed at an angle of 180° from the sensor emitter/receiver surface.

## Ratings and Specifications

| Sensing method            |            | Retroreflective with P-opaquing (*1) and MSR functions  |                                    |
|---------------------------|------------|---|------------------------------------|
| Model                     | NPN output | E3ZM-B61(-C)/-B66(-C)   | E3ZM-B61T(-C)/-B66T(-C) (*2)       |
| Item                      | PNP output | E3ZM-B81(-C)/-B86(-C)   | E3ZM-B81T(-C)/-B86T(-C) (*2)       |
| Sensing distance          |            | 100 to 500 mm (Using E39-RP1)   |                                    |
| Standard sensing object   |            | 500-ml, transparent, round PET bottle (65-mm dia.)  |                                    |
| Directional angle         |            | Sensor: 3° to 10°<br>Reflector: 30°   |                                    |
| Light source (wavelength) |            | Red LED (650 nm)  |                                    |
| Power supply voltage      |            | 10 to 30 VDC, including 10% ripple (p-p)  |                                    |
| Current consumption       |            | 450 mW max. (current consumption for a 30-V power supply voltage: 15 mA max.)   |                                    |
| Control output            |            | Load power supply voltage: 30 VDC max., Load current: 100 mA max. (Residual voltage: 2 V max.)<br>Open-collector output (NPN/PNP output depending on model) |                                    |
| Operation mode            |            | Light ON/Dark ON cable switch selectable  | Light ON/Dark ON switch selectable |
| Protection circuits       |            | Reversed power supply polarity, Load short-circuit protection, Mutual interference prevention, and Reversed output polarity protection                      |                                    |
| Response time             |            | Operate or reset: 1 ms max.   |                                    |
| Sensitivity adjustment    |            | Teaching method   | One-turn adjuster                  |
| Ambient illumination      |            | Incandescent lamp: 3,000 lx max., Sunlight: 10,000 lx max.  |                                    |
| Ambient temperature range |            | Operating: -40 to 60°C (*3), Storage: -40 to 70°C (with no icing or condensation)   |                                    |
| Ambient humidity range    |            | Operating: 35% to 85%, Storage: 35% to 95% (with no condensation)   |                                    |
| Insulation resistance     |            | 20 MΩ min. at 500 VDC   |                                    |
| Dielectric strength       |            | 1,000 VAC, 50/60 Hz for 1 min   |                                    |
| Vibration resistance      |            | Destruction: 10 to 55 Hz, 1.5-mm double amplitude for 2 hours each in X, Y, and Z directions  |                                    |
| Shock resistance          |            | Destruction: 500 m/s <sup>2</sup> 3 times each in X, Y, and Z directions  |                                    |
| Degree of protection *4   |            | IEC IP67, DIN 40050-9: IP69K  |                                    |
| Connection method         |            | Pre-wired cable (standard length: 2 m) or M8 4-pin connector  |                                    |
| Indicators                |            | Operation indicator (yellow), Stability indicator (green), and Teaching indicator (red)   |                                    |
| Weight (packed state)     |            | Pre-wired models: Approx. 85 g<br>Connector models: Approx. 35 g  |                                    |
| Materials                 | Housing    | SUS316L   |                                    |
|                           | Lens       | PMMA (polymethylmethacrylate)   |                                    |
|                           | Indication | PES (polyethersulfone)  |                                    |
|                           | Buttons    | Fluoro rubber   |                                    |
|                           | Cable      | PVC (polyvinyl chloride)  |                                    |
| Accessories *5            |            | Instruction sheet, Special Reflector (E3ZM-B□□-C only)  |                                    |

\*1. For information on the P-opaquing function, refer to → pages 1 and 9.

\*2. If a sensing object such as a glass plate is being used, the light reception level may not be attenuated sufficiently.

In the following cases, be sure to test operation sufficiently under actual operating conditions.

1) If the temperature varies more than 5°C

2) If the Sensor or Reflector moves due to vibration


\*3. Do not bend the cable in temperatures of -25°C or lower.

\*4. IP69K Degree of Protection Specification

IP69K is a protection standard against high temperature and high-pressure water defined in the German standard DIN 40050, Part 9. The test piece is sprayed with water at 80°C at a water pressure of 80 to 100 BAR using a specified nozzle shape at a rate of 14 to 16 liters/min.


The distance between the test piece and nozzle is 10 to 15 cm, and water is sprayed horizontally for 30 seconds each at 0°, 30°, 60°, and 90° while rotating the test piece on a horizontal plane.

\*5. Mounting Brackets must be ordered separately.




Engineering Data (Typical)


Parallel Operating Range (Horizontal)  
 E3ZM-B□1/B□6 +  
 E39-RP1 (Special Reflector)



Parallel Operating Range (Vertical)  
 E3ZM-B□1/B□6 +  
 E39-RP1 (Special Reflector)




Excess Gain vs. Distance  
 E3ZM-B□1/B□6 +  
 E39-RP1 (Special Reflector)




Note: The AC<sup>3</sup> function controls the excess gain ratio to be a constant multiple of 2.

Dark Excess Gain vs. Sensing Object Characteristics



Dark Excess Gain vs. Position



## I/O Circuit Diagrams

### NPN Output


| Model                  | Operation mode | Timing charts | Operation selector switch                             | Output circuit |
|------------------------|----------------|---------------|---|----------------|
| E3ZM-B61<br>E3ZM-B66   | Light ON       |               | Connect pink lead (2) to brown lead (1).              |                |
|                        | Dark ON        |               | Connect pink lead (2) to blue lead (3) or leave open. |                |
| E3ZM-B61T<br>E3ZM-B66T | Light ON       |               | L side (LIGHT ON)                                     |                |
|                        | Dark ON        |               | D side (DARK ON)                                      |                |

### PNP Output

| Model                  | Operation mode | Timing charts | Operation selector switch                             | Output circuit |
|------------------------|----------------|---------------|---|----------------|
| E3ZM-B81<br>E3ZM-B86   | Light ON       |               | Connect pink lead (2) to brown lead (1).              |                |
|                        | Dark ON        |               | Connect pink lead (2) to blue lead (3) or leave open. |                |
| E3ZM-B81T<br>E3ZM-B86T | Light ON       |               | L side (LIGHT ON)                                     |                |
|                        | Dark ON        |               | D side (DARK ON)                                      |                |

### Plugs (Sensor I/O Connectors)

#### M8 4-pin Connectors



XS3F-E421-402-A XS3F-E422-402-A  
XS3F-E421-405-A XS3F-E422-405-A

| Classification | Wire color | Connector pin No. | Application           |
|----------------|------------|-------------------|-----------------------|
| DC             | Brown      | 1                 | Power supply (+V)     |
|                | White      | 2                 | Operation selection * |
|                | Blue       | 3                 | Power supply (0 V)    |
|                | Black      | 4                 | Output                |


Note: The above M8 Connectors made by OMRON are IP67. Do not use them in an environment where IP69K is required.

\*Not available on the E3ZM-B□□T.

Nomenclature


Teaching Models

E3ZM-B□



One-turn Adjuster Models

E3ZM-B□T




Note: When the Sensor is first unpacked and used, the teaching indicator (red) will flash slowly to show that teaching has not yet been done. This does not indicate a malfunction. Use the following procedure to conduct teaching.

Teaching Method

**1. Install the Sensor and Reflector and adjust the optical axis** (without placing a Sensing objects between them). Then press and hold the TEACH button for at least 2 seconds.

The teaching indicator (red) will start flashing quickly. Perform the following operation within 7 seconds after first starting to press the TEACH button. (After 7 seconds, the Unit will return to its initial condition.)




The stability indicator (green) and operation indicator (yellow) will retain their lit or OFF status, and the teaching indicator (red) will flash.

**2. Press the TEACH button again.** Teaching will then begin. The teaching indicator (red) will remain lit during the teaching operation.




When Teaching Is Successful

The teaching indicator (red) will go out. The Unit will then enter normal operating condition.




When Teaching Is Not Successful

The teaching indicator (red) will flash slowly or quickly.



The teaching indicator (red) will then begin flashing even more slowly, indicating that the teaching operation should begin.



Repeat the operation starting with step 1.

Note: Depending on the amount of light received, the operation indicator and stability indicator may also change during the teaching operation.




## Technical Descriptions

### New Technology for Detecting Transparent Objects Exhibiting Birefringence **Patented** **P-opaquing (Polarization-opaquing)**

Conventional photoelectric sensors for detecting PET bottles depend on refraction due to the bottle's shape or on the attenuation of light intensity caused by surface reflection. However, it is difficult to attain a sufficient level of excess gain with these methods.


The E3ZM-B utilizes the birefringent (double refraction) property of PET bottles to dramatically increase the level of excess gain. The polarization component that is disturbed by the PET bottles as they pass along the line is cut by a special and unique OMRON polarization filter. This greatly lowers the intensity of the light received to provide stable detection with simple sensitivity adjustment.

“P-opaquing” is a word that was coined to refer to the process of applying polarization in order to opaque transparent objects that exhibit the property of birefringence.



The excess gain of the E3ZM-B is doubled for both light-ON and dark-ON applications.

The excellent stability of the E3ZM-B prevents malfunctions from occurring even if something causes the intensity of light received to fluctuate by  $\pm 50\%$ .




### New Technology for Achieving Long-term Stability **Patented** **AC<sup>3</sup> (AC cube: Auto Compensation Control for Contamination)** (Not available on the E3ZM-B□T)

Conventional photoelectric sensors with built-in amplifiers are not equipped with functions to compensate for changes in the intensity of light received caused by dust and other lens-soiling matter, ambient temperature, and changes that occur in the LED over time. This makes it comparatively difficult to achieve long-term, stable detection of objects that exhibit little change in the intensity of light received, such as transparent objects.

The AC<sup>3</sup> (AC cube) function provided on the E3ZM-B periodically feeds the intensity of light received during light-ON operation back to the light-emitting circuit, to keep the intensity equal to the value set by teaching.

This allows the E3ZM-B to attain long-term, stable detection while helping to cut down on maintenance requirements and improve the equipment operating ratio.

Note: The AC<sup>3</sup> function cannot be used for dark-ON operation.



Intensity of light received is compensated every 30 s.  
 E3ZM-B

## Safety Precautions

Refer to *Warranty and Limitations of Liability*.

### WARNING

This product is not designed or rated for directly or indirectly ensuring safety of persons.

Do not use it for such a purpose.



### CAUTION

Do not use the product with voltage in excess of the rated voltage.

Excess voltage may result in malfunction or fire.



Never use the product with an AC power supply.

Otherwise, explosion may result.



When cleaning the product, do not apply a high-pressure spray of water to one part of the product. Otherwise, parts may become damaged and the degree of protection may be degraded.



### Precautions for Safe Use

The following precautions must be observed to ensure safe operation of the Sensor.

#### Operating Environment

Do not use the Sensor in an environment where explosive or flammable gas is present.

#### Connecting Connectors

Be sure to hold the connector cover when inserting or removing the connector.

When using an XS3F Connector, be sure to tighten the connector lock by hand; do not use pliers or other tools. If the tightening is insufficient, the degree of protection will not be maintained and the Sensor may become loose due to vibration. The appropriate tightening torque is 0.3 to 0.4 N·m. When using another, commercially available connector, follow the usage and tightening torque instructions provided by the manufacturer.

#### Load

Do not use a load that exceeds the rated load.

#### Low-temperature Environments

Do not touch the metal surface with your bare hands when the temperature is low. Touching the surface may result in a cold burn.

#### Oily Environments

Do not use the Sensor in oily environments. They may damage parts and reduce the degree of protection.

#### Modifications

Do not attempt to disassemble, repair, or modify the Sensor.

#### Outdoor Use

Do not use the Sensor in locations subject to direct sunlight.

#### Cleaning

Do not use thinner, alcohol, or other organic solvents. Otherwise, the optical properties and degree of protection may be degraded.

#### Cleaning

Do not use highly concentrated cleaning agents. Otherwise, malfunction may result. Also, do not use high-pressure water with a level of pressure that exceeds the stipulated level. Otherwise, the degree of protection may be reduced.

#### Surface Temperature

Burn injury may occur. The Sensor surface temperature rises depending on application conditions, such as the ambient temperature and the power supply voltage. Use caution when operating or performing maintenance on the Sensor.

#### Cable Bending

Do not bend the cable in temperatures of  $-25^{\circ}\text{C}$  or below. Otherwise, the cable may be damaged.

### Precautions for Correct Use

Do not use the Sensor in any atmosphere or environment that exceeds the ratings.

**Do not install the Sensor in the following locations.**

- (1) Locations subject to direct sunlight
- (2) Locations subject to condensation due to high humidity
- (3) Locations subject to corrosive gas
- (4) Locations where the Sensor may receive direct vibration or shock

### Connecting and Mounting

- (1) The maximum power supply voltage is 30 VDC. Before turning the power ON, make sure that the power supply voltage does not exceed the maximum voltage.
- (2) Laying Sensor wiring in the same conduit or duct as high-voltage wires or power lines may result in malfunction or damage due to induction. As a general rule, wire the Sensor in a separate conduit or use shielded cable.
- (3) Use an extension cable with a minimum thickness of 0.3 mm<sup>2</sup> and less than 100 m long.
- (4) Do not pull on the cable with excessive force.
- (5) Pounding the Photoelectric Sensor with a hammer or other tool during mounting will impair water resistance. Also, use M3 screws.
- (6) Mount the Sensor either using the bracket (order separately) or on a flat surface.
- (7) Be sure to turn OFF the power supply before inserting or removing the connector.

### Power Supply

If a commercial switching regulator is used, ground the FG (frame ground) terminal.

### Power Supply Reset Time

The Sensor will be able to detect objects 100 ms after the power supply is turned ON. Start using the Sensor 100 ms or more after turning ON the power supply. If the load and the Sensor are connected to separate power supplies, be sure to turn ON the Sensor first.

### Turning OFF the Power Supply

Output pulses may be generated even when the power supply is OFF. Therefore, it is recommended to first turn OFF the power supply for the load or the load line.

### Load Short-circuit Protection


This Sensor is equipped with load short-circuit protection, but be sure to not short circuit the load. Be sure to not use an output current flow that exceeds the rated current. If a load short circuit occurs, the output will turn OFF, so check the wiring before turning ON the power supply again. The short-circuit protection circuit will be reset. The load short-circuit protection will operate when the current flow reaches 1.8 times the rated load current. When using a capacitive load, use an inrush current of 1.8 times the rated load current or lower.

### Water Resistance

Do not use the Sensor in water, rainfall, or outdoors.

**When disposing of the Sensor, treat it as industrial waste.**

### Mounting Diagram



### Resistance to Detergents, Disinfectants, and Chemicals

- The Sensor will maintain sufficient performance in typical detergents and disinfectants, but performance may suffer in some types of detergents, disinfectants, and chemicals. Refer to the following table prior to use.
- The E3ZM has passed detergent and disinfectant resistance testing for the substances listed in the following table. Use this table as a guide when considering detergents and disinfectants.

| Type                       | Product name                                     | Concentration | Temperature | Time  |
|----------------------------|--|---------------|-------------|-------|
| Chemicals                  | Sodium hydroxide, NaOH                           | 1.5%          | 70°C        | 240 h |
|                            | Potassium hydroxide, KOH                         | 1.5%          | 70°C        | 240 h |
|                            | Phosphoric acid, H <sub>3</sub> PO <sub>4</sub>  | 2.5%          | 70°C        | 240 h |
|                            | Sodium hypochlorite, NaClO                       | 0.3%          | 25°C        | 240 h |
|                            | Hydrogen peroxide, H <sub>2</sub> O <sub>2</sub> | 6.5%          | 25°C        | 240 h |
| Alkaline foaming cleansers | Topax 66s (Ecolab)                               | 3.0%          | 70°C        | 240 h |
| Acidic foaming cleansers   | Topax 56 (Ecolab)                                | 5.0%          | 70°C        | 240 h |
| Disinfectants              | Oxonia Active 90 (Ecolab)                        | 1.0%          | 25°C        | 240 h |
|                            | TEK121 (ABC Compounding)                         | 1.1%          | 25°C        | 240 h |

Note: The Sensor was immersed in the above chemicals, detergents, and disinfectants for 240 h at the temperatures given, and then passed an insulation resistance test at 100 MΩ min.


Dimensions

Sensors

Retro-reflective Models

Pre-wired Models


- E3ZM-B61
- E3ZM-B81



Retro-reflective Models

M8 Connector

- E3ZM-B66
- E3ZM-B86




## Retro-reflective Models

### Pre-wired Models

E3ZM-B61T(-C)

E3ZM-B81T(-C)




## Retro-reflective Models

### M8 Connector


E3ZM-B66T(-C)

E3ZM-B86T(-C)




Accessory

Special Retroreflective Reflector E39-RP1



Material: <Reflective surface> acrylic  
<Rear surface> ABS


Special Retroreflective Reflector E39-RP37



Material: <Reflective surface> acrylic  
<Mounting plate> stainless steel (SUS301)

Note: The reflective plate and mounting plate (1) come as a set.

Special Retroreflective Reflector E39-RSP1



## Read and Understand This Catalog

Please read and understand this catalog before purchasing the products. Please consult your OMRON representative if you have any questions or comments.

## Warranty and Limitations of Liability

### WARRANTY

OMRON's exclusive warranty is that the products are free from defects in materials and workmanship for a period of one year (or other period if specified) from date of sale by OMRON.

OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, REGARDING NON-INFRINGEMENT, MERCHANTABILITY, OR FITNESS FOR PARTICULAR PURPOSE OF THE PRODUCTS. ANY BUYER OR USER ACKNOWLEDGES THAT THE BUYER OR USER ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE. OMRON DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED.

### LIMITATIONS OF LIABILITY

OMRON SHALL NOT BE RESPONSIBLE FOR SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED ON CONTRACT, WARRANTY, NEGLIGENCE, OR STRICT LIABILITY.

In no event shall the responsibility of OMRON for any act exceed the individual price of the product on which liability is asserted.

IN NO EVENT SHALL OMRON BE RESPONSIBLE FOR WARRANTY, REPAIR, OR OTHER CLAIMS REGARDING THE PRODUCTS UNLESS OMRON'S ANALYSIS CONFIRMS THAT THE PRODUCTS WERE PROPERLY HANDLED, STORED, INSTALLED, AND MAINTAINED AND NOT SUBJECT TO CONTAMINATION, ABUSE, MISUSE, OR INAPPROPRIATE MODIFICATION OR REPAIR.

## Application Considerations

### SUITABILITY FOR USE

OMRON shall not be responsible for conformity with any standards, codes, or regulations that apply to the combination of products in the customer's application or use of the products.

At the customer's request, OMRON will provide applicable third party certification documents identifying ratings and limitations of use that apply to the products. This information by itself is not sufficient for a complete determination of the suitability of the products in combination with the end product, machine, system, or other application or use.

The following are some examples of applications for which particular attention must be given. This is not intended to be an exhaustive list of all possible uses of the products, nor is it intended to imply that the uses listed may be suitable for the products:

- Outdoor use, uses involving potential chemical contamination or electrical interference, or conditions or uses not described in this catalog.
- Nuclear energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equipment, and installations subject to separate industry or government regulations.
- Systems, machines, and equipment that could present a risk to life or property.

Please know and observe all prohibitions of use applicable to the products.

NEVER USE THE PRODUCTS FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCTS ARE PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

### PROGRAMMABLE PRODUCTS

OMRON shall not be responsible for the user's programming of a programmable product, or any consequence thereof.

## Disclaimers

### CHANGE IN SPECIFICATIONS

Product specifications and accessories may be changed at any time based on improvements and other reasons.

It is our practice to change model numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the products may be changed without any notice. When in doubt, special model numbers may be assigned to fix or establish key specifications for your application on your request. Please consult with your OMRON representative at any time to confirm actual specifications of purchased products.

### DIMENSIONS AND WEIGHTS

Dimensions and weights are nominal and are not to be used for manufacturing purposes, even when tolerances are shown.

### PERFORMANCE DATA

Performance data given in this catalog is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of OMRON's test conditions, and the users must correlate it to actual application requirements. Actual performance is subject to the OMRON Warranty and Limitations of Liability.

### ERRORS AND OMISSIONS

The information in this document has been carefully checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical, or proofreading errors, or omissions.

2011.8

In the interest of product improvement, specifications are subject to change without notice.

**OMRON Corporation**  
Industrial Automation Company

<http://www.ia.omron.com/>

(c)Copyright OMRON Corporation 2011 All Right Reserved.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Omron:

[E3ZM-B61-C 2M](#) [E3ZM-B81-C 2M](#)



## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9