
Photologic® Slotted Optical Switch
OPB930 and OPB940 (L and W Series)

TT electronics
OPTEK Technology

Features:

- Choice of aperture size
- Choice of output configurations
- Choice of opaque or IR transmissive shell
- Choice of pins (L) or wires (W)
- 0.125” (3.18 mm) slot width
- 0.320” (8.128 mm) lead spacing for PCBoard (side mounting)
- Data rates to 250 kBaud



Description:

The **OPB930** and **OPB940** series of Photologic® photo integrated circuit switches provide optimum flexibility for the design engineer. Building from a standard housing with a 0.125” (3.18 mm) wide slot, a user can specify the type and polarity of TTL output, discrete shell material, aperture width and either 0.350” (8.9 mm) long pins **(L Series)** or 24” (610 mm) AWG, UL listed wire leads **(W Series)**.

All housings are made from an opaque grade of injection-molded plastic that minimizes the assembly’s sensitivity to both visible and near-infrared ambient radiation. Discrete shells (exposed on the parallel faces inside the device throat) are either IR transmissive plastic (for applications where aperture contamination may occur) or opaque plastic (for maximum protection against ambient light).

Electrical output can be specified as either TTL Totem Pole or TTL Open Collector, either of which can be supplied with buffer or inverter output polarity. All devices have the added stability of a built-in hysteresis amplifier.

Custom electrical, wire and cabling and connectors are available. Contact your local representative or OPTEK for more information.

Applications:

- Mechanical switch replacement
- Speed indication (tachometer)
- Mechanical limit indication

Part Number Guide — OPB930 and OPB940 Series

OPB 9 X X X X X Z — **For “W” series only**

Optek Assembly

Photologic® Photo Integrated Circuit Sensor Family

Discrete Shell Material:
3 — Side mount IR transmissive Plastic discrete shell
4 — Side mount opaque Plastic discrete shell

Electrical Specification Variations:
0 = Buffered Totem-Pole Output
1 = Buffered Open-Collector Output
2 = Inverted Totem-Pole Output
3 = Inverted Open-Collector Output

Sensor Aperture:
1 — 0.010” (2.54 mm)
5 — 0.050” (12.70 mm)

Emitter Aperture:
5 — 0.050” (12.70 mm)

Mounting configurations:
L — Solder leads termination
W — Wire termination


CONTAINS POLYSULFONE
To avoid stress cracking, we suggest using ND Industries’ **Vibra-Tite** for thread-locking. **Vibra-Tite** evaporates fast without causing structural failure in OPTEK’s molded plastics.

Pb
RoHS


OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPTEK Technology Inc. — 1645 Wallace Drive, Carrollton, Texas 75006
Phone: (972) 323-2200 or (800) 341-4747 FAX: (972) 323-2396 sensors@optekinc.com www.optekinc.com


OPB930, OPB940 Buffered Totem-Pole




OPB931, OPB941 Buffered Open-Collector



OPB932, OPB942 Inverted Totem-Pole



OPB933 & OPB943 Inverted Open-Collector



Absolute Maximum Ratings (T_A=25°C unless otherwise noted)

Supply Voltage, V_{CC} (not to exceed 3 seconds)	10 V
Operating Temperature Range	-40°C to +70° C
Storage Temperature Range	-40°C to +85° C
Lead Soldering Temperature [1/16 inch (1.6mm) from the case for 5 sec. with soldering iron] (1)	260° C

Input Infrared LED

Input Diode Power Dissipation (2)	100 mW
Output Photologic® Power Dissipation (3)	200 mW
Total Device Power Dissipation (4)	300 mW


Output Photologic®

Voltage at Output Lead (Open Collector Output)	35 V
Diode Forward DC Current	40 mA
Diode Reverse DC Voltage	2 V

Notes:
(1) RMA flux is recommended. Duration can be extended to 10 seconds maximum when flow soldering.
(2) Derate linearly 2.22 mW/°C above 25°.
(3) Derate linearly 4.44 mW/°C above 25°.
(4) Derate linearly 6.66 mW/°C above 25°.
(5) OPB930L/OPB940L series devices are terminated with 0.020" square leads designed for PCBoard mounting.
(6) Methanol and isopropanol are recommended as cleaning agents. Plastic housing is soluble in chlorinated hydrocarbons and ketones.
(7) All parameters tested using pulse technique.


OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPTEK Technology Inc. — 1645 Wallace Drive, Carrollton, Texas 75006
Phone: (972) 323-2200 or (800) 341-4747 FAX: (972) 323-2396 sensors@optekinc.com www.optekinc.com



Color- Pin #	Description
Red—1	Anode
Black—2	Cathode
White—3	V_{CC}
Blue—4	Output
Green—5	Ground

PCBoard (L) version



Wired (W) version

The W Series includes wire terminations of 24” (610 mm) 7-strand, 26 AWG UL insulated wire on each terminal. Each device incorporates a wire strain relief at the housing surface. The insulation functions and colors are: anode (red), cathode (black), phototransistor collector (white) and phototransistor emitter (green).

OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.


Electrical Characteristics (T_A = 25°C unless otherwise noted)


SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
Input Diode						
V_F	Forward Voltage	-	-	1.7	V	I_F = 20 mA
I_R	Reverse Current	-	-	100	µA	V_R = 2.0 V
Output Photologic® Sensor						
V_{CC}	Operating D.C. Supply Voltage	4.75	-	5.25	V	-
I_{CCL}	Low Level Supply Current: Totem Pole & Open-Collector	-	-	15	mA	V_{CC} = 5.25, I_F = 0 mA(1)
	Inverted Totem-Pole & Inverted Open-Collector	-	-	15	mA	V_{CC} = 5.25, I_F = 15 mA
I_{CCH}	High Level Supply Current: Totem Pole & Open-Collector	-	-	15	mA	V_{CC} = 5.25, I_F = 15 mA
	Inverted Totem-Pole & Inverted Open-Collector	-	-	15	mA	V_{CC} = 5.25, I_F = 0 mA(1)
V_{OL}	Low Level Output Voltage: Totem Pole & Open-Collector	-	-	0.4	V	V_{CC} = 4.75, I_{OL} = 12.8 mA, I_F = 0 mA(1)
	Inverted Totem-Pole & Inverted Open-Collector	-	-	0.4	V	V_{CC} = 4.75, I_{OL} = 12.8 mA, I_F = 15 mA
V_{OH}	High Level Output Voltage: Totem-Pole & Open-Collector	2.4	-	-	V	V_{CC} = 4.75, I_{OH} = -800 µA, I_F = 15 mA
	Inverted Totem-Pole & Inverted Open-Collector	2.4	-	-	V	V_{CC} = 4.75, I_{OH} = -800 µA, I_F = 0 mA(1)
I_{OH}	High Level Output Current: Totem Pole & Open-Collector	-	-	100	µA	V_{CC} = 4.75, V_{OH} = 30 V, I_F = 15 mA,
	Inverted Totem-Pole & Inverted Open-Collector	-	-	100	µA	V_{CC} = 4.75, V_{OH} = 30 V, I_F = 0 mA(1)
$I_F(+)$	LED Positive-Going Threshold Current	-	-	15	mA	V_{CC} = 5.0 V
$I_F(+)$, $I_F(-)$	Hysteresis	-	2.0	-	V	V_{CC} = 5.0 V
I_{OS}	Short Circuit Output Current: Totem Pole & Open-Collector	-15	-	-60	mA	V_{CC} = 5.25 V, I_F = 15 mA, Output = GND
	Inverted Totem-Pole & Inverted Open-Collector	-15	-	-60	mA	V_{CC} = 5.25 V, I_F = 0 mA(1), Output = GND
t_r,t_r	Output Rise Time, Output Fall Time	-	70	-	ns	V_{CC} = 5 V, I_F = 0 or 15 mA
T_{PLH}	Propagation Delay Low-High	-	5.0	-	µs	R_L = 8TTL loads (Totem Pole)
T_{PHL}	Propagation Delay High-Low	-	5.0	-	µs	R_L = 360 Ω (Open-Collector)


Notes:
(1) Normal application would be with light source blocked, simulated by I_F = 0 mA.
(2) All parameters are tested using pulse techniques.


OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPTEK Technology Inc. — 1645 Wallace Drive, Carrollton, Texas 75006
Phone: (972) 323-2200 or (800) 341-4747 FAX: (972) 323-2396 sensors@optekinc.com www.optekinc.com











OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.


OPB930_51, OPB940_51 - Flag Next to Emitter




OPB930_51, OPB940_51 - Flag Next to Sensor



OPB930_51, OPB940_51 - Flag in Middle of Slot







OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

OPTEK Technology Inc. — 1645 Wallace Drive, Carrollton, Texas 75006
Phone: (972) 323-2200 or (800) 341-4747 FAX: (972) 323-2396 sensors@optekinc.com www.optekinc.com


OPB930_55, OPB940_55 - Flag Next to Emitter




OPB930_55, OPB940_55 - Flag Next to Sensor



OPB930_55, OPB940_55 - Flag in Middle of Slot





OPTEK reserves the right to make changes at any time in order to improve design and to supply the best product possible.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9