

Is Now Part of



ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild <a href="general-regarding-numbers-n

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any EDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officer



December 2010

NC7SVL32 TinyLogic[®] Low-I_{CCT} Two-Input OR Gate

Features

- 0.9V to 3.6V V_{CC} Supply Operation
- 3.6V Over-Voltage Tolerant I/Os at Vcc from 0.9V to 3.6V
- Power-Off High-Impedance Inputs and Outputs
- Proprietary Quiet SeriesTM Noise / EMI Reduction Circuitry
- Ultra-Small MicroPak™ Packages
- Ultra-Low Dynamic Power

Description

The NC7SVL32 is a single two-input OR gate with a Low-l_{CCT} input design from Fairchild's Ultra-Low Power (ULP-A) series of TinyLogic®. The NC7SVL32 features very low quiescent current, even when the input voltage is lower than the V_{CC} supply. This feature services mobile handset applications very well, allowing for direct interface with baseband processor general-purpose I/Os. Since mobile devices rely on a battery supply, the NC7SVL32 facilitates lower power consumption in mixed-voltage rail environments.

This product is designed on an advanced CMOS technology for a wide low-voltage operating range (0.9V to 3.6V $V_{\rm CC}$), high drive needs (up to 24mA), and speed (maximum propagation delay of 3.5ns, $V_{\rm CC}$ =3.3V). It achieves this performance while maintaining low CMOS power dissipation.

Ordering Information


Part Number	Top Mark	Package	Packing Method
NC7SVL32P5X	L32	5-Lead SC70, EIAJ SC-88a, 1.25mm Wide	3000 Units on Tape & Reel
NC7SVL32L6X	CF	6-Lead MicroPak™, 1.00mm Wide	5000 Units on Tape & Reel
NC7SVL32FHX	CF	6-Lead, MicroPak2™, 1x1mm Body, .35mm Pitch	5000 Units on Tape & Reel

Connection Diagram



Figure 1. Logic Symbol

Pin Configurations



A 1 6 V_{CC}
B 2 5 NC
GND 3 4 Y

Figure 2. SC70 (Top View)

Figure 3. MicroPak™ (Top Through View)

Pin Definitions

Pin # SC70	Pin # MicroPak™	Name	Description
1	1	A	Input
2	2	В	Input
3	3	GND	Ground
4	4	Y	Output
	5	NC	No Connect
5	6	Vcc	Supply Voltage

Function Table

Y = A+B

Inp	outs	Output
Α	В	Y
L	L	L
L	Н	Н
Н	L	Н
Н	Н	Н

H = HIGH Logic Level

L = LOW Logic Level

Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Symbol	Para	meter	Min.	Max.	Unit
V _{CC}	Supply Voltage		-0.5	4.6	V
V _{IN}	DC Input Voltage		-0.5	4.6	V
\/	DC Output Valtage	HIGH or LOW State ⁽¹⁾	-0.5	V _{CC} + 0.5	V
V_{OUT}	DC Output Voltage	$V_{CC} = 0V$	-0.5	4.6	V
I _{IK}	DC Input Diode Current	V _{IN} < 0V		-50	mA
	DO Custout Diede Comment	V _{OUT} < 0V		-50	A
l _{OK}	DC Output Diode Current	V _{OUT} > V _{CC}		+50	mA
I _{OH} / I _{OL}	DC Output Source/Sink Current	DC Output Source/Sink Current			mA
I _{CC} or I _{GND}	DC V _{CC} or Ground Current per S	Supply Pin		±50	mA
T _{STG}	Storage Temperature Range		-65	+150	°C
TJ	Junction Temperature Under Bi	as		+150	°C
TL	Junction Lead Temperature, So	oldering 10 Seconds		+260	°C
		SC70-5		150	
P_D	Power Dissipation at +85°C	MicroPak™-6		130	mW
		MicroPak2™-6		120	
FCD	Human Body Model, JEDEC:JE		4000	V	
ESD	Charge Device Model, JEDEC:	JESD22-C101		2000	V

Note:

Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to Absolute Maximum Ratings.

Symbol	Parameter	Conditions	Min.	Max.	Unit
V _{CC}	Supply Voltage		0.9	3.6	V
V _{IN}	Input Voltage		0	3.6	V
V	Output Voltage	V _{CC} =0V	0	3.6	V
V _{OUT}	Output Voltage	HIGH or LOW State	0	V _{CC}	7 °
		V _{CC} =3.0V to 3.6V		±24.0	
	Output Current in I _{OH} /I _{OL}	V _{CC} =2.3V to 2.7V		±18.0	
1 /1		V _{CC} =1.65V to 1.95V		±6.0	
I _{OH} /I _{OL}		V _{CC} =1.4V to 1.6V		±4.0	mA
		V _{CC} =1.1V to 1.3V		±2.0	
		V _{CC} =0.9V		±0.1	
T _A	Operating Temperature, Free Air		-40	+85	°C
Δt/ΔV	Minimum Input Edge Rate	V _{IN} =0.8V to 2.0, V _{CC} =3.0V		10	ns/V
		SC70-5		425	
θ_{JA}	Thermal Resistance	MicroPak™-6		500	°C/W
		MicroPak2™-6		560	1

Note:

^{1.} Io absolute maximum ratings must be observed.

^{2.} Unused inputs must be held HIGH or LOW. They may not float.

DC Electrical Characteristics

0		.,	0 1111	T _A =2	5°C	T _A =-40	to +85°C	1
Symbol	Parameter	V _{cc}	Conditions	Min.	Max.	Min.	Max.	Units
		0.90		.65 x V _{CC}		.65 x V _{CC}		
		$1.10 \le V_{CC} \le 1.30$.65 x V _{CC}		.65 x V _{CC}		
\/	HIGH Level Input	$1.40 \le V_{CC} \le 1.60$.65 x V _{CC}		.65 x V _{CC}		
V _{IH}	Voltage	$1.65 \le V_{CC} \le 1.95$		0.90		0.90		V
		$2.30 \leq V_{CC} \leq 2.70$		1.50		1.50		
		$2.70 \leq V_{CC} \leq 3.60$		1.50		1.50		
		0.90			.25 x V _{CC}		.25 x V _{CC}	
		$1.10 \le V_{CC} \le 1.30$.25 x V _{CC}		.25 x V _{CC}	1
	LOW Level Input	$1.40 \le V_{CC} \le 1.60$.25 x V _{CC}		.25 x V _{CC}	V
V_{IL}	Voltage	$1.65 \le V_{CC} \le 1.95$.25 x V _{CC}		.25 x V _{CC}]
		$2.30 \leq V_{CC} \leq 2.70$			0.70		0.70	
		$2.70 \leq V_{CC} \leq 3.60$			0.80		0.80	1
1		0.90		V _{CC} -0.10		V _{CC} -0.10		
		$1.10 \le V_{CC} \le 1.30$		V _{CC} -0.10		V _{CC} -0.10		
		$1.40 \le V_{CC} \le 1.60$	100	V _{CC} -0.20		V _{CC} -0.20		
		$1.65 \le V_{CC} \le 1.95$	I _{OH} =-100μA	V _{CC} -0.20		V _{CC} -0.20		Ī.
		$2.30 \leq V_{CC} \leq 2.70$		V _{CC} -0.20		V _{CC} -0.20		
		$2.70 \leq V_{CC} \leq 3.60$		V _{CC} -0.20		V _{CC} -0.20		
		$1.10 \le V_{CC} \le 1.30$	I _{OH} =-2mA	.75 x V _{CC}		.75 x V _{CC}		
V_{OH}	HIGH Level Output Voltage	$1.40 \le V_{CC} \le 1.60$	I _{OH} =-4mA	.75 x V _{CC}		.75 x V _{CC}		V
	Voltage	$1.65 \le V_{CC} \le 1.95$	I _{OH} =-6mA	1.25		1.25		
		$2.30 \leq V_{CC} \leq 2.70$	IOH=-OITIA	2.00		2.00		
		$2.30 \leq V_{CC} \leq 2.70$	1 12m A	1.80		1.80		
		$2.70 \leq V_{CC} \leq 3.60$	I _{OH} =-12mA	2.20		2.20		
		$2.30 \leq V_{CC} \leq 2.70$	1 40m A	1.70		1.70		
		$2.70 \leq V_{CC} \leq 3.60$	I _{OH} =-18mA	2.40		2.40		Ī
		$2.70 \leq V_{CC} \leq 3.60$	I _{OH} =-24mA	2.20	7	2.20		Ī

Continued on the following page...

DC Electrical Characteristics (Continued)

Comple al	Davamatar	V	Conditions	T _A =	25°C	T _A =-40	to +85°C	l luita
Symbol	Parameter	V _{CC}	Conditions	Min.	Max.	Min.	Max.	Units
		0.90			0.1		0.1	
		$1.10 \leq V_{CC} \leq 1.30$			0.1		0.1	
		$1.40 \le V_{CC} \le 1.60$	1		0.2		0.2	
		$1.65 \leq V_{CC} \leq 1.95$	I _{OL} =100μA		0.2		0.2	
		$2.30 \leq V_{CC} \leq 2.70$			0.2		0.2	
		$2.70 \leq V_{CC} \leq 3.60$			0.2		0.2	
	LOW Level	$1.10 \leq V_{CC} \leq 1.30$	I _{OL} =2mA		0.25 x V _{CC}		0.25 x V _{CC}	V
V _{OL}	Output Voltage	$1.40 \le V_{CC} \le 1.60$	I _{OL} =4mA		0.25 x V _{CC}		0.25 x V _{CC}	V
		$1.65 \leq V_{CC} \leq 1.95$	I _{OL} =6mA		0.30		0.3	
		$2.30 \leq V_{CC} \leq 2.70$	I _{OL} =12mA		0.40		0.40	
		$2.70 \leq V_{CC} \leq 3.60$	I _{OL} =12IIIA		0.40		0.40	
		$2.30 \leq V_{CC} \leq 2.70$	I _{OL} =18mA		0.60		0.60	
		$2.70 \leq V_{CC} \leq 3.60$	IOL=TOTTIA		0.40		0.40	
		$2.70 \leq V_{CC} \leq 3.60$	I _{OL} =24mA		0.55		0.55	
I _{IN}	Input Leakage Current	0.90 to 3.60	$0 \leq V_{IN} \leq 3.60V$		±0.1		±0.5	μA
l _{OFF}	Power Off Leakage Current	0	$0 \le (V_{IN}, V_O) \le 3.60V$		0.5		0.5	μΑ
	Quiescent	0.00 to 2.60	V _{IN} =V _{CC} , or GND		0.9		0.9	
Icc	Supply Current	0.90 to 3.60	$V_{CC} \leq V_{IN} \leq 3.60 V$				±0.9	μA
Ісст	Increase in I _{CC}	1.95	V _{IN} =0.9V		6		8	μA
ICCI	per Input	3.60	V _{IN} =1.5V		6		8	μΛ

AC Electrical Characteristics

Cumbal	Doromotor	V	Canditions	Conditions T _A =25°C		С	T _A =-40	to 85°C	Units	Figure
Symbol Paramete	Parameter	V _{CC}	Conditions	Min.	Тур.	Max.	Min.	Max.	Units	rigure
		0.90	$C_L=15pF, R_L=1M\Omega$		42.0	- 2			7	
		$1.10 \le V_{CC} \le 1.30$	C 45=5 D 01:0	3.5	8.2	17.0	3.0	30.5		
	Propagation	$1.40 \le V_{CC} \le 1.60$	$C_L=15pF, R_L=2k\Omega$	1.5	4.0	7.0	1.5	7.5		Figure 4 Figure 5
lphL, lpLH	t _{PHL} , t _{PLH} Delay	$1.65 \le V_{CC} \le 1.95$	$C_L=30pF, R_L=500\Omega$	1.1	3.2	5.5	1.0	6.0		
		$2.30 \leq V_{CC} \leq 2.70$		0.6	2.3	4.0	0.6	4.5		
		$2.70 \leq V_{CC} \leq 3.60$		0.5	1.9	3.5	0.5	4.0		21
C _{IN}	Input Capacitance	0			3				pF	3/
C _{PD}	Power Dissipation Capacitance	0.90 to 3.60	V _{IN} =0V or V _{CC} , f=10MHz		5				pF	

AC Loadings and Waveforms





Figure 4. AC Test Circuit



Symbol	V _{CC}							
Syllibol	3.3V ± 0.3V	0.3V 2.5V ± 0.2V 1.8V ± 0.15V 1.5V ± 0.1V 1.2V ± 0.1V						
V _{mi}	1.5V	V _{CC} /2	V _{CC} /2	V _{CC} /2	V _{CC} /2	V _{CC} /2		
V_{mo}	1.5V	V _{CC} /2	V _{CC} /2	V _{CC} /2	V _{CC} /2	V _{CC} /2		

Physical Dimensions




Figure 6. 5-Lead, SC70, EIAJ SC-88a, 1.25mm Wide

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.


Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings: http://www.fairchildsemi.com/packaging/.

Tape and Reel Specifications

Please visit Fairchild Semiconductor's online packaging area for the most recent tape and reel specifications: http://www.fairchildsemi.com/products/analog/pdf/sc70-5 tr.pdf.

Package Designator	ckage Designator Tape Section		Cavity Status	Cover Type Status
	Leader (Start End)	125 (Typical)	Empty	Sealed
P5X	Carrier	3000	Filled	Sealed
	Trailer (Hub End)	75 (Typical)	Empty	Sealed

Physical Dimensions



- Notes:
- 1. CONFORMS TO JEDEC STANDARD M0-252 VARIATION UAAD
- 2. DIMENSIONS ARE IN MILLIMETERS
- 3. DRAWING CONFORMS TO ASME Y14.5M-1994
- FILENAME AND REVISION: MAC06AREV4
- 5. PIN ONE IDENTIFIER IS 2X LENGTH OF ANY

OTHER LINE IN THE MARK CODE LAYOUT.

Figure 7. 6-Lead, MicroPak™, 1.0mm Wide

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings: http://www.fairchildsemi.com/packaging/.

Tape and Reel Specifications

Please visit Fairchild Semiconductor's online packaging area for the most recent tape and reel specifications: http://www.fairchildsemi.com/products/logic/pdf/micropak_tr.pdf.

Package Designator Tape Secti		Cavity Number	Cavity Status	Cover Type Status
	Leader (Start End)	125 (Typical)	Empty	Sealed
L6X	Carrier	5000	Filled	Sealed
	Trailer (Hub End)	75 (Typical)	Empty	Sealed

Physical Dimensions 0.89 ○ 0.05 C 1.00 В 2X 5X 0.40 PIN 1 0.66 MIN 250uM 1.00 1X 0.45 6X 0.19 ○ 0.05 C **TOP VIEW** RECOMMENDED LAND PATTERN 2X FOR SPACE CONSTRAINED PCB // 0.05 C 0.55MAX С 5X 0.52 SIDE VIEW 0.73 (0.08) 4X 1X 0 57 0.09 0.19 6X DETAIL A 2 3

NOTES:

0.35

5X 0.35 0.25

- A. COMPLIES TO JEDEC MO-252 STANDARD
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 1994

0.60


(80.0)


4X

 \oplus

- D. LANDPATTERN RECOMMENDATION IS BASED ON FSC DESIGN.
- E. DRAWING FILENAME AND REVISION: MGF06AREV3

BOTTOM VIEW





FOR UNIVERSAL APPLICATION

Figure 8. 6-Lead, MicroPak2™, 1x1mm Body, .35mm Pitch

.05 C

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings: http://www.fairchildsemi.com/packaging/.

Tape and Reel Specifications

Please visit Fairchild Semiconductor's online packaging area for the most recent tape and reel specifications: http://www.fairchildsemi.com/packaging/MicroPAK2_6L_tr.pdf.

Package Designator	Tape Section	Cavity Number	Cavity Status	Cover Type Status
	Leader (Start End)	125 (Typical)	Empty	Sealed
FHX	Carrier	5000	Filled	Sealed
	Trailer (Hub End)	75 (Typical)	Empty	Sealed





TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™ Auto-SPM™ Build it Now™ CorePLUS™ CorePOWER™ CROSSVOLT** CTL™. Current Transfer Logic™ DEUXPEED⁶

GTO™ IntelliMAX*** ISOPLANAR™ Dual Cool™ MegaBuck™ EcoSPARK® MICROCOUPLER" EfficientMax™ MicroFET™ ESBC# MicroPak™ MicroPak2™ MillerDrive™ Fairchild® MotionMa×™ Fairchild Semiconductor® Motion-SPM™ FACT Quiet Series™ OptoHiT™ FACT® OPTOLOGIC® OPTOPLANAR® FastvCore™ FETBench™ FlashVVriter®*

F-PESTM

FREET

GmaxTM

Green FPS™

Global Power Resources

Green FPS™ e-Series™

PowerTrench⁶ PowerXS™

Programmable Active Droop™

OFFT QSTM Ouiet Series™ RapidConfigure™

Saving our world, 1mWWWkW at a time™

SignalWise™ SmartMax™ SMART START™ SPM® STEALTH™ SuperFET® SuperSOT**3 SuperSOT™6 SuperSOT**-8 SupreMOS[®] SyncFET™ Sync-Lock™ SYSTEM SERVICE

The Power Franchise® The Right Technology for Your Success™



TinyBuck™ TinyCalc™ TinyLogic⁶ TINYOPTO** TinyPower™ Tiny₽WM™ TinyWire™ TriFault Detect™ TRUECURRENT"" μSerDes™

UHC Ultra FRFET™ UniFET** VCXTM VisualMax™

PDP SPM™

Power-SPM™

DISCLAIMER

FPSTM

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user
- 2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com,

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. 151

^{*} Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

ON Semiconductor and in are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdt/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor and see any inability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and ex

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800-282-9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ON Semiconductor:

NC7SVL32FHX NC7SVL32P5X NC7SVL32L6X

ПОСТАВКА ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

многоканальный

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru_6 moschip.ru_4 moschip.ru_9