

# General Specifications

## Electrical Capacity (Resistive Load)

|                                                  |                                                                                   |
|--------------------------------------------------|-----------------------------------------------------------------------------------|
| <b>Power Level (silver):</b>                     | 1A @ 125V AC or 1A @ 30V DC                                                       |
| <b>Logic Level (gold):</b>                       | 0.4VA maximum @ 28V AC/DC maximum<br>(Applicable Range 0.1mA ~ 0.1A @ 20mV ~ 28V) |
| <b>Logic/Power Level:<br/>(gold over silver)</b> | Combines silver & gold ratings                                                    |

Note: Find additional explanation of dual rating & operating range in Supplement section.

## Other Ratings

|                                 |                                                                                                                            |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| <b>Contact Resistance:</b>      | 20 milliohms maximum for silver; 30 milliohms maximum for gold                                                             |
| <b>Insulation Resistance:</b>   | 1,000 megohms minimum @ 500V DC                                                                                            |
| <b>Dielectric Strength:</b>     | 1,000V AC minimum between contacts for 1 minute minimum;<br>1,500V AC minimum between contacts & case for 1 minute minimum |
| <b>Mechanical Life:</b>         | 200,000 operations minimum                                                                                                 |
| <b>Electrical Life:</b>         | 25,000 operations minimum for silver; 100,000 operations minimum for gold                                                  |
| <b>Nominal Operating Force:</b> | Single pole 2.94N & double pole 4.90N                                                                                      |
| <b>Contact Timing:</b>          | Nonshorting (break-before-make)                                                                                            |
| <b>Travel:</b>                  | Pretravel .023" (0.6mm); Overtravel .016" (0.4mm); Total Travel .039" (1.0mm)                                              |

## Materials & Finishes

|                             |                                                                                                                             |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <b>Plunger:</b>             | Brass with nickel plating                                                                                                   |
| <b>Support Bracket:</b>     | Brass with tin plating                                                                                                      |
| <b>Bushing/Housing:</b>     | Glass fiber reinforced polyamide (UL94V-0)                                                                                  |
| <b>Sealing Ring:</b>        | Nitrile butadiene rubber                                                                                                    |
| <b>Base:</b>                | Glass fiber reinforced polyamide (UL94V-0)                                                                                  |
| <b>Movable Contacts:</b>    | Silver alloy with silver plating (code W); copper with gold plating (code G);<br>or silver alloy with gold plating (code A) |
| <b>Stationary Contacts:</b> | Silver alloy with silver plating (code W); copper with gold plating (code G);<br>or silver alloy with gold plating (code A) |
| <b>Terminals:</b>           | Brass with silver or gold plating                                                                                           |

## Environmental Data

|                              |                                                                                                                                                 |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Operating Temp Range:</b> | -30°C through +85°C (-22°F through +185°F)                                                                                                      |
| <b>Humidity:</b>             | 90 ~ 95% humidity for 96 hours @ 40°C (104°F)                                                                                                   |
| <b>Vibration:</b>            | 10 ~ 55Hz with peak-to-peak amplitude of 1.5mm traversing the frequency range & returning<br>in 1 minute; 3 right angled directions for 2 hours |
| <b>Shock:</b>                | 50G (490m/s <sup>2</sup> ) acceleration (tested in 6 right angled directions, with 5 shocks in each direction)                                  |

## Installation

|                                |                                                                 |
|--------------------------------|-----------------------------------------------------------------|
| <b>Cap Installation Force:</b> | 49.0N (11.0 lbf) for plunger A & 79.4N (17.9 lbf) for plunger B |
|--------------------------------|-----------------------------------------------------------------|

## PCB Processing

|                   |                                                                                                                            |
|-------------------|----------------------------------------------------------------------------------------------------------------------------|
| <b>Soldering:</b> | Wave Soldering Recommended: See Profile B in Supplement section.<br>Manual Soldering: See Profile B in Supplement section. |
| <b>Cleaning:</b>  | Automated cleaning. See Cleaning specifications in Supplement section.                                                     |

## Standards & Certifications

|                                |                                                                                                                                                                                                                                        |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Flammability Standards:</b> | UL94V-0 rated bushing/housing & base                                                                                                                                                                                                   |
| <b>UL:</b>                     | <b>File No. E44145 - Recognized only when ordered with marking on switch.</b><br>Add "/U" or "/CUL" before dash in part number to order UL recognized switch.<br>All models recognized at 1A @ 125V AC, 1A @ 30V DC, or 0.4A @ 28V DC. |
| <b>CSA:</b>                    | <b>File No. 023535_0_000 - Certified only when ordered with marking on switch.</b><br>Add "/C" before dash in part number to order CSA certified switch.<br>All models certified at 1A @ 125V AC, 1A @ 30V DC, or 0.4A @ 28V DC.       |

## Distinctive Characteristics

Snap-acting contact mechanism gives short travel, sensitive actuation, light touch, smooth feel, audible feedback, and a longer electrical life.

Single unit construction of the bushing and top of the housing gives protection from cleaning fluids or other liquids.


O-ring surrounding actuator at top of bushing interior prevents liquids from reaching switch mechanism.

Ultrasonic welding of upper and lower housing seals out contaminants and allows automated soldering and cleaning.


Terminals are epoxy sealed to prevent entry of flux, solvents, and other contaminants.

Bracketed models have crimped bracket legs to ensure secure PC mounting and prevent dislodging during automated soldering.

Logic level and power capabilities are available to suit varying applications.



Actual Size



Toggles

Rockers

**C** Pushbuttons

Illuminated PB

Programmable

Keylocks

Rotaries

Slides

Tactiles

Tilt

Touch

Indicators

Accessories

Supplement

### TYPICAL SWITCH ORDERING EXAMPLE

**M2B**

**15**

**A**

**A5**

**G**

**30**

**F**

**C**

#### Poles & Circuits

|                 |      |    |      |
|-----------------|------|----|------|
| 15              | SPDT | ON | (ON) |
| 25              | DPDT | ON | (ON) |
| ( ) = Momentary |      |    |      |

#### Plungers

|   |                                            |
|---|--------------------------------------------|
| A | .282" (7.16mm) Long<br>for cap codes F & H |
| B | .307" (7.8mm) Long<br>for cap codes B & C  |

#### Bushing

|    |                                  |
|----|----------------------------------|
| A5 | .250" (6.35mm)<br>Double Flatted |
|----|----------------------------------|

#### Contact Materials & Ratings

|   |                                                                        |
|---|------------------------------------------------------------------------|
| W | Silver;<br>Rated 1A @ 125V AC<br>& 1A @ 30V DC                         |
| G | Gold;<br>Rated 0.4VA maximum<br>@ 28V AC/DC maximum                    |
| A | Gold over Silver; Rated<br>1A @ 125V AC & 0.4VA<br>max @ 28V AC/DC max |

#### PC Terminals

|    |                                         |
|----|-----------------------------------------|
| 03 | Straight                                |
| 13 | Straight with<br>.460" (11.7mm) Bracket |
| 30 | .150" (3.81mm) Right Angle              |
| 40 | .150" (3.81mm) Vertical                 |

#### Snap-on Caps

|               |                         |
|---------------|-------------------------|
| For Plunger A |                         |
| F             | .201" (5.1mm) Diameter  |
| H             | .295" (7.5mm) Diameter  |
| For Plunger B |                         |
| B             | .315" (8.0mm) Diameter  |
| C             | .394" (10.0mm) Diameter |

#### Cap Colors

|                               |        |
|-------------------------------|--------|
| A                             | Black  |
| B                             | White  |
| C                             | Red    |
| * E                           | Yellow |
| * F                           | Green  |
| * G                           | Blue   |
| * H                           | Gray   |
| * For cap codes<br>B & C only |        |


#### IMPORTANT:




Switches are supplied without UL, cULus & CSA marking unless specified.  
**UL, cULus & CSA recognized only when ordered with marking on the switch.**  
Specific models, ratings, & ordering instructions are noted on General Specifications page.

#### DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

**M2B15AA5G30-FC**



| POLES & CIRCUITS |       |                                                                                   |                                                                                   |                                                                                   |                                                                                   |                                                                                             |
|------------------|-------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
|                  |       | Plunger Position<br>( ) = Momentary                                               |                                                                                   | Connected Terminals                                                               |                                                                                   | Throw & Schematics                                                                          |
| Pole             | Model | Normal                                                                            | Down                                                                              | Normal                                                                            | Down                                                                              |                                                                                             |
|                  |       |  |  |  |  | Note: Terminal numbers are not actually on the switch.                                      |
| SP               | M2B15 | ON                                                                                | (ON)                                                                              | 1-3                                                                               | 1-2                                                                               | SPDT<br> |
| DP               | M2B25 | ON                                                                                | (ON)                                                                              | 1-3 4-6                                                                           | 1-2 4-5                                                                           | DPDT<br> |


PLUNGERS

A

.282" (7.16mm) Long

For cap codes F & H

Material:  
Chrome over brass




B

.307" (7.8mm) Long

For cap codes B & C



Material:  
Chrome over brass



BUSHING

A5

.250" (6.35mm) Double Flatted



CONTACT MATERIALS & RATINGS

W

Silver over Silver

Power Level

1A @ 125V AC & 1A @ 30V DC

G

Gold over Brass or Copper

Logic Level

0.4VA maximum @ 28V AC/DC maximum

Complete explanation of operating range in Supplement section.

A

Gold over Silver


Power Level  
or Logic Level

1A @ 125V AC  
or 0.4VA maximum @ 28V AC/DC maximum


Note: This dual rated option is suitable when two or more identical switches are used in logic and in power circuits within the same application. See Supplement section for complete explanation of dual rating and operating range.

### PC TERMINALS


**03** Straight




**13** Straight with .460" (11.7mm) Bracket



**30** .150" (3.81mm) Right Angle



**40** .150" (3.81mm) Vertical




### SNAP-ON CAPS

#### For Plunger Type A

**F** AT475  
.201" (5.1mm) Diameter

Material: Polyamide


Colors Available:  
A, B, C



**H** AT496  
.295" (7.5mm) Diameter

Material: Polyamide

Colors Available:  
A, B, C




#### For Plunger Type B

**B** AT443  
.315" (8.0mm) Diameter

Material: Polycarbonate


Colors Available:  
A, B, C, E, F, G, H



**C** AT442  
.394" (10.0mm) Diameter

Material: Polycarbonate

Colors Available:  
A, B, C, E, F, G, H



Cap Colors  
Codes:

**A**

Black

**B**

White

**C**

Red

**E**

Yellow

**F**

Green

**G**




Blue

**H**

Gray

## TYPICAL SWITCH DIMENSIONS

### Single Pole






### Straight PC



M2B15AA5G03-FC

### Double Pole






### Straight PC



M2B25AA5G03-FC

### Single & Double Pole



### Straight PC • Bracket







M2B15AA5G13-FC

### TYPICAL SWITCH DIMENSIONS

#### Right Angle PC





#### Single Pole



M2B15AA5G30-FC

#### Right Angle PC





#### Double Pole



M2B25AA5G30-FC

#### Vertical PC





#### Single Pole



M2B15AA5G40-FC

#### Vertical PC

#### Double Pole



M2B25AA5G40-FC

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9