






Dimensions: [mm]




Scale - 6:1

Product Marking:


|         |    |
|---------|----|
| Marking | CR |
|---------|----|

Recommended Land Pattern: [mm]



Scale - 6:1

Schematic:



Electrical Properties:

| Properties                                 | Test conditions        |                    | Value | Unit | Tol. |
|--------------------------------------------|------------------------|--------------------|-------|------|------|
| DC Operating Voltage                       |                        | V <sub>DC</sub>    | 40    | V    | max. |
| (Reverse) Breakdown Voltage                | 1 mA                   | V <sub>BR</sub>    | 46.75 | V    | ±5%  |
| Clamping Voltage                           | I <sub>PEAK</sub>      | V <sub>Clamp</sub> | 64.5  | V    | max. |
| (Reverse) Peak Pulse Current               | 10/1000 µs             | I <sub>Peak</sub>  | 6.2   | A    | max. |
| (Forward) Peak Pulse Current <sup>1)</sup> |                        | I <sub>Peak</sub>  | 40    | A    | max. |
| Leakage Current                            | V <sub>DC</sub>        | I <sub>LEAK</sub>  | 1     | µA   | max. |
| Steady State Power Dissipation             | T <sub>A</sub> = 50 °C | P <sub>DISS</sub>  | 3.3   | W    | max. |
| Power Dissipation <sup>2)</sup>            | 10/1000 µs             | P <sub>DISS</sub>  | 400   | W    | max. |
| Polarity                                   | Unidirectional         |                    |       |      |      |

<sup>1)</sup> 8.3 ms single half-sine wave or equivalent square wave, Duty cycle = 4 pulses per minute  
<sup>2)</sup> Mounted on 5.0 mm x 5.0 mm (0.03 mm thick) Copper Pads to each terminal

General Information:

|                                                                                                            |                      |
|------------------------------------------------------------------------------------------------------------|----------------------|
| It is recommended that the temperature of the component does not exceed +150°C under worst case conditions |                      |
| Operating Temperature                                                                                      | -65 °C up to +150 °C |
| Storage Temperature (in original packaging)                                                                | -40 °C up to +60 °C  |
| Test conditions of Electrical Properties: +20°C, 33% RH if not specified differently                       |                      |

Würth Elektronik eiSos GmbH & Co. KG  
EMC & Inductive Solutions

Max-Eyth-Str. 1  
74638 Waldenburg  
Germany  
Tel. +49 (0) 79 42 945 - 0

www.we-online.com  
eiSos@we-online.com




|                                               |                     |                                      |                                |             |
|-----------------------------------------------|---------------------|--------------------------------------|--------------------------------|-------------|
| CREATED<br>KaS                                | CHECKED<br>RoD      | GENERAL TOLERANCE<br>DIN ISO 2768-1m | PROJECTION METHOD<br>          |             |
| DESCRIPTION<br><b>WE-TVSP Power TVS Diode</b> |                     |                                      | ORDER CODE<br><b>824500401</b> |             |
| SIZE<br>DO-214AC                              | REVISION<br>001.000 | STATUS<br>Draft                      | DATE<br>2015-11-10             | PAGE<br>1/7 |

Properties & Approvals:

|                                     |                 |
|-------------------------------------|-----------------|
| UL Approval                         | UL497B: E478010 |
| Plastic Housing Flammability Rating | UL94-V0         |

Maximum Peak Pulse Power Rating




|                                                                                       |  |  |                                               |                     |                                      |                                                                                                            |             |
|---------------------------------------------------------------------------------------|--|--|-----------------------------------------------|---------------------|--------------------------------------|------------------------------------------------------------------------------------------------------------|-------------|
| Würth Elektronik eiSos GmbH & Co. KG<br>EMC & Inductive Solutions                     |  |  | CREATED<br>KaS                                | CHECKED<br>RoD      | GENERAL TOLERANCE<br>DIN ISO 2768-1m | PROJECTION METHOD<br> |             |
| Max-Eyth-Str. 1<br>74638 Waldenburg<br>Germany<br>Tel. +49 (0) 79 42 945 - 0          |  |  | DESCRIPTION<br><b>WE-TVSP Power TVS Diode</b> |                     |                                      |                                                                                                            |             |
| www.we-online.com<br>eiSos@we-online.com                                              |  |  | ORDER CODE<br><b>824500401</b>                |                     |                                      |                                                                                                            |             |
|  |  |  | SIZE<br>DO-214AC                              | REVISION<br>001.000 | STATUS<br>Draft                      | DATE<br>2015-11-10                                                                                         | PAGE<br>2/7 |


This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Peak Pulse Power and Current Derating




Steady State Power Dissipation Derating




|                                                                                                                                                                                                                                                                                                                                                                           |          |             |            |                   |                   |                                                                                       |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|-------------|------------|-------------------|-------------------|---------------------------------------------------------------------------------------|--|--|--|
| <div>Würth Elektronik eiSos GmbH &amp; Co. KG</div> <div>EMC &amp; Inductive Solutions</div> <div>Max-Eyth-Str. 1</div> <div>74638 Waldenburg</div> <div>Germany</div> <div>Tel. +49 (0) 79 42 945 - 0</div> <div>www.we-online.com</div> <div>eiSos@we-online.com</div> <div></div> |          | CREATED     | CHECKED    | GENERAL TOLERANCE | PROJECTION METHOD |  |  |  |  |
|                                                                                                                                                                                                                                                                                                                                                                           |          | KaS         | RoD        | DIN ISO 2768-1m   |                   |                                                                                       |  |  |  |
|                                                                                                                                                                                                                                                                                                                                                                           |          | DESCRIPTION |            |                   | ORDER CODE        |                                                                                       |  |  |  |
|                                                                                                                                                                                                                                                                                                                                                                           |          |             |            |                   |                   |                                                                                       |  |  |  |
| WE-TVSP Power TVS Diode                                                                                                                                                                                                                                                                                                                                                   |          |             | 824500401  |                   |                   |                                                                                       |  |  |  |
| SIZE                                                                                                                                                                                                                                                                                                                                                                      | REVISION | STATUS      | DATE       | BUSINESS UNIT     | PAGE              |                                                                                       |  |  |  |
| DO-214AC                                                                                                                                                                                                                                                                                                                                                                  | 001.000  | Draft       | 2015-11-10 | eiSos             | 3/7               |                                                                                       |  |  |  |

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Maximum Non-Repetitive Forward Surge Current



Typical Junction Capacitance



|                                                                                       |  |                                               |                     |                                      |                                                                                                            |                        |
|---------------------------------------------------------------------------------------|--|-----------------------------------------------|---------------------|--------------------------------------|------------------------------------------------------------------------------------------------------------|------------------------|
| Würth Elektronik eiSos GmbH & Co. KG<br>EMC & Inductive Solutions                     |  | CREATED<br>KaS                                | CHECKED<br>RoD      | GENERAL TOLERANCE<br>DIN ISO 2768-1m | PROJECTION METHOD<br> |                        |
| Max-Eyth-Str. 1<br>74638 Waldenburg<br>Germany<br>Tel. +49 (0) 79 42 945 - 0          |  | DESCRIPTION<br><b>WE-TVSP Power TVS Diode</b> |                     |                                      | ORDER CODE<br><b>824500401</b>                                                                             |                        |
| www.we-online.com<br>eiSos@we-online.com                                              |  | SIZE<br>DO-214AC                              | REVISION<br>001.000 | STATUS<br>Draft                      | DATE<br>2015-11-10                                                                                         | BUSINESS UNIT<br>eiSos |
|  |  |                                               |                     |                                      | PAGE<br>4/7                                                                                                |                        |

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Classification Reflow Profile for SMT components:



Classification Reflow Soldering Profile:


| Profile Feature                                                  |                    | Value             |
|------------------------------------------------------------------|--------------------|-------------------|
| Preheat Temperature Min                                          | $T_{s\text{ min}}$ | 150 °C            |
| Preheat Temperature Max                                          | $T_{s\text{ max}}$ | 200 °C            |
| Preheat Time $t_s$ from $T_{s\text{ min}}$ to $T_{s\text{ max}}$ | $t_s$              | 60 - 120 seconds  |
| Ramp-up Rate ( $T_L$ to $T_p$ )                                  |                    | 3 °C/ second max. |
| Liquidous Temperature                                            | $T_L$              | 217 °C            |
| Time $t_L$ maintained above $T_L$                                | $t_L$              | 60 - 150 seconds  |
| Peak package body temperature                                    | $T_p$              | see table below   |
| Time within 5°C of actual peak tempereau                         | $t_p$              | 20 - 30 seconds   |
| Ramp-down Rate ( $T_L$ to $T_p$ )                                |                    | 6 °C/ second max. |
| Time 25°C to peak temperature                                    |                    | 8 minutes max.    |

refer to IPC/ JEDEC J-STD-020E

Package Classification Reflow Temperature:

| Properties                                           | Volume mm <sup>3</sup><br><350 | Volume mm <sup>3</sup><br>350-2000 | Volume mm <sup>3</sup><br>>2000 |
|------------------------------------------------------|--------------------------------|------------------------------------|---------------------------------|
| PB-Free Assembly I Package Thickness < 1.6 mm        | 260 °C                         | 260 °C                             | 260 °C                          |
| PB-Free Assembly I Package Thickness 1.6 mm - 2.5 mm | 260 °C                         | 250 °C                             | 245 °C                          |
| PB-Free Assembly I Package Thickness ≥ 2.5 mm        | 250 °C                         | 245 °C                             | 245 °C                          |

refer to IPC/ JEDEC J-STD-020E

|                                                                                                                                                                                                       |  |                                               |                     |                                      |                                                                                                            |                        |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------------------------------------------|---------------------|--------------------------------------|------------------------------------------------------------------------------------------------------------|------------------------|
| Würth Elektronik eiSos GmbH & Co. KG<br>EMC & Inductive Solutions<br><br>Max-Eyth-Str. 1<br>74638 Waldenburg<br>Germany<br>Tel. +49 (0) 79 42 945 - 0<br><br>www.we-online.com<br>eiSos@we-online.com |  | CREATED<br>KaS                                | CHECKED<br>RoD      | GENERAL TOLERANCE<br>DIN ISO 2768-1m | PROJECTION METHOD<br> |                        |
|                                                                                                                                                                                                       |  | DESCRIPTION<br><b>WE-TVSP Power TVS Diode</b> |                     |                                      | ORDER CODE<br><b>824500401</b>                                                                             |                        |
|                                                                                                                                                                                                       |  | SIZE<br>DO-214AC                              | REVISION<br>001.000 | STATUS<br>Draft                      | DATE<br>2015-11-10                                                                                         | BUSINESS UNIT<br>eiSos |
|                                                                                                                  |  |                                               |                     | PAGE<br>5/7                          |                                                                                                            |                        |

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

## Cautions & Warnings:

The following conditions apply to all goods within the product series of WE-TVSP of Würth Elektronik eiSos GmbH & Co. KG:

### General:

All recommendations according to the general technical specifications of the data-sheet have to be complied with. Further the TVS Diode is not designed for voltage stabilization with continuous power dissipation.

The disposal and operation of the product within ambient conditions which probably alloy or harm the component surface has to be avoided.

The exposure of steam, saline spray, atmosphere with reduced oxygen content, corrosive gases, rain or condensation and direct sunlight shall be prohibited.

If the product is potted in customer applications, the potting material might shrink and react chemically during and after hardening. According to this the product is exposed to the pressure and material of the potting material with the effect that the body and termination is possibly damaged by this pressure or the chemically reaction and so the electrical as well as the mechanical characteristics and the life time are in danger to be affected. After the potting material is cured, the body and termination of the product have to be checked if any reduced electrical or mechanical functions or destructions have occurred.

The responsibility for the applicability of customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products do also apply for customer specific products.

Cleaning agents that are used to clean the application might damage or change the characteristics of the component, body, pins or termination and might reduce the life time.

Direct mechanical impact to the product shall be prevented as the material of the body could flake or in the worst case it could break.

Signals operated continuously with a high ratio of direct-current voltage might have an influence on the product life time.

### Product specific:

Follow all instructions mentioned in the data sheet, especially:

- The solder profile has to be complied with according to the technical reflow soldering specification, otherwise no warranty will be sustained.
- All products shall be used before the end of the period of 12 months based on the product date-code, if not a 100% solderability can not be warranted.
- Violation of the technical product specifications such as exceeding the nominal rated voltage will result in the loss of warranty.

The general and product specific cautions comply with the state of the scientific and technical knowledge and are believed to be accurate and reliable; however, no responsibility is assumed for inaccuracies or incompleteness.

|                                                                                                                                                                                                                                                                                                                                        |                                               |                |                                      |  |                                                                                                            |                     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|----------------|--------------------------------------|--|------------------------------------------------------------------------------------------------------------|---------------------|
| <div>Würth Elektronik eiSos GmbH &amp; Co. KG<br/>EMC &amp; Inductive Solutions</div> <div>Max-Eyth-Str. 1<br/>74638 Waldenburg<br/>Germany<br/>Tel. +49 (0) 79 42 945 - 0</div> <div>www.we-online.com<br/>eiSos@we-online.com</div> <div></div> | CREATED<br>KaS                                | CHECKED<br>RoD | GENERAL TOLERANCE<br>DIN ISO 2768-1m |  | PROJECTION METHOD<br> |                     |
|                                                                                                                                                                                                                                                                                                                                        | DESCRIPTION<br><b>WE-TVSP Power TVS Diode</b> |                |                                      |  | ORDER CODE<br><b>824500401</b>                                                                             |                     |
|                                                                                                                                                                                                                                                                                                                                        |                                               |                |                                      |  | SIZE<br>DO-214AC                                                                                           | REVISION<br>001.000 |

## Important Notes

The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

### 1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

### 2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications. In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component. Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at [www.we-online.com](http://www.we-online.com).

### 3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

### 4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

### 5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.

### 6. Product Life Cycle


Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered. The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

### 7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG. Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

### 8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the “General Terms and Conditions of Würth Elektronik eiSos Group”, last version available at [www.we-online.com](http://www.we-online.com).

|                                                                                                                                                                                                                                                                                                                                                                                                                        |                                               |                |                                      |  |                                                                                                            |                     |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|----------------|--------------------------------------|--|------------------------------------------------------------------------------------------------------------|---------------------|
| <div>Würth Elektronik eiSos GmbH &amp; Co. KG<br/>EMC &amp; Inductive Solutions</div> <div>Max-Eyth-Str. 1<br/>74638 Waldenburg<br/>Germany<br/>Tel. +49 (0) 79 42 945 - 0</div> <div><a href="http://www.we-online.com">www.we-online.com</a><br/><a href="mailto:eiSos@we-online.com">eiSos@we-online.com</a></div> <div></div> | CREATED<br>KaS                                | CHECKED<br>RoD | GENERAL TOLERANCE<br>DIN ISO 2768-1m |  | PROJECTION METHOD<br> |                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                        | DESCRIPTION<br><b>WE-TVSP Power TVS Diode</b> |                |                                      |  | ORDER CODE<br><b>824500401</b>                                                                             |                     |
|                                                                                                                                                                                                                                                                                                                                                                                                                        |                                               |                |                                      |  | SIZE<br>DO-214AC                                                                                           | REVISION<br>001.000 |

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9