


Applications


- Defense & Aerospace
- Broadband Wireless



Product Features

- Frequency Range: DC - 18 GHz
- 44.3 dBm Nominal P_{SAT} at 6 GHz
- 64.4% Maximum PAE at 6 GHz
- 17.6 dB Linear Gain at 6 GHz
- Bias: V_D = 12 - 32 V, I_{DQ} = 100 - 250 mA
- Technology: QGaN25 on SiC
- Chip Dimensions: 0.82 x 1.44 x 0.10 mm

Functional Block Diagram



General Description

The Qorvo TGF2023-2-05 is a discrete 5 mm GaN on SiC HEMT which operates from DC-18 GHz. The TGF2023-2-05 is designed using Qorvo's proven QGaN25 production process. This process features advanced field plate techniques to optimize microwave power and efficiency at high drain bias operating conditions.

The TGF2023-2-05 typically provides 44.3 dBm of saturated output power with power gain of 14.6 dB at 6 GHz. The maximum power added efficiency is 64.4 % which makes the TGF2023-2-05 appropriate for high efficiency applications.

Lead-free and RoHS compliant

Pad Configuration

Pad No.	Symbol
1-4	V _G / RF IN
5	V _D / RF OUT
Backside	Source / Ground

Ordering Information

Part	ECCN	Description
TGF2023-2-05	3A001b.3.b	25 Watt GaN HEMT

Absolute Maximum Ratings

Parameter	Value
Drain to Gate Voltage (V_{DG})	100 V
Gate Voltage Range (V_G)	-10 to 0 V
Drain Current (I_D)	5 A
Gate Current (I_G)	-5 to 14 mA
Power Dissipation, CW (P_D)	See graph on pg.5.
CW Input Power (P_{IN})	+37 dBm
Channel Temperature (T_{CH})	275 °C
Mounting Temperature	320 °C
Storage Temperature	-65 to 150 °C

Operation of this device outside the parameter ranges given above may cause permanent damage. These are stress ratings only, and functional operation of the device at these conditions is not implied.

Recommended Operating Conditions⁽¹⁾

Parameter	Value
Drain Voltage Range (V_D)	12 - 40 V
Drain Quiescent Current (I_{DQ})	250 mA
Drain Current Under RF Drive (I_D) ²	0.5 A (Typ.)
Gate Voltage (V_G)	-3.0 V (Typ.)
Channel Temperature (T_{CH})	225 °C (Max.)
Dissipation Power, CW (P_D)	16 W
Dissipation Power, Pulsed (P_D) ^{2,3}	17.5 W

1. Electrical specifications are measured at specified test conditions. Specifications are not guaranteed over all recommended operating conditions.

2. 2.66 mS Pulse Width, 10% Duty Cycle

3. Carrier plate temperature is at 85 °C.

Model RF Characterization – Optimum Power Tune

Simulation conditions: T = 25 °C, Signal Duty Cycle = 10%

Parameter	Typical Value								Units
	3		6		8		10		
Frequency (F)	3		6		8		10		GHz
Drain Voltage (V_D)	28	28	28	28	28	28	28	28	V
Bias Current (I_{DQ})	100	250	100	250	100	250	100	250	mA
Output P3dB (P_{3dB})	44.2	44.1	44.4	44.3	44.4	44.3	44.4	44.3	dBm
PAE @ P3dB (PAE_{3dB})	61.7	60.9	60	59.2	57.4	57.5	55.3	55.4	%
Gain @ P3dB (G_{3dB})	19.1	20	13.8	14.6	11.5	12.2	9.7	10.4	dB
Parallel Resistance ⁽¹⁾ (R_p)	63.5	63.6	61.4	60.6	57.9	58	53.1	52.6	Ω ·mm
Parallel Capacitance ⁽¹⁾ (C_p)	0.268	0.275	0.297	0.303	0.297	0.303	0.320	0.325	pF/mm
Load Reflection Coefficient ⁽²⁾ (Γ_L)	0.44 \angle 17°	0.44 \angle 17°	0.46 \angle 37°	0.45 \angle 37°	0.46 \angle 48°	0.46 \angle 49°	0.47 \angle 62°	0.47 \angle 63°	--

Notes:

1. Large signal equivalent output network (normalized).
2. Characteristic Impedance (Z_0) = 5 Ω .

Model RF Characterization – Optimum Efficiency Tune

Simulation conditions: T = 25 °C, Signal Duty Cycle = 10%

Parameter	Typical Value								Units
	3		6		8		10		
Frequency (F)	3		6		8		10		GHz
Drain Voltage (V_D)	28	28	28	28	28	28	28	28	V
Bias Current (I_{DQ})	100	250	100	250	100	250	100	250	mA
Output P3dB (P_{3dB})	42.7	42.7	43.1	43.1	43.1	43.1	43.3	43.3	dBm
PAE @ P3dB (PAE_{3dB})	67.1	65.9	65.1	64.4	63	62.7	60.3	60.4	%
Gain @ P3dB (G_{3dB})	20.8	21.5	15.2	15.8	12.8	13.3	10.8	11.5	dB
Parallel Resistance ⁽¹⁾ (R_p)	115	112	103	98.6	98.9	93.9	84.5	82.7	Ω ·mm
Parallel Capacitance ⁽¹⁾ (C_p)	0.347	0.340	0.361	0.359	0.368	0.369	0.368	0.373	pF/mm
Load Reflection Coefficient ⁽²⁾ (Γ_L)	0.65 \angle 19°	0.64 \angle 19°	0.64 \angle 40°	0.63 \angle 40°	0.66 \angle 48°	0.64 \angle 52°	0.64 \angle 63°	0.64 \angle 64°	--

Notes:

1. Large signal equivalent output network (normalized).
2. Characteristic Impedance (Z_0) = 5 Ω .

Thermal and Reliability - CW ⁽¹⁾

Parameter	Test Conditions	Value	Units
Thermal Resistance, θ_{JC}	$P_D = 3\text{ W}$, $T_{baseplate} = 85^\circ\text{C}$	9.3	$^\circ\text{C/W}$
Channel Temperature, T_{CH}		113	$^\circ\text{C}$
Median Lifetime, T_M		2.5E11	Hrs
Thermal Resistance, θ_{JC}	$P_D = 6\text{ W}$, $T_{baseplate} = 85^\circ\text{C}$	10	$^\circ\text{C/W}$
Channel Temperature, T_{CH}		145	$^\circ\text{C}$
Median Lifetime, T_M		4.4E9	Hrs
Thermal Resistance, θ_{JC}	$P_D = 9\text{ W}$, $T_{baseplate} = 85^\circ\text{C}$	10.8	$^\circ\text{C/W}$
Channel Temperature, T_{CH}		182	$^\circ\text{C}$
Median Lifetime, T_M		8.6E7	Hrs
Thermal Resistance, θ_{JC}	$P_D = 12\text{ W}$, $T_{baseplate} = 85^\circ\text{C}$	11.8	$^\circ\text{C/W}$
Channel Temperature, T_{CH}		226	$^\circ\text{C}$
Median Lifetime, T_M		1.7E6	Hrs
Thermal Resistance, θ_{JC}	$P_D = 15\text{ W}$, $T_{baseplate} = 85^\circ\text{C}$	12.9	$^\circ\text{C/W}$
Channel Temperature, T_{CH}		278	$^\circ\text{C}$
Median Lifetime, T_M		3.6E4	Hrs

Notes:

- Assumes eutectic attach using 1.5 mil thick 80/20 AuSn mounted to a 10 mm x 10 mm x 40 mil CuMo Carrier Plate.


Thermal and Reliability - Pulsed ⁽¹⁾

Parameter	Test Conditions	Value	Units
Thermal Resistance, θ_{JC}	$P_D = 17.5\text{ W}$, $T_{baseplate} = 85^\circ\text{C}$ Pulse Width = 100 μs Duty Cycle = 5%	4.7	$^\circ\text{C/W}$
Channel Temperature, T_{CH}		168	$^\circ\text{C}$
Median Lifetime, T_M		7.1E9	Hrs
Thermal Resistance, θ_{JC}	$P_D = 17.5\text{ W}$, $T_{baseplate} = 85^\circ\text{C}$ Pulse Width = 100 μs Duty Cycle = 10%	5.0	$^\circ\text{C/W}$
Channel Temperature, T_{CH}		172	$^\circ\text{C}$
Median Lifetime, T_M		2.3E9	Hrs
Thermal Resistance, θ_{JC}	$P_D = 17.5\text{ W}$, $T_{baseplate} = 85^\circ\text{C}$ Pulse Width = 100 μs Duty Cycle = 20%	5.3	$^\circ\text{C/W}$
Channel Temperature, T_{CH}		177	$^\circ\text{C}$
Median Lifetime, T_M		6.9E8	Hrs
Thermal Resistance, θ_{JC}	$P_D = 17.5\text{ W}$, $T_{baseplate} = 85^\circ\text{C}$ Pulse Width = 100 μs Duty Cycle = 50%	6.6	$^\circ\text{C/W}$
Channel Temperature, T_{CH}		200	$^\circ\text{C}$
Median Lifetime, T_M		3.1E7	Hrs


Notes:

- Assumes eutectic attach using 1.5 mil thick 80/20 AuSn mounted to a 10 mm x 10 mm x 40 mil CuMo Carrier Plate.


Median Lifetime







Maximum Channel Temperature - CW



Peak Channel Temperature - Pulsed




Maximum Gain Performance



Model Load Pull Contours – 3 GHz

Simulated signal: 10% pulses
 Vd = 28 V, Idq = 100 mA


3GHz, Load-pull



Model Load Pull Contours – 6 GHz

Simulated signal: 10% pulses
 Vd = 28 V, Idq = 100 mA


6GHz, Load-pull



Model Load Pull Contours – 8 GHz

Simulated signal: 10% pulses
Vd = 28 V, Idq = 100 mA


8GHz, Load-pull



Model Load Pull Contours – 10 GHz

Simulated signal: 10% pulses
 Vd = 28 V, Idq = 100 mA


10GHz, Load-pull



Model Load Pull Contours – 3 GHz

Simulated signal: 10% pulses
 Vd = 28 V, Idq = 250 mA


3GHz, Load-pull



Model Load Pull Contours – 6 GHz

Simulated signal: 10% pulses
 Vd = 28 V, Idq = 250 mA


6GHz, Load-pull



Model Load Pull Contours – 8 GHz

Simulated signal: 10% pulses
Vd = 28 V, Idq = 250 mA


8GHz, Load-pull







Model Load Pull Contours – 10 GHz

Simulated signal: 10% pulses
 Vd = 28 V, Idq = 250 mA





10GHz, Load-pull







Model Drive-up Data – 3 GHz







Model Drive-up Data – 6 GHz



Model Drive-up Data – 8 GHz




Model Drive-up Data – 10 GHz



Model

A non-linear model is available for download from Modelithics (at <http://www.modelithics.com/mvp/Qorvo&tab=3>) by approved Qorvo customers. The model is compatible with the industry's most popular design software including Agilent ADS and National Instruments/AWR applications. Once on the Modelithics web page, the user will need to register for a free license before being granted the download.

Mechanical Drawing



Bond Pads

Pad No.	Description	Dimensions
1-4	Gate	0.154 x 0.115
5	Drain	0.154 x 1.01
Die Backside	Source / Ground	0.824 x 1.442

Notes:

1. Units: millimeters
2. Thickness: 0.100 mm
3. Die x,y size tolerance: +/- 0.050 mm

Assembly Notes

Component placement and adhesive attachment assembly notes:

- Vacuum pencils and/or vacuum collets are the preferred method of pick up.
- Air bridges must be avoided during placement.
- The force impact is critical during auto placement.
- Organic attachment (i.e. epoxy) not recommended.

Reflow process assembly notes:

- Use AuSn (80/20) solder and limit exposure to temperatures above 300°C to 3-4 minutes, maximum.
- An alloy station or conveyor furnace with reducing atmosphere should be used.
- Do not use any kind of flux.
- Coefficient of thermal expansion matching is critical for long-term reliability.
- Devices must be stored in a dry nitrogen atmosphere.

Interconnect process assembly notes:

- Ball bonding is the preferred interconnect technique, except where noted on the assembly diagram.
- Force, time, and ultrasonics are critical bonding parameters.
- Aluminum wire should not be used.
- Devices with small pad sizes should be bonded with 0.0007-inch wire.

Disclaimer

GaN/SiC devices are susceptible to damage from Electrostatic Discharge. Proper precautions should be observed during handling, assembly and test.

Bias-up Procedure

1. Set V_G to -5 V.
2. Set I_D limit to 280 mA.
3. Set V_D to 28 V.
4. Adjust V_G more positive until quiescent I_D is 250 mA.
5. Set I_D limit to 2 A.
6. Apply RF signal.

Bias-down Procedure

1. Turn off RF signal.
2. Turn off V_D and wait 1 second to allow drain capacitor dissipation.
3. Turn off V_G .

Product Compliance Information

ESD Sensitivity Ratings



Caution! ESD-Sensitive Device

GaN devices are susceptible to damage from Electrostatic Discharge. Proper precautions should be observed during handling, assembly and test.

Not HAST compliant.

Solderability

Compatible with gold/tin (320°C maximum reflow temperature) soldering processes.

RoHs Compliance

This part is compliant with EU 2002/95/EC RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C₁₅H₁₂Br₄O₂) Free
- PFOS Free
- SVHC Free

Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about Qorvo:

Web: www.qorvo.com

Tel: +1.972.994.8465

Email: info-sales@qorvo.com Fax: +1.972.994.8504

For technical questions and application information: Email: info-products@qorvo.com

Important Notice

The information contained herein is believed to be reliable. Qorvo makes no warranties regarding the information contained herein. Qorvo assumes no responsibility or liability whatsoever for any of the information contained herein. Qorvo assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for Qorvo products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

Qorvo products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9