Frequency Synthesizer SSN-1932A-119+

50Ω 1832 to 1932 MHz

The Big Deal

- Fractional N synthesizer
- Low phase noise and spurious
- Very small size 0.60" x 0.60" x 0.138"



CASE STYLE: KJ1367

Product Overview

The SSN-1932A-119+ is a Frequency Synthesizer, designed to operate from 1832 to 1932 MHz for WiMAX 2.5GHz application. The SSN-1932A-119+ is packaged in a metal case (size of 0.60" x 0.60" x 0.138") to shield against unwanted signals and noise.

Key Features

Feature	Advantages
Low phase noise and spurious: • Phase Noise: -99 dBc/Hz typ. @ 10 kHz offset • Step Size Spurious: -87 dBc typ. • Comparison Spurious: -95 dBc typ. • Reference Spurious: -92 dBc typ.	Low phase noise and spurious improve system EVM (Error Vector Magnitude).
Robust design and construction	To enhance the robustness of SSN-1932A-119+, each internal component is secured to the substrate with chip bonder, thereby eliminating the risk of tombstoning during subsequent solder reflow operations by the customer.
Small size, 0.60" x 0.60" x 0.138"	The small size enables the SSN-1932A-119+ to be used in compact designs.

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Surface Mount

Frequency Synthesizer

SSN-1932A-119+

50Ω 1832 to 1932 MHz

Features

- Fractional N synthesizer
- Integrated VCO + PLL
- Low phase noise and spurious
- Robust design and construction
- Low operating voltage (VCC VCO=+4.85V, VCC PLL=+3.2V)
- Small size 0.60" x 0.60" x 0.138"



CASE STYLE: KJ1367
PRICE: $29.95 ea. QTY (1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.


Applications

- WiMAX 2.5GHz

General Description

The SSN-1932A-119+ is a Frequency Synthesizer, designed to operate from 1832 to 1932 MHz for WiMAX 2.5GHz application. The SSN-1932A-119+ is packaged in a metal case (size of 0.60" x 0.60" x 0.138") to shield against unwanted signals and noise. To enhance the robustness of SSN-1932A-119+, each internal component is secured to the substrate with chip bonder, thereby eliminating the risk of tombstoning during subsequent solder reflow operations by the customer.

Simplified Schematic



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Electrical Specifications *(over operating temperature -40°C to +85°C)*

Parameters		Test Conditions	Min.	Typ.	Max.	Units
Frequency Range		-	1832	-	1932	MHz
Step Size		-	-	125	-	kHz
Comparison Frequency		-	-	13	-	MHz
Settling Time		Within ± 1 kHz	-	30	50	mSec
Output Power		-	+1.0	+4.0	+7.0	dBm
SSB Phase Noise		@ 100 Hz offset	-	-83	-	dBc/Hz
		@ 1 kHz offset	-	-87	-83	
		@ 10 kHz offset	-	-99	-94	
		@ 100 kHz offset	-	-126	-121	
		@ 1 MHz offset	-	-147	-141	
Integrated SSB Phase Noise		@1kHz to 10MHz	-	-50	-	dBc
Step Size Spurious Suppression		Step Size 125 kHz	-	-87	-66	dBc
0.5 Step Size Spurious Suppression		0.5 Step Size 62.5 kHz	-	-84	-65	
Reference Spurious Suppression		Ref. Freq. 52 MHz	-	-92	-65	
Comparison Spurious Suppression		Comp. Freq. 13 MHz	-	-95	-84	
Non - Harmonic Spurious Suppression		-	-	-90	-	
Harmonic Suppression		-	-	-23	-16	
VCO Supply Voltage		+5.00	+4.75	+4.85	+5.25	V
PLL Supply Voltage		+3.20	+3.10	+3.20	+3.30	
VCO Supply Current		-	-	46	55	mA
PLL Supply Current		-	-	14	22	
Reference Input (External)	Frequency	52 (square wave)	-	52	-	MHz
	Amplitude	1	-	1	-	V_{P-P}
	Input impedance	-	-	100	-	KΩ
	Phase Noise @ 1 kHz offset	-	-	-135	-	dBc/Hz
RF Output port Impedance		-	-	50	-	Ω
Input Logic Level	Input high voltage	-	2.65	-	-	V
	Input low voltage	-	-	-	0.60	V
Digital Lock Detect	Locked	-	2.70	-	3.30	V
	Unlocked	-	-	-	0.40	V
Frequency Synthesizer PLL		-	ADF4153			
PLL Programming		-	3-wire serial 3.2V CMOS			
Register Map @ 1932 MHz	R0_Register	-	(MSB) 10010100000000100000000 (LSB)			
	R1_Register	-	(MSB) 10101000000000110100001 (LSB)			
	R2_Register	-	(MSB) 111100010 (LSB)			
	R3_Register	-	(MSB) 1111000111 (LSB)			

Absolute Maximum Ratings

Parameters	Ratings
VCO Supply Voltage	5.6V
PLL Supply Voltage	4.0V
VCO Supply Voltage to PLL Supply Voltage	-0.3V to +5.8V
Reference Frequency Voltage	-0.3Vmin, VCC PLL +0.3Vmax
Data, Clock, LE Levels	-0.3Vmin, VCC PLL +0.3Vmax
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +100°C

Permanent damage may occur if any of these limits are exceeded

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Typical Performance Data

FREQUENCY (MHz)	POWER OUTPUT (dBm)			VCO CURRENT (mA)			PLL CURENT (mA)		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
1832	3.74	4.28	4.63	45.08	47.13	48.68	13.26	14.83	17.37
1838	3.70	4.25	4.60	44.98	47.04	48.61	13.45	15.03	17.60
1852	3.71	4.01	4.58	44.89	46.96	48.49	13.51	15.10	17.69
1866	3.69	4.13	4.51	44.73	46.84	48.39	13.50	15.09	17.68
1880	3.61	4.17	4.42	44.48	46.63	48.23	13.45	15.05	17.65
1894	3.63	4.13	4.42	44.36	46.49	48.12	13.41	15.01	17.61
1908	3.64	4.10	4.36	44.17	46.32	48.02	13.40	14.99	17.61
1922	3.61	3.85	4.37	44.06	46.21	47.90	13.32	14.91	17.52
1932	3.59	4.04	4.30	43.92	46.11	47.83	13.46	15.06	17.68

FREQUENCY (MHz)	HARMONICS (dBc)					
	F2			F3		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
1832	-29.94	-32.20	-33.86	-22.79	-23.52	-24.52
1838	-29.75	-32.60	-34.13	-22.87	-23.33	-24.46
1852	-31.49	-34.43	-35.12	-22.24	-23.44	-24.50
1866	-34.54	-37.55	-37.83	-22.13	-23.04	-23.96
1880	-34.74	-38.34	-38.68	-21.37	-22.53	-23.41
1894	-37.18	-41.65	-41.89	-21.38	-23.06	-23.93
1908	-37.93	-42.43	-43.38	-21.25	-22.10	-23.12
1922	-37.93	-43.70	-47.72	-21.60	-23.47	-25.00
1932	-38.18	-46.13	-49.63	-20.96	-22.10	-23.10

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @OFFSETS +25°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
1832	-82.91	-90.85	-99.71	-127.02	-147.21
1838	-83.59	-91.85	-100.27	-127.27	-148.31
1852	-82.07	-90.31	-100.26	-127.42	-147.64
1866	-82.91	-90.00	-100.15	-127.25	-147.47
1880	-83.49	-91.92	-99.84	-126.82	-147.50
1894	-84.35	-89.70	-100.01	-126.85	-147.44
1908	-82.81	-88.66	-99.28	-126.81	-147.07
1922	-82.93	-91.19	-100.29	-126.47	-147.26
1932	-84.68	-87.47	-99.86	-126.44	-147.12

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @OFFSETS -45°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
1832	-85.82	-93.86	-98.94	-127.89	-148.82
1838	-83.69	-92.58	-99.87	-128.13	-149.29
1852	-85.94	-92.90	-99.12	-128.07	-148.60
1866	-81.76	-93.06	-100.53	-128.31	-147.73
1880	-82.55	-93.40	-99.79	-127.96	-149.06
1894	-83.16	-92.87	-99.74	-127.72	-148.40
1908	-83.68	-92.50	-99.26	-127.41	-148.56
1922	-83.65	-93.16	-99.93	-127.32	-148.34
1932	-79.98	-91.35	-99.26	-127.22	-147.70

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @OFFSETS +85°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
1832	-84.17	-90.34	-99.76	-126.07	-146.66
1838	-86.69	-92.19	-98.67	-125.53	-146.40
1852	-84.86	-90.44	-98.58	-125.65	-145.97
1866	-83.85	-89.59	-99.36	-125.78	-146.09
1880	-85.40	-90.53	-99.27	-125.51	-146.01
1894	-84.70	-89.94	-98.09	-125.25	-145.92
1908	-83.89	-89.70	-99.20	-125.47	-145.94
1922	-85.46	-88.24	-99.28	-125.26	-145.91
1932	-84.12	-90.05	-98.73	-125.20	-145.66

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

COMPARISON SPURIOUS ORDER	COMPARISON SPURIOUS @Fcarrier 1832MHz+(n*Fcomparison) (dBc) note 1			COMPARISON SPURIOUS @Fcarrier 1882MHz+(n*Fcomparison) (dBc) note 1			COMPARISON SPURIOUS @Fcarrier 1932MHz+(n*Fcomparison) (dBc) note 1		
n	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-5	-97.62	-97.39	-94.61	-94.04	-94.88	-93.56	-94.06	-93.76	-94.66
-4	-102.22	-97.74	-96.39	-94.92	-97.91	-93.74	-96.25	-94.34	-93.04
-3	-96.34	-97.09	-98.65	-94.97	-94.55	-98.46	-96.71	-96.41	-94.40
-2	-94.99	-97.09	-94.99	-92.83	-92.19	-97.09	-94.29	-96.35	-97.24
-1	-100.21	-96.97	-94.34	-92.18	-92.38	-94.62	-95.29	-97.20	-100.57
0 note 2	-	-	-	-	-	-	-	-	-
+1	-99.17	-100.54	-96.15	-93.21	-94.87	-97.04	-95.32	-99.01	-101.27
+2	-99.28	-103.85	-97.35	-98.61	-97.15	-98.88	-98.75	-99.00	-102.15
+3	-102.28	-104.08	-101.56	-101.30	-101.01	-100.85	-100.53	-101.78	-102.74
+4	-104.22	-118.78	-108.00	-113.60	-110.89	-115.91	-108.66	-109.71	-118.54
+5	-102.18	-109.10	-103.34	-116.91	-109.74	-107.99	-106.30	-106.45	-112.27

Note 1: Comparison frequency 13 MHz
Note 2: All spurs are referenced to carrier signal (n=0).

REFERENCE SPURIOUS ORDER	REFERENCE SPURIOUS @Fcarrier 1832MHz+(n*Freference) (dBc) note 3			REFERENCE SPURIOUS @Fcarrier 1882MHz+(n*Freference) (dBc) note 3			REFERENCE SPURIOUS @Fcarrier 1932MHz+(n*Freference) (dBc) note 3		
n	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-5	-92.47	-92.42	-95.44	-90.13	-91.53	-96.14	-90.04	-91.66	-95.15
-4	-94.42	-94.90	-97.57	-94.70	-95.64	-95.37	-92.87	-94.89	-87.66
-3	-89.05	-93.42	-98.18	-90.79	-94.10	-95.12	-73.02	-77.01	-82.71
-2	-89.09	-91.09	-95.14	-87.64	-89.97	-93.78	-88.11	-89.90	-92.65
-1	-102.17	-97.57	-96.61	-94.83	-97.42	-93.86	-96.21	-94.56	-92.90
0 note 4	-	-	-	-	-	-	-	-	-
+1	-104.40	-120.04	-107.36	-110.93	-110.76	-116.84	-108.01	-109.36	-118.08
+2	-106.30	-106.95	-103.06	-107.85	-104.49	-113.85	-98.89	-102.26	-113.64
+3	-113.04	-104.89	-108.49	-91.35	-94.64	-100.39	-75.83	-80.17	-86.29
+4	-94.80	-94.30	-95.77	-95.69	-94.43	-94.29	-89.87	-97.73	-91.87
+5	-91.96	-96.10	-103.57	-90.90	-95.85	-98.29	-90.73	-94.93	-94.65

Note 3: Reference frequency 52 MHz
Note 4: All spurs are referenced to carrier signal (n=0).


Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.


STEP SIZE SPURIOUS ORDER	0.5 STEP SIZE & STEP SIZE SPURIOUS @Fcarrier 1832MHz+(n*Fstep size) (dBc) note 5			0.5 STEP SIZE & STEP SIZE SPURIOUS @Fcarrier 1882MHz+(n*Fstep size) (dBc) note 5			0.5 STEP SIZE & STEP SIZE SPURIOUS @Fcarrier 1932MHz+(n*Fstep size) (dBc) note 5		
n	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-5.0	-111.38	-115.70	-114.06	-115.77	-112.72	-113.72	-111.68	-112.29	-111.77
-4.5	-110.62	-110.17	-112.69	-114.07	-110.95	-112.05	-108.40	-107.69	-107.58
-4.0	-111.99	-110.75	-105.25	-112.32	-112.35	-111.06	-112.45	-109.58	-106.15
-3.5	-110.90	-110.21	-107.98	-110.92	-108.90	-106.34	-104.06	-98.96	-100.95
-3.0	-108.58	-105.31	-107.89	-107.31	-105.86	-106.24	-108.87	-106.75	-103.13
-2.5	-102.69	-101.61	-104.86	-102.31	-103.08	-104.32	-102.01	-103.58	-101.47
-2.0	-100.58	-101.69	-98.78	-100.77	-101.84	-101.58	-98.57	-96.16	-101.94
-1.5	-96.19	-90.10	-96.36	-91.45	-93.48	-96.90	-96.58	-92.39	-94.34
-1.0	-86.82	-85.53	-88.04	-88.55	-85.68	-86.75	-88.24	-85.14	-88.62
-0.5	-86.07	-87.06	-83.62	-86.74	-87.58	-84.77	-84.73	-85.57	-83.36
0 note 6	-	-	-	-	-	-	-	-	-
+0.5	-83.17	-82.94	-83.81	-82.50	-82.12	-86.70	-86.21	-86.31	-83.96
+1.0	-89.06	-87.92	-85.32	-88.45	-90.36	-89.60	-87.24	-88.71	-86.74
+1.5	-93.07	-92.79	-93.84	-95.89	-96.90	-94.79	-94.06	-93.30	-95.84
+2.0	-96.70	-101.04	-101.59	-98.60	-99.67	-99.21	-100.78	-95.93	-100.00
+2.5	-103.00	-105.56	-101.08	-101.54	-99.91	-100.56	-103.83	-103.10	-100.74
+3.0	-109.17	-109.16	-105.38	-101.33	-107.15	-108.90	-103.03	-105.39	-102.78
+3.5	-106.14	-110.26	-108.96	-107.02	-109.47	-108.91	-106.60	-100.63	-101.74
+4.0	-112.19	-108.42	-106.53	-110.03	-109.33	-109.73	-112.47	-111.31	-112.72
+4.5	-114.77	-113.52	-110.65	-107.42	-113.66	-112.37	-109.72	-107.28	-107.56
+5.0	-113.52	-110.75	-113.01	-111.41	-112.36	-112.35	-111.30	-112.98	-112.84


Note 5: Step size 125 kHz
Note 6: All spurs are referenced to carrier signal (n=0).

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Typical Performance Curves









Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.


PHASE NOISE @100Hz offset




PHASE NOISE @1kHz offset




PHASE NOISE @10kHz offset



PHASE NOISE @100kHz offset




PHASE NOISE @1MHz offset




Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.


COMPARISON SPURIOUS
Vs FREQ. OFFSET @ Fcar = 1832MHz




REFERENCE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 1832MHz




COMPARISON SPURIOUS
Vs FREQ. OFFSET @ Fcar = 1882MHz




REFERENCE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 1882MHz



COMPARISON SPURIOUS
Vs FREQ. OFFSET @ Fcar = 1932MHz




REFERENCE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 1932MHz




Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.


0.5 STEP SIZE & STEP SIZE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 1832MHz



0.5 STEP SIZE & STEP SIZE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 1882MHz




0.5 STEP SIZE & STEP SIZE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 1932MHz



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Pin Configuration




Pin Connection

Pin Number	Function
1	CLOCK
2	DATA
3	LE
4	REF IN
5	GND
6	GND
7	VCC VCO
8	GND
9	RF OUT
10	GND
11	LOCK DET
12	VCC PLL


Recommended Application Circuit

Note: REF IN and RF OUT ports are internally AC coupled.



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Device Marking



Additional Detailed Technical Information

Additional information is available on our web site. To access this information enter the model number on our web site home page.

Case Style: KJ1367

Tape & Reel: TR-F95

Suggested Layout for PCB Design: PL-317

Evaluation Board: TB-552+

Environment Ratings: ENV03T2

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9