

## High-current terminal block - PTPOWER 95-3L/N/FE - 3260118

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



High-current terminal block, Blocked, Connection method: Push-in connection, Number of positions: 5, Cross section: 25 mm<sup>2</sup> - 95 mm<sup>2</sup>, AWG: 4 - 3/0, Width: 125 mm, Color: gray/blue/black-yellow, Mounting type: NS 35/15

### Product Features

- ✓ Quick and easy connection is now also possible for large conductors with the high-current terminal block
- ✓ The Push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors
- ✓ The compact design enables wiring in a confined space
- ✓ In addition to using the existing test connection, pick-off terminal blocks can be connected, each of which can also accommodate two test cables



### Key commercial data

|                                      |           |
|--------------------------------------|-----------|
| Packing unit                         | 1 pc      |
| Minimum order quantity               | 2 pc      |
| Weight per Piece (excluding packing) | 970.0 GRM |
| Custom tariff number                 | 85369010  |
| Country of origin                    | Poland    |

### Technical data

#### General

|                                         |                                                         |
|-----------------------------------------|---------------------------------------------------------|
| Number of levels                        | 1                                                       |
| Number of connections                   | 2                                                       |
| Color                                   | gray/blue/black-yellow                                  |
| Insulating material                     | PA                                                      |
| Inflammability class according to UL 94 | V0                                                      |
| Maximum load current                    | 232 A (with 95 mm <sup>2</sup> conductor cross section) |
| Rated surge voltage                     | 8 kV                                                    |
| Pollution degree                        | 3                                                       |
| Surge voltage category                  | III                                                     |

# High-current terminal block - PTPOWER 95-3L/N/FE - 3260118

## Technical data

### General

|                                  |                                                         |
|----------------------------------|---------------------------------------------------------|
| Insulating material group        | I                                                       |
| Connection in acc. with standard | IEC 60947-7-1                                           |
| Maximum load current             | 232 A (with 95 mm <sup>2</sup> conductor cross section) |
| Nominal current I <sub>N</sub>   | 232 A                                                   |
| Nominal voltage U <sub>N</sub>   | 1500 V                                                  |
| Maximum load current             | 232 A (with 95 mm <sup>2</sup> conductor cross section) |
| Open side panel                  | nein                                                    |
| Number of positions              | 5                                                       |

### Dimensions

|                 |          |
|-----------------|----------|
| Width           | 125 mm   |
| Length          | 105.5 mm |
| Height NS 35/15 | 108.7 mm |

### Connection data

|                                                                            |                    |
|----------------------------------------------------------------------------|--------------------|
| Connection in acc. with standard                                           | IEC 60947-7-1      |
| Connection method                                                          | Push-in connection |
| Conductor cross section solid min.                                         | 25 mm <sup>2</sup> |
| Conductor cross section solid max.                                         | 95 mm <sup>2</sup> |
| Conductor cross section AWG/kcmil min.                                     | 4                  |
| Conductor cross section AWG/kcmil max.                                     | 3/0                |
| Conductor cross section stranded min.                                      | 25 mm <sup>2</sup> |
| Conductor cross section stranded max.                                      | 95 mm <sup>2</sup> |
| Min. AWG conductor cross section, stranded                                 | 4                  |
| Max. AWG conductor cross section, stranded                                 | 4/0                |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 25 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 95 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule with plastic sleeve min.    | 25 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule with plastic sleeve max.    | 95 mm <sup>2</sup> |
| Cross section with insertion bridge, solid max.                            | 95 mm <sup>2</sup> |
| Cross section with insertion bridge, stranded max.                         | 70 mm <sup>2</sup> |
| Cross section with insertion bridge, solid max.                            | 95 mm <sup>2</sup> |
| Cross section with insertion bridge, stranded max.                         | 70 mm <sup>2</sup> |
| Stripping length                                                           | 40 mm              |

## High-current terminal block - PTPOWER 95-3L/N/FE - 3260118

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141120 |
| eCl@ss 4.1 | 27141120 |
| eCl@ss 5.0 | 27141120 |
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 7.0 | 27141120 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Approvals

#### Approvals

---

##### Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

---

##### Ex Approvals

---

##### Approvals submitted

---

##### Approval details

## High-current terminal block - PTPOWER 95-3L/N/FE - 3260118

### Approvals

|                                                                                                 |        |
|-------------------------------------------------------------------------------------------------|--------|
| UL Recognized  |        |
| mm²/AWG/kcmil                                                                                   | 4-4/0  |
| Nominal current I <sub>N</sub>                                                                  | 230 A  |
| Nominal voltage U <sub>N</sub>                                                                  | 1000 V |

|                                                                                                  |        |
|--------------------------------------------------------------------------------------------------|--------|
| cUL Recognized  |        |
|                                                                                                  | C      |
| mm²/AWG/kcmil                                                                                    | 4-4/0  |
| Nominal current I <sub>N</sub>                                                                   | 230 A  |
| Nominal voltage U <sub>N</sub>                                                                   | 1000 V |

|     |
|-----|
| EAC |
|-----|

|                                                                                                      |
|------------------------------------------------------------------------------------------------------|
| cULus Recognized  |
|------------------------------------------------------------------------------------------------------|

### Drawings

Circuit diagram



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9