

NOTES:

1. PARTS ARE SHIPPED NON-ASSEMBLED.
2. SEE SHEET 4 FOR PACKAGING PLAN.

| REVISIONS |                     |           |          |
|-----------|---------------------|-----------|----------|
| REV.      | DESCRIPTION         | DATE      | APPROVED |
| B         | Engineering Release | 7/11/2018 | G.O.     |

PART NUMBER CONFIGURATION,

LPV3-XXXXX-XXX

LED COLOR (SEE PAGE 3)

LIGHT PIPE CALLOUT (SEE PAGE 2, TABLES A & B)




**FLAT FACE LENS**

DIMENSIONS ARE APPLICABLE TO BOTH LENS FACES UNLESS OTHERWISE NOTED



PCB SURFACE



**DOME FACE LENS**

|                                                 |                  |                                                                                |                |
|-------------------------------------------------|------------------|--------------------------------------------------------------------------------|----------------|
| STANDARD TOLERANCE (UNLESS OTHERWISE SPECIFIED) |                  | <p>4 THOMAS, IRVINE, CA. 92618<br/>TEL: (949) 951-8808 FAX: (949) 951-3974</p> |                |
| DECIMALS                                        | ANGULAR          |                                                                                |                |
| .X $\pm .1$                                     | X° $\pm 1^\circ$ | TITLE: BIVAR LIGHT PIPE SYSTEM                                                 |                |
| .XX $\pm .02$                                   |                  | SAT VERTICAL, 3MM, SINGLE STATION                                              |                |
| .XXX $\pm .010$                                 |                  | PART NO: LPV3-XXXXX-XXX                                                        | REVISION: B    |
| DESIGNED: K. BARON                              | DATE: 07/11/18   | CAGE CODE: 32559                                                               |                |
| REVISED: N/A                                    | DATE: N/A        | SCALE: 2:1                                                                     | SHEET # 1 OF 5 |
| CHECKED: TD. NGUYEN                             | DATE: 07/11/18   | CAD GENERATED DOCUMENT, DO NOT MEASURE DRAWING                                 |                |

| REVISIONS |             |      |          |
|-----------|-------------|------|----------|
| REV.      | DESCRIPTION | DATE | APPROVED |
|           | See Sheet 1 |      |          |

## STANDARD ORDERING INFORMATION

| TABLE A - FLAT FACE LENS |                |
|--------------------------|----------------|
| PART NO.                 | H ± .01        |
| LPV3-0350F-XXX           | 0.350 [8.9mm]  |
| LPV3-0400F-XXX           | 0.400 [10.2mm] |
| LPV3-0450F-XXX           | 0.450 [11.4mm] |
| LPV3-0500F-XXX           | 0.500 [12.7mm] |
| LPV3-0550F-XXX           | 0.550 [14.0mm] |
| LPV3-0600F-XXX           | 0.600 [15.2mm] |
| LPV3-0750F-XXX           | 0.750 [19.1mm] |
| LPV3-1000F-XXX           | 1.000 [25.4mm] |
| LPV3-1250F-XXX           | 1.250 [31.8mm] |
| LPV3-1500F-XXX           | 1.500 [38.1mm] |
| LPV3-1750F-XXX           | 1.750 [44.5mm] |
| LPV3-2000F-XXX           | 2.000 [50.8mm] |

| TABLE B - DOME FACE LENS |                |
|--------------------------|----------------|
| PART NO.                 | H ± .01        |
| LPV3-0350D-XXX           | 0.350 [8.9mm]  |
| LPV3-0400D-XXX           | 0.400 [10.2mm] |
| LPV3-0450D-XXX           | 0.450 [11.4mm] |
| LPV3-0500D-XXX           | 0.500 [12.7mm] |
| LPV3-0550D-XXX           | 0.550 [14.0mm] |
| LPV3-0600D-XXX           | 0.600 [15.2mm] |
| LPV3-0750D-XXX           | 0.750 [19.1mm] |
| LPV3-1000D-XXX           | 1.000 [25.4mm] |
| LPV3-1250D-XXX           | 1.250 [31.8mm] |
| LPV3-1500D-XXX           | 1.500 [38.1mm] |
| LPV3-1750D-XXX           | 1.750 [44.5mm] |
| LPV3-2000D-XXX           | 2.000 [50.8mm] |

|                                                |                |
|------------------------------------------------|----------------|
| <b>BIVAR</b> <sup>®</sup>                      |                |
| PART NO:<br>LPV3-XXXXX-XXX                     | REVISION:<br>B |
| SCALE: NONE                                    | SHEET # 2 OF 5 |
| CAD GENERATED DOCUMENT, DO NOT MEASURE DRAWING |                |



| Order Code<br>XXX | Emitted<br>Color | Peak<br>Wave L.        | Electro-Optical Data @20mA, 25°C |     |     |             | Polarity<br>Diagram |
|-------------------|------------------|------------------------|----------------------------------|-----|-----|-------------|---------------------|
|                   |                  | $\lambda_p$ [nm]       | $V_f$ [V]                        |     |     | $I_v$ [mcd] |                     |
|                   |                  | Chroma                 | MIN                              | TYP | MAX | TYP         |                     |
|                   |                  | TYP                    |                                  |     |     |             |                     |
| R130              | Red              | 640                    | 1.7                              | 2.0 | 2.5 | 130         | FIGURE A            |
| R480              | Red              | 630                    | 1.7                              | 2.0 | 2.5 | 480         | FIGURE B            |
| A220              | Amber            | 610                    | 1.7                              | 2.0 | 2.5 | 220         |                     |
| O170              | Orange           | 590                    | 1.7                              | 2.0 | 2.5 | 170         |                     |
| Y50               | Yellow           | 570                    | 1.7                              | 2.0 | 2.5 | 50          |                     |
| G850              | Green            | 520                    | 2.8                              | 3.2 | 3.7 | 850         |                     |
| B150              | Blue             | 465                    | 2.8                              | 3.2 | 3.7 | 150         |                     |
| W305              | White            | X = 0.308<br>Y = 0.305 | 2.8                              | 3.0 | 3.7 | 1750        |                     |
| OY                | Orange           | 590                    | 1.7                              | 2.0 | 2.5 | 190         | FIGURE C            |
|                   | Yellow           | 572                    | 1.7                              | 2.0 | 2.5 | 60          |                     |
| RY                | Red              | 640                    | 1.7                              | 2.0 | 2.5 | 110         | FIGURE D            |
|                   | Yellow           | 572                    | 1.7                              | 2.0 | 2.5 | 55          |                     |
| RG                | Red              | 640                    | 1.7                              | 2.0 | 2.5 | 200         | FIGURE E            |
|                   | Green            | 520                    | 2.8                              | 3.2 | 3.7 | 810         |                     |
| RW                | Red              | 630                    | 1.7                              | 2.0 | 2.5 | 130         | FIGURE F            |
|                   | White            | X = 0.28<br>Y = 0.29   | 2.8                              | 3.2 | 3.7 | 520         |                     |
| RB                | Red              | 650                    | 1.7                              | 2.0 | 2.5 | 80          | FIGURE G            |
|                   | Blue             | 465                    | 2.8                              | 3.2 | 3.7 | 150         |                     |
| RGB               | Red              | 643                    | 1.7                              | 2.0 | 2.5 | 95          | FIGURE H            |
|                   | Green            | 515                    | 2.8                              | 3.3 | 3.7 | 730         |                     |
|                   | Blue             | 460                    | 2.8                              | 3.3 | 3.7 | 120         |                     |

Note: 10% Duty Cycle, Pulse Width  $\leq 0.1$ msec for Peak If.



FIG. A



FIG. B



FIG. C



FIG. D



FIG. E



FIG. F



FIG. G



FIG. H

**BIVAR**®

PART NO:  
LPV3-XXXXX-XXX

REVISION:  
B

SCALE: 2:1

SHEET # 3 OF 5

CAD GENERATED DOCUMENT, DO NOT MEASURE DRAWING

**PACKAGING PLAN**

PARTS ARE SHIPPED IN QUANTITY OF 400 AS IN THE FOLLOWING:

1. ONE BAG CONTAINING FOUR LIGHT PIPE PACKAGES, 100 EACH, AND ONE LEVEL 4 MOISTURE SEALED TRAY WITH 400 SURFACE MOUNT ADAPTERS.
2. BAG SIZE IS APPROXIMATELY 16 X 18 INCHES (406.4 X 457.2 mm).
3. TRAY SIZE IS APPROXIMATELY 10 X 14 X 0.6 INCHES (254 X 355.6 X 15.2 mm), INCLUDING TOP COVER AND BOTTOM TRAY. ADAPTERS ARE ARRANGED AS SHOWN IN FIGURE 1.

10 ADAPTERS IN EACH POCKET




FIGURE 1

# RECOMMENDED REFLOW SOLDERING PROFILE



## NOTE:

1. DO NOT CLEAN AFTER SOLDERING. ONLY USE NO-CLEAN SOLDER PASTE.

|                                                |                       |                              |
|------------------------------------------------|-----------------------|------------------------------|
| <b>BIVAR<sup>®</sup></b>                       |                       |                              |
| <b>PART NO:</b><br>LPV3-XXXXX-XXX              |                       | <b>REVISION:</b><br><b>B</b> |
| <b>SCALE:</b> NONE                             | <b>SHEET # 5 OF 5</b> |                              |
| CAD GENERATED DOCUMENT, DO NOT MEASURE DRAWING |                       |                              |

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9