

OVH Series

Features

- 105°C, 2,000 hours assured
- Ultra low ESR, solid capacitors of SMD type
- RoHS Compliance



Marking color: Blue


Specifications

Items	Performance																							
Category Temperature Range	-55℃ ~ +105℃																							
Capacitance Tolerance	±20% (at 120Hz, 20℃)																							
Leakage Current (at 20℃)*	Rated voltage applied, after 2 minutes at 20℃. See Standard Ratings																							
Tanδ (at 120Hz, 20℃)	See Standard Ratings																							
ESR (at 100k ~ 300k Hz, 20℃)	See Standard Ratings																							
Endurance	<table><tr><td>Test Time</td><td colspan="3">2,000 Hrs</td></tr><tr><td>Capacitance Change</td><td colspan="3">Within ±20% of initial value</td></tr><tr><td>Tanδ</td><td colspan="3">Less than 150% of specified value</td></tr><tr><td>ESR</td><td colspan="3">Less than 150% of specified value</td></tr><tr><td>Leakage Current</td><td colspan="3">Within specified value</td></tr></table>				Test Time	2,000 Hrs			Capacitance Change	Within ±20% of initial value			Tanδ	Less than 150% of specified value			ESR	Less than 150% of specified value			Leakage Current	Within specified value		
	Test Time	2,000 Hrs																						
	Capacitance Change	Within ±20% of initial value																						
	Tanδ	Less than 150% of specified value																						
	ESR	Less than 150% of specified value																						
	Leakage Current	Within specified value																						
* The above specifications shall be satisfied when the capacitors are restored to 20℃ after the rated voltage applied for 2,000 hours at 105℃.																								
Moisture Resistance	<table><tr><td>Test Time</td><td colspan="3">1,000 Hrs</td></tr><tr><td>Capacitance Change</td><td colspan="3">Within ±20% of initial value</td></tr><tr><td>Tanδ</td><td colspan="3">Less than 150% of specified value</td></tr><tr><td>ESR</td><td colspan="3">Less than 150% of specified value</td></tr><tr><td>Leakage Current</td><td colspan="3">Within specified value</td></tr></table>				Test Time	1,000 Hrs			Capacitance Change	Within ±20% of initial value			Tanδ	Less than 150% of specified value			ESR	Less than 150% of specified value			Leakage Current	Within specified value		
	Test Time	1,000 Hrs																						
	Capacitance Change	Within ±20% of initial value																						
	Tanδ	Less than 150% of specified value																						
	ESR	Less than 150% of specified value																						
	Leakage Current	Within specified value																						
* The above specifications shall be satisfied when the capacitors are restored to 20℃ after subjecting them at 60℃, 90 to 95% RH for 1,000 hours. Leakage current should be tested after voltage treatment*.																								
Resistance to Soldering Heat * (Please refer to page 25 for reflow soldering conditions)	<table><tr><td>Capacitance Change</td><td colspan="3">Within ±10% of initial value</td></tr><tr><td>Tanδ</td><td colspan="3">Within specified value</td></tr><tr><td>ESR</td><td colspan="3">Within specified value</td></tr><tr><td>Leakage Current</td><td colspan="3">Within specified value</td></tr></table>				Capacitance Change	Within ±10% of initial value			Tanδ	Within specified value			ESR	Within specified value			Leakage Current	Within specified value						
	Capacitance Change	Within ±10% of initial value																						
	Tanδ	Within specified value																						
	ESR	Within specified value																						
	Leakage Current	Within specified value																						
Ripple Current and Frequency Multipliers	<table><tr><td>Frequency (Hz)</td><td>120 ≤ f < 1k</td><td>1k ≤ f < 10k</td><td>10k ≤ f < 100k</td><td>100k ≤ f < 500k</td></tr><tr><td>Multiplier</td><td>0.05</td><td>0.3</td><td>0.7</td><td>1.0</td></tr></table>				Frequency (Hz)	120 ≤ f < 1k	1k ≤ f < 10k	10k ≤ f < 100k	100k ≤ f < 500k	Multiplier	0.05	0.3	0.7	1.0										
	Frequency (Hz)	120 ≤ f < 1k	1k ≤ f < 10k	10k ≤ f < 100k	100k ≤ f < 500k																			
Multiplier	0.05	0.3	0.7	1.0																				

* For any doubt about measured values, measure the leakage current again after the following voltage treatment.

Voltage treatment: DC rated voltage is applied to the capacitors for 2 hours at 105 °C.

Diagram of Dimensions



Lead Spacing and Diameter

Unit: mm



φ D	L	A	B	C	W	P ± 0.2
6.3	4.4 ± 0.2	6.6	6.6	7.2	0.5 ~ 0.8	2.0
6.3	5.9 + 0.1 / - 0.3	6.6	6.6	7.2	0.5 ~ 0.8	2.0
8	6.7 ± 0.3	8.3	8.3	9.0	0.7 ~ 1.1	3.1
10	7.7 ± 0.3	10.3	10.3	11.0	0.7 ~ 1.3	4.7
10	9.9 + 0.1 / - 0.3	10.3	10.3	11.0	0.7 ~ 1.3	4.7

(*): For 6.3φ is 0.4 max.

Marking

φ D = 6.3

φ D = 8 ~ 10



Dimension: ϕ D×L(mm)

Ripple Current: mA/rms at 100k Hz, 105°C

Standard Ratings

Rated Volt. (V)	Surge Voltage (V)	Capacitance (μ F)	Size ϕ D×L(mm)	Tan δ (120Hz, 20°C)	L C (μ A)	E S R (m Ω /at 100k ~ 300k Hz, 20°C max.)	Rated R. C. (mA/rms at 100k Hz, 105°C)
2.5V (0E)	2.9	330	6.3 × 4.4	0.12	500	14	3,180
		390	6.3 × 5.9	0.12	293	10	3,900
		560	6.3 × 5.9	0.12	700	10	3,900
			8 × 6.7	0.12	420	9	4,200
		680	8 × 6.7	0.12	510	9	4,500
		1,200	10 × 7.7	0.12	900	9	5,000
		2,200	10 × 9.9	0.12	1,650	8	6,000
4V (0G)	4.6	330	6.3 × 5.9	0.12	396	10	3,900
		470	8 × 6.7	0.12	564	9	4,500
		560	8 × 6.7	0.12	894	9	4,500
		1,000	10 × 7.7	0.12	1,200	9	5,000
		1,800	10 × 9.9	0.12	2,160	8	6,000
6.3V (0J)	7.2	220	6.3 × 4.4	0.12	500	15	3,180
			6.3 × 5.9	0.12	416	10	3,900
		330	8 × 6.7	0.12	624	9	4,500
		390	8 × 6.7	0.12	737	9	4,500
		820	10 × 7.7	0.12	1,550	9	5,000
		1,500	10 × 9.9	0.12	2,835	8	6,000

Part Numbering System

OVH Series	820 μ F	±20%	6.3V	Carrier Tape		10 ϕ × 7.7L	Pb-free and PET coating case
OVH	821	M	0J	TR	-	1008	
Series Name	Capacitance	Capacitance Tolerance	Rated Voltage	Package Type	Terminal Type	Case size	Lead Wire and Coating Type

Note: For more details, please refer to "Part Numbering System (SMD Type)" on page 15.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9