

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

www.tripplite.com

# SmartRack 8U/12U/22U Expandable Low-Profile UPS-Depth Wall-Mount 2-Post Open-Frame Rack

MODEL NUMBER: SRW08U22DP







#### Description

The SRWO8U22DP SmartRack 8U/12U/22U Expandable Low-Profile UPS-Depth Wall-Mount 2-Post Open-Frame Rack is ideal for storing UPS systems, battery packs, power cords, network switches, patch panels and related cabling in secure IT areas with limited floor space. Mounted to the wall or resting on the floor, this rack offers fast, easy access to components and cabling. It's compatible with EIA-standard 19-inch rack equipment that supports two-post mounting and a maximum mounting depth of 23.5 inches.

#### **Highlights**

- Maximum load capacity of 150 lb.
- Secures 19 in. rack equipment up to 23.5 in. deep
- Configures to 8U, 12U or 22U of rack space
- Heavy-duty steel construction designed to last
- Easy to assemble with included hardware

#### Package Includes

- (24) 12-24 equipment mounting screws
- (16) M5 button-head cap screws
- (8) M6 x 12 Phillips-head screws
- (2) Short vertical mounting rails
- (2) Long vertical mounting rails
- (2) Mounting rail tie plates
- (2) Metal support straps
- (2) Top/bottom panel frames
- (8) Zip ties
- 3 mm L-shaped hex key
- · Owner's manual

Constructed from heavy-duty steel in a durable black powder-coated finish, the open-frame rack has a maximum load capacity of 150 pounds. The expandable design allows you to assemble the rack in an 8U, 12U or 22U configuration to meet your current needs, while leaving rack space in reserve for future expansion. It saves precious space and allows IT managers easy access for organizing, installing and servicing equipment and cabling.

The rack is easy to assemble using the included hardware. The vertical mounting rails have threaded 12-24 holes for securing equipment to the steel frame.

#### **Features**

#### Saves Valuable Workspace

- Perfect for installing UPS systems, battery packs, network switches and patch panels in secure IT areas with limited floor space
- Houses EIA-standard 19 in. rack equipment up to 23.5 in. deep
- Maximum load capacity of 150 lb.

#### Open-Frame Design in 3 Configurations

- Assembles in 8U, 12U or 22U to meet current needs
- Expands to add equipment later without buying a bigger rack
- Allows easy access for organizing, installing and servicing equipment and cabling

#### Easy Assembly and Installation

• Made from heavy-duty steel in a durable black powder-coated finish



- Easy to assemble with included hardware
- Vertical mounting rails with threaded 12-24 holes
- Wall-mounting holes spaced 16 in. apart to accommodate standard wall stud placement

# **Specifications**

Shipping Dimensions (hwd / in.) 3.5 Shipping Dimensions (hwd / cm) 8.9	3.5 9.69 .54 x 21.46 x 28.00 .99 x 54.51 x 71.12 9.4
Maximum Device Depth (in.)  23.  Maximum Device Depth (cm)  59.  Shipping Dimensions (hwd / in.)  Shipping Dimensions (hwd / cm)  8.9	3.5 9.69 .54 x 21.46 x 28.00 .99 x 54.51 x 71.12 9.4
Maximum Device Depth (cm) 59. Shipping Dimensions (hwd / in.) 3.5 Shipping Dimensions (hwd / cm) 8.9	9.69 .54 x 21.46 x 28.00 .99 x 54.51 x 71.12
Shipping Dimensions (hwd / in.) 3.5 Shipping Dimensions (hwd / cm) 8.9	.54 x 21.46 x 28.00 .99 x 54.51 x 71.12 9.4
Shipping Dimensions (hwd / cm) 8.9	9.4
	9.4
Shipping Weight (lbs.)	.8
Shipping Weight (kg) 8.8	
Unit Dimensions (hwd / in.)	7.8 (8U) , 24.8 (12U), 42.3 (22U) x 20.11 x 24.00
Unit Dimensions (hwd / cm) 45.	5.22 (8U), 63 (12U), 107.45 (22U) x 51.08 x 60.96
Unit Weight (lbs.)	7.2
Unit Weight (kg) 7.8	.80
Color	lack
Unit Weight Details We	/eight varies depending on configuration 8U = 13.03lbs, 12U = 14.04lbs, 22U = 16.87lbs
Maximum Weight Capacity (lbs.) 150	50
Maximum Weight Capacity (kg) 68	8
Maximum Device Depth (mm) 59	97
CERTIFICATIONS	
Approvals E1A	IA-310-D, IEC 60297-3-100, RoHS
WARRANTY	
Product Warranty Period (Worldwide) 5-y	-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies

## **ПОСТАВКА** ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

# Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

### http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

## Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru\_6 moschip.ru 4 moschip.ru 9