

Ceramic Disc Capacitors Class 1 and 2, 1 kV_{DC}, 2 kV_{DC}, 3 kV_{DC} and 6 kV_{DC}, General Purpose



Capacitors with 5 mm (0.20"), 7.5 mm (0.30") and
10 mm (0.40") lead spacing

| QUICK REFERENCE DATA | | |
|----------------------------|------------------------|--------------------------------------|
| DESCRIPTION | CLASS 1 (SL0, S3N) | CLASS 2 (Y5P, X7R, Z5U, Y5V, X5F) |
| Voltage (V _{DC}) | 1000, 2000, 3000, 6000 | |
| Min. Capacitance (pF) | 10 | 100 |
| Max. Capacitance (pF) | 220 | 33 000 |
| Mounting | Through hole | |

MARKING

Straight and kinked leaded versions are gold coloured
Marking indicates capacitance value and tolerance in
accordance with "EIA 198" and voltage:

OPERATING TEMPERATURE RANGE

Class 1 SL0, S3N, - 55 °C to + 125 °C

Class 2, X7R - 55 °C to + 125 °C

Class 2, Y5P, Z5U, Y5V, - 30 °C to + 85 °C

Class 2, X5F - 55 °C to + 85 °C

TEMPERATURE COEFFICIENTS

Class 1 SL0, S3N

Class 2 X7R, Y5P, Z5U, Y5V, X5F

SECTIONAL SPECIFICATIONS

Class 1, IEC 60 384-8,

Class 2, IEC 60 384-9,

EIA 198

CLIMATIC CATEGORY

Class 1, SL0, 55/125/21

Class 2, X7R, 55/125/21

Class 2, Y5P, Z5U, Y5V, 30/85/21

Class 2, X5F, 55/85/21

FEATURES

- Low losses
- High stability
- High capacitance in small size
- Kinked (preferred) or straight leads
- Compliant to RoHS directive 2002/95/EC



RoHS
COMPLIANT

APPLICATIONS

- DC high voltage
- Pulse high voltage
- SMPS
- HV power supply
- HF ballast

DESIGN

The capacitors consist of a ceramic disc both sides of which are silver-plated. Connection leads are made of tinned copper having a diameter of 0.6 mm or 0.8 mm up to 3 kV and 0.8 mm for 6 kV.

The capacitors may be supplied with kinked or straight leads with a lead spacing of 5 mm (0.20"), 7.5 mm (0.30") or 10 mm (0.40") and a lead length from 4 mm to 30 mm. The standard tolerance on capacitance is 5 % or 10 % for class 1 capacitors and ± 10 % or ± 20 % for class 2 capacitors. Encapsulation is made of gold-colored epoxy-resin, flammable resistant in accordance with "UL 94 V-0"

CAPACITANCE RANGE

Class 1, at 1 MHz, 1.2 V_{RMS}; 10 pF to 220 pF

1 kHz, 1 V_{RMS} ± 0.2 V_{RMS} for capacitance values higher than 1000 pF

Class 2, at 1 kHz, 1 V_{RMS} ± 0.2 V_{RMS}; 100 pF to 33 000 pF

RATED DC VOLTAGE

1 kV; 2 kV; 3 kV; 6 kV

DIELECTRIC STRENGTH

200 % of rated voltage

INSULATION RESISTANCE AT 500 V_{DC}

≥ 10 000 MΩ

TOLERANCE ON CAPACITANCE

± 5 %; ± 10 %; ± 20 %; + 80/- 20 %

Other tolerances available on request

DISSIPATION FACTOR

Class 1, C ≤ 30 pF; ≤ 20 x (10/C + 0.7) x 10⁻⁴ max.

Class 1, C > 30 pF; ≤ 0.2 %

Class 2, ≤ 3.0 %

| ORDERING INFORMATION 1 kV _{DC} , STRAIGHT | | | | | | | | |
|--|-------------|---------------------------|----------------------|---------------------------|--|-----|-----|------------------|
| C (pF) | TOL. (%) | D _{MAX.} (mm) | LEAD SPACING (mm) | SH ⁽¹⁾ (mm) | CLEAR TEXT CODE | | | |
| | | | | | 13 TH DIGIT: T = REEL; U = AMMO; 3 = BULK 16 TH DIGIT: R = RoHS COMPLIANT | | | |
| CLASS 1 SLO | | | | | | | | |
| 10 | ± 5 | 6.5 | 5.0 | 4.0 | S100J25SL0N6.J5. | | | |
| | ± 10 | | | | S100K25SL0N6.J5. | | | |
| 12 | ± 5 | | | | S120J25SL0N6.J5. | | | |
| | ± 10 | | | | S120K25SL0N6.J5. | | | |
| 15 | ± 5 | | | | S150J25SL0N6.J5. | | | |
| | ± 10 | | | | S150K25SL0N6.J5. | | | |
| 18 | ± 5 | | | | S180J25SL0N6.J5. | | | |
| | ± 10 | | | | S180K25SL0N6.J5. | | | |
| 22 | ± 5 | | | | S220J25SL0N6.J5. | | | |
| | ± 10 | | | | S220K25SL0N6.J5. | | | |
| 27 | ± 5 | | | | S270J25SL0N6.J5. | | | |
| | ± 10 | | | | S270K25SL0N6.J5. | | | |
| 33 | ± 5 | | | | S330J25SL0N6.J5. | | | |
| | ± 10 | | | | S330K25SL0N6.J5. | | | |
| 39 | ± 5 | | | | S390J25SL0N6.J5. | | | |
| | ± 10 | | | | S390K25SL0N6.J5. | | | |
| 47 | ± 5 | | | | S470J25SL0N6.J5. | | | |
| | ± 10 | | | | S470K25SL0N6.J5. | | | |
| 56 | ± 5 | 7.5 | 5.0 | 4.0 | S560J29SL0N6.J5. | | | |
| | ± 10 | | | | S560K29SL0N6.J5. | | | |
| 68 | ± 5 | | | | S680J29SL0N6.J5. | | | |
| | ± 10 | | | | S680K29SL0N6.J5. | | | |
| 82 | ± 5 | | | | S820J29SL0N6.J5. | | | |
| | ± 10 | | | | S820K29SL0N6.J5. | | | |
| 100 | ± 5 | | | | S101J29SL0N6.J5. | | | |
| | ± 10 | | | | S101K29SL0N6.J5. | | | |
| 120 | ± 5 | | | | S121J33SL0N6.J5. | | | |
| | ± 10 | | | | S121K33SL0N6.J5. | | | |
| 150 | ± 10 | | | | 8.5 | 5.0 | 4.0 | S151K33SL0N6.J5. |
| 220 | | | | | | | | S221K39SL0N6.J5. |
| CLASS 2 X7R | | | | | | | | |
| 100 | ± 10 | 6.5 | 5.0 | 4.0 | S101K25X7RN6.J5. | | | |
| 150 | | | | | S151K25X7RN6.J5. | | | |
| 220 | | | | | S221K25X7RN6.J5. | | | |
| 330 | | | | | S331K25X7RN6.J5. | | | |
| 470 | | | | | S471K29X7RN6.J5. | | | |
| 680 | | | | | S681K29X7RN6.J5. | | | |
| 1000 | | 8.5 | 7.5 | 4.8 | S102K33X7RN6.J5. | | | |
| 1500 | | 10 | | | S152K39X7RN6.J5. | | | |
| 2200 | | 11 | | | S222K43X7RN6.J5. | | | |
| 3 300 | | 12 | | | S332K47X7RN6.J7. | | | |
| 4 700 | | 15 | | | S472K59X7RN6.J7. | | | |
| | | | | | | | | |
| CLASS 2 Y5P | | | | | | | | |
| 100 | ± 10 | 6.5 | 5.0 | 4.0 | S101K25Y5PN6.J5. | | | |
| 150 | | | | | S151K25Y5PN6.J5. | | | |
| 220 | | | | | S221K25Y5PN6.J5. | | | |
| 330 | | | | | S331K25Y5PN6.J5. | | | |
| 470 | | | | | S471K25Y5PN6.J5. | | | |
| 680 | | | | | S681K29Y5PN6.J5. | | | |
| 1000 | | 7.5 | 8.5 | S102K29Y5PN6.J5. | | | | |
| 1500 | | 8.5 | | S152K33Y5PN6.J5. | | | | |
| | | | | | | | | |
| | | | | | | | | |



Ceramic Disc Capacitors Class 1 and 2,
1 kV_{DC}, 2 kV_{DC}, 3 kV_{DC} and 6 kV_{DC}, General Purpose

Vishay BCcomponents

| ORDERING INFORMATION 1 kV_{DC}, STRAIGHT | | | | | |
|---|-------------|---------------------------|----------------------|---------------------------|--|
| C (pF) | TOL. (%) | D _{MAX.} (mm) | LEAD SPACING (mm) | SH ⁽¹⁾ (mm) | CLEAR TEXT CODE |
| | | | | | 13 TH DIGIT: T = REEL; U = AMMO; 3 = BULK 16 TH DIGIT: R = RoHS COMPLIANT |
| CLASS 2 Y5P | | | | | |
| 2200 | ± 10 | 10 | 5.0 | 4.0 | S222K39Y5PN6.J5. |
| 3300 | | 11 | | | S332K43Y5PN6.J5. |
| 4700 | | 13.5 | 7.5 | 4.8 | S472K53Y5PN63J7. |
| 6800 | | 15 | | | S682K59Y5PN63J7. |
| 10 000 | | 19 | | | 10 |
| CLASS 2 Z5U | | | | | |
| 1000 | ± 20 | 6.5 | 5.0 | 4.0 | S102M25Z5UN6.J5. |
| 1500 | | | | | S152M29Z5UN6.J5. |
| 2200 | | | | | S222M29Z5UN6.J5. |
| 3300 | | | | | S332M33Z5UN6.J5. |
| 4700 | | S472M39Z5UN6.J5. | | | |
| 6800 | | 11 | S682M43Z5UN6.J5. | | |
| 10 000 | | 12 | 7.5 | 4.8 | S103M47Z5UN63J7. |
| 15 000 | | 15 | | | S153M59Z5UN63J7. |
| 22 000 | | 19 | | | 10 |
| CLASS 2 Y5V | | | | | |
| 1000 | + 80/- 20 | 6.5 | 5.0 | 4.0 | S102Z25Y5VN6.J5. |
| 1500 | | | | | S152Z25Y5VN6.J5. |
| 2200 | | | | | S222Z29Y5VN6.J5. |
| 3300 | | | | | S332Z29Y5VN6.J5. |
| 4700 | | 8.5 | S472Z33Y5VN6.J5. | | |
| 6800 | | 10 | S682Z39Y5VN6.J5. | | |
| 10 000 | | 11 | S103Z43Y5VN6.J5. | | |
| 15 000 | | 13.5 | 7.5 | 4.8 | S153Z53Y5VN6.J7. |
| 22 000 | | 15 | | | S223Z59Y5VN6.J7. |
| 33 000 | | 19 | | | 10 |

| ORDERING INFORMATION 1 kV_{DC}, KINKED | | | | | |
|---|-------------|---------------------------|----------------------|---------------------------|--|
| C (pF) | TOL. (%) | D _{MAX.} (mm) | LEAD SPACING (mm) | SH ⁽²⁾ (mm) | CLEAR TEXT CODE |
| | | | | | 13 TH DIGIT: T = REEL; U = AMMO; 3 = BULK 16 TH DIGIT: R = RoHS COMPLIANT |
| CLASS 2 X5F | | | | | |
| 100 | ± 10 | 6.5 | 5.0 | 4.0 | S101K25X5FN6.J5R |
| 220 | | | | | S221K25X5FN6.J5R |
| 270 | | | | | S271K25X5FN6.J5R |
| 330 | | | | | S331K25X5FN6.J5R |
| 390 | | | | | S391K25X5FN6.J5R |
| 470 | | | | | S471K25X5FN6.J5R |
| 680 | | | | | S681K29X5FN6.J5R |
| 820 | | 7.5 | S821K29X5FN6.J5R | | |
| 1000 | | 11 | S102K29X5FN6.J5R | | |
| 2200 | | 13.5 | 7.5 | 4.8 | S222K43X5FN6.J5R |
| 3300 | | 16 | | | S332K53X5FN6.J7R |
| 4700 | | S472K63X5FN63J7R | | | |

Notes

- ⁽¹⁾ SH = seated height
- Maximum thickness 4.0 mm
- Lead style codes refer to inward kinked leads. Other styles available on request

| ORDERING INFORMATION 2 kV _{DC} , KINKED | | | | | | | | | | |
|--|------------------|---------------------------|----------------------|---------------------------|--|------------------|------------------|------------------|------------------|------------------|
| C (pF) | TOL. (%) | D _{MAX.} (mm) | LEAD SPACING (mm) | SH ⁽¹⁾ (mm) | CLEAR TEXT CODE | | | | | |
| | | | | | 13 TH DIGIT: T = REEL; U = AMMO; 3 = BULK 16 TH DIGIT: R = RoHS COMPLIANT | | | | | |
| CLASS 1 SLO | | | | | | | | | | |
| 10 | ± 5 | 6.5 | 5.0 | 4.0 | S100J25SLOP6.K5. | | | | | |
| | ± 10 | | | | S100K25SLOP6.K5. | | | | | |
| 12 | ± 5 | | | | S120J25SLOP6.K5. | | | | | |
| | ± 10 | | | | S120K25SLOP6.K5. | | | | | |
| 15 | ± 5 | | | | S150J25SLOP6.K5. | | | | | |
| | ± 10 | | | | S150K25SLOP6.K5. | | | | | |
| 18 | ± 5 | | | | S180J25SLOP6.K5. | | | | | |
| | ± 10 | | | | S180K25SLOP6.K5. | | | | | |
| 22 | ± 5 | | | | S220J25SLOP6.K5. | | | | | |
| | ± 10 | | | | S220K25SLOP6.K5. | | | | | |
| 27 | ± 5 | | | | S270J25SLOP6.K5. | | | | | |
| | ± 10 | | | | S270K25SLOP6.K5. | | | | | |
| 33 | ± 5 | 7.5 | 5.0 | 4.0 | S330J29SLOP6.K5. | | | | | |
| | ± 10 | | | | S330K29SLOP6.K5. | | | | | |
| 39 | ± 5 | | | | S390J29SLOP6.K5. | | | | | |
| | ± 10 | | | | S390K29SLOP6.K5. | | | | | |
| 47 | ± 5 | | | | S470J29SLOP6.K5. | | | | | |
| | ± 10 | | | | S470K29SLOP6.K5. | | | | | |
| 56 | ± 5 | | | | S560J29SLOP6.K5. | | | | | |
| | ± 10 | | | | S560K29SLOP6.K5. | | | | | |
| 68 | ± 5 | | | | 8.5 | 5.0 | 4.0 | S680J33SLOP6.K5. | | |
| | ± 10 | | | | | | | S680K33SLOP6.K5. | | |
| 82 | ± 5 | | | | | | | S820J33SLOP6.K5. | | |
| | ± 10 | | | | | | | S820K33SLOP6.K5. | | |
| 100 | ± 5 | 10 | 5.0 | 4.0 | | | | S101J39SLOP6.K5. | | |
| | ± 10 | | | | | | | S101K39SLOP6.K5. | | |
| 120 | ± 5 | | | | S121J39SLOP6.K5. | | | | | |
| | ± 10 | | | | S121K39SLOP6.K5. | | | | | |
| 150 | ± 5 | | | | 11 | 5.0 | 4.0 | S151K43SLOP6.K5. | | |
| | ± 10 | | | | | | | | | |
| CLASS 2 X7R | | | | | | | | | | |
| 100 | ± 10 | 6.5 | 5.0 | 4.0 | S101K25X7RP6.K5. | | | | | |
| 150 | | | | | S151K25X7RP6.K5. | | | | | |
| 220 | | | | | S221K25X7RP6.K5. | | | | | |
| 330 | | | | | S331K25X7RP6.K5. | | | | | |
| 470 | | | | | S471K29X7RP6.K5. | | | | | |
| 680 | | | | | S681K33X7RP6.K5. | | | | | |
| 1000 | | 7.5 | 5.0 | 4.0 | 4.0 | S102K39X7RP6.K5. | | | | |
| 1500 | | | | | | S152K43X7RP6.K5. | | | | |
| 2200 | | | | | | 13.5 | 7.5 | 4.8 | S222K53X7RP6.K7. | |
| 3300 | | | | | | | | | S332K59X7RP6.K7. | |
| CLASS 2 Y5P | | | | | | | | | | |
| 100 | | | | | | ± 10 | 6.5 | 5.0 | 4.0 | S101K25Y5PP6.K5. |
| 150 | S151K25Y5PP6.K5. | | | | | | | | | |
| 220 | S221K25Y5PP6.K5. | | | | | | | | | |
| 330 | S331K25Y5PP6.K5. | | | | | | | | | |
| 470 | S471K29Y5PP6.K5. | | | | | | | | | |
| 680 | S681K29Y5PP6.K5. | | | | | | | | | |
| 1000 | 7.5 | 5.0 | 4.0 | 4.0 | S102K33Y5PP6.K5. | | | | | |
| 1500 | | | | | S152K39Y5PP6.K5. | | | | | |
| 2200 | | | | | 11 | | 7.5 | 4.8 | S222K43Y5PP6.K5. | |
| 3300 | | | | | | | | | S332K53Y5PP63K7. | |
| 4700 | | | | | 17.5 | | S472K69Y5PP63K7. | | | |



Ceramic Disc Capacitors Class 1 and 2,
1 kV_{DC}, 2 kV_{DC}, 3 kV_{DC} and 6 kV_{DC}, General Purpose

Vishay BCcomponents

| ORDERING INFORMATION 2 kV_{DC}, KINKED | | | | | |
|---|-----------|------------------------|-------------------|------------------------|--|
| C (pF) | TOL. (%) | D _{MAX.} (mm) | LEAD SPACING (mm) | SH ⁽¹⁾ (mm) | CLEAR TEXT CODE |
| | | | | | 13 TH DIGIT: T = REEL; U = AMMO; 3 = BULK 16 TH DIGIT: R = RoHS COMPLIANT |
| CLASS 2 Z5U | | | | | |
| 1000 | ± 20 | 7.5 | 5.0 | 4.0 | S102M29Z5UP6.K5. |
| 1500 | | | | | S152M29Z5UP6.K5. |
| 2200 | | | | | S222M33Z5UP6.K5. |
| 3300 | | 11 | 7.5 | 4.8 | S332M43Z5UP6.K5. |
| 4700 | | 12 | | | S472M47Z5UP63K7. |
| 6800 | | 13.5 | | | S682M53Z5UP63K7. |
| 10 000 | | 17.5 | | | S103M69Z5UP63K7. |
| CLASS 2 Y5V | | | | | |
| 1000 | + 80/- 20 | 7.5 | 5.0 | 4.0 | S102Z29Y5VP6.K5. |
| 1500 | | | | | S152Z29Y5VP6.K5. |
| 2200 | | | | | S222Z33Y5VP6.K5. |
| 3300 | | 10.5 | 7.5 | 4.8 | S322Z39Y5VP6.K5. |
| 4700 | | 11 | | | S472Z43Y5VP6.K5. |
| 6800 | | 12 | | | S682Z47Y5VP6.K7. |
| 10 000 | | 15 | | | S103Z59Y5VP6.K7. |
| CLASS 2 X5F | | | | | |
| 1 00 | ± 10 | 6.5 | 5.0 | 4.0 | S101K25X5FP6.K5R |
| 220 | | | | | S221K25X5FP6.K5R |
| 330 | | | | | 7.5 |
| 470 | | 8 | 7.5 | 4.8 | S471K31X5FP6.K5R |
| 680 | | 10 | | | S681K39X5FP6.K5R |
| 1000 | | 11 | | | S102K43X5FP6.K5R |
| 2200 | | 15 | | | S222K59X5FP6.K7R |
| 3300 | 16.5 | S332K65X5FP63K7R | | | |

Notes

⁽¹⁾ SH = seated height

- Maximum thickness 4.0 mm
- Lead style codes refer to inward kinked leads. Other styles available on request

| ORDERING INFORMATION CLASS 3 kV_{DC}, KINKED | | | | | |
|---|----------|------------------------|-------------------|------------------------|--|
| C (pF) | TOL. (%) | D _{MAX.} (mm) | LEAD SPACING (mm) | SH ⁽¹⁾ (mm) | CLEAR TEXT CODE |
| | | | | | 13 TH DIGIT: T = REEL; U = AMMO; 3 = BULK 16 TH DIGIT: R = RoHS COMPLIANT |
| CLASS 1 SL | | | | | |
| 10 | ± 10 | 8.5 | 7.5 | 4.0 | S100K33SL0R63K7. |
| 15 | | | | | S150K33SL0R63K7. |
| 22 | | | | | S220K33SL0R63K7. |
| 33 | | | | | S330K33SL0R63K7. |
| 47 | | | | | S470K33SL0R63K7. |
| 68 | 10 | S680K39SL0R63K7. | | | |
| CLASS 2 X7R | | | | | |
| 100 | ± 10 | 8.5 | 7.5 | 4.0 | S101K33X7RR63K7. |
| 150 | | | | | S151K33X7RR63K7. |
| 220 | | | | | S221K33X7RR63K7. |
| 330 | | | | | S331K33X7RR63K7. |
| 470 | | | | | S471K33X7RR63K7. |
| 680 | | 10 | 4.8 | S681K39X7RR63K7. | |
| 1000 | | 11 | | S102K43X7RR63K7. | |
| 1500 | 13.5 | S152K53X7RR63K7. | | | |
| 2200 | 17.5 | S222K59X7RR83K7. | | | |

| ORDERING INFORMATION CLASS 3 kV _{DC} , KINKED | | | | | |
|--|-----------|------------------------|-------------------|------------------------|--|
| C (pF) | TOL. (%) | D _{MAX.} (mm) | LEAD SPACING (mm) | SH ⁽¹⁾ (mm) | CLEAR TEXT CODE |
| | | | | | 13 TH DIGIT: T = REEL; U = AMMO; 3 = BULK 16 TH DIGIT: R = RoHS COMPLIANT |
| CLASS 2 Y5P | | | | | |
| 100 | ± 10 | 8.5 | 7.5 | 4.0 | S101K33Y5PR63K7. |
| 150 | | | | | S151K33Y5PR63K7. |
| 220 | | | | | S221K33Y5PR63K7. |
| 330 | | | | | S331K33Y5PR63K7. |
| 470 | | | | | S471K33Y5PR63K7. |
| 680 | | | | | S681K39Y5PR63K7. |
| 1000 | | 10 | 4.8 | S102K43Y5PR63K7. | |
| 1500 | | 11 | | S152K47Y5PR63K7. | |
| 2200 | | 12 | | S222K59Y5PR63K7. | |
| 3 300 | | 15 | | S332K75Y5PR83K0. | |
| | | 19 | 10 | | |
| CLASS 2 Z5U | | | | | |
| 470 | ± 20 | 8.5 | 7.5 | 4.0 | S471M33Z5UR63K7. |
| 680 | | | | | S681M33Z5UR63K7. |
| 1000 | | | | | S102M33Z5UR63K7. |
| 1500 | | 10 | 4.8 | S152M39Z5UR63K7. | |
| 2200 | | 11 | | S222M43Z5UR63K7. | |
| 3300 | | 13.5 | | S332M53Z5UR63K7. | |
| 4700 | 17.5 | S472M69Z5UR83K7. | | | |
| CLASS 2 Y5V | | | | | |
| 1000 | + 80/- 20 | 8.5 | 7.5 | 4.0 | S102Z33Y5VR63K7. |
| 1500 | | | | | S152Z33Y5VR63K7. |
| 2200 | | | | | S222Z39Y5VR63K7. |
| 3300 | | 10 | 4.8 | S322Z43Y5VR63K7. | |
| 4700 | | 11 | | S472Z47Y5VR63K7. | |
| 6800 | | 12 | | S682Z59Y5VR63K7. | |
| | | 15 | | | |

Notes

- ⁽¹⁾ SH = seated height
- Maximum thickness 4.0 mm
- Lead style codes refer to inward kinked leads. Other styles available on request

| ORDERING INFORMATION CLASS 6 kV _{DC} , KINKED | | | | | |
|--|----------|------------------------|-------------------|------------------------|--|
| C (pF) | TOL. (%) | D _{MAX.} (mm) | LEAD SPACING (mm) | SH ⁽¹⁾ (mm) | CLEAR TEXT CODE |
| | | | | | 13 TH DIGIT: T = REEL; U = AMMO; 3 = BULK 16 TH DIGIT: R = RoHS COMPLIANT |
| CLASS 1 SL | | | | | |
| 10 | ± 20 | 10 | 10 | 3.0 | S100M39SL0U83L0. |
| 15 | | | | | S150M43SL0U83L0. |
| 22 | | S220M43SL0U83L0. | | | |
| 33 | | 13.5 | | | S330M53SL0U83L0. |
| CLASS 1 S3N | | | | | |
| 47 | ± 20 | 11 | 10 | 3.0 | S470M43S3NU83L0. |
| 68 | | 13.5 | | | S680M53S3NU83L0. |
| 100 | | 15 | | | S101M59S3NU83L0. |
| 150 | | 15 | | | S151M59S3NU83L0. |
| CLASS 2 Z5U | | | | | |
| 220 | ± 20 | 10 | 10 | 3.0 | S221M39Z5UU83L0. |
| 330 | | 11 | | | S331M43Z5UU83L0. |
| 470 | | 12 | | | S471M47Z5UU83L0. |

| ORDERING INFORMATION CLASS 6 kV _{DC} , KINKED | | | | | |
|--|----------|------------------------|-------------------|------------------------|---|
| C (pF) | TOL. (%) | D _{MAX.} (mm) | LEAD SPACING (mm) | SH ⁽¹⁾ (mm) | CLEAR TEXT CODE 13 TH DIGIT: T = REEL; U = AMMO; 3 = BULK 16 TH DIGIT: R = RoHS COMPLIANT |
| CLASS 2 Z5U | | | | | |
| 680 | ± 20 | 13.5 | 10 | 3.0 | S681M53Z5UU83L0. |
| 1000 | | 15 | | | S102M59Z5UU83L0. |
| 1500 | | 17.5 | | | S152M69Z5UU83L0. |
| 2200 | | 19 | | | S222M75Z5UU83L0. |

Notes

⁽¹⁾ SH = seated height

- Maximum thickness 4.0 mm
- Lead style codes refer to inward kinked leads. Other styles available on request

| PACKAGING | | | | | |
|---------------------------------|-----------|-----------------|----------------------------|------|-------------------------------|
| PACKAGING TYPE | SIZE CODE | LEAD SPACE (mm) | VOLTAGE (V _{DC}) | SPQ | BOX DIMENSIONS L x W x H (mm) |
| Bulk (long lead L ≥ 25.4 mm) | 20 to 47 | all | all | 1000 | 245 x 120 x 65 |
| | | | | 1000 | |
| | 53 to 75 | | | 1000 | |
| | 84 to 96 | | | 500 | |
| Tape and reel | ≤ 47 | ≤ 6.40 | < 500 | 2500 | 370 x 370 x 60 |
| | | | 500 ≤ WV ≤ 2000 | 2000 | |
| | | ≥ 7.5 | 3000 | 1000 | |
| | | | all | 1000 | |
| Ammopack | ≤ 47 | ≤ 6.40 | < 500 | 2000 | 335 x 240 x 50 |
| | | | 500 ≤ WV < 2000 | 1500 | 335 x 290 x 50 |
| | | ≥ 7.5 | 2000 and 3000 | 1500 | 360 x 330 x 55 |
| | | | all | 1500 | |

Note

- The capacitors are supplied in bulk packaging (cardboard boxes), in tape on reel or in ammopack



| DIMENSIONS OF TAPE | | | |
|-------------------------------|--------------------------------------|-----------------|---------------|
| SYMBOL | PARAMETER | DIMENSIONS (mm) | |
| | | NOMINAL | TOLERANCE |
| D | Body diameter | 11.0 maximum | - |
| d | Lead diameter | 0.6 | ± 0.05 |
| P | Pitch between capacitors | 12.7 | ± 1.0 |
| P ₀ ⁽¹⁾ | Feed-hole pitch | 12.7 | ± 0.3 |
| ΔP | Plane deviation | 1.0 maximum | - |
| P ₁ ⁽²⁾ | Feed-hole center to lead center | 3.85 | ± 0.7 |
| P ₂ ⁽²⁾ | Feed-hole center to component center | 6.35 | ± 1.3 |
| F | Lead spacing | 5.0 | 0.6 - 0.4 |
| Δh | Component alignment | 0 | ± 1.0 |
| W | Tape width | 18.0 | 1.0 - 0.5 |
| W ₀ | Hold-down tape width | 5.0 minimum | - |
| W ₁ | Hole position | 9.0 | 0.75 - 0.5 |
| W ₂ | Hold-down tape margin | 3.0 maximum | - |
| H ₀ | Height to seating plane | 16.0 | ± 0.5 |
| H ₁ | Maximum component height | 32.0 | - |
| e | Lead end protrusion | 1.0 maximum | - |
| L | Maximum length of snapped lead | 11.0 | - |
| D ₀ | Feed-hole diameter | 4.0 | ± 0.2 |
| t | Total tape thickness | 0.9 maximum | - |
| t ₁ | Maximum thickness of tape and wires | 1.5 maximum | - |

Notes

(1) Cumulative pitch error: $\pm \leq 1 \text{ mm}/20 \text{ pitches}$

(2) Obliquity maximum 3°

REEL AND TAPE DATA in millimeters





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9