

# Chip Inductors – 0402CS (1005)



Continuing in our long tradition of innovation and leadership, Coilcraft introduced the industry's first 0402 wirewound inductor.

This series shares all of the characteristics of Coilcraft's other ceramic inductors: exceptionally high Q factors, especially at use frequencies; outstanding self-resonant frequency; tight inductance tolerance; and excellent batch-to-batch consistency.

## Typical L vs Frequency



## Typical Q vs Frequency



## Irms Derating



| A     | B     | C     | D     | E     | F     | G     | H     | I     | J     |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| max   | max   | max   | ref   |       |       |       |       |       |       |
| 0.047 | 0.025 | 0.026 | 0.010 | 0.020 | 0.009 | 0.022 | 0.026 | 0.014 | 0.018 |
| 1,19  | 0,64  | 0,66  | 0,25  | 0,51  | 0,23  | 0,56  | 0,66  | 0,36  | 0,46  |

- Core material** Ceramic
- Environmental** RoHS compliant, halogen free optional
- Terminations** RoHS compliant silver-palladium-platinum-glass frit. Other terminations available at additional cost.
- Weight** 0.8 – 1.0 mg
- Ambient temperature** –40°C to +125°C with Irms current, +125°C to +140°C with derated current
- Storage temperature** Component: –40°C to +140°C. Tape and reel packaging: –40°C to +80°C
- Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles
- Temperature Coefficient of Inductance (TCL)** +25 to +125 ppm/°C
- Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)
- Failures in Time (FIT) / Mean Time Between Failures (MTBF)** One per billion hours / one billion hours, calculated per Telcordia SR-332
- Packaging** 2000 or 5000 per 7" reel Paper tape: 8 mm wide, 1.68 mm thick, 2 mm pocket spacing
- PCB washing** Tested with pure water or alcohol only. For other solvents, see Doc787\_PCB\_Washing.pdf.



**US** +1-847-639-6400 sales@coilcraft.com  
**UK** +44-1236-730595 sales@coilcraft-europe.com  
**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw  
**China** +86-21-6218 8074 sales@coilcraft.com.cn  
**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 198-1 Revised 05/03/13  
 © Coilcraft Inc. 2013  
 This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

# 0402CS Series (1005)

Designer's Kits **C328A** and **B** contain 20 each of all 5% values  
 Designer's Kits **C328A-2** and **B-2** contain 20 each of all 2% values

| Part number <sup>1</sup> | Inductance <sup>2</sup><br>(nH) | Percent<br>tolerance <sup>3</sup> | 900 MHz |                    | 1.7 GHz |                    | SRF min <sup>5</sup><br>(GHz) | DCR max <sup>6</sup><br>(Ohms) | Irms <sup>7</sup><br>(mA) |
|--------------------------|---------------------------------|-----------------------------------|---------|--------------------|---------|--------------------|-------------------------------|--------------------------------|---------------------------|
|                          |                                 |                                   | L typ   | Q typ <sup>4</sup> | L typ   | Q typ <sup>4</sup> |                               |                                |                           |
| 0402CS-1N0XJL_           | 1.0                             | <b>5</b>                          | 1.02    | 77                 | 1.02    | 69                 | 12.70                         | 0.045                          | 1360                      |
| 0402CS-1N2XJL_           | 1.2                             | <b>5</b>                          | 1.17    | 28                 | 1.17    | 38                 | 12.90                         | 0.090                          | 740                       |
| 0402CS-1N8XJL_           | 1.8                             | <b>5,3,2</b>                      | 1.78    | 54                 | 1.78    | 75                 | 12.00                         | 0.070                          | 1040                      |
| 0402CS-1N9XJL_           | 1.9                             | <b>5,3,2</b>                      | 1.72    | 68                 | 1.74    | 82                 | 11.30                         | 0.070                          | 1040                      |
| 0402CS-2N0X_L_           | 2.0                             | <b>5,3,2</b>                      | 1.93    | 54                 | 1.93    | 75                 | 11.10                         | 0.070                          | 1040                      |
| 0402CS-2N2X_L_           | 2.2                             | <b>5,3,2</b>                      | 2.19    | 59                 | 2.23    | 100                | 10.80                         | 0.070                          | 960                       |
| 0402CS-2N4X_L_           | 2.4                             | <b>5,3,2</b>                      | 2.24    | 51                 | 2.27    | 68                 | 10.50                         | 0.068                          | 790                       |
| 0402CS-2N7X_L_           | 2.7                             | <b>5,3,2</b>                      | 2.58    | 42                 | 2.60    | 61                 | 10.40                         | 0.120                          | 640                       |
| 0402CS-3N3X_L_           | 3.3                             | <b>5,3,2</b>                      | 3.10    | 65                 | 3.12    | 87                 | 7.00                          | 0.066                          | 840                       |
| 0402CS-3N6X_L_           | 3.6                             | <b>5,3,2</b>                      | 3.56    | 45                 | 3.62    | 71                 | 6.80                          | 0.066                          | 840                       |
| 0402CS-3N9X_L_           | 3.9                             | <b>5,3,2</b>                      | 3.89    | 50                 | 4.00    | 75                 | 6.00                          | 0.066                          | 840                       |
| 0402CS-4N3X_L_           | 4.3                             | <b>5,3,2</b>                      | 4.19    | 47                 | 4.30    | 71                 | 6.00                          | 0.091                          | 700                       |
| 0402CS-4N7X_L_           | 4.7                             | <b>5,3,2</b>                      | 4.55    | 48                 | 4.68    | 68                 | 4.77                          | 0.130                          | 640                       |
| 0402CS-5N1X_L_           | 5.1                             | <b>5,3,2</b>                      | 5.15    | 56                 | 5.25    | 82                 | 4.80                          | 0.083                          | 800                       |
| 0402CS-5N6X_L_           | 5.6                             | <b>5,3,2</b>                      | 5.16    | 54                 | 5.28    | 81                 | 4.80                          | 0.083                          | 760                       |
| 0402CS-6N2X_L_           | 6.2                             | <b>5,3,2</b>                      | 6.16    | 52                 | 6.37    | 76                 | 4.80                          | 0.083                          | 760                       |
| 0402CS-6N8X_L_           | 6.8                             | <b>5,3,2</b>                      | 6.56    | 63                 | 6.93    | 78                 | 4.80                          | 0.083                          | 680                       |
| 0402CS-7N5X_L_           | 7.5                             | <b>5,3,2</b>                      | 7.91    | 60                 | 8.22    | 88                 | 4.80                          | 0.10                           | 680                       |
| 0402CS-8N2X_L_           | 8.2                             | <b>5,3,2</b>                      | 8.50    | 57                 | 8.85    | 84                 | 4.40                          | 0.10                           | 680                       |
| 0402CS-8N7X_L_           | 8.7                             | <b>5,3,2</b>                      | 8.78    | 54                 | 9.21    | 73                 | 4.10                          | 0.20                           | 480                       |
| 0402CS-9N0X_L_           | 9.0                             | <b>5,3,2</b>                      | 9.07    | 62                 | 9.53    | 78                 | 4.16                          | 0.10                           | 680                       |
| 0402CS-9N5X_L_           | 9.5                             | <b>5,3,2</b>                      | 9.42    | 54                 | 9.98    | 69                 | 4.00                          | 0.20                           | 480                       |
| 0402CS-10NX_L_           | 10                              | <b>5,3,2</b>                      | 9.8     | 50                 | 10.10   | 67                 | 3.90                          | 0.20                           | 480                       |
| 0402CS-11NX_L_           | 11                              | <b>5,3,2</b>                      | 10.7    | 52                 | 11.20   | 78                 | 3.68                          | 0.12                           | 640                       |
| 0402CS-12NX_L_           | 12                              | <b>5,3,2</b>                      | 11.9    | 53                 | 12.70   | 71                 | 3.60                          | 0.12                           | 640                       |
| 0402CS-13NX_L_           | 13                              | <b>5,3,2</b>                      | 13.4    | 51                 | 14.63   | 57                 | 3.45                          | 0.21                           | 440                       |
| 0402CS-15NX_L_           | 15                              | <b>5,3,2</b>                      | 14.6    | 55                 | 15.50   | 77                 | 3.28                          | 0.17                           | 560                       |
| 0402CS-16NX_L_           | 16                              | <b>5,3,2</b>                      | 16.6    | 46                 | 18.86   | 47                 | 3.10                          | 0.22                           | 560                       |
| 0402CS-18NX_L_           | 18                              | <b>5,3,2</b>                      | 18.3    | 57                 | 20.28   | 62                 | 3.10                          | 0.23                           | 420                       |
| 0402CS-19NX_L_           | 19                              | <b>5,3,2</b>                      | 19.1    | 50                 | 21.10   | 67                 | 3.04                          | 0.20                           | 480                       |
| 0402CS-20NX_L_           | 20                              | <b>5,3,2</b>                      | 20.7    | 52                 | 23.66   | 53                 | 3.00                          | 0.25                           | 420                       |
| 0402CS-22NX_L_           | 22                              | <b>5,3,2</b>                      | 23.2    | 53                 | 26.75   | 53                 | 2.80                          | 0.30                           | 400                       |
| 0402CS-23NX_L_           | 23                              | <b>5,3,2</b>                      | 23.8    | 49                 | 26.90   | 64                 | 2.72                          | 0.30                           | 400                       |
| 0402CS-24NX_L_           | 24                              | <b>5,3,2</b>                      | 25.1    | 51                 | 29.50   | 50                 | 2.70                          | 0.30                           | 400                       |
| 0402CS-27NX_L_           | 27                              | <b>5,3,2</b>                      | 28.7    | 49                 | 33.50   | 63                 | 2.48                          | 0.30                           | 400                       |
| 0402CS-30NX_L_           | 30                              | <b>5,3,2</b>                      | 31.1    | 46                 | 38.50   | 39                 | 2.35                          | 0.30                           | 400                       |
| 0402CS-33NX_L_           | 33                              | <b>5,3,2</b>                      | 34.9    | 31                 | 41.74   | 32                 | 2.35                          | 0.30                           | 400                       |
| 0402CS-36NX_L_           | 36                              | <b>5,3,2</b>                      | 39.5    | 44                 | 48.40   | 53                 | 2.32                          | 0.44                           | 320                       |
| 0402CS-39NX_L_           | 39                              | <b>5,3,2</b>                      | 41.7    | 47                 | 50.23   | 45                 | 2.10                          | 0.55                           | 200                       |
| 0402CS-40NX_L_           | 40                              | <b>5,3,2</b>                      | 39.0    | 44                 | 47.40   | 33                 | 2.24                          | 0.44                           | 320                       |
| 0402CS-43NX_L_           | 43                              | <b>5,3,2</b>                      | 45.8    | 46                 | 61.55   | 34                 | 2.03                          | 0.81                           | 100                       |
| 0402CS-47NX_L_           | 47                              | <b>5,3,2</b>                      | 50.0    | 38                 | –       | –                  | 2.10                          | 0.83                           | 150                       |
| 0402CS-51NX_L_           | 51                              | <b>5,3,2</b>                      | 56.6    | 40                 | –       | –                  | 1.75                          | 0.82                           | 100                       |
| 0402CS-56NX_L_           | 56                              | <b>5,3,2</b>                      | 62.8    | 42                 | –       | –                  | 1.76                          | 0.97                           | 100                       |
| 0402CS-68NX_L_           | 68                              | <b>5,3,2</b>                      | 78.2    | 36                 | –       | –                  | 1.62                          | 1.12                           | 100                       |
| 0402CS-82NX_L_           | 82                              | <b>5,3,2</b>                      | –       | –                  | –       | –                  | 1.26                          | 1.55                           | 50                        |
| 0402CS-R10X_L_           | 100                             | <b>5,3,2</b>                      | –       | –                  | –       | –                  | 1.16                          | 2.00                           | 30                        |
| 0402CS-R12X_L_           | 120                             | <b>5,3,2</b>                      | –       | –                  | –       | –                  | 1.90                          | 2.20                           | 50                        |

1. When ordering, specify **tolerance, termination and packaging** codes:

## 0402CS-68NXJLW

**Tolerance:** G = 2% H = 3% J = 5%

(Table shows stock tolerances in bold.)

**Termination:** L = RoHS compliant silver-palladium-platinum-glass frit.

E = Halogen free component. RoHS compliant silver-palladium-platinum-glass frit terminations.

Special order: T = RoHS tin-silver-copper (95.5/4/0.5) or S = non-RoHS tin-lead (63/37).

**Packaging:** W = 7" machine-ready reel. EIA-481 punched paper tape (2000 parts per full reel).

Q = 7" machine-ready reel. EIA-481 punched paper tape (5000 parts per full reel).

U = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter W instead.

2. Inductance measured at 250 MHz using a Coilcraft SMD-F test fixture and Coilcraft-provided correlation pieces with an Agilent/HP 4286 impedance analyzer.

3. Tolerances in bold are stocked for immediate shipment.

4. Q measured using an Agilent/HP 4291A with an Agilent/HP 16193 test fixture.

5. For SRF >6 GHz, measured using an Agilent/HP 8722ES network analyzer and a Coilcraft SMD-D test fixture. For SRF ≤6 GHz, measured using an Agilent/HP 8753D network analyzer and a Coilcraft SMD-D test fixture.

6. DCR measured on a micro-ohmmeter.

7. Current that causes a 15°C temperature rise from 25°C ambient.

8. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.

**S-Parameter files**  
ON OUR WEB SITE

**SPICE models**  
ON OUR WEB SITE



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com

UK +44-1236-730595 sales@coilcraft-europe.com

Taiwan +886-2-2264 3646 sales@coilcraft.com.tw

China +86-21-6218 8074 sales@coilcraft.com.cn

Singapore +65-6484 8412 sales@coilcraft.com.sg

Document 198-2 Revised 05/03/13

© Coilcraft Inc. 2013

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9